

# LA-UR-12-26915

Approved for public release; distribution is unlimited.

Title: Individual Permit for Stormwater Public Update December 2012

Author(s): Lopez, Lorraine B.

Intended for: Individual Permit for Stormwater Public Update, 2012-12-13 (Los Alamos, New Mexico, United States)  
Environmental Programs



**Disclaimer:**

Los Alamos National Laboratory, an affirmative action/equal opportunity employer, is operated by the Los Alamos National Security, LLC for the National Nuclear Security Administration of the U.S. Department of Energy under contract DE-AC52-06NA25396. By approving this article, the publisher recognizes that the U.S. Government retains nonexclusive, royalty-free license to publish or reproduce the published form of this contribution, or to allow others to do so, for U.S. Government purposes. Los Alamos National Laboratory requests that the publisher identify this article as work performed under the auspices of the U.S. Department of Energy. Los Alamos National Laboratory strongly supports academic freedom and a researcher's right to publish; as an institution, however, the Laboratory does not endorse the viewpoint of a publication or guarantee its technical correctness.



# Individual Permit for Stormwater

## Public Update

December 2012

# Scope of Meeting

- **Purpose of this meeting**
  - Share information
  - Project status
  - Not designed to include
    - Discussions about the scope of the permit
    - LANL's programmatic priorities
- **Focus is on permit compliance actions**
- **A Q&A sessions**
  - after the LANL presentations
  - after all presentations if time allows

# General Ground Rules

- Please wait until the scheduled time to provide comments or to ask questions
- Please identify yourself before speaking
- Please keep your questions short
  - remember there may be others waiting to ask questions
- Please honor the process by keeping questions and comments civil and by using appropriate language
- Please yield the floor if requested by the facilitator
- Please help the participants and facilitator ensure that the agenda content and timeframes are met

# Agenda

<b>Time</b>	<b>Subject</b>	<b>Speaker</b>
5:30	View Posters	
5:35	Meeting opening	Bruce MacAllister
	Introduction	Dave McInroy
	Individual Permit Overview	Steve Veenis
5:50	Data Results for 2012	Armand Groffman
6:05	Enhanced Controls Installation	Jeff Walterscheid
6:20	Designing for Total Stormwater Retention	Bill Foley
6:40	Low-Impact Design for Stormwater Management	Rachel Conn Erin English
7:00	Integrated Stormwater Approach in Upper Sandia Canyon	Debbie Apodaca Pesiri
7:20	Alternative Compliance	Steve Veenis
7:30	Meeting end	




# Introduction

LANL Individual Permit  
Public Meeting  
December 13, 2012

Dave McInroy  
Environmental Cleanup  
Program Director

# Welcome



# Individual Permit Public Involvement Activities

## IP Public Website

<http://www.lanl.gov/environment/>

Los Alamos National Laboratory

Science & Innovation | Collaboration | Careers, Jobs | Comm

Community, Environment > Environmental Stewardship > Environmental Protection > Obeying Environmental Laws > Individual Permit for Stormwater

### Individual Permit for Stormwater

The Individual Permit **authorizes** the discharge of stormwater associated with **industrial activities** at LANL.

#### CONTACT

**Environmental Communications & Public Involvement**  
Email

#### What is the Individual Permit for Stormwater?

The National Pollutant Discharge Elimination System Individual Permit authorizes the discharge of stormwater associated with industrial activities at the Los Alamos National Laboratory from specified Solid Waste Management Units and Areas of Concern, collectively referred to as Sites.

The Permit - NPDES No. NM0030759<sup>02</sup> - was issued by the U.S. Environmental Protection Agency, Region 6, on September 30, 2010 to Los Alamos National Security, LLC and the U.S. Department of Energy (the Permittees). The Individual Permit became effective on November 1, 2010.

#### Requirements

The Individual Permit requires LANL to implement non-numeric technology-based effluent limitations (control measures also known as "Best Management Practices"), coupled with a comprehensive monitoring program, to minimize pollutants in LANL's storm water discharges. The EPA believes compliance with these technology-based

**In the Individual Permit, to 'minimize' means to reduce and/or eliminate discharges of pollutants in stormwater to the extent achievable.**

Los Alamos NATIONAL LABORATORY EST. 1943

TOP STORIES  
<http://www.lanl.gov>

Climate, energy, security, health  
**What is LANL doing?**

## E-mail Notifications



Public Meetings twice per year




# Intellus Website for Environmental Data

[www.intellusmdata.com](http://www.intellusmdata.com)



ABOUT DOCUMENTS REPORTING MAPS INTELLUS PROJECT CONTACT US



# Individual Permit Commitments

## **We are committed to:**

- **Improving environmental protection and stewardship**
- **Mitigating transport of legacy contaminants by stormwater**
- **Ongoing implementation of Permit requirements**
- **Meeting permit milestones**
- **Sharing results with the public**
- **Incorporate feedback from stakeholders**




# Project Overview

**Steve Veenis**

# Individual Permit Project Overview


- Permit Issued – November 1, 2010 (5 year Permit Cycle)
  - 405 Solid Waste Management Units (SWMU)/Areas Of Concern (AOC)
- Installation of Baseline Control Measures complete (May 2011)
- Collect storm water samples at 250 Surface Monitoring Areas (SMAs)
  - >Target Action Levels (TALs) - Initiate Corrective Action
- Annual Reporting
- Public Involvement



# IP Surface Monitoring Area (SMA)

IP regulates **point source discharges** of storm water from SWMUs and AOCs

1. Discharges must be from SWMUs or AOCs
2. **Significant industrial materials** must be exposed to storm water
3. Must have potential to discharge to receiving waters



# IP Corrective Action Options

If stormwater monitoring results  
above target action levels

Then complete Corrective Action per Part I, E

Install  
enhanced  
control  
measures  
and continue  
monitoring

Total retention  
of stormwater

Eliminate  
exposure to  
stormwater

Certificate of  
Completion  
under Consent  
Order with  
NMED

# Individual Permit Project Overview


- **IP Compliance**
  - 45 Corrective Actions completed and certified
  - Deliverables submitted on schedule
  - Inspection/Maintenance
  - Monitoring
    - Drought condition impacts
    - Corrective Action has been initiated at approximately 1/3 of Sites
- **Public Involvement**
  - 4th public meeting
  - 5 technical meetings with Western Environmental Law Center (WELC)
  - Public website
- **Process Improvements**
  - Telemetry upgrades
  - Precipitation network enhancements
  - Field processes



# 2012 Monitoring Season Annual Update Armand Groffman



# 2012 Precipitation




**2012 precipitation less than 2011**  
**Storms were shorter in duration**  
**Rain events are very localized**

# Summary of Stormwater Samples Collected at SMAs in 2012


**25 stormwater runoff samples collected from 23 SMAs in 2012**

**Less precipitation and better controls resulted in lower number of stormwater samples collected**

**The program is continually improving management of stormwater runoff**




# 2012 Metals and Rad Monitoring Results Normalized to Target Action Limits



	Aluminum	Antimony	Arsenic	Boron	Cadmium	Chromium	Cobalt	Copper	Lead	Mercury	Nickel	Selenium	Silver	Thallium	Vanadium	Zinc	Cyanide, weak acid dissociable	Gross alpha	Radium-226 and Radium-228
std used in ratio calculations	MTAL	ATAL	ATAL	ATAL	MTAL	MTAL	ATAL	MTAL	MTAL	ATAL	MTAL	ATAL	MTAL	ATAL	ATAL	MTAL	ATAL	ATAL	ATAL
std value	750	640	9	5000	1	210	1000	4.3	17	0.77	170	5	0.5	6.3	100	42	0.01	15	30
unit	ug/L	ug/L	ug/L	ug/L	ug/L	ug/L	ug/L	ug/L	ug/L	ug/L	ug/L	ug/L	ug/L	ug/L	ug/L	ug/L	mg/L	pCi/L	pCi/L

$$\frac{\text{Result}}{\text{TAL}} = \text{TAL Exceedance Ratio}$$


## 2012 Organic Monitoring Results Normalized to Target Action Limits



	Aldrin	Benzo(a)pyrene	BHC[gamma-]	Chlordane (alpha/gamma)	Chlordane[alpha-]	Chlordane[gamma-]	DDD[4,4'-]	DDE[4,4'-]	DDT[4,4'-]	Dieldrin	Endosulfan I	Endosulfan II	Endrin	Heptachlor	Heptachlor Epoxide	Hexachlorobenzene	Pentachlorophenol	RDX	Tetrachlorodibenzo dioxin[2,3,7,8-]	Total PCB	Toxaphene (Technical Grade)	Trinitrotoluene [2,4,6-]	
std used in ratio calculations	-	ATAL	-	-	-	-	-	-	-	-	-	-	-	-	-	ATAL	MTAL	ATAL	-	ATAL	-	-	ATAL
std value	-	5	-	-	-	-	-	-	-	-	-	-	-	-	-	5	19	200	-	0.0006	-	-	20
unit	ug/L	ug/L	ug/L	ug/L	ug/L	ug/L	ug/L	ug/L	ug/L	ug/L	ug/L	ug/L	ug/L	ug/L	ug/L	ug/L	ug/L	ug/L	ug/L	ug/L	ug/L	ug/L	ug/L

$$\frac{\text{Result}}{\text{TAL}} = \text{TAL Exceedance Ratio}$$

# 2012 TAL Exceedances



## PCBs


- There are contaminated sites at the Laboratory (LANL)
- Target Action Limit of **0.64 ng/L** (Human Health Criteria); **14 ng/L** (Wildlife Std).
- A nano gram is one billionth of a gram (1/1,000,000,000 gram) or think of it as one drop of ink in a large tanker truck.
- PCB federal and state drinking water standard is **500 ng/L**.
- The following baseline upper tolerance limits are presented in the Baseline PCB report:  
**13 ng/L** remote watersheds on the Pajarito Plateau; **24 ng/L** northern New Mexico tributaries; **98 ng/L** urban runoff from developed landscape on the Pajarito Plateau.



# 2012 TAL Exceedances

## Aluminum

- Aluminum is the third most common element in the earth's crust.
- Naturally occurring background; mineral bound aluminum.
- Aluminum is not soluble at near neutral pH (6 to 8).
- Detections are most likely due to filter breakthrough of colloidal size aluminum bearing minerals.



# 2012 TAL Exceedances



## Copper and Zinc

- Naturally occurring background at some locations, urban run-on, also, some SMAs have contamination

## Common Sources of Zinc and Copper in Stormwater Runoff from Urban Landscapes and Industrial Facilities

- Roofs—galvanized HVAC, ducts, ventilation fans, turbines, galvanized downspouts and culverts, chain-link fences and flashing, guard rails, cooling water systems, copper pipes, copper flashing
- Parking areas—automobiles, trucks, forklifts, motor oil, tire particles, hydraulic fluid, truck/trailer or bus parking, vehicle break pads
- Material storage, galvanized metals, chain link fences, printed circuit boards, and vehicles (as above)



# 2012 TAL Exceedances





## Gross Alpha

- Derived from naturally occurring background uranium and thorium containing minerals and their daughter products radium and radon.
- Some select locations where historical releases have occurred.
- For the most part, minerals that contain potassium, uranium, and thorium are radioactive emitting alpha and gamma radiation
- Granite and volcanic rocks contain trace quantities of uranium, thorium, radium, and radioactive potassium ( $K^{40}$ ); granite counter tops
- As these rocks weather they are reduced to fine grain sediments that are transported by water and wind
- Water samples containing sediments derived from granites and volcanic rocks will generally yield positive gross alpha and gamma analytical results





- 
- A photograph of a sunset over a body of water. The sun is low on the horizon, creating a bright, vertical reflection on the water's surface. The sky is a mix of orange, yellow, and blue, and the water is dark with some ripples.
- Collected 25 stormwater runoff samples from 23 SMAs
  - Less runoff in 2012 due to better controls and reduced precipitation
  - Exceedances most often are aluminum, copper, zinc, gross alpha, and PCBs
  - Exceedances are most likely within range of background or baseline values
  - How do stormwater run-on (non-SWMU sources) pollutants affect IP TAL results?



# Enhanced Stormwater Control Measures

Jeff Walterscheid

# Why Corrective Action?

- **The Individual Permit states “if confirmation monitoring shows target action levels are not being met at a particular Site, Permittees must take corrective action through installation of measures reasonably expected to:**
  - I. Meet applicable target action levels at the Site;
  - II. Achieve total retention of stormwater discharges from the Site;
  - III. Totally eliminate exposure of pollutants to stormwater;
  - IV. Demonstration that the Site has achieved RCRA “no further action” status or a Certificate of Completion under NMED’s Consent Order.”  
(Permit No. NM0030759, section E.)
  
- Based on monitoring results, Site Monitoring Areas (SMAs) with confirmation samples exceeding Target Action Levels (TALs) are evaluated for the above criteria.

# What is an Enhanced Control Measure?

“Corrective action may entail the design and installation of enhanced (additional, expanded, or better tailored control measures) reasonably expected to achieve compliance with target action levels identified in the Permit for all Sites within the SMA drainage area.” (Permit No. NM0030759, section E.1.)

- Add additional controls
- Modify existing controls
- Replace existing controls

# Types of Controls

- **Baseline controls**

- Limited by Permit requirements that all controls be installed within six months of permit issuance. Controls were installed during the winter months 2010-2011

- **Augmented controls**

- Review of baseline controls that demonstrates additional or bigger more robust controls are warranted (not required by the Permit)

- **Enhanced controls**

- Additional, expanded, or better tailored controls following a TAL exceedance using a low-impact development (LID) approach
- Possible opportunity for remediation of contaminants

# SMA Status

33 High Priority PCB SMAs

3 Years to complete

Baseline Sufficient  
(12)

Augmented  
Controls  
(9)

Enhanced Controls  
(12)

48 Moderate Priority  
(PCB) SMAs

5 Years to complete

Baseline Sufficient  
(22)

Augmented  
Controls  
(9)

Enhanced Controls  
(17)

169 Moderate Priority SMAs

5 Years to complete

Baseline Sufficient  
(82)

Augmented  
Controls  
(36)

Enhanced Controls  
(51)

# Challenges to Completing Field Work

- **Seasonal restrictions**

  - Weather

  - Threatened and endangered species

- **Health and safety issues**

  - Accessibility (steep slopes, limited access points, etc.)

  - Potential site specific concerns (UXO, HE, utilities. etc.)

  - Operational and historical considerations

- **Cultural protections**

  - Archaeological sites

  - Historical sites/trails

- **Property ownership**


  - Access agreements with Forest Service, LA County, private property owners

# Enhanced Controls Installation Tracking

SMA	Asset ID	Classification Name	Run-on Control?	Runoff Control?	Sediment Control?	Erosion Control?
LA-SMA-10.12	L030A03010026	Earthen Berm	X	-	X	-
LA-SMA-10.12	L030A03060028	Straw Wattles	X	-	X	-
LA-SMA-10.12	L030A03060029	Straw Wattles	-	X	X	-
LA-SMA-10.12	L030A02010031	Permanent Vegetation Gr	-	-	-	X
LA-SMA-10.12	L030A03120030	Rock Berm	-	X	X	-
LA-SMA-10.12	L030A03010027	Earthen Berm	-	X	X	-
<b># Controls installed</b>		<b>6</b>				
STRM-SMA-5.05	J03103010009	Earthen Berm	X	-	X	-
STRM-SMA-5.05	J03103010010	Earthen Berm	-	X	X	-
STRM-SMA-5.05	J03101040011	Seeding	-	-	-	X
<b># Controls installed</b>		<b>3</b>				



# STRM-SMA-5.05




- Sampler location
- Gage station
- Storm water discharge**
- Storm water discharge
- Industrial MSGP Outfall
- Main drainage
- Non-storm water discharge**
- NPDES outfall
- Fire hydrant
- Site drainage
- Direction of flow
- Perennial drainage
- Storm drain/culvert
- Monitored SWMU/AOC
- Wetland
- Fence
- Dirt road
- Paved road
- Paved parking
- Structure
- LANL boundary

**BMP Type**

Berm	Permanent Vegetation
Channel/Swale	Sediment Trap/Basin
Check Dam	Gabion
Seed and Mulch	Cap

State Plane Coordinate System  
 New Mexico, Central Zone, US Feet  
 NAD 1983 Datum  
 Grid Interval = 200ft  
 Contour Interval = 2ft



**NPDES Individual Permit NM0030759**

**Storm Water Permitted Feature  
 J031: STRM-SMA-5.05**

**Pajarito Canyon**

Water Pollution Control Drawing

Map Created By: Dave Frank, EP-ET-ER GIS Team, August 1, 2012,  
 Map #J031-10-0017-182-STRM5.05-R5

This map was created for work processes associated with the NPDES Individual Permit. All other uses for this map should be confirmed with LANL EP-WES staff.

# Enhanced Controls Installed At STRM-SMA-5.05

SMA	Asset ID	Classification Name	Run-on Control	Runoff Control	Sediment Control	Erosion Control
STRM-SMA-5.05	J03103010009	Earthen Berm	X	-	X	-
STRM-SMA-5.05	J03103010010	Earthen Berm	-	X	X	-
STRM-SMA-5.05	J03101040011	Seeding	-	-	-	X
<b># Controls installed</b>	3					

Run-on Control Berm



Run-off Control Berm



# Enhanced Controls


LA-SMA-0.85



- Run-off
- Control berm
- Spillway

# Enhanced Controls

## CDB-SMA-1



- Run-off
- Control berm
- Spillway

# Enhanced Controls

M-SMA-1



- Erosion control
- Low head weir

# Enhanced Controls




CDV-SMA-1.4



- Run-on
- Sediment control berm

# Enhanced Controls

## CDV-SMA-1.4



- Retention

# Enhanced Controls

## W-SMA-1.5

Before



After



- Run-off
- Control berm
- Spillway
- Rock check dam



## Enhanced Controls



Before



After




After

- Multiple channels
- Run-off
- Control berms
- Spillways

# Enhanced Controls

## W-SMA-11.7



- Sheet flow
- Run-off
- Rock check dams
- Control berms

# Enhanced Controls

W-SMA-11.7



- Sheet flow
- Control berm with mulch

# Enhanced Controls

## W-SMA-14.1

Before



After

- Run-off
- Control berms
- Spillways

# Enhanced Controls



PT-SMA-0.5



- Run-on & Run-off
- Control berms

# Enhanced Control at S-SMA-1.1 – Total Retention



Before



After



## Design Storm for “Total Retention”


**Bill Foley**

# Total Retention – Background

- **The Individual Permit (IP)**
  - Regulates stormwater discharges from “Sites” (i.e., SWMUs and AOCs)
  - Monitored at Site Monitoring Area (SMA) scale (i.e. drainage basins)
- **IP requires “corrective action” when a stormwater sample exceeds a target action level for one or more constituents.**
- **One method of corrective action is “total retention.”**
- **The IP does not specify a design storm for total retention**




# Differences between detention and retention




# Is your objective to detain stormwater?

- Reduce peak flows
- Reduce impacts of downstream flooding and erosion



# Is your objective to retain stormwater?


- Stormwater leaves via infiltration, evaporation, or transpiration
- Provides similar benefits as detention
- Provides additional water quality treatment for same volume



# What Is a “Design Storm?”

- **Storm characteristics**

- Frequency
- Intensity
- Duration



# What is a “Design Storm?”


- **Storm events defined in two ways**
  - Return period
    - e.g. 5 year - 1 day
  - Percentile rainfall event
    - e.g. 80<sup>th</sup> percentile = 80 out of 100 are smaller
- **Applicable regulation and guidance**

# Issues To Consider When Choosing a Design Storm

- **Storm events**


1. Independent of each other, local variations
2. Pre-existing / antecedent conditions
3. Soil conditions, time between storms, etc.

# Gage Station Location




# Selecting a Design Storm for the IP

## Gage Data Rainfall Distribution






# How Do You Use the Design Storm?




# Issues To Consider When Selecting Design Alternatives


- **SMA variations**
  - Area, development condition, physical characterization, etc.
- **Site relation to SMA**
  - Relative size and location within SMA, etc.



# Design Storm Used for Total Retention Evaluation Example



# Design Storm Used for Total Retention Evaluation Example



# Summary

- **The 95<sup>th</sup> percentile design storm (1.0 in.) for total retention is**
  - Consistent with U.S. Environmental Protection Agency guidance,
  - Based on decades of local precipitation data, and
  - Conservative
- **The Laboratory proposes to use the 95<sup>th</sup> percentile design storm as the metric for meeting total retention under Section E.2.(b) of the IP**
- **This approach has been proposed to EPA and WELC**

# Integrated Stormwater Approach in Upper Sandia Canyon

Deborah Apodaca Pesiri





# Upper Sandia Map

S-SMA-0.25 (33 acres)



- Location: Main Campus
- Highly developed area
- Buildings, pavement, roads
- Stormwater: urban runoff

S-SMA-2 (50 acres)



# Sandia High Priority SMA's in Corrective Action

- **S-SMA-0.25**: LID Bioretention basins and ponds, zuni bowl and Sedimentation Ponds
- **S-SMA-1.1**: LID (Total Retention, inlet and outlet protection, bio-swale and Run-on Conveyance)
- **S-SMA-2.0**: LID (SWMMM model and LID in progress)
- **S-SMA-2.01**: LID retention
- **S-SMA-3.53**: LID Disconnect impervious areas/run-on diversion (Plug and cap Outfall, Re-route SW through open swale)
- **S-3.6**: Enhanced done (berms and ditch blocks); Design-Re-route Pipes and inlets through SWMU
- **S-6.0**: Design complete, Phase 1: Sedimentation Ponds; Phase 2-Total Retention and No Exposure
- **S-4.1**: Enhanced done-No exposure for part of SWMU, Run-on diversion
- **Sandia Wetlands**
  - Grade control Structure Design 100% complete
  - Road constructed this fall
  - Construction take place in Spring


# Approach in Upper Sandia at LANL

- Improve water quality
- Reduce peak flows
- Reduce contaminant levels
- Capture, infiltrate, treat and slowly discharge stormwater

## **Strategy:** Integrated Stormwater System


- Upper areas-Low Impact Development (LID)
- Middle- LID and typical stormwater controls
- Anchor Point – Maintain Wetlands

# LID Concept: to restore pre-development hydrology and reduce pollutant loads



- Minimize clearing – save trees/vegetation
- Minimize soil compaction of pervious areas
- Minimize impervious area
- Infiltrate or reuse water
- Reduce runoff volume

# S-SMA-0.25: WELC/Biohabitats LID Alternatives




**Legend**

- Bioretention Basin
- Sedimentation Pond
- Bioretention Garden
- Zuni Bowl/Outlet Protection
- Wetland
- Roof Drains
- SWMU/AOC
- ★ IP Sampler
- Curb Cuts

## S-SMA-0.25 : IP Work History

- **LANL Conceptual Design and Alternatives Analysis**
  - 03-052(f): trapezoidal concrete channel or extend outfalls
  - 03-013(a): slip line pipe
- **WELC Technical Group (Biohabitats)**
- **LANL cost analysis, utilities research, FOD discussions, hydraulic modeling**
- **90% Design**


# S-SMA-0.25: LANL LID areas in Design





**Legend**

- Bioretention Basin
- Sedimentation Pond
- Bioretention Garden
- Zuni Bowl/Outlet Protection
- Wetland
- Roof Drains
- SWMU/AOC
- ★ IP Sampler
- Curb Cuts

# S-SMA-0.25: EPA Stormwater Management Model



# S-SMA-0.25 SWMM Results




ate LID locations

60% Review, Not for Construction






# LID at S-SMA-0.25 (Node 67:2.5X Peak Reduction)




60% Review, Not for Construction

# LID at S-SMA-0.25 Node 67: 2X Peak Reduction



60% Review, Not for Construction

# LID areas for S-SMA-2.0



**Legend**

- Bioretention Basin
- Sedimentation Pond
- Bioretention Garden
- Zuni Bowl/Outlet Protection
- Wetland
- Roof Drains
- SWMU/AOC
- ★ IP Sampler
- - Curb Cuts


# LID at S-SMA-2.0



**Legend**

- Bioretention Basin
- Sedimentation Pond
- Bioretention Garden
- Zuni Bowl/Outlet Protection
- Wetland
- Roof Drains
- SWMU/AOC
- ★ IP Sampler
- Curb Cuts

# S-SMA-1.1 Integrated approach overview



# S-SMA-1.1: Total Retention



Before




After

# S-SMA-1.1: Inlet protection, detention, run-on conveyance



Before



After

# S-SMA-1.1: Outlet protection



Before



After



# Wetland: Anchor Point for Upper Sandia



# Upper Wetlands Current Conditions



Upper Wetlands

- 72-inch culvert to stable basin
- Defined stream channel in upper third

- Stable wetland environment

Middle Wetlands



# Terminus Wetlands Current Conditions

- Restore lower wetland conditions by planting and stabilization plan

Grade Control Structures and cascading pool



Active Headcut

- Arrest headcut to create permanent grade
- Increase area of delineated wetland



# Cascading Pool Example






# Alternative Compliance

Steve Veenis

# Corrective Action Process/Alternative Compliance Pathway



# Alternative Compliance Path

## Potential Scenarios

- SMAs with large drainage areas within light industrial settings
  - Impractical to totally retain discharges or cover the Site
- >TAL due to Pollutants of Concern contributed by other sources
- SMAs with very low >TAL due to background concentrations
- SMAs with Force Majeure issues
  - Site Access issues
  - Long-term solutions in planning phase