LA-UR-21-32467

Approved for public release; distribution is unlimited.

Title: MSGP Stormwater Polllution Prevention Plan TA-16 Stockpile Area

Author(s): Wheeler, Holly Lynn Bileen, Kelkenny

Intended for:Environmental Regulatory DocumentIssued:2021-12-23 (rev.1)









Los Alamos National Laboratory, an affirmative action/equal opportunity employer, is operated by Triad National Security, LLC for the National Nuclear Security Administration of U.S. Department of Energy under contract 89233218CNA000001. By approving this article, the publisher recognizes that the U.S. Government retains nonexclusive, royalty-free license to publish or reproduce the published form of this contribution, or to allow others to do so, for U.S. Government purposes. Los Alamos National Laboratory requests that the publisher identify this article as work performed under the auspices of the U.S. Department of Energy. Los Alamos National Laboratory strongly supports academic freedom and a researcher's right to publish; as an institution, however, the Laboratory does not endorse the viewpoint of a publication or guarantee its technical correctness.

MSGP Stormwater Pollution Prevention Plan

TA-16 Stockpile Area

Triad National Security, LLC Los Alamos National laboratory

> December 2021 Revision 3

Page intentionally blank

TABLE OF CONTENTS

PREFA	CE	. 7
1.0	FACILITY DESCRIPTION	. 7
1.1	Facility Information	. 7
1.2	Stormwater Pollution Prevention Team (PPT)	. 8
1.3	Site Description	. 9
1.4	General Location Map	10
1.5	Site Map	10
2.0	POTENTIAL POLLUTANT SOURCES	11
2.1	Potential Pollutants Associated with Industrial Activity	11
2.2	Spill and Leaks	14
2.3	Unauthorized Non-Stormwater Discharges	15
2.4	Salt Storage	15
2.5	Historical Data Summary	15
3.0	STORMWATER CONTROL MEASURES	16
3.1	Non-Numeric Technology-Based Effluent Limits	16
	3.1.1 Minimize Exposure	
	3.1.2 Good Housekeeping3.1.3 Maintenance	
	3.1.4 Spill Prevention and Response	
	3.1.5 Erosion and Sediment Control	
	3.1.6 Management of Runoff	19
	3.1.7 Salt Storage Piles or Piles Containing Salt	20
	3.1.8 Dust Generation and Vehicle Tracking of industrial Materials	
3.2	Numeric Effluent Limitations Based on Effluent Limitations Guidelines	20
3.3	Water Quality-Based Effluent Limitations and Water Quality Standards	20
4.0	SCHEDULES AND PROCEDURES	20
4.1	Good Housekeeping	20
4.2	Maintenance	21
4.3	Spill Prevention and Response	21
4.4	Erosion and Sediment Control	21

4.5	Employee Training	21
4.6	Routine Facility Inspections and Quarterly Visual Assessments	22
4.7	4.6.1 Routine Facility Inspections4.6.2 Quarterly Visual AssessmentsMonitoring	23
5.0	DOCUMENTATION FOR ELIGIBILITY CONSIDERATIONS UNDER OTHER FEDERAL LAWS	527
5.1	Endangered Species	27
5.2	Historic Properties	27
6.0	CORRECTIVE ACTIONS AND DEADLINES	27
6.1	Immediate Actions	28
6.2	Subsequent Actions	29
6.3	AIM Baseline Status and Triggering Events	29
	6.3.1 AIM Level 1 6.3.2 AIM Level 2 6.3.3 AIM Level 3 6.3.4 AIM Exceptions	30 30
6.4	Corrective Action and AIM Documentation	31
7.0	ACRONYMS	32
8.0	SWPPP CERTIFICATION	33
FIGURI	E A: GENERAL LOCATION MAP	34
FIGURI	E B-1: FACILITY SITE MAP	36
FIGURI	E B-2: NEARBY RECEIVING WATERS MAP	38
FIGURI	E B-3: LANL ENDANGERED SPECIES MAP	40
ΑΤΤΑϹ	HMENT 1: NOTICE OF INTENT, SUPPORTING DOCUMENTATION, AND UPDATES	42
ATTAC	HMENT 2: SWPPP AMENDMENTS	43
ATTAC	HMENT 3: CERTIFICATION OF NO UNAUTHORIZED STORMWATER DISCHARGES	44
ΑΤΤΑϹ	HMENT 4: DULY AUTHORIZED SIGNATORY MEMORANDUM	45
ΑΤΤΑϹ	HMENT 5: DISCHARGE MONITORING REPORTS	46

ATTACHMENT 6:	ANNUAL REPORTS	7
ATTACHMENT 7:	ROUTINE FACILITY INSPECTIONS	8
ATTACHMENT 8:	QUARTERLY VISUAL ASSESSMENTS 49	9
ATTACHMENT 9:	CORRECTIVE ACTION DOCUMENTATION AND CERTIFICATION	D
ATTACHMENT 10:	SCHEDULED MAINTENANCE LOG	1
ATTACHMENT 11:	TRAINING DOCUMENTATION	2
ATTACHMENT 12:	MSGP (OR ACTIVE URL)	3
	THREATENDED AND ENDANGERED SPECIES HABITAT MANAGEMENT LOS ALAMOS NATIONAL LABORATORY	4
ATTACHMENT 14:	MSGP IPAC TRUST RESOURCES REPORT	5
ATTACHMENT 15:	EPC-CP-PIP-2101, NPDES MULTI-SECTOR GENERAL PERMIT	6
ATTACHMENT 16:	EPC-CP-QP-2108, MSGP ROUTINE FACILITY INSPECTIONS5	7
ATTACHMENT 17:	EPC-CP-QP-022, MSGP CORRECTIVE ACTIONS58	8
ATTACHMENT 18:	EPC-CP-QP-2105, MSGP STORMWATER VISUAL ASSESSMENTS	Э
	EPC-CP-QP-2103, INSPECTING ISCO STORMWATER RUNOFF SAMPLERS EVING SAMPLES	D
ATTACHMENT 20:	EPC-CP-QP-2106, PROCESSING MSGP STORMWATER SAMPLES6	1
	EPC-DO-QP-0903, ENVIRONMENTAL REPORTING REQUIREMENTS FOR DR EVENTS	2
ATTACHMENT 22:	EPC-CP-QP-1007, SPILL INVESTIGATIONS63	3
	EPC-CP-QP-2110, <i>MSGP STORMWATER POLLUTION PREVENTION PLAN</i> ION AND MAINTENANCE	4
	WFO-IWD-00016, SPILL RESPONSE AND CLEAN UP IN WEAPONS OPERATIONS (WFO) AREAS65	5

TA-16 Stockpile Area STORMWATER POLLUTION PREVENTION PLAN

PREFACE

This Stormwater Pollution Prevention Plan (SWPPP) was developed in accordance with the provisions of the Clean Water Act (33 U.S.C. §§1251 et seq., as amended), and the *United States Environmental Protection Agency (EPA) National Pollutant Discharge Elimination System (NPDES) Multi-Sector General Permit for Stormwater Discharges Associated with Industrial Activity (MSGP)* (U.S. EPA, January 2021) issued by EPA. The SWPPP uses the industry specific permit requirements for Sector P: Land Transportation and Warehousing as a guide. The applicable stormwater discharge permit is EPA General Permit Tracking Number NMR050013 MSGP 2021 [Triad National Security, LLC (Triad)]. Click here to view contents of the <u>2021 Multi-Sector General Permit</u>

This SWPPP applies to discharges of stormwater from the operational areas of the TA-16 Stockpile Area within Weapons Facility Operations (WFO) Facility Operations Directorate (FOD) at Los Alamos National Laboratory. Los Alamos National Laboratory (also referred to as LANL or the "Laboratory") is owned by the Department of Energy (DOE), and is operated by Triad. Throughout this document, the term "facilities" refers to the TA-16 Stockpile Area. The current MSGP expires at midnight on February 28, 2026.

1.0 FACILITY DESCRIPTION

1.1 Facility Information

Name of Facility: TA-16 Stockpile Area					
Street: PO Box 1663					
City: Los Alamos	State: NM	ZIP Code: 87545			
County: Los Alamos					
NPDES ID (i.e., permit tracking number): NMR050013 M	SGP 2021				
Primary Industrial Activity Sector and Subsector (2021 MSGP, Appendix D and Part 8): Sector P,					
Subsector P1					
Estimated area of industrial activity at site exposed to stormwater: 1.2 acres					
Discharge Information					
Name(s) of surface water(s)/segment that receives stormwater from your facility: Cañon de Valle (within LANL) below LANL Gage E256					

Does this facility discharge industrial stormwater directly into any segment of an "impaired water" (see definition in 2021 MSGP, Appendix A)?
Yes No

Pollutants causing the impairment: Adjusted Gross Alpha

Pollutants causing the impairment (see above) that may be present in industrial stormwater discharges from this Facility: Adjusted Gross Alpha

Are any of your stormwater discharges subject to effluent limitation guidelines (ELGs) (2021 MSGP Table 1-1)?

If Yes, which guidelines apply? Not applicable.

1.2 Stormwater Pollution Prevention Team (PPT)

The TA-16 Stockpile Area is part of the Weapons Facility Operation (WFO) Facility Operations Division (FOD) at Los Alamos National Laboratory with day-to-day management provided by Logistics Division-Heavy Equipment Roads & Grounds, which has established a PPT whose members are responsible for assisting the facility manager in developing and revising the facility's SWPPP as well as maintaining control measures and taking corrective actions when required. All PPT members have access to either a hard copy or an electronic version of this SWPPP.

The specific duties of individual team members of the PPT are listed below.

Staff Names	Individual Responsibilities
FOD	Responsible for managing the operation and maintenance of all aspects
Manager/Representative	of the TA-16 Stockpile Area listed within this Plan. The Operations
John Branch, Operations Manager, WFO-HE	Manager shall provide review and ensure coordination with core personnel and the PPT, as appropriate, when tenants within the WFO FOD propose a new process or a new site or operation that may be subject to the MSGP. The FOD Manager/Representative is key to ensuring adequate communication and coordination of issues regarding implementation of the MSGP and this SWPPP.
Deployed Environmental	Responsible for the support and oversight of all environmental programs
Professional (DEP)	and issues for the TA-16 Stockpile Area. The DEP is responsible for
Kelkenny Bileen, EPC-CP	training, recordkeeping, and SWPPP revision. The DEP ensures that all PPT, operations site workers (as appropriate), and applicable supervisors receive annual MSGP and SWPPP training. The DEP ensures documentation of inspections and other required MSGP records relative to the SWPPP are managed in accordance with the permit and established document control procedures and that the SWPPP is kept current. The DEP provides technical and regulatory support and regularly communicates with facility and operations personnel and the PPT

	regarding implementation of the MSGP and this SWPPP. Lastly, the DEP conducts routine facility inspections and if necessary, visual assessments, in accordance with the Permit. Identified conditions requiring corrective actions from routine facility inspections are entered into the Environmental Protection and Compliance-Compliance Programs (EPC- CP) Corrective Action Report (CAR) database. The DEP is responsible for tracking and updating the status of corrective actions that cannot be implemented immediately. The DEP is also responsible for immediate and timely communication to appropriate facility and operations management personnel to ensure that they are aware of non-compliant issues within the MSGP facility boundary and that they understand immediate action is required to correct the non-compliance.
EPC Core Holly Wheeler, MSGP Program Lead, EPC-CP	The MSGP Program Lead is responsible for managing and administering the MSGP Program for all industrial facilities operated by Triad within Los Alamos National Laboratory. The MSGP Program Lead advises and provides guidance to facility and operations personnel on NPDES MSGP regulations/requirements. The MSGP Program Lead also acts as the institutional point of contact for all interactions with the regulatory authority (EPA) and supervises personnel implementing stormwater monitoring requirements for the facility.
Facility Staff Randy Archuleta, Logistics Superintendent Field Work Execution (LOG- SUP)	Responsible for day-to-day operations at the facility. Assisting DEPs and EPC with inspections; spill reporting; implementing, installing and maintaining stormwater controls (also known as Best management Practices) (BMPs); and providing documentation as requested by other team members. The Superintendent is key to ensuring adequate communication and coordination of issues regarding implementation of the MSGP and this Plan. The Superintendent also assists the DEP/EPC with SWPPP training and/or briefings, as requested.

1.3 Site Description

Activities associated with the TA-16 Stockpile Area fall under Industrial Sector P, Land Transportation and Warehousing, of the 2021 MSGP.

The TA-16 Stockpile Area includes two industrial activity areas: 1) the material storage area where construction materials (sand, gravel, rock, base course, soil and clean fill) are staged, and 2) the pothole washout area where two containment basins are located to manage pothole washout water and associated sediment. The 1.2 acre TA-16 Stockpile Area is 0.9 miles east of TA-16-0969 WFO-Division Office, on the east side of K-Site Road. Activities include the following:

- Storage of trucks and heavy equipment used to transport/haul material.
- Staging of soil or clean fill prior to reuse.
- Potholing washout and culvert cleanout area.

• Storage of sand, gravel, rock, base course, and other landscaping materials related to grounds keeping, road maintenance and construction.

The area surrounding the TA-16 Stockpile Area (formerly, TA-16-280) is primarily undeveloped except for the paved K-Site Road located west of the site. Areas within the TA-16 Stockpile Area are stabilized with base course, pavement and native vegetation. The boundary of industrial activity is approximately 1.2 acres with 10 percent impervious cover. Earthen berms serve as perimeter controls to prevent offsite sediment migration from the material storage area. Bermed catchment basins serve as containment controls for the potholing staging area. Monitored outfall 078 is located on the northwest corner of the site on the spillway for the earthen berm perimeter control. There are no substantially identical outfalls for this facility.

1.4 General Location Map

A general location map for the facility can be found in Figure A. Figure B-1 contains the site map. Figure B-2 identifies nearby receiving waters associated with stormwater discharges from the facility. 100% percent of the site flows to Canon de Valle. The canyon at this location is an ephemeral stream and eventually flows to the Rio Grande approximately nine and a half miles southeast of the site.

1.5 Site Map

The site map provided as Figure B-1 illustrates the facility's activities including the facility boundary, structures, impervious surfaces, industrial activity areas, spills, operational areas, and drainage patterns, stormwater controls, monitoring locations, outfalls and direction of the receiving stream.

As required by the 2021 MSGP, the following information specific to the facility is either shown on the site map or provided elsewhere in this SWPPP.

- Site boundary and acreage. The site covers approximately 1.2 acres.
- Significant structures and impervious surfaces. The site is 10 percent impervious (pavement).
- Direction of stormwater flow and site drainage. Direction of flow is indicated with arrows. Areas have been regraded to ensure stormwater flows are directed from the stockpile area toward monitored outfall 078 and the perimeter berm located along the northwest perimeter of the site. The containment basins in the pothole washout area promotes infiltration and prevent discharge of sediments to the surrounding area. The earthen berm located southeast of the stockpile area acts to manage run-on from the slope to the south and manage sediments along the southern boundary of the stockpile area, next to former outfall and associated drain line [AOC 16-030(d)]. Run-on from K-Site Road is managed by a vegetated swale that directs flows to the north, along the western boundary of the site.
- Locations of stormwater control measures. The earthen berm located along the northwestern perimeter of the stockpile area manages runoff and acts to prevent offsite sediment migration. The earthen berm located southeast of the stockpile area acts to manage run-on from the slope to the south and manage sediments along the southern boundary of the stockpile area. The containment basins located in the pothole washout area along the southern boundary of industrial activity, manage sediments and pothole washout water. Run-on from K-Site Road is managed by a vegetated swale that directs flows to the north, along the western boundary of the site.

- Locations of all receiving waters. The site discharges to a tributary of Canon de Valle which is impaired for Adjusted Gross Alpha. TMDLs for the receiving waters are not established and wetlands are not present. A map of nearby receiving waters is provided as Figure B-2.
- Locations of all stormwater conveyances. This includes all ditches, pipes, and swales.
- Locations of potential pollutant sources.
- Locations of significant spills or leaks.
- Locations of all stormwater monitoring points.
- Locations of stormwater inlets and outfalls Monitoring is conducted via automated sampler MSGP07801 at monitored outfall 078 (northwest corner of the boundary of industrial activity, north of earthen berm #1600103010001). There are no substantially identical discharge points (SIDPs) associated with this site.
- This facility is currently not associated with a municipal separate storm sewer system (MS4).
- Areas of designated critical habitat for endangered or threatened species. There are no areas in the direct vicinity of the facility. However, a map for threatened and endangered species within LANL property is included as Figure B-3.
- Locations of the following activities where such activities are exposed to precipitation:
 - Material Storage Area (storage and loading/unloading of sand, gravel, rock, base course, related to road maintenance and construction and storage of trucks and heavy equipment used to transport/haul material);
 - Pothole Staging Area (loading/unloading of pothole washout water and culvert cleanout water into the containment basins); and
 - Immediate access roads (used or traveled by carriers of raw materials and pothole washout culvert cleanout water).

2.0 POTENTIAL POLLUTANT SOURCES

Industrial activities that could potentially result in releases to the environment are summarized in Section 2.1 below. The site map for the facility is provided in Figure B-1.

2.1 Potential Pollutants Associated with Industrial Activity

Storage of Trucks and Heavy Equipment for Material Loading and Unloading

Potential pollutants for this activity include spills of fuel, oil, grease, fluids (transmission and hydraulic), and anti-freeze and associated heavy metals. Perimeter berms are installed in strategic locations to contain spills in the event a leak involving a potential pollutant occurs.

Material Loading/Unloading Operations

Front-end loaders are used to load and unload sand, soil, clean fill, base course and rock in the material storage area. Dust is a potential pollutant of concern from this operation and is controlled, as needed, by wetting the materials with a water truck. Other potential pollutants of concern from this equipment include leaks and spills (i.e. hydraulic fluids or diesel fuel) from loading and unloading trucks. On site containment berms and spill response protocol ensure all spills are managed appropriately.

Raw Material Storage Area

The potential pollutant associated with this activity is offsite migration of sediment. Perimeter berms are installed in strategic locations to manage stormwater runoff and prevent sediment migration.

Pothole Staging Area

Potholing washout and culvert cleanout water is screened to verify it is from area free from contamination. The potential pollutant is offsite migration of sediment. One primary containment basin and a reserve containment basin function to contain, infiltrate, and evaporate pothole washout and culvert cleanout water. Sediments are removed as needed to ensure the catchments have adequate capacity to manage pothole washout and culvert cleanout water. Other potential pollutants include leaks or spills of fuel, oil, grease, fluids (transmission and hydraulic), anti-freeze and associated heavy metals from heavy equipment performing work in the area. In the event a leak is identified, LANL spill response protocol is followed (i.e., on-site spill response kit and notifications) as specified in Section 3.1.4.

Clean Fill Material

Clean fill is defined in the LANL policy "Excavation/Fill/Soil Disturbance," Policy Number P-101-17, as uncontaminated, non-water-soluble, non-decomposable inert solid material. Fill material (concrete and/or asphalt from LANL decontamination and decommissioning efforts or other projects) or soil used as fill material at LANL must be demonstrated to be free of contamination, must not be placed in a watercourse, and must not create a public nuisance or impact the environment.

Clean fill used in accordance with P101-17 is not managed as waste and therefore, not subject to waste management regulations. The use of clean fill includes the transportation, processing, storage, management and reuse.

Environmental due diligence is performed to determine whether material can be managed as clean fill, or will be managed as waste in accordance with applicable waste management regulations. If any of the following indicators are present, the material may contain potential pollutants.

- Operations conducted at the location of origin that may have resulted in contamination of the fill material or soil [e.g., operations within the High Explosives corridor, within an open detonation blast radius, beryllium contamination area, area potentially contaminated with depleted uranium, or soil taken from outside of Phermex, or potential release sites (also known as Consent Order Site)];
- Visual examination identifies signs of staining;
- Material removed from potentially radioactively-contaminated areas; or
- Unusual odors or other indicators of contamination are detected.

If there is a possibility that the material may contain potential pollutants, contact the Sample Management Office (SMO) at <u>Sample_Managment@lanl.gov</u> and request assistance with sampling and analysis of the material.

If the following occurs, the material is appropriate for acceptance at the TA-16 Stockpile Area and may be reused within WFO-FOD as clean fill.

- Evaluation of the material is approved per Attachment 26.
- If potential pollutants may be present in the material, representative samples will be collected and analyzed for all potential pollutants. If none are present in the material or are present at or below background concentrations.

If it is determined that the material is contaminated, it will be managed as waste in accordance with applicable waste management regulations and P-409. Contact the assigned Waste Management Coordinator for assistance.

NOTE: Clean fill does not include decomposable material such as land clearing wood and other materials.

If a project requires fill or material transfer, and the original Excavation Permit (EXID) does not include it in the scope of work, a separated EXID must be requested. Prior to transfer of material to the TA-16 Stockpile Area, obtain concurrence from the FOD/designee (at the receiving location) in the form of written approval on an EXID. Material moving from any TA within WFO FOD other than TA-16 will require approval on the EXID. Prior to releasing fill material or soil for use outside of the LANL facility boundary, the Project Coordinator, PIC, or FOD/designee will submit to Environmental Protection Division, Waste Management Programs Group (667-6259) documentation establishing that the material or soil is not contaminated and obtain approval or submit a Waste Steam Profile for approval prior to off-site disposition of this material.

Do not abandon excavated material, debris or equipment onsite at LANL because doing so is considered mismanagement and abandonment of waste.

Other Potential Pollutant Sources

The following two areas Solid Waste Management Unit (SWMU) or Consent Order Site 16-003(h) and Area of Concern (AOC) 16-030(d) are located within the boundary of industrial activity for the TA-16 Stockpile Area. Earthen berm (#1600103010002) located south of the stockpile area manages sediment and runoff from the southern portion of the site. Therefore, it is unlikely that SWMU 16-003(h) and AOC 16-030(d) would be impacted by stormwater runoff generated from the site.

 16-030(d) – Former NPDES-permitted outfall [Environmental Protection Agency (EPA) 05A061] and associated drain line formerly connected to (HE) sump 16-003(h). Decision-level data for SWMU 16-030(d) consists of results from 11 samples collected at 7 locations in 1995 at and down gradient of the AOC 16-030(d) outfall. The 2006 investigation work plan concluded the nature and extent of contamination have not been defined and additional sampling is recommended. Human health and ecological risk assessments have not been conducted since the nature and extent of contamination have not been defined. All detected inorganic chemical concentrations are below residential soil screening levels (SSLs) except chromium, which was detected above the residential SSL in one sample. Numerous organic chemicals were detected in the 1995 samples; nine SVOCs [(polycyclic aromatic hydrocarbons (PAHs)] were detected at concentrations above residential and construction worker SSLs. 16-003(h) – Inactive high explosive (HE) sump. Decision-level data for SWMU 16-003(h) consists of results from 11 samples collected at 7 locations in 1995 at the site and down gradient of the AOC 16-030(d) outfall. The 2006 investigation work plan concluded the nature and extent of contamination have not been defined and additional sampling is recommended. Human health and ecological risk assessments have not been conducted since the nature and extent of contamination have not been defined. All detected inorganic chemical concentrations are below residential SSLs except chromium, which was detected above the residential SSL in one sample. Numerous organic chemicals were detected in the 1995 samples; nine SVOCs (PAHs) were detected at concentrations above residential and construction worker SSLs.

2.2 Spill and Leaks

No spills or leaks have occurred at this location to date. Therefore, there is no information contained in Table 1A below.

Date	Description	Outfall(s) Affected
2021	No spills have occu	rred

Table 1A: Spill and Leak History

Table 1B: – Areas Where Spills/Leaks Could Occur

Specific Equipment/Industrial Activity Areas and Location	Outfall Affected
Material Storage Area	078
Pothole Washout Area	N/A

In the event of any future spill or leak at any of the facility areas, a spill report, documenting the occurrence and the nature of the spill or leak, will be completed. The spill report will be filed promptly upon completion and documentation of the spill clean-up, and will be summarized in this section of the SWPPP (see Table 1A above). In addition, spills within MSGP facility boundaries will be entered as conditions requiring corrective action in the MSGP CAR database and will be updated as corrective action occurs, in accordance with EPC-CP-QP-022, *MSGP Corrective Actions*.

The probability of spills or releases at the facility is minimized by the application of good housekeeping procedures and appropriate operational methods. Appropriate response measures for a spill or release of hazardous materials are applied when addressing spills. The specific spill response and cleanup process depends on the nature of the spilled material. Specific spill response and reporting procedures for LANL are listed in Section 3.1.4.

2.3 Unauthorized Non-Stormwater Discharges

NPDES non-stormwater discharges, unpermitted outfalls, or unauthorized discharges associated with the facility are not anticipated. There are no potential sources of non-stormwater discharges (e.g., testing of fire hydrants) identified at the site. The "Certification of No Unauthorized Stormwater Discharges" is located in Attachment 3. This form certifies that the facility and stormwater outfall has been evaluated for the presence of non-stormwater discharges. This form is updated whenever a change in possible non-stormwater discharges is determined.

2.4 Salt Storage

No salt storage or piles that contain salt are present at the facility.

2.5 Historical Data Summary

CY 2020 and CY 2021

Outfall 078 at the TA-16 Stockpile Area did not flow during 2020 or 2021. Therefore, there is no historical data to summarize. It was not operational prior to that time.

3.0 STORMWATER CONTROL MEASURES

Control measures at the facility are designed to minimize the potential release of pollutants that could adversely affect water quality. Perimeter sediment controls for material storage consist of earthen berms installed along the northwest and southern portions of the industrial activity area. These berms are strategically located to intercept runoff from the stockpiles and manage sediment and other potential pollutants from potential spills generated from heavy equipment or trucks used to transport, load and unload material. The run-on control at the material storage area consists of a vegetated swale located east of K-Site Road which functions to intercept sheet flow from the paved surface and convey flow to the north, away from the material storage area. Erosion controls for the material storage area include existing vegetation, base course, and pavement that function as stabilization for all surfaces impacted by the TA-16 Stockpile Area activities. Two catchment basins located in the pothole washout area located on the southern perimeter of the industrial activity boundary function to contain, infiltrate and promote evaporation for pothole washout and culvert cleanout water.

3.1 Non-Numeric Technology-Based Effluent Limits

Specific non-numeric technology-based effluent limits for Sector P are identified below.

Good Housekeeping

Refer to Section 3.1.2 below. None of the following occur at this facility.

- Fueling;
- Vehicle and equipment cleaning; or
- Vehicle or equipment maintenance.

Vehicle and Equipment Storage Area

• Only well maintained vehicles and heavy equipment are stored at the TA-60 Stockpile Area. Drip pans are placed under any vehicle/heavy equipment found to be leaking and it is then sent off for maintenance. Any identified spills or leaks are managed in accordance with Section 3.1.4.

Material Storage Area

• Gravel, rock, base course, sand, soil and clean fill are transported, unloaded, staged and loaded in this area. Heavy equipment and trucks are used to facilitate this operation.

Potholing Staging Area

• This area consists of two catchments used to place pothole washout materials. These catchments function to infiltrate and facilitate the evaporation of the pothole washout water. Sediments are removed once the catchments are filled to seventy-five percent capacity. Heavy equipment and trucks are used to facilitate this operation. Sections 3.1.5 and 3.1.6 describe how non-numeric limits area met.

Non-numeric technology-based effluent limits for all industrial sectors are identified in the following subsections.

3.1.1 Minimize Exposure

Control measures at the facility are designed to minimize the potential for spills, releases, exposure of materials, or any other events that could adversely affect the quality of water and sediment that may be transported out of the area by stormwater runoff. Section 3.0 "Stormwater Control Measures" identifies the structural controls specific to the two industrial activity areas at the facility. Spill response to leaks from heavy equipment or vehicles used to transport and load/unload material is described in Section 3.1.4, *Spill Prevention and Response*.

3.1.2 Good Housekeeping

Good housekeeping practices specifically applicable to the prevention of stormwater contamination include the following measures:

- Sweep or vacuum at regular intervals or, alternatively, wash down the area and collect and/or treat, and properly dispose of the wash-down water.
- All site areas are walked down during daily operations and quarterly routine facility inspections to ensure that the grounds are kept in an orderly condition. The entire site, including loading/unloading areas, the potholing staging area, and the outfall, are inspected for floatable debris, garbage, waste and all other potential pollutants.
- During loading and unloading operations at the material storage area, all vehicles and equipment are confined to the designated boundary of industrial activity to prevent impact to existing vegetation at the site. Stockpiles are managed by the perimeter earthen berms in order to minimize the potential for off-site sediment migration. Base course stabilization is maintained at all times to minimize the potential for tracking onto K-Site Road. If tracking is observed, sweeping will be performed by close of business that day.
- The potholing staging area catchments are inspected during daily operations and quarterly routine facility inspections to determine whether adequate capacity is available to prevent overflow conditions in the event of a precipitation event. Twenty-five percent of the total catchment capacity will be available at all times to accommodate precipitation and prevent inadvertent discharge of pothole or culvert cleanout water. Inspections are conducted when the catchments are dry to assess sediment accumulation and to determine if sediment removal is required. Base course stabilization along the surfaces of the access road to the catchments is maintained at all times to minimize the potential for tracking onto K-Site Road. If tracking is observed, sweeping will be performed by close of business that day.
- Trucks and heavy equipment used to transport, load, and unload material staged at the material storage area are properly maintained to minimize the potential for leaks. During daily operations and quarterly, inspections are conducted to check for spills or leaks and the facility procedure (WFO-IWD-0016, *Spill Response and Clean Up in Weapons Facilities Operations (WFO) Areas)* is followed if a leak is discovered. Heavy equipment repair and maintenance is never performed at this site.
- Garbage and floatables are routinely picked up by facility personnel. Garbage containers are not staged at this site.

3.1.3 Maintenance

Control measures at the facility are kept in effective operating condition by the implementation of scheduled preventive maintenance, standard operating procedures (SOPs), and engineering guidance. If control measures need to be replaced or repaired to maintain compliance with the 2021 MSGP, corrective action is taken in accordance with the timelines specified in the *Corrective Action and Deadlines* requirements in Section 6.0 of this SWPPP.

Deficient items identified during routine facility inspections, walk-downs, or by any other means of identification, are documented on the routine facility inspection forms and entered into the MSGP CAR database. All reasonable steps are taken immediately to address any identified condition requiring corrective action. The condition requiring corrective action will remain open until proper maintenance or corrective action has been completed. CAR information, along with documentation of maintenance/repair of control measures, is in Attachment 9 of the SWPPP.

NOTE: "All reasonable steps" means that the permittee has responded to the condition(s) triggering the action, such as, cleaning up any exposed material that may be discharged in a storm event (e.g., through sweeping, vacuuming) or making arrangements (i.e., scheduling) for a new stormwater control measure (SCM) to be installed."

Trucks and heavy equipment used to transport, load, and unload material staged at the material storage area are properly maintained to minimize the potential for leaks. During daily operations and quarterly, inspections are conducted to check for leaks and the facility procedure is followed if a leak is discovered.

The pothole washout area catchments are inspected during daily operations and quarterly routine facility inspections to check for adequate capacity to prevent overflow conditions in the event of a precipitation event. Twenty-five percent of the total catchment capacity will be available at times to accommodate precipitation and prevent inadvertent discharge of pothole or culvert cleanout water. Routine facility inspections are conducted when the catchments are dry to assess sediment accumulation and to determine if sediment removal is required. If sediments/solids/ are removed they are managed, characterized, and disposed of in accordance with the applicable LANL waste management policies and procedures, unless the material can be demonstrated to be free of contamination. If the sediments/solids are free of contamination and other trash, the material may be used as clean fill at WFO FOD (see Section 2.1 and Attachment 26 for additional information regarding the management of clean fill material.

Earthen berms located around the perimeter of the material storage area are inspected during daily operations and quarterly routine facility inspections.

3.1.4 Spill Prevention and Response

Spills, leaks, or other releases are minimized and/or prevented by maintaining heavy equipment and trucks, staged at the material storage area, on a regular basis and inspecting for leaks daily during operations and quarterly during routine facility inspections. The approach to spill cleanup within WFO is provided in Attachment 24. This procedure is for cleanup of spills deemed a non-emergency (or identified as simple spills) by Emergency Management Division-Emergency Response (EMD-ER) and EPC-CP. Spills are categorized as either simple spills or complex spills. Simple spills are defined as ones that do not spread rapidly, do not endanger people or property (except by direct contact), do not endanger

the environment, and do not involve fire or an explosive condition or the potential for such. All other spills are identified as complex spills and require assistance from the Emergency Operations Support Center (EOSC). Simple spills are cleaned up by knowledgeable chemical workers (workers with knowledge of the chemical, appropriate training, material and PPE needed to clean the spill). For incidental releases, Micro-Blaze[®] or dry absorbents can be used and spill clean-up materials are containerized and managed as waste.

All complex/emergency spills or releases are reported to the EOSC by calling 667-2400 and the Facility Duty Officer by dialing pager number 664-2926 and 664-4100 for RCT support (if needed). All spills or releases are reported to EPC-CP by using the spills pager (505) 664-7722. If fire or explosion is present, or if the potential for such exists, the situation is reported by dialing 911 from a non-cellular phone or by activating a fire pull box. In the event of a spill, EMD-ER will coordinate appropriate cleanup procedures and EPC-CP will notify the individuals or organizations responsible for completing spill reports and providing information needed to fulfill regulatory reporting requirements.

Unauthorized releases or discharges within industrial facility boundaries are entered into the MSGP CAR database in accordance with EPC-CP-QP-022, *MSGP Corrective Actions*. In addition, the completion of an Unplanned Release Report is required in the event of a spill. The report is submitted to EPC-CP personnel and handled according to internal spill record keeping procedures. Spills may be "reportable" (requiring external agency notification) depending on the nature of the spilled material and the location of the release. External agency notification may consist of verbal and/or written notification to the National Response Center, Environmental Protection Agency Region VI, or the New Mexico Environment Department (NMED). EMD-ER, the FOD and EPC-CP, in accordance with Laboratory and DOE policies and federal and state regulatory reporting requirements, will make the determination for the type of reporting required. EPC-DO-QP-101, *Environmental Reporting Requirements for Releases or Events* is used for this purpose (see Attachment 21).

Copies of internal spill reports are maintained by the responsible organization and in the EPC-CP database. The EPC-CP procedure for spill reporting and response, ENV-CP-QP-007, *Spill Investigations*, can be found in Attachment 22 of this SWPPP.

3.1.5 Erosion and Sediment Control

Erosion at the site will be controlled through the preservation of existing native vegetation and the installation and maintenance of base course stabilization along access areas and material storage areas where stockpiles are staged. Sediment control perimeter berms and pothole washout and culvert cleanout catchments function to retain sediments and prevent offsite sediment migration.

3.1.6 Management of Runoff

Runoff from the site is minimized through preservation of existing vegetation and stabilization measures involving impervious material such as base course. Run-on is minimal at the site as all flows generated from K-Site Road are captured by the vegetated swale located along the western perimeter of the industrial activity boundary. Runoff is managed by perimeter berms located on the southern and northwestern perimeters of the site.

3.1.7 Salt Storage Piles or Piles Containing Salt

No salt storage or piles containing salt are present at the facility.

3.1.8 Dust Generation and Vehicle Tracking of industrial Materials

Dust generation and vehicle tracking are controlled with pavement/base course stabilization, street sweeping and or dust suppression with potable water.

3.2 Numeric Effluent Limitations Based on Effluent Limitations Guidelines

This facility does not meet the industrial category requirements for effluent monitoring as listed in Part 2.1.3 (*Table 2-1 Applicable Effluent Limitation Guidelines*) of the 2021 MSGP. Benchmark monitoring not required.

Part 8 of the 2021 MSGP identifies sector-specific requirements for Sector P – Land Transportation and Warehousing, in addition to the numeric limits outlined in this section. The facility must comply with requirements associated with the primary industrial activities described in Section 1.3 and any co-located industrial activities as defined in Appendix A of the 2021 MSGP. Sector-specific requirements apply only to areas where sector-specific activities occur.

3.3 Water Quality-Based Effluent Limitations and Water Quality Standards

Impaired Receiving Waters/No TMDLs

Impaired waters monitoring is performed annually at the facility as listed in Section 4.7 of this SWPPP. The pollutants monitored can change yearly based on the requirements of the MSGP. The table in Section 4.7 lists the current year monitoring requirements and standards.

Stormwater from the TA-16 Stockpile Area discharges to Assessment Unit NM-126.A_01, Canon de Valle (within LANL) Below LANL Gage E256. This reach of Canon de Valle has been identified as an impaired water for Adjusted Gross Alpha by the NMED Surface Water Quality Bureau (SWQB) per the 2018-2020 State of NM Clean Water Act 303b/305b Integrated Report and Final List. EPA has not yet approved or established TMDLs for Canon de Valle. Sections 3.1.5 and 3.1.6 describe controls measures used to ensure discharges from industrial activities meet the water quality standards. Refer to Section 4.7 for specific actions that will be taken when a water quality standard is exceeded.

4.0 SCHEDULES AND PROCEDURES

Preventative maintenance of control measures used to comply with non-numeric effluent limits can avoid situations that result in discharges to the environment. Part 5.2.5 of the 2021 MSGP specifies control measures will have a schedule or frequency for maintenance and procedures specifying how maintenance is conducted. Part 5.5 requires documentation of maintenance and repairs including the date(s) of regular maintenance. See Attachment 10 for the Scheduled Maintenance Log.

4.1 Good Housekeeping

See Section 3.1.2 of this SWPPP.

4.2 Maintenance

See Section 3.1.3 of this SWPPP.

4.3 Spill Prevention and Response

See Section 3.1.4 of this SWPPP. All referenced procedures are provided in Attachments 21 and 22 of this SWPPP.

4.4 Erosion and Sediment Control

See Section 3.1.5 of this SWPPP.

4.5 Employee Training

Employee training is essential for effective implementation of the SWPPP and MSGP requirements. The goals for the training program are to ensure that employees: (1) are aware of what happens when pollutants come in contact with stormwater; (2) are familiar with and will implement the requirements of this SWPPP; (3) are capable of preventing spills; (4) respond safely and effectively to an accident when one occurs; (5) recognize when there is an issue with a control measure; (6) recognize when additional control measures are necessary; and (7) identify situations that could lead to stormwater contamination.

Per Part 2.1.2.8 of the 2021 MSGP, training relevant to the SWPPP and MSGP is required for all workers at the facility that work in areas where industrial materials or activities are exposed to stormwater (MSGP sites); workers, managers, and supervisors who are responsible for implementing activities necessary to meet the conditions of this permit (e.g., inspectors, maintenance personnel); and all members of the PPT. Training is designed to ensure these personnel understand the MSGP and SWPPP requirements, as well as their specific responsibilities regarding these requirements.

Training provided and assigned to these personnel cover both the specific control measures used at the facility; along with monitoring, inspection, planning, reporting, and documentation requirements described in this SWPPP. Training will be conducted at least annually. The DEP, Deployed Environment Safety and Health (DESH) Group Leader and PPT members are responsible for ensuring all appropriate personnel receive this training.

Training activities are documented in accordance with LANL's Training Standards. In cases where training is formalized enough to require specific curricula and reoccurrence, the training activity will be recorded in LANL's official U-TRAIN database. Informal briefings, such as those included in-group safety meetings are not typically recorded in U-TRAIN. Sign-in sheets are used to document attendance and are considered official use only (OUO). All training records are managed in accordance with P204-1, *Controlled Unclassified Information*. Information on employees receiving training is available upon request.

The topics in this SWPPP that are covered in the latest version of the facility-specific annual MSGP training (see Attachment 11) include the following:

- Overview of the SWPPP contents;
- Spill response and cleanup procedures, good housekeeping, maintenance requirements, and material management practices to prevent stormwater pollution;
- The location of all controls on the site required by this permit and how they are maintained;
- The proper procedures to follow with respect to the permit's pollution prevention requirements; and
- When and how to conduct inspections, record applicable findings, and take corrective actions.

4.6 Routine Facility Inspections and Quarterly Visual Assessments

Routine inspections at this facility are conducted and documented quarterly in accordance with EPC-CP-QP-023, *MSGP Routine Facility Inspections* (Attachment 16).

Visual assessments are conducted in accordance with EPC-CP-QP-064, *MSGP Stormwater Visual Assessments* (Attachment 18).

4.6.1 Routine Facility Inspections

At least once each calendar year, the routine facility inspection is conducted during a period when a stormwater discharge is occurring. A qualified member of the PPT (typically the DEP, a representative from the EPC-CP Storm Water Permitting/Compliance Team or EPC-CP Program Lead) performs the inspection. The 2021 MSGP consolidates the different and separate documentation requirements in the Comprehensive Site Inspection Procedures and Routine Facility Inspection Procedures from the 2008 MSGP. EPC-CP will perform at least one routine facility inspection per year.

Routine inspections will evaluate the following areas, at a minimum:

- Areas where industrial materials or activities are exposed to stormwater;
- Areas identified in the SWPPP and those that are potential pollutant sources;
- Areas where spills and leaks have occurred in the last three years;
- Discharge points(outfalls/ SIDPs; and
- Control measures used to comply with the effluent limits contained in this permit.

Specific areas of the facility to be inspected are described in Section 2.1. During routine inspections, the following must be evaluated:

- Industrial materials, residue or trash that may have or could come into contact with stormwater;
- Leaks or spills from industrial equipment, drums, tanks and other containers;
- Offsite tracking of industrial or waste materials, or sediment where vehicles enter or exit the site;
- Tracking or blowing of raw, final or waste materials from areas of no exposure to exposed areas; and
- Control measures needing maintenance, repairs or replacement.

Inspections performed by the PPT member are documented by completing the routine facility inspection form, which identifies all conditions requiring corrective action and other potential stormwater pollution issues that were encountered. All conditions requiring corrective actions identified during the inspection

are addressed in accordance with Section 6.0 *Corrective Actions and Deadlines* of this plan. Facility personnel or the DEP may also perform daily, weekly, or other periodic facility surveys (walk downs) between quarterly routine facility inspections to ensure compliance with the SWPPP and MSGP. Completed routine facility inspection forms are provided in Attachment 7 of this SWPPP and meet the requirements listed in the 2021 MSGP (Part 3.1.2.).

4.6.2 Quarterly Visual Assessments

Once each quarter, (January-March, April-June, July-September, October-December) a stormwater sample is obtained and visual assessment performed at each outfall, if a measureable storm event occurred. A qualified member of the PPT (DEP, EPC-CP Storm Water Permitting/Compliance team member or MSGP Program Lead) conducts the visual assessment. The visual assessment will be:

- Of a sample in a clean, clear colorless glass or plastic container and examined in a well-lit area;
- On samples collected within the first 30 minutes of an actual discharge from a storm event or as soon as practicable thereafter. Alternatively, document why it was not possible to collect the sample within the first 30 minutes (i.e. adverse conditions, not enough flow, etc.); and
- Conducted at least 72 hours since the last storm event; or document that the 72-hour period is representative of local storm events during the sampling period.

NOTE: Snowmelt samples need only be collected during a period of measurable discharge.

The visual assessment will inspect for the following water quality characteristics: color, odor, clarity, floating solids, settled solids, suspended solids, foam, oil sheen, and other obvious indicators of stormwater pollution.

If a visual assessments is not conducted:

- Document rationale if a visual assessment is unable to be collected in a quarter (no precipitation event or adverse conditions, etc.); and
- Perform an additional assessment during the next qualifying storm event if unable to perform in a particular quarter.

Perform one quarterly assessment during snowmelt discharge (taken during a measurable discharge from the site).

For facilities with SIDPs, quarterly visual assessments may be performed at only one of the outfalls, provided that you perform visual inspections on a rotating basis at each SIDP.

The PPT member performing the visual assessment documents potential stormwater pollution problems that were observed during the assessment on the quarterly visual assessment form. Any conditions requiring corrective action identified during the assessment is addressed in accordance with Section 6.0 *Corrective Actions and Deadlines* of this plan. Completed quarterly visual assessments are provided in Attachment 8 of this SWPPP and meet the requirements listed in the 2021 MSGP (Part 3.2.2).

4.7 Monitoring

Analytical monitoring comprised of Impaired Waters monitoring is performed annually on stormwater discharges from the site. Pre- and polyfluoroalkyl substance (PFAS) monitoring will occur annually unless it is not detected or is detected below the PFAS screening level for New Mexico. If either of these scenarios occur, PFAS monitoring will cease. Indicator parameters are monitored quarterly. Monitoring occurs when storm events result in an actual discharge from the site and follow the preceding measurable storm event by at least 72 hours (3 days), unless documented that the storm event is representative of local storm events during the sampling period. For runoff from snowmelt, the monitoring is performed at a time when a measurable discharge from the site occurs.

Monitoring is conducted according to test procedures approved under 40 CFR Part 136. Runoff samples are collected by taking a minimum of one grab sample from a discharge, collected within the first 30 minutes of a measurable storm event. If it is not possible to collect the sample within the first 30 minutes of a measurable storm event, the sample is collected as soon as practicable after the first 30 minutes and documentation is kept with the SWPPP explaining why it was not possible.

LANL is located in a high elevation, semi-arid climate where the majority of rainfall occurs during a period between July and September. Freezing conditions that would prevent runoff from occurring for extended periods may also occur during the winter months. If adverse weather conditions prevent the collection of a sample according to the relevant monitoring schedule, a sample will be collected during the next qualifying storm event or as soon as practicable.

Monitoring occurs at automated sampling station **MSGP07801** as identified in Section 1.4. Discharge from the facility is east to Canon de Valle (impaired waters), which is a tributary of the Rio Grande located approximately two miles east of the facility.

For impaired waters pollutants, monitoring is required annually in the first and fourth year of permit coverage. If any pollutant associated with the impairment is detected, annual monitoring will continue. If the impaired water constituent value exceeds the New Mexico Water Quality criterion, the Pollution Prevention Team will:

- Review the selection, design, installation, and implementation of control measures to determine if modifications are necessary to meet the effluent limits;
- Implement the necessary modifications within the timeframe specified for corrective action; and
- Continue annual monitoring of the constituent (as required by Part 4.2.5 of the 2021 MSGP).

For each monitoring event, except snowmelt monitoring, the following information is recorded and maintained through work orders, LANL database systems, and Discharge Monitoring Records:

- The date, exact place, and time of sampling or measurements;
- The date and duration (in hours) of the rainfall event;
- Rainfall total (in inches) for that rainfall event;
- The individual(s) who performed the sampling or measurements;
- The date(s) analyses were performed;
- The individual(s) who performed the analyses;
- The analytical techniques or methods used; and

• The results of such analyses.

All records of monitoring information, including all calibration and maintenance records are maintained for a minimum period of at least three years from the date the permit expires.

LANL's applicable stormwater monitoring procedures can be found in the following Attachments:

- EPC-CP-QP-2103, Inspecting ISCO Stormwater Runoff Samplers and Retrieving Samples (Attachment 19)
- EPC-CP-QP-048, Processing MSGP Stormwater Samples (Attachment 20).

The table on the following page lists the current Summary of Monitoring Requirements. The monitoring values have been modified to reflect New Mexico water quality standards and are based on the most protective water quality standards from the Standards for Interstate and Intrastate Surface Waters (effective on February 28, 2018), 20.6.4.900 NMAC; and as set forth in Part 9.6.2.2 of the 2021 MSGP.

Outfall: 078

Monitoring Requirement	Industrial Sector	Assessment Unit	Analyte	Filtered/ Unfiltere d	Regulatory Standard	Units	Regulatory Standard Type	Regulatory Standard Reference
Impaired Waters	-	NM- 128.A_01	Adjusted Gross Alpha	UF	15	pCi/L	NM 2010 Livestock Watering	20.6.4.900 NMAC Subpart J
Indicator Parameters	Р	COD, TSS, and pH						
Quarterly Benchmark	Р	No Benchmark Monitoring Required						

NM=New Mexico

UF=Unfiltered

pCi=Picocurie

L=Liter

NMAC=New Mexico Administrative Code

COD=Chemical Oxygen Demand

TSS=Total Suspended Solids

5.0 DOCUMENTATION FOR ELIGIBILITY CONSIDERATIONS UNDER OTHER FEDERAL LAWS

5.1 Endangered Species

The Final Site-Wide Environmental Impact Statement (EIS) for the Operation of Los Alamos National Laboratory (DOE/EIS-0380) was issued in May 2008, and a Record of Decision in September 2008. Stormwater issues and associated pollution prevention requirements and activities at LANL are analyzed in Chapters 4 and 5 of the 2008 Site-Wide EIS. These activities are integrated into environmental reviews on a project-specific level through LANL's Integrated Review Tool (IRT), which incorporates both the Excavation Permit (EX-ID) and Permit Requirements Identification (PR-ID) process. Stormwater issues are identified and pollution prevention activities are implemented during the design and construction phases of all LANL projects, and as part of facility operations, including routine maintenance. LANL staff monitors stormwater pollution prevention compliance at MSGP sites in accordance with Section 4.7 *Monitoring* of this plan. Corrective actions are taken as necessary as described in Section 6.0 *Corrective Actions and Deadlines* of this plan.

Part2.3 of the 2021 MSGP requires areas of designated critical habitat for endangered or threatened species, as applicable, be included in the SWPPP. The *Threatened and Endangered Species Habitat Management Plan for Los Alamos National Laboratory* (LA-UR-17-29454) was last updated in October 2017 (see Attachment 13). This document provides a management strategy for the protection of threatened and endangered species and their habitats on LANL property. The MSGP IPaC Trust Resource Report (see Attachment 14) is also attached for informational purposes.

5.2 Historic Properties

In April 2021, August, 2015, and December 2008, the Cultural Resources Team (using Global Positioning System spatial data as well as conducting visual inspections), reviewed the Laboratory industrial sites (see list below) and their associated outfalls and monitoring stations subject to the 2021 Multi-Sector General Permit (Permit #NMR050000) for effects on historic properties. All of these sites were found to be undertakings of no effect and in compliance with Section 106 of the National Historic Preservation Act (i.e., Criterion B).

- TA-09-0214 Metals Fabrication Shop
- TA-3-38 Metal Fabrication Shop
- TA-16 Stockpile Area
- TA-60 Asphalt Batch Plant
- TA-60-1 Heavy Equipment Yard
- TA-60 Material Recycle Facility
- TA-60 Roads and Grounds
- TA-60-2 Warehouse

6.0 CORRECTIVE ACTIONS AND DEADLINES

When any of the following conditions occur or are detected during an inspection, Level 1, 2, or 3 additional implementation measures (AIM) monitoring or any other means, this SWPPP (e.g., sources of pollution; spill and leak procedures; non-stormwater discharges; the selection, design, installation and implementation of control measures) is reviewed and revised (as appropriate).

- An unauthorized release or discharge (e.g., spill, leak, or discharge of non-stormwater not authorized by this or another NPDES permit to a water of the U.S.) occurs at the facility;
- A discharge violates a numeric effluent limit;
- Stormwater control measures are not stringent enough for stormwater discharge to be controlled as necessary such that the receiving water of the United States will meet applicable water quality standards or to meet the non-numeric effluent limits in the permit;
- An inspection identifies that a required control measure was never installed, was installed incorrectly or is not being properly operated or maintained; or
- Whenever a visual assessment shows evidence of stormwater pollution.

The purpose is to ensure effluent limits of the 2021 MSGP permit are met and pollutant discharges are minimized.

When any of the following conditions occur, a review of the selection, design, installation, and implementation of control measures is performed to determine if modifications are necessary to meet the effluent limits in this permit:

- Construction or a change in design, operation, or maintenance at the facility significantly changes the nature of pollutants discharged in stormwater from the facility, or significantly increases the quantity of pollutants discharged; or
- If an impaired water constituent exceeds the NM Water Quality criterion (see Section 4.7).

If any of the AIM triggering events (i.e., an annual average exceeds an applicable benchmark threshold) in Parts 5.2.3, 5.2.4, or 5.2.5 occur, PPT members must follow the response procedures described in those parts. An annual average exceedance for a benchmark parameter can occur if:

1) The four-quarter annual average for a parameter exceeds the benchmark threshold, or

2) Fewer than four quarterly samples are collected, but a single sample or the sum of any sample results within the sampling year exceeds the benchmark threshold by more than four times for a parameter.

There are three AIM levels: AIM Level 1, Level 2, and Level 3. PPT members must respond, as required, to different AIM levels which prescribe sequential and increasingly robust responses when a benchmark exceedance occurs. The corresponding AIM level responses and deadlines described in Parts 5.2.3.1, 5.2.3.2, 5.2.4.1, 5.2.4.2, 5.2.5.1 and 5.2.5.2 must be followed unless the facility qualifies for an exception under Part 5.2.6."

When the review identifies the need to modify the SWPPP, it will be revised within 14 calendar days of completion of the associated condition requiring corrective action.

6.1 Immediate Actions

When a condition requiring corrective action is identified, all reasonable steps necessary to minimize or prevent the discharge of pollutants are immediately taken (i.e. spill clean-up, scheduling repairs) until a permanent solution (if needed) can be implemented. Immediate action means all reasonable steps are

taken the same workday or no later than the following workday (when it is too late in the day to take corrective action).

6.2 Subsequent Actions

When additional corrective actions are required (e.g. installing or making operational a new or modified control, completing repairs, ordering BMPs) they will be completed by the next storm event, if possible, or within 14 calendar days (from initial discovery). When it is determined that it is infeasible to complete corrective actions within 14 days, documentation of infeasibility and a schedule for completion of the work is documented in the CAR database, which will be completed no later than 45 days (from initial discovery). When it is determined that corrective actions will exceed 45 days, EPA is notified and provided justification of why actions will exceed the timeframe; and a minimal amount of additional time to complete the work may be approved.

6.3 AIM Baseline Status and Triggering Events

Once the facility is authorized to discharge under the MSGP, it is considered to be in a baseline status for all applicable benchmark parameters required by that facility to be monitored. If an AIM triggering event occurs, the facility may return directly to baseline status once the corresponding AIM-level response and conditions are met.

6.3.1 AIM Level 1

When an annual average exceeds an applicable benchmark threshold, the PPT must immediately review the MSGP SWPPP and the selection, design, installation, and implementation of stormwater control measures to ensure the effectiveness of existing measures and determine if modifications are necessary to meet the benchmark threshold for the parameter that exceeded.

NOTE: An AIM triggering event is outfall and parameter specific.

After reviewing the SWPPP, additional measures, considering good engineering practices, will be implemented, that will reasonably be expected to bring the exceedance below the parameter's benchmark threshold.

NOTE: If it is determined that nothing further is required to bring the exceedance below the parameter's benchmark threshold for the next 12-month period, document this in the MSGP CAR database.

All modifications and additional control measures required in response to AIM Level 1 will be implemented within 14 days of identification of an AIM Level 1 exceedance. If doing so within 14 days is infeasible, documentation is entered into the MSGP CAR database as to why it is infeasible. Completion of the response must occur within 45 days.

NOTE: There is no provision in the 2021 MSGP for exceeding the 45-day time frame for response to AIM Level 1.

An additional four quarters of Benchmark monitoring will occur at the outfall where the parameter exceeded the benchmark threshold for AIM Level 1. This monitoring will begin no later than the next full quarter after all responses and deadlines required by AIM Level 1 have

been completed. After four quarters of monitoring, the parameter will either return to baseline (see Section 6.3) if it does not exceed the same benchmark threshold or, another annual average exceeds the benchmark threshold causing the facility to move to AIM Level 2

6.3.2 AIM Level 2

When a second benchmark threshold exceedance occurs at an outfall, the PPT will review the SWPPP and implement additional pollution prevention/good housekeeping SCMs, (considering good engineering practices), beyond those implemented in response to AIM Level 1.

Additional control measures required in response to AIM Level 2 will be implemented within 14 days of identification of the AIM Level 2 exceedance. If it is feasible to implement a measure, but not within 14 days, facility personnel may take up to 45 days to implement the measure. In this case, documentation will be entered into the MSGP CAR database identifying why it was infeasible to implement the control measure within 14 days. EPA may grant an extension beyond 45 days, based on an appropriate demonstration by the operator.

An additional four quarters of benchmark monitoring will occur at the outfall where the parameter exceeded the benchmark threshold for AIM Level 2. This monitoring will begin no later than the next full quarter after all responses and deadlines required by AIM Level 2 have been completed. After four quarters of monitoring, the parameter will either return to baseline (see Section 6.3) if it does not exceed the same benchmark threshold or, the parameter continues to exceed the benchmark threshold causing the facility to move to AIM Level 3.

6.3.3 AIM Level 3

When a third benchmark threshold exceedance occurs at an outfall, facility personnel will install structural source controls (e.g., permanent controls such as permanent cover, berms, and secondary containment), and/or treatment controls (e.g., sand filters, hydrodynamic separators, oil-water separators, retention ponds, and infiltration structures). The controls, treatment technologies, or treatment train installed will be appropriate for the pollutant that triggered AIM Level 3, will be sufficient to bring the exceedance below the benchmark threshold and, will be more rigorous that the SCMs implemented under AIM Level 2. These controls will be installed for the outfall that exceeded the benchmark threshold and SIDPs, unless monitoring of the SIDPs demonstrates AIM Level 3 requirements are not triggered at those discharge points.

A schedule for installing the structural source and/or treatment stormwater control measures will be identified and documented in the MSGP CAR database within 14 days. Control measures in response to AIM Level 3 will be installed within 60 days unless it is not feasible to install them within 60 days. In this case, up to 90 days can be taken provided justification identifying why it is infeasible to install the measure within 60 days is documented in the MSGP CAR database. EPA may grant an extension beyond 90 days, based on an appropriate demonstration by the operator.

An additional four quarters of benchmark monitoring will occur at the outfall where the parameter exceeded the benchmark threshold for AIM Level 3. This monitoring will begin no later than the next full quarter after all responses and deadlines required by AIM Level 3 have been completed. After four quarters of monitoring, the parameter will either return to baseline (see Section 6.3) if it does not exceed the same benchmark threshold or, the facility will remain in AIM Level 3 and EPA may require the facility to apply for an individual permit.

6.3.4 AIM Exceptions

Any AIM Level exceedance may qualify for an exception from specific AIM requirements and continued benchmark monitoring after four quarters of monitoring, provided the requirements to demonstrate qualification of the exception are followed (see Parts 5.2.6.1 through 5.2.6.5 of the permit). These exceptions include the following for benchmark exceedances:

1) Solely attributable to natural background pollutant levels;

- 2) Due to run-on;
- 3) Due to an abnormal event;

4) Demonstrated to not result in an exceedance of facility-specific value using the national recommended water quality criteria in-lieu of the applicable MSGP benchmark threshold (for aluminum and copper benchmark parameters only); or

5) Demonstrated to not result in any exceedance of water quality standards.

NOTE: There are very specific and complicated documentation requirements and time frames that have to be met to qualify for any of these exceptions. Therefore, any demonstration to qualify for an exception will be coordinated through a representative of the EPC-CP Storm Water Permitting/Compliance Team.

6.4 Corrective Action and AIM Documentation

Upon discovery, conditions requiring corrective action are documented by the DEP or EPC-CP on a Routine Facility Inspection Form and/or entered into the CAR database. The action will be kept open in the database until the issue has been resolved. Documentation of maintenance and repairs of SCMs are kept in Attachment 10 of this SWPPP. Where corrective actions result in changes to procedures or controls documented in this SWPPP, modifications to the SWPPP are made accordingly within 14 calendar days of completing the corrective action(s). LANL procedure EPC-CP-QP-022, *MSGP Corrective Actions* can be found in Attachment 17.

Any AIM Level triggering event will conform to the requirements and time frames provided in Sections 6.3 and 6.3.1 through 6.3.4.

7.0 ACRONYMS

AIM	Additional Implementation Measures
BMP	Best Management Practice
CAR	Corrective Action Report
DEP	Deployed Environmental Professional
DESH	Deployed Environmental Safety and Health
DOE	Department of Energy
EIS	Environmental Impact Statement
ELG	Effluent Limitation Guidelines
EMD-ER	Emergency Management Division-Emergency Response
EOSC	Emergency Operations Support Center
EPA	Environmental Protection Agency
EPC-CP	Environmental Protection and Compliance – Compliance Programs
FOD	Facility Operations Division
IPaC	Information for Planning and Consultation
MRF	Material Recycling Facility
LANL or the Laboratory	Los Alamos National Laboratory
MSGP or Permit	Multi-Sector General Permit
NOI	Notice of Intent
NPDES	National Pollutant Discharge Elimination System
000	Official Use Only
РАН	Polycyclic Aromatic Hydrocarbons
РРТ	Pollution Prevention Team
SCM	Stormwater Control Measure
SIDP	Substantially Identical Discharge Points
SWPPP	Stormwater Pollution Prevention Plan
URL	Uniform Resource Locator
WFO	Weapons Facilities Operations

8.0 SWPPP CERTIFICATION


STORMWATER POLLUTION PREVENTION PLAN TA-16 Stockpile Area Los Alamos National Laboratory

CERTIFICATION STATEMENT

I certify under penalty of law that this document and all attachments were prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gathered and evaluated the information submitted. Based on my inquiry of the person or persons who manage the system, or those persons directly responsible for gathering the information, the information submitted is, to the best of my knowledge and belief, true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment for knowing violations.

Signature_	John	- Bun	mt	Date	e 12-22-	2021
(\sim	(

John Branch Operations Manager, High Explosives/Weapons Facilities (WFO-HE) Weapons Facilities Operations FIGURE A: GENERAL LOCATION MAP



TA-16 Stockpile Area MSGP Stormwater Pollution Prevention Plan Revision 3, December 2021

FIGURE B-1: FACILITY SITE MAP




FIGURE B-2: NEARBY RECEIVING WATERS MAP


TA-16 Stockpile Area MSGP Stormwater Pollution Prevention Plan Revision 3, December 2021






39

FIGURE B-3: LANL ENDANGERED SPECIES MAP



ATTACHMENT 1: NOTICE OF INTENT, SUPPORTING DOCUMENTATION, AND UPDATES



Permit Information

Master Permit Number: NMR050000

NPDES ID: NMR050013

Eligibility Information

State/territory where your facility is discharging: NM

Does your facility discharge to federally recognized Indian Country lands? No

Are you a "Federal Operator" as defined in Appendix A (https://www.epa.gov/sites/production/files/2021-01/documents/2021_msgp_-_appendix_a_-_definitions.pdf)?

Yes

Which type of form would you like to submit? Notice of Intent (NOI)

By indicating "Yes" below, I confirm that I understand that the MSGP only authorizes the stormwater discharges in Part 1.1.2 and the allowable non-stormwater discharges listed in Part 1.2.2. Any discharges not expressly authorized in this permit cannot become authorized or shielded from liability under CWA section 402(k) by disclosure to EPA, state, or local authorities after issuance of this permit via any means, including the Notice of Intent (NOI) to be covered by the permit, the Stormwater Pollution Prevention Plan (SWPPP), during an inspection, etc. If any discharges requiring NPDES permit coverage other than the allowable stormwater and non-stormwater discharges listed in Parts 1.2.1. and 1.2.2. will be discharged, they must be covered under another NPDES permit.

Yes

Are you a new discharger or a new source as defined in Appendix A (https://www.epa.gov/sites/production/files/2021-01/documents/2021_msgp_-_appendix_a_-_definitions.pdf)?

No

Have stormwater discharges from your facility been covered previously under an NPDES permit? Yes

- If yes, provide your most current NPDES ID (i.e., permit tracking number) if you had coverage under EPA's MSGP or the NPDES permit number if you had coverage under an EPA individual permit: NMR050013
- Are you discharging to any waters of the U.S. that are designated by the state or tribal authority under its antidegradation policy as a Tier 3 water (Outstanding National Resource water)? (See Appendix L (https://www.epa.gov/sites/production/files/2021-01/documents/2021_msgp_-_appendix_I_-_list_of_tier_3_tier_2_and_tier_2.5_waters.pdf))
 No

Do you anticipate the discharge of groundwater or spring water from your facility? No

What is the legal name of the Operator as defined in Appendix A (https://www.epa.gov/sites/production/files/2021-01/documents/2021_msgp_-_appendix_a_-_definitions.pdf)?

Triad National Security LLC

What is the name of your facility or activity as defined in Appendix A (https://www.epa.gov/sites/production/files/2021-01/documents/2021_msgp__appendix_a_-_definitions.pdf)? LOS ALAMOS NATIONAL LABORATORY

Operator Information

Operator Information

Operator Mailing Address

Address Line 1: PO Box 1663

Address Line 2: MS K490

ZIP/Postal Code: 87545

City: Los Alamos

State: NM

County or Similar Division: Los Alamos

Operator Point of Contact Information

First Name Middle Initial Last Name: TERRILL LEMKE

Title: Environmental Manager

Phone: 5056652397

Ext.:

Email: tlemke@lanl.gov

NOI Preparer Information

 $\ensuremath{\textcircled{}}$ This NOI is being prepared by someone other than the certifier.

 First Name
 Middle Initial
 Last Name:
 Holly
 L
 Wheeler

 Organization:
 Triad National Security LLC
 Ext.:
 Ext.:

 Email:
 hbenson@lanl.gov
 Ext.:
 Ext.:

Facility Information

Facility Information

Facility Name: LOS ALAMOS NATIONAL LABORATORY

Facility Address

Address Line 1: PO BOX 1663

Address Line 2: MS K490

ZIP/Postal Code: 87545

County or Similar Division: Los Alamos

Latitude/Longitude for the Facility

Latitude/Longitude: 35.872777°N, 106.321127°W

Latitude/Longitude Data Source: GIS

Horizontal Reference Datum: WGS 84

City: LOS ALAMOS

State: NM

General Facility Information

What is the ownership type of the facility? Federal Facility (U.S. Government)

Estimated area of industrial activity at your facility exposed to stormwater (rounded to the nearest quarter acre): 39.75

Is your facility presently inactive and unstaffed? No

Exception for Inactive and Unstaffed Facilities: The requirement for indicator monitoring, impaired waters monitoring, and/or benchmark monitoring does not apply at a facility that is inactive and unstaffed, as long as there are no industrial materials or activities exposed to stormwater.

If circumstances change during the permit term that affect your qualifications for this exception to monitoring requirements (i.e. industrial materials or activities exposure to stormwater or your facility's active/inactive and staffed/unstaffed status) you must submit a NOI notifying EPA of the change in circumstances.

Sector-Specific Information

Discharge Information

By indicating "Yes" below, I confirm that I understand that the MSGP only authorizes the stormwater discharges in Part 1.2.1 and the allowable non-stormwater discharges listed in Part 1.2.2. Any discharges not expressly authorized in this permit cannot become authorized or shielded from liability under CWA section 402(k) by disclosure to EPA, state, or local authorities after issuance of this permit via any means, including the Notice of Intent (NOI) to be covered by the permit, the Stormwater Pollution Prevention Plan (SWPPP), during an inspection, etc. If any discharges requiring NPDES permit coverage other than the authorized stormwater and non-stormwater discharges listed in Parts 1.2.1 and 1.2.2 will be discharged, they must be covered under another NPDES permit.

Yes

Federal Effluent Limitation Guidelines

Identify the Effluent Limitation Guideline(s) that apply to your stormwater discharges.

40 CFR Part/Subpart	Eligible Discharges	Affected MSGP Sector	New Source Date	Applicability
Part 443, Subpart A	Runoff from asphalt emulsion facilities	D	07/28/1975	Does your facility have any discharges subject to this effluent limitation guideline? Yes

Are you requesting permit coverage for any stormwater discharges subject to effluent limitation guidelines? Yes

Other Discharge Information

Do you anticipate the discharge of groundwater or spring water from your facility? No

Does your facility discharge into a Municipal Separate Sewer System (MS4)? No

Receiving Waters Information

List all of the stormwater discharge points from your facility.

Discharge Point 023: TA-60-1 Heavy Equipment Yard SIO to 022

Applicable Sectors

Select the Sectors/Subsector(s) that apply to this discharge point.

	Sector	Subsector	SIC/Activity Code
	D - ASPHALT PAVING AND ROOFING MATERIALS AND LUBRICANTS	D1 - Asphalt Paving and Roofing Materials	2951
	N - SCRAP RECYCLING FACILITIES	N2 - Source-separated Recycling Facility	5093
2	P - LAND TRANSPORTATION AND WAREHOUSING	P1 - Railroad Transportation; Local and Highway Passenger Transportation; Motor Freight Transportation and Warehousing; United States Postal Service; Petroleum Bulk Stations and Terminals	4212
	AA - FABRICATED METAL PRODUCTS	AA1 - Fabricated Metal Products, Except Machinery and Transportation Equipment, and Coating, Engraving, and Allied Services; Jewelry, Silverware, and Plated Ware	3499

Latitude/Longitude: 35.873193°N, 106.313116°W

☑ This discharge point is Substantially Identical to an existing discharge point.

✤ Substantially Identical to Discharge Point ID: 022

Receiving Water

GNIS Name:

Waterbody Name: SANDIA CANYON (SIGMA CANYON TO NPDES OUTFALL 001) Listed Water ID: NM-9000.A_047

Is this receiving water saltwater or freshwater? Freshwater

Is this receiving water designated by the state or tribal authority under its antidegradation policy as a Tier 2 (or Tier 2.5) water (water quality exceeds levels necessary to support propagation of fish, shellfish, and wildlife and recreation in and on the water)?

No

Will you have stormwater discharges from paved surfaces that will be initially sealed or re-sealed with coal-tar sealcoat where industrial activities are located during coverage under this permit?

No

Benchmark Monitoring

Are you subject to benchmark monitoring requirements for a hardness-dependent metal? Yes

✤ What is the hardness of your receiving water(s)? 61

(mg/L)

NOTE: The information automatically populated in this section for determining if the receiving water is listed as impaired on the 303(d) list and in need of a TMDL, the cause(s) of the impairment if the receiving water is impaired on the CWA 303(d) list, if a TMDL has been completed for the receiving waterbody, and the TMDL ID and pollutants for which there is a TMDL may be outdated and inaccurate. It is recommended that you consult with your state's guidance for discharges into impaired waters to determine the correct pollutants and TMDLS and update the causes for the impairment and TMDL information accordingly.

Is the receiving water listed as impaired on the 303(d) list and in need of a TMDL? Yes

Cause of Impairment Group	Pollutant
METALS (OTHER THAN MERCURY)	Aluminum, total recoverable
POLYCHLORINATED BIPHENYLS (PCBS)	Poly chlorinated bipheny Is [PCBs]
METALS (OTHER THAN MERCURY)	Copper, dissolved [as Cu]

Has a TMDL been completed for this receiving waterbody? No

Discharge Point 024: TA-60-1 Heavy Equipment Yard SIO to 022

Applicable Sectors

Select the Sectors/Subsector(s) that apply to this discharge point.

	Sector	Subsector	SIC/Activity Code
	D - ASPHALT PAVING AND ROOFING MATERIALS AND LUBRICANTS	D1 - Asphalt Paving and Roofing Materials	2951
	N - SCRAP RECYCLING FACILITIES	N2 - Source-separated Recycling Facility	5093
•	P - LAND TRANSPORTATION AND WAREHOUSING	P1 - Railroad Transportation; Local and Highway Passenger Transportation; Motor Freight Transportation and Warehousing; United States Postal Service; Petroleum Bulk Stations and Terminals	4212
¥	AA - FABRICATED METAL PRODUCTS	AA1 - Fabricated Metal Products, Except Machinery and Transportation Equipment, and Coating, Engraving, and Allied Services; Jewelry, Silverware, and Plated Ware	3499

Latitude/Longitude: 35.873046°N, 106.315069°W

☑ This discharge point is Substantially Identical to an existing discharge point.

✤ Substantially Identical to Discharge Point ID: 022

Receiving Water

GNIS Name:

Waterbody Name: SANDIA CANYON (SIGMA CANYON TO NPDES OUTFALL 001) Listed Water ID: NM-9000.A_047

Is this receiving water saltwater or freshwater? Freshwater

Is this receiving water designated by the state or tribal authority under its antidegradation policy as a Tier 2 (or Tier 2.5) water (water quality exceeds levels necessary to support propagation of fish, shellfish, and wildlife and recreation in and on the water)?

Will you have stormwater discharges from paved surfaces that will be initially sealed or re-sealed with coal-tar sealcoat where industrial activities are located during coverage under this permit?

Benchmark Monitoring

Are you subject to benchmark monitoring requirements for a hardness-dependent metal? Yes

✤ What is the hardness of your receiving water(s)? 61

(mg/L)

Impaired Waters Monitoring

NOTE: The information automatically populated in this section for determining if the receiving water is listed as impaired on the 303(d) list and in need of a TMDL, the cause(s) of the impairment if the receiving water is impaired on the CWA 303(d) list, if a TMDL has been completed for the receiving waterbody, and the TMDL ID and pollutants for which there is a TMDL may be outdated and inaccurate. It is recommended that you consult with your state's guidance for discharges into impaired waters to determine the correct pollutants and TMDLS and update the causes for the impairment and TMDL information accordingly.

Is the receiving water listed as impaired on the 303(d) list and in need of a TMDL? Yes

Cause of Impairment Group	Pollutant
POLYCHLORINATED BIPHENYLS (PCBS)	Poly chlorinated bipheny Is [PCBs]
METALS (OTHER THAN MERCURY)	Aluminum, total recoverable
METALS (OTHER THAN MERCURY)	Copper, dissolved [as Cu]

Has a TMDL been completed for this receiving waterbody? No

Discharge Point 039: TA-60 Roads and Grounds

Applicable Sectors

Select the Sectors/Subsector(s) that apply to this discharge point.

	Sector	Subsector	SIC/Activity Code
	D - ASPHALT PAVING AND ROOFING MATERIALS AND LUBRICANTS	D1 - Asphalt Paving and Roofing Materials	2951
	N - SCRAP RECYCLING FACILITIES	N2 - Source-separated Recycling Facility	5093
¥	P - LAND TRANSPORTATION AND WAREHOUSING	P1 - Railroad Transportation; Local and Highway Passenger Transportation; Motor Freight Transportation and Warehousing; United States Postal Service; Petroleum Bulk Stations and Terminals	4212
	AA - FABRICATED METAL PRODUCTS	AA1 - Fabricated Metal Products, Except Machinery and Transportation Equipment, and Coating, Engraving, and Allied Services; Jewelry, Silverware, and Plated Ware	3499

Latitude/Longitude: 35.867826°N, 106.291726°W

□ This discharge point is Substantially Identical to an existing discharge point.

Receiving Water

GNIS Name:

Waterbody Name: SANDIA CANYON (SIGMA CANYON TO NPDES OUTFALL 001) Listed Water ID: NM-9000.A_047

Is this receiving water saltwater or freshwater? Freshwater

Is this receiving water designated by the state or tribal authority under its antidegradation policy as a Tier 2 (or Tier 2.5) water (water quality exceeds levels necessary to support propagation of fish, shellfish, and wildlife and recreation in and on the water)? No

Will you have stormwater discharges from paved surfaces that will be initially sealed or re-sealed with coal-tar sealcoat where industrial activities are located during coverage under this permit?

No

Benchmark Monitoring

Are you subject to benchmark monitoring requirements for a hardness-dependent metal? No

Impaired Waters Monitoring

NOTE: The information automatically populated in this section for determining if the receiving water is listed as impaired on the 303(d) list and in need of a TMDL, the cause(s) of the impairment if the receiving water is impaired on the CWA 303(d) list, if a TMDL has been completed for the receiving waterbody, and the TMDL ID and pollutants for which there is a TMDL may be outdated and inaccurate. It is recommended that you consult with your state's guidance for discharges into impaired waters to determine the correct pollutants and TMDLS and update the causes for the impairment and TMDL information accordingly.

Is the receiving water listed as impaired on the 303(d) list and in need of a TMDL? Yes

Cause of Impairment Group	Pollutant
METALS (OTHER THAN MERCURY)	Aluminum, total recoverable
POLYCHLORINATED BIPHENYLS (PCBS)	Polychlorinated biphenyls [PCBs]
METALS (OTHER THAN MERCURY)	Copper, dissolved [as Cu]

Has a TMDL been completed for this receiving waterbody? No

Discharge Point 032: TA-60 Roads and Grounds

Applicable Sectors

Select the Sectors/Subsector(s) that apply to this discharge point.

	Sector	Subsector	SIC/Activity Code
	D - ASPHALT PAVING AND ROOFING MATERIALS AND	D1 - Asphalt Paving and Roofing Materials	2951
	LUBRICANTS		

	N - SCRAP RECYCLING FACILITIES	N2 - Source-separated Recycling Facility	5093
¥	P - LAND TRANSPORTATION AND WAREHOUSING	P1 - Railroad Transportation; Local and Highway Passenger Transportation; Motor Freight Transportation and Warehousing; United States Postal Service; Petroleum Bulk Stations and Terminals	4212
	AA - FABRICATED METAL PRODUCTS	A41 - Fabricated Metal Products, Except Machinery and Transportation Equipment, and Coating, Engraving, and Allied Services; Jewelry, Silverware, and Plated Ware	3499

Latitude/Longitude: 35.870741°N, 106.306812°W

□ This discharge point is Substantially Identical to an existing discharge point.

Receiving Water

GNIS Name:

Waterbody Name: SANDIA CANYON (SIGMA CANYON TO NPDES OUTFALL 001) Listed Water ID: NM-9000.A_047

Is this receiving water saltwater or freshwater? Freshwater

Is this receiving water designated by the state or tribal authority under its antidegradation policy as a Tier 2 (or Tier 2.5) water (water quality exceeds levels necessary to support propagation of fish, shellfish, and wildlife and recreation in and on the water)? No

Will you have stormwater discharges from paved surfaces that will be initially sealed or re-sealed with coal-tar sealcoat where industrial activities are located during coverage under this permit?

No

Benchmark Monitoring

Are you subject to benchmark monitoring requirements for a hardness-dependent metal? No

Impaired Waters Monitoring

NOTE: The information automatically populated in this section for determining if the receiving water is listed as impaired on the 303(d) list and in need of a TMDL, the cause(s) of the impairment if the receiving water is impaired on the CWA 303(d) list, if a TMDL has been completed for the receiving waterbody, and the TMDL ID and pollutants for which there is a TMDL may be outdated and inaccurate. It is recommended that you consult with your state's guidance for discharges into impaired waters to determine the correct pollutants and TMDLS and update the causes for the impairment and TMDL information accordingly.

Is the receiving water listed as impaired on the 303(d) list and in need of a TMDL? Yes

Cause of Impairment Group	Pollutant
POLYCHLORINATED BIPHENYLS (PCBS)	Poly chlorinated bipheny Is [PCBs]
METALS (OTHER THAN MERCURY)	Aluminum, total recoverable
METALS (OTHER THAN MERCURY)	Copper, dissolved [as Cu]

Has a TMDL been completed for this receiving waterbody? No

Applicable Sectors

Select the Sectors/Subsector(s) that apply to this discharge point.

	Sector	Subsector	SIC/Activity Code
	D - ASPHALT PAVING AND ROOFING MATERIALS AND LUBRICANTS	D1 - Asphalt Paving and Roofing Materials	2951
	N - SCRAP RECYCLING FACILITIES	N2 - Source-separated Recy cling Facility	5093
V	P - LAND TRANSPORTATION AND WAREHOUSING	P1 - Railroad Transportation; Local and Highway Passenger Transportation; Motor Freight Transportation and Warehousing; United States Postal Service; Petroleum Bulk Stations and Terminals	4212
	AA - FABRICATED METAL PRODUCTS	AA1 - Fabricated Metal Products, Except Machinery and Transportation Equipment, and Coating, Engraving, and Allied Services; Jewelry, Silverware, and Plated Ware	3499

Latitude/Longitude: 35.870603°N, 106.306055°W

☑ This discharge point is Substantially Identical to an existing discharge point.

✤ Substantially Identical to Discharge Point ID: 032

Receiving Water

GNIS Name:

Waterbody Name: SANDIA CANYON (SIGMA CANYON TO NPDES OUTFALL 001) Listed Water ID: NM-9000.A_047

Is this receiving water saltwater or freshwater? Freshwater

Is this receiving water designated by the state or tribal authority under its antidegradation policy as a Tier 2 (or Tier 2.5) water (water quality exceeds levels necessary to support propagation of fish, shellfish, and wildlife and recreation in and on the water)?

No

Will you have stormwater discharges from paved surfaces that will be initially sealed or re-sealed with coal-tar sealcoat where industrial activities are located during coverage under this permit?

No

Benchmark Monitoring

Are you subject to benchmark monitoring requirements for a hardness-dependent metal? No

Impaired Waters Monitoring

NOTE: The information automatically populated in this section for determining if the receiving water is listed as impaired on the 303(d) list and in need of a TMDL, the cause(s) of the impairment if the receiving water is impaired on the CWA 303(d) list, if a TMDL has been completed for the receiving waterbody, and the TMDL ID and pollutants for which there is a TMDL may be outdated and inaccurate. It is recommended that you consult with your state's guidance for discharges into impaired waters to determine the correct pollutants and TMDLS and update the causes for the impairment and TMDL information accordingly.

Is the receiving water listed as impaired on the 303(d) list and in need of a TMDL? Yes

Cause of Impairment Group	Pollutant
POLYCHLORINATED BIPHENYLS (PCBS)	Poly chlorinated bipheny Is [PCBs]
METALS (OTHER THAN MERCURY)	Aluminum, total recoverable
METALS (OTHER THAN MERCURY)	Copper, dissolved [as Cu]

Has a TMDL been completed for this receiving waterbody? No

Discharge Point 028: TA-60-2 Warehouse SIO to 026

Applicable Sectors

Select the Sectors/Subsector(s) that apply to this discharge point.

	Sector	Subsector	SIC/Activity Code
	D - ASPHALT PAVING AND ROOFING MATERIALS AND LUBRICANTS	D1 - Asphalt Paving and Roofing Materials	2951
	N - SCRAP RECYCLING FACILITIES	N2 - Source-separated Recycling Facility	5093
V	P - LAND TRANSPORTATION AND WAREHOUSING	P1 - Railroad Transportation; Local and Highway Passenger Transportation; Motor Freight Transportation and Warehousing; United States Postal Service; Petroleum Bulk Stations and Terminals	4212
	AA - FABRICATED METAL PRODUCTS	AA1 - Fabricated Metal Products, Except Machinery and Transportation Equipment, and Coating, Engraving, and Allied Services; Jewelry, Silverware, and Plated Ware	3499

Latitude/Longitude: 35.872505°N, 106.313542°W

☑ This discharge point is Substantially Identical to an existing discharge point.

✤ Substantially Identical to Discharge Point ID: 026

Receiving Water

GNIS Name:

Waterbody Name: SANDIA CANYON (SIGMA CANYON TO NPDES OUTFALL 001) Listed Water ID: NM-9000.A_047

Is this receiving water saltwater or freshwater? Freshwater

Is this receiving water designated by the state or tribal authority under its antidegradation policy as a Tier 2 (or Tier 2.5) water (water quality exceeds levels necessary to support propagation of fish, shellfish, and wildlife and recreation in and on the water)?

No

Will you have stormwater discharges from paved surfaces that will be initially sealed or re-sealed with coal-tar sealcoat where industrial activities are located during coverage under this permit?

No

Benchmark Monitoring

Are you subject to benchmark monitoring requirements for a hardness-dependent metal? No

Impaired Waters Monitoring

NOTE: The information automatically populated in this section for determining if the receiving water is listed as impaired on the 303(d) list and in need of a TMDL, the cause(s) of the impairment if the receiving water is impaired on the CWA 303(d) list, if a TMDL has been completed for the receiving waterbody, and the TMDL ID and pollutants for which there is a TMDL may be outdated and inaccurate. It is recommended that you consult with your state's guidance for discharges into impaired waters to determine the correct pollutants and TMDLS and update the causes for the impairment and TMDL information accordingly.

Is the receiving water listed as impaired on the 303(d) list and in need of a TMDL? Yes

Cause of Impairment Group	Pollutant
POLYCHLORINATED BIPHENYLS (PCBS)	Poly chlorinated bipheny Is [PCBs]
METALS (OTHER THAN MERCURY)	Aluminum, total recoverable
METALS (OTHER THAN MERCURY)	Copper, dissolved [as Cu]

Has a TMDL been completed for this receiving waterbody? No

Discharge Point 035: TA-60 Roads and Grounds SIO to 032

Applicable Sectors

Select the Sectors/Subsector(s) that apply to this discharge point.

	Sector	Subsector	SIC/Activity Code
	D - ASPHALT PAVING AND ROOFING MATERIALS AND LUBRICANTS	D1 - Asphalt Paving and Roofing Materials	2951
	N - SCRAP RECYCLING FACILITIES	N2 - Source-separated Recycling Facility	5093
¥	P - LAND TRANSPORTATION AND WAREHOUSING	P1 - Railroad Transportation; Local and Highway Passenger Transportation; Motor Freight Transportation and Warehousing; United States Postal Service; Petroleum Bulk Stations and Terminals	4212
	AA - FABRICATED METAL PRODUCTS	AA1 - Fabricated Metal Products, Except Machinery and Transportation Equipment, and Coating, Engraving, and Allied Services; Jewelry, Silverware, and Plated Ware	3499

Latitude/Longitude: 35.870474°N, 106.305432°W

This discharge point is Substantially Identical to an existing discharge point.

✤ Substantially Identical to Discharge Point ID: 032

Receiving Water

GNIS Name:

Waterbody Name: SANDIA CANYON (SIGMA CANYON TO NPDES OUTFALL 001) Listed Water ID: NM-9000.A_047

Is this receiving water saltwater or freshwater? Freshwater

Is this receiving water designated by the state or tribal authority under its antidegradation policy as a Tier 2 (or Tier 2.5) water (water quality exceeds levels necessary to support propagation of fish, shellfish, and wildlife and recreation in and on the water)?

No

Will you have stormwater discharges from paved surfaces that will be initially sealed or re-sealed with coal-tar sealcoat where industrial activities are located during coverage under this permit?

No

Benchmark Monitoring

Are you subject to benchmark monitoring requirements for a hardness-dependent metal? No

Impaired Waters Monitoring

NOTE: The information automatically populated in this section for determining if the receiving water is listed as impaired on the 303(d) list and in need of a TMDL, the cause(s) of the impairment if the receiving water is impaired on the CWA 303(d) list, if a TMDL has been completed for the receiving waterbody, and the TMDL ID and pollutants for which there is a TMDL may be outdated and inaccurate. It is recommended that you consult with your state's guidance for discharges into impaired waters to determine the correct pollutants and TMDLS and update the causes for the impairment and TMDL information accordingly.

Is the receiving water listed as impaired on the 303(d) list and in need of a TMDL? \underline{Yes}

Cause of Impairment Group	Pollutant
POLYCHLORINATED BIPHENYLS (PCBS)	Poly chlorinated bipheny Is [PCBs]
METALS (OTHER THAN MERCURY)	Aluminum, total recoverable
METALS (OTHER THAN MERCURY)	Copper, dissolved [as Cu]

Has a TMDL been completed for this receiving waterbody? No

Discharge Point 043: TA-60 Asphalt Batch Plant

Applicable Sectors

Select the Sectors/Subsector(s) that apply to this discharge point.

	Sector	Subsector	SIC/Activity Code
¥	D - ASPHALT PAVING AND ROOFING MATERIALS AND LUBRICANTS	D1 - Asphalt Paving and Roofing Materials	2951
	N - SCRAP RECYCLING FACILITIES	N2 - Source-separated Recycling Facility	5093
	P - LAND TRANSPORTATION AND WAREHOUSING	P1 - Railroad Transportation; Local and Highway Passenger Transportation; Motor Freight Transportation and Warehousing; United States Postal Service; Petroleum Bulk Stations and Terminals	4212
	AA - FABRICATED METAL PRODUCTS	AA1 - Fabricated Metal Products, Except Machinery and Transportation Equipment, and Coating, Engraving, and Allied Services; Jewelry, Silverware, and Plated Ware	3499

L3ati86666846001.g1006d290165°W

 $\hfill\square$ This discharge point is Substantially Identical to an existing discharge point.

Receiving Water

GNIS Name:

Waterbody Name: MORTANDAD CANYON (WITHIN LANL) Listed Water ID: NM-9000.A_042

Is this receiving water saltwater or freshwater? Freshwater

Is this receiving water designated by the state or tribal authority under its antidegradation policy as a Tier 2 (or Tier 2.5) water (water quality exceeds levels necessary to support propagation of fish, shellfish, and wildlife and recreation in and on the water)? No

Will you have stormwater discharges from paved surfaces that will be initially sealed or re-sealed with coal-tar sealcoat where industrial activities are located during coverage under this permit?

No

Benchmark Monitoring

Are you subject to benchmark monitoring requirements for a hardness-dependent metal? No

Impaired Waters Monitoring

NOTE: The information automatically populated in this section for determining if the receiving water is listed as impaired on the 303(d) list and in need of a TMDL, the cause(s) of the impairment if the receiving water is impaired on the CWA 303(d) list, if a TMDL has been completed for the receiving waterbody, and the TMDL ID and pollutants for which there is a TMDL may be outdated and inaccurate. It is recommended that you consult with your state's guidance for discharges into impaired waters to determine the correct pollutants and TMDLS and update the causes for the impairment and TMDL information accordingly.

Is the receiving water listed as impaired on the 303(d) list and in need of a TMDL? Yes

Cause of Impairment Group	Pollutant
POLYCHLORINATED BIPHENYLS (PCBS)	Poly chlorinated bipheny Is [PCBs]
MERCURY	Mercury, total [as Hg]
METALS (OTHER THAN MERCURY)	Copper, dissolved [as Cu]
RADIATION	Alpha, gross adjusted

Has a TMDL been completed for this receiving waterbody? No

Discharge Point 031: TA-60 Roads and Grounds

Applicable Sectors

Select the Sectors/Subsector(s) that apply to this discharge point.

Subsector

SIC/Activity Code

	D - ASPHALT PAVING AND ROOFING MATERIALS AND LUBRICANTS	D1 - Asphalt Paving and Roofing Materials	2951
	N - SCRAP RECYCLING FACILITIES	N2 - Source-separated Recycling Facility	5093
¥	P - LAND TRANSPORTATION AND WAREHOUSING	P1 - Railroad Transportation; Local and Highway Passenger Transportation; Motor Freight Transportation and Warehousing; United States Postal Service; Petroleum Bulk Stations and Terminals	4212
	AA - FABRICATED METAL PRODUCTS	A41 - Fabricated Metal Products, Except Machinery and Transportation Equipment, and Coating, Engraving, and Allied Services; Jewelry, Silverware, and Plated Ware	3499

Latitude/Longitude: 35.869227°N, 106.305685°W

□ This discharge point is Substantially Identical to an existing discharge point.

Receiving Water

GNIS Name:

Waterbody Name: MORTANDAD CANYON (WITHIN LANL) Listed Water ID: NM-9000.A_042

Is this receiving water saltwater or freshwater? Freshwater

Is this receiving water designated by the state or tribal authority under its antidegradation policy as a Tier 2 (or Tier 2.5) water (water quality exceeds levels necessary to support propagation of fish, shellfish, and wildlife and recreation in and on the water)? No

Will you have stormwater discharges from paved surfaces that will be initially sealed or re-sealed with coal-tar sealcoat where industrial activities are located during coverage under this permit?

No

Benchmark Monitoring

Are you subject to benchmark monitoring requirements for a hardness-dependent metal? No

Impaired Waters Monitoring

NOTE: The information automatically populated in this section for determining if the receiving water is listed as impaired on the 303(d) list and in need of a TMDL, the cause(s) of the impairment if the receiving water is impaired on the CWA 303(d) list, if a TMDL has been completed for the receiving waterbody, and the TMDL ID and pollutants for which there is a TMDL may be outdated and inaccurate. It is recommended that you consult with your state's guidance for discharges into impaired waters to determine the correct pollutants and TMDLS and update the causes for the impairment and TMDL information accordingly.

Is the receiving water listed as impaired on the 303(d) list and in need of a TMDL? Yes

Cause of Impairment Group	Pollutant
POLYCHLORINATED BIPHENYLS (PCBS)	Poly chlorinated bipheny Is [PCBs]
MERCURY	Mercury, total [as Hg]
METALS (OTHER THAN MERCURY)	Copper, dissolved [as Cu]
RADIATION	Alpha, gross adjusted

Has a TMDL been completed for this receiving waterbody? No

Applicable Sectors

Select the Sectors/Subsector(s) that apply to this discharge point.

	Sector	Subsector	SIC/Activity Code
	D - ASPHALT PAVING AND ROOFING MATERIALS AND LUBRICANTS	D1 - Asphalt Paving and Roofing Materials	2951
	N - SCRAP RECYCLING FACILITIES	N2 - Source-separated Recycling Facility	5093
•	P - LAND TRANSPORTATION AND WAREHOUSING	P1 - Railroad Transportation; Local and Highway Passenger Transportation; Motor Freight Transportation and Warehousing; United States Postal Service; Petroleum Bulk Stations and Terminals	4212
	AA - FABRICATED METAL PRODUCTS	AA1 - Fabricated Metal Products, Except Machinery and Transportation Equipment, and Coating, Engraving, and Allied Services; Jewelry, Silverware, and Plated Ware	3499

Latitude/Longitude: 35.870712°N, 106.306443°W

This discharge point is Substantially Identical to an existing discharge point.

✤ Substantially Identical to Discharge Point ID: 032

Receiving Water

GNIS Name:

Waterbody Name: SANDIA CANYON (SIGMA CANYON TO NPDES OUTFALL 001) Listed Water ID: NM-9000.A_047

Is this receiving water saltwater or freshwater? Freshwater

Is this receiving water designated by the state or tribal authority under its antidegradation policy as a Tier 2 (or Tier 2.5) water (water quality exceeds levels necessary to support propagation of fish, shellfish, and wildlife and recreation in and on the water)?

No

Will you have stormwater discharges from paved surfaces that will be initially sealed or re-sealed with coal-tar sealcoat where industrial activities are located during coverage under this permit?

No

Benchmark Monitoring

Are you subject to benchmark monitoring requirements for a hardness-dependent metal? No

Impaired Waters Monitoring

NOTE: The information automatically populated in this section for determining if the receiving water is listed as impaired on the 303(d) list and in need of a TMDL, the cause(s) of the impairment if the receiving water is impaired on the CWA 303(d) list, if a TMDL has been completed for the receiving waterbody, and the TMDL ID and pollutants for which there is a TMDL may be outdated and inaccurate. It is recommended that you consult with your state's guidance for discharges into impaired waters to determine the correct pollutants and TMDLS and update the causes for the impairment and TMDL information accordingly.

Is the receiving water listed as impaired on the 303(d) list and in need of a TMDL? Yes

Cause of Impairment Group	Pollutant
POLYCHLORINATED BIPHENYLS (PCBS)	Poly chlorinated bipheny Is [PCBs]
METALS (OTHER THAN MERCURY)	Aluminum, total recoverable
METALS (OTHER THAN MERCURY)	Copper, dissolved [as Cu]

Has a TMDL been completed for this receiving waterbody? No

Discharge Point 027: TA-60-2 Warehouse SIO to 026

Applicable Sectors

Select the Sectors/Subsector(s) that apply to this discharge point.

	Sector	Subsector	SIC/Activity Code
	D - ASPHALT PAVING AND ROOFING MATERIALS AND LUBRICANTS	D1 - Asphalt Paving and Roofing Materials	2951
	N - SCRAP RECYCLING FACILITIES	N2 - Source-separated Recycling Facility	5093
¥	P - LAND TRANSPORTATION AND WAREHOUSING	P1 - Railroad Transportation; Local and Highway Passenger Transportation; Motor Freight Transportation and Warehousing; United States Postal Service; Petroleum Bulk Stations and Terminals	4212
	AA - FABRICATED METAL PRODUCTS	A41 - Fabricated Metal Products, Except Machinery and Transportation Equipment, and Coating, Engraving, and Allied Services; Jewelry, Silverware, and Plated Ware	3499

Latitude/Longitude: 35.872401°N, 106.313391°W

☑ This discharge point is Substantially Identical to an existing discharge point.

✤ Substantially Identical to Discharge Point ID: 026

Receiving Water

GNIS Name:

Waterbody Name: SANDIA CANYON (SIGMA CANYON TO NPDES OUTFALL 001) Listed Water ID: NM-9000.A_047

Is this receiving water saltwater or freshwater? Freshwater

Is this receiving water designated by the state or tribal authority under its antidegradation policy as a Tier 2 (or Tier 2.5) water (water quality exceeds levels necessary to support propagation of fish, shellfish, and wildlife and recreation in and on the water)?

No

Will you have stormwater discharges from paved surfaces that will be initially sealed or re-sealed with coal-tar sealcoat where industrial activities are located during coverage under this permit?

No

Benchmark Monitoring

Impaired Waters Monitoring

NOTE: The information automatically populated in this section for determining if the receiving water is listed as impaired on the 303(d) list and in need of a TMDL, the cause(s) of the impairment if the receiving water is impaired on the CWA 303(d) list, if a TMDL has been completed for the receiving waterbody, and the TMDL ID and pollutants for which there is a TMDL may be outdated and inaccurate. It is recommended that you consult with your state's guidance for discharges into impaired waters to determine the correct pollutants and TMDLS and update the causes for the impairment and TMDL information accordingly.

Is the receiving water listed as impaired on the 303(d) list and in need of a TMDL? Yes

Cause of Impairment Group	Pollutant
POLYCHLORINATED BIPHENYLS (PCBS)	Poly chlorinated bipheny Is [PCBs]
METALS (OTHER THAN MERCURY)	Aluminum, total recoverable
METALS (OTHER THAN MERCURY)	Copper, dissolved [as Cu]

Has a TMDL been completed for this receiving waterbody? No

Discharge Point 030: TA-60 Roads and Grounds SIO to 031

Applicable Sectors

Select the Sectors/Subsector(s) that apply to this discharge point.

	Sector	Subsector	SIC/Activity Code
	D - ASPHALT PAVING AND ROOFING MATERIALS AND LUBRICANTS	D1 - Asphalt Paving and Roofing Materials	2951
	N - SCRAP RECYCLING FACILITIES	N2 - Source-separated Recycling Facility	5093
¥	P - LAND TRANSPORTATION AND WAREHOUSING	P1 - Railroad Transportation; Local and Highway Passenger Transportation; Motor Freight Transportation and Warehousing; United States Postal Service; Petroleum Bulk Stations and Terminals	4212
D	AA - FABRICATED METAL PRODUCTS	AA1 - Fabricated Metal Products, Except Machinery and Transportation Equipment, and Coating, Engraving, and Allied Services; Jewelry, Silverware, and Plated Ware	3499

Latitude/Longitude: 35.869325°N, 106.306926°W

☑ This discharge point is Substantially Identical to an existing discharge point.

Substantially Identical to Discharge Point ID: 031

Receiving Water

GNIS Name:

Waterbody Name: MORTANDAD CANYON (WITHIN LANL) Listed Water ID: NM-9000.A_042 Is this receiving water saltwater or freshwater? Freshwater

Is this receiving water designated by the state or tribal authority under its antidegradation policy as a Tier 2 (or Tier 2.5) water (water quality exceeds levels necessary to support propagation of fish, shellfish, and wildlife and recreation in and on the water)?

No

Will you have stormwater discharges from paved surfaces that will be initially sealed or re-sealed with coal-tar sealcoat where industrial activities are located during coverage under this permit?

No

Benchmark Monitoring

Are you subject to benchmark monitoring requirements for a hardness-dependent metal? No

Impaired Waters Monitoring

NOTE: The information automatically populated in this section for determining if the receiving water is listed as impaired on the 303(d) list and in need of a TMDL, the cause(s) of the impairment if the receiving water is impaired on the CWA 303(d) list, if a TMDL has been completed for the receiving waterbody, and the TMDL ID and pollutants for which there is a TMDL may be outdated and inaccurate. It is recommended that you consult with your state's guidance for discharges into impaired waters to determine the correct pollutants and TMDLS and update the causes for the impairment and TMDL information accordingly.

Is the receiving water listed as impaired on the 303(d) list and in need of a TMDL? Yes

Cause of Impairment Group	Pollutant
POLYCHLORINATED BIPHENYLS (PCBS)	Poly chlorinated bipheny Is [PCBs]
MERCURY	Mercury, total [as Hg]
METALS (OTHER THAN MERCURY)	Copper, dissolved [as Cu]
RADIATION	Alpha, gross adjusted

Has a TMDL been completed for this receiving waterbody? No

Discharge Point 029: TA-60 Metals Recycling Facility

Applicable Sectors

Select the Sectors/Subsector(s) that apply to this discharge point.

	Sector	Subsector	SIC/Activity Code
	D - ASPHALT PAVING AND ROOFING MATERIALS AND LUBRICANTS	D1 - Asphalt Paving and Roofing Materials	2951
¥	N - SCRAP RECYCLING FACILITIES	N2 - Source-separated Recycling Facility	5093
	P - LAND TRANSPORTATION AND WAREHOUSING	P1 - Railroad Transportation; Local and Highway Passenger Transportation; Motor Freight Transportation and Warehousing; United States Postal Service; Petroleum Bulk Stations and Terminals	4212

 AA1 - Fabricated Metal Products, Except Machinery and Transportation Equipment, and
 3499

 Coating, Engraving, and Allied Services; Jewelry, Silverware, and Plated Ware
 3499

Latitude/Longitude: 35.873969°N, 106.313281°W

□ This discharge point is Substantially Identical to an existing discharge point.

Receiving Water

GNIS Name:

Waterbody Name: SANDIA CANYON (SIGMA CANYON TO NPDES OUTFALL 001) Listed Water ID: NM-9000.A_047

Is this receiving water saltwater or freshwater? Freshwater

Is this receiving water designated by the state or tribal authority under its antidegradation policy as a Tier 2 (or Tier 2.5) water (water quality exceeds levels necessary to support propagation of fish, shellfish, and wildlife and recreation in and on the water)?

No

Will you have stormwater discharges from paved surfaces that will be initially sealed or re-sealed with coal-tar sealcoat where industrial activities are located during coverage under this permit?

No

Benchmark Monitoring

Are you subject to benchmark monitoring requirements for a hardness-dependent metal? No

Impaired Waters Monitoring

NOTE: The information automatically populated in this section for determining if the receiving water is listed as impaired on the 303(d) list and in need of a TMDL, the cause(s) of the impairment if the receiving water is impaired on the CWA 303(d) list, if a TMDL has been completed for the receiving waterbody, and the TMDL ID and pollutants for which there is a TMDL may be outdated and inaccurate. It is recommended that you consult with your state's guidance for discharges into impaired waters to determine the correct pollutants and TMDLS and update the causes for the impairment and TMDL information accordingly.

Is the receiving water listed as impaired on the 303(d) list and in need of a TMDL? Yes

Cause of Impairment Group	Pollutant
POLYCHLORINATED BIPHENYLS (PCBS)	Poly chlorinated bipheny Is [PCBs]
METALS (OTHER THAN MERCURY)	Aluminum, total recoverable
METALS (OTHER THAN MERCURY)	Copper, dissolved [as Cu]

Has a TMDL been completed for this receiving waterbody? No

Discharge Point 075: TA-60-2 Warehouse

Applicable Sectors

Select the Sectors/Subsector(s) that apply to this discharge point.

	Sector	Subsector	SIC/Activity Code
	D - ASPHALT PAVING AND ROOFING MATERIALS AND LUBRICANTS	D1 - Asphalt Paving and Roofing Materials	2951
	N - SCRAP RECYCLING FACILITIES	N2 - Source-separated Recycling Facility	5093
V	P - LAND TRANSPORTATION AND WAREHOUSING	P1 - Railroad Transportation; Local and Highway Passenger Transportation; Motor Freight Transportation and Warehousing; United States Postal Service; Petroleum Bulk Stations and Terminals	4212
	AA - FABRICATED METAL PRODUCTS	AA1 - Fabricated Metal Products, Except Machinery and Transportation Equipment, and Coating, Engraving, and Allied Services; Jewelry, Silverware, and Plated Ware	3499

Latitude/Longitude: 35.871154°N, 106.31294°W

□ This discharge point is Substantially Identical to an existing discharge point.

Receiving Water

GNIS Name:

Waterbody Name: SANDIA CANYON (SIGMA CANYON TO NPDES OUTFALL 001) Listed Water ID: NM-9000.A_047

Is this receiving water saltwater or freshwater? Freshwater

Is this receiving water designated by the state or tribal authority under its antidegradation policy as a Tier 2 (or Tier 2.5) water (water quality exceeds levels necessary to support propagation of fish, shellfish, and wildlife and recreation in and on the water)?

No

Will you have stormwater discharges from paved surfaces that will be initially sealed or re-sealed with coal-tar sealcoat where industrial activities are located during coverage under this permit?

No

Benchmark Monitoring

Are you subject to benchmark monitoring requirements for a hardness-dependent metal? No

Impaired Waters Monitoring

NOTE: The information automatically populated in this section for determining if the receiving water is listed as impaired on the 303(d) list and in need of a TMDL, the cause(s) of the impairment if the receiving water is impaired on the CWA 303(d) list, if a TMDL has been completed for the receiving waterbody, and the TMDL ID and pollutants for which there is a TMDL may be outdated and inaccurate. It is recommended that you consult with your state's guidance for discharges into impaired waters to determine the correct pollutants and TMDLS and update the causes for the impairment and TMDL information accordingly.

Is the receiving water listed as impaired on the 303(d) list and in need of a TMDL? Yes

Cause of Impairment Group	Pollutant
POLYCHLORINATED BIPHENYLS (PCBS)	Poly chlorinated bipheny Is [PCBs]
METALS (OTHER THAN MERCURY)	Aluminum, total recoverable
METALS (OTHER THAN MERCURY)	Copper, dissolved [as Cu]

Has a TMDL been completed for this receiving waterbody? No

Discharge Point 021: TA-60-1 Heavy Equipment Yard SIO to 022

Applicable Sectors

Select the Sectors/Subsector(s) that apply to this discharge point.

	Sector	Subsector	SIC/Activity Code
	D - ASPHALT PAVING AND ROOFING MATERIALS AND LUBRICANTS	D1 - Asphalt Paving and Roofing Materials	2951
0	N - SCRAP RECYCLING FACILITIES	N2 - Source-separated Recycling Facility	5093
•	P - LAND TRANSPORTATION AND WAREHOUSING	P1 - Railroad Transportation; Local and Highway Passenger Transportation; Motor Freight Transportation and Warehousing; United States Postal Service; Petroleum Bulk Stations and Terminals	4212
¥	AA - FABRICATED METAL PRODUCTS	AA1 - Fabricated Metal Products, Except Machinery and Transportation Equipment, and Coating, Engraving, and Allied Services; Jewelry, Silverware, and Plated Ware	3499

Latitude/Longitude: 35.872514°N, 106.313562°W

This discharge point is Substantially Identical to an existing discharge point.

✤ Substantially Identical to Discharge Point ID: 022

Receiving Water

GNIS Name:

Waterbody Name: SANDIA CANYON (SIGMA CANYON TO NPDES OUTFALL 001) Listed Water ID: NM-9000.A_047

Is this receiving water saltwater or freshwater? Freshwater

Is this receiving water designated by the state or tribal authority under its antidegradation policy as a Tier 2 (or Tier 2.5) water (water quality exceeds levels necessary to support propagation of fish, shellfish, and wildlife and recreation in and on the water)?

No

Will you have stormwater discharges from paved surfaces that will be initially sealed or re-sealed with coal-tar sealcoat where industrial activities are located during coverage under this permit?

No

Benchmark Monitoring

Are you subject to benchmark monitoring requirements for a hardness-dependent metal? Yes

What is the hardness of your receiving water(s)? 61

(mg/L)

Impaired Waters Monitoring

NOTE: The information automatically populated in this section for determining if the receiving water is listed as impaired on the 303(d) list and in need of a TMDL, the cause(s) of the impairment if the receiving water is impaired on the CWA 303(d) list, if a TMDL has been completed for the receiving

waterbody, and the TMDL ID and pollutants for which there is a TMDL may be outdated and inaccurate. It is recommended that you consult with your state's guidance for discharges into impaired waters to determine the correct pollutants and TMDLS and update the causes for the impairment and TMDL information accordingly.

Is the receiving water listed as impaired on the 303(d) list and in need of a TMDL? Yes

Cause of Impairment Group	Pollutant
POLYCHLORINATED BIPHENYLS (PCBS)	Poly chlorinated bipheny Is [PCBs]
METALS (OTHER THAN MERCURY)	Aluminum, total recoverable
METALS (OTHER THAN MERCURY)	Copper, dissolved [as Cu]

Has a TMDL been completed for this receiving waterbody? No

Discharge Point 042: TA-60 Roads and Grounds

Applicable Sectors

Select the Sectors/Subsector(s) that apply to this discharge point.

	Sector	Subsector	SIC/Activity Code
	D - ASPHALT PAVING AND ROOFING MATERIALS AND LUBRICANTS	D1 - Asphalt Paving and Roofing Materials	2951
	N - SCRAP RECYCLING FACILITIES	N2 - Source-separated Recycling Facility	5093
2	P - LAND TRANSPORTATION AND WAREHOUSING	P1 - Railroad Transportation; Local and Highway Passenger Transportation; Motor Freight Transportation and Warehousing; United States Postal Service; Petroleum Bulk Stations and Terminals	4212
	AA - FABRICATED METAL PRODUCTS	AA1 - Fabricated Metal Products, Except Machinery and Transportation Equipment, and Coating, Engraving, and Allied Services; Jewelry, Silverware, and Plated Ware	3499

Latitude/Longitude: 35.867047°N, 106.289163°W

□ This discharge point is Substantially Identical to an existing discharge point.

Receiving Water

GNIS Name:

Waterbody Name: SANDIA CANYON (SIGMA CANYON TO NPDES OUTFALL 001) Listed Water ID: NM-9000.A_047

Is this receiving water saltwater or freshwater? Freshwater

Is this receiving water designated by the state or tribal authority under its antidegradation policy as a Tier 2 (or Tier 2.5) water (water quality exceeds levels necessary to support propagation of fish, shellfish, and wildlife and recreation in and on the water)?

No

Will you have stormwater discharges from paved surfaces that will be initially sealed or re-sealed with coal-tar sealcoat where industrial activities are located during coverage under this permit?

No

Benchmark Monitoring

Are you subject to benchmark monitoring requirements for a hardness-dependent metal? No

Impaired Waters Monitoring

NOTE: The information automatically populated in this section for determining if the receiving water is listed as impaired on the 303(d) list and in need of a TMDL, the cause(s) of the impairment if the receiving water is impaired on the CWA 303(d) list, if a TMDL has been completed for the receiving waterbody, and the TMDL ID and pollutants for which there is a TMDL may be outdated and inaccurate. It is recommended that you consult with your state's guidance for discharges into impaired waters to determine the correct pollutants and TMDLS and update the causes for the impairment and TMDL information accordingly.

Is the receiving water listed as impaired on the 303(d) list and in need of a TMDL? Yes

Cause of Impairment Group	Pollutant
METALS (OTHER THAN MERCURY)	Aluminum, total recoverable
METALS (OTHER THAN MERCURY)	Copper, dissolved [as Cu]
POLYCHLORINATED BIPHENYLS (PCBS)	Poly chlorinated bipheny Is [PCBs]

Has a TMDL been completed for this receiving waterbody? No

Discharge Point 022: TA-60-1 Heavy Equipment Yard

Applicable Sectors

Select the Sectors/Subsector(s) that apply to this discharge point.

	Sector	Subsector	SIC/Activity Code
	D - ASPHALT PAVING AND ROOFING MATERIALS AND LUBRICANTS	D1 - Asphalt Paving and Roofing Materials	2951
	N - SCRAP RECYCLING FACILITIES	N2 - Source-separated Recycling Facility	5093
¥	P - LAND TRANSPORTATION AND WAREHOUSING	P1 - Railroad Transportation; Local and Highway Passenger Transportation; Motor Freight Transportation and Warehousing; United States Postal Service; Petroleum Bulk Stations and Terminals	4212
¥	AA - FABRICATED METAL PRODUCTS	AA1 - Fabricated Metal Products, Except Machinery and Transportation Equipment, and Coating, Engraving, and Allied Services; Jewelry, Silverware, and Plated Ware	3499

Latitude/Longitude: 35.872661°N, 106.313691°W

□ This discharge point is Substantially Identical to an existing discharge point.

Receiving Water

GNIS Name:

Waterbody Name: SANDIA CANYON (SIGMA CANYON TO NPDES OUTFALL 001) Listed Water ID: NM-9000.A_047

Is this receiving water saltwater or freshwater? Freshwater

Is this receiving water designated by the state or tribal authority under its antidegradation policy as a Tier 2 (or Tier 2.5) water (water quality exceeds levels necessary to support propagation of fish, shellfish, and wildlife and recreation in and on the water)?

No

Will you have stormwater discharges from paved surfaces that will be initially sealed or re-sealed with coal-tar sealcoat where industrial activities are located during coverage under this permit?

No

Benchmark Monitoring

Are you subject to benchmark monitoring requirements for a hardness-dependent metal? Yes

✤ What is the hardness of your receiving water(s)? 61

(mg/L)

Impaired Waters Monitoring

NOTE: The information automatically populated in this section for determining if the receiving water is listed as impaired on the 303(d) list and in need of a TMDL, the cause(s) of the impairment if the receiving water is impaired on the CWA 303(d) list, if a TMDL has been completed for the receiving waterbody, and the TMDL ID and pollutants for which there is a TMDL may be outdated and inaccurate. It is recommended that you consult with your state's guidance for discharges into impaired waters to determine the correct pollutants and TMDLS and update the causes for the impairment and TMDL information accordingly.

Is the receiving water listed as impaired on the 303(d) list and in need of a TMDL? Yes

Cause of Impairment Group	Pollutant
METALS (OTHER THAN MERCURY)	Aluminum, total recoverable
POLYCHLORINATED BIPHENYLS (PCBS)	Poly chlorinated bipheny Is [PCBs]
METALS (OTHER THAN MERCURY)	Copper, dissolved [as Cu]

Has a TMDL been completed for this receiving waterbody? No

Discharge Point 025: TA-60-1 Heavy Equipment Yard SIO to 022

Applicable Sectors

Select the Sectors/Subsector(s) that apply to this discharge point.

	Sector	Subsector	SIC/Activity Code
	D - ASPHALT PAVING AND ROOFING MATERIALS AND LUBRICANTS	D1 - Asphalt Paving and Roofing Materials	2951
	N - SCRAP RECYCLING FACILITIES	N2 - Source-separated Recycling Facility	5093
۷	P - LAND TRANSPORTATION AND WAREHOUSING	P1 - Railroad Transportation; Local and Highway Passenger Transportation; Motor Freight Transportation and Warehousing; United States Postal Service; Petroleum Bulk Stations and Terminals	4212

	AA - FABRICATED METAL PRODUCTS	AA1 - Fabricated Metal Products, Except Machinery and Coating, Engraving, and Allied Services; Jewelry, Silvery		3499
atitu	ide/Longitude: 35.872928°N, 10	6.3154°W		
¦ Thi	is discharge point is Substanti	ally Identical to an existing discharge point.		
*	Substantially Identical to Disc	narge Point ID: 022		
Rec	eiving Water			
GNIS	Name:	Waterbody Name: SANDIA CANYON (SIGMA CANYON TO NPDES OUTFALL 001)	Listed Water ID: NM-9000.A_047	
s thi	s receiving water saltwater or f	reshwater? Freshwater		
		y the state or tribal authority under its antidegradation p propagation of fish, shellfish, and wildlife and recreation		vater (water quali
No				
-	you have stormwater discharge ties are located during coverag	s from paved surfaces that will be initially sealed or re-so ge under this permit?	ealed with coal-tar sealcoat wh	nere industrial

Benchmark Monitoring

Are you subject to benchmark monitoring requirements for a hardness-dependent metal? Yes

✤ What is the hardness of your receiving water(s)? 61

(mg/L)

Impaired Waters Monitoring

NOTE: The information automatically populated in this section for determining if the receiving water is listed as impaired on the 303(d) list and in need of a TMDL, the cause(s) of the impairment if the receiving water is impaired on the CWA 303(d) list, if a TMDL has been completed for the receiving waterbody, and the TMDL ID and pollutants for which there is a TMDL may be outdated and inaccurate. It is recommended that you consult with your state's guidance for discharges into impaired waters to determine the correct pollutants and TMDLS and update the causes for the impairment and TMDL information accordingly.

Is the receiving water listed as impaired on the 303(d) list and in need of a TMDL? Yes

Cause of Impairment Group	Pollutant
METALS (OTHER THAN MERCURY)	Aluminum, total recoverable
POLYCHLORINATED BIPHENYLS (PCBS)	Poly chlorinated bipheny Is [PCBs]
METALS (OTHER THAN MERCURY)	Copper, dissolved [as Cu]

Has a TMDL been completed for this receiving waterbody? No

Applicable Sectors

Select the Sectors/Subsector(s) that apply to this discharge point.

	Sector	Subsector	SIC/Activity Code
	D - ASPHALT PAVING AND ROOFING MATERIALS AND LUBRICANTS	D1 - Asphalt Paving and Roofing Materials	2951
0	N - SCRAP RECYCLING FACILITIES	N2 - Source-separated Recycling Facility	5093
¥	P - LAND TRANSPORTATION AND WAREHOUSING	P1 - Railroad Transportation; Local and Highway Passenger Transportation; Motor Freight Transportation and Warehousing; United States Postal Service; Petroleum Bulk Stations and Terminals	4212
	AA - FABRICATED METAL PRODUCTS	AA1 - Fabricated Metal Products, Except Machinery and Transportation Equipment, and Coating, Engraving, and Allied Services; Jewelry, Silverware, and Plated Ware	3499

Latitude/Longitude: 35.872114°N, 106.313105°W

□ This discharge point is Substantially Identical to an existing discharge point.

Receiving Water

GNIS Name:

Waterbody Name: SANDIA CANYON (SIGMA CANYON TO NPDES OUTFALL 001) Listed Water ID: NM-9000.A_047

Is this receiving water saltwater or freshwater? Freshwater

Is this receiving water designated by the state or tribal authority under its antidegradation policy as a Tier 2 (or Tier 2.5) water (water quality exceeds levels necessary to support propagation of fish, shellfish, and wildlife and recreation in and on the water)? No

Will you have stormwater discharges from paved surfaces that will be initially sealed or re-sealed with coal-tar sealcoat where industrial activities are located during coverage under this permit?

No

Benchmark Monitoring

Are you subject to benchmark monitoring requirements for a hardness-dependent metal? No

Impaired Waters Monitoring

NOTE: The information automatically populated in this section for determining if the receiving water is listed as impaired on the 303(d) list and in need of a TMDL, the cause(s) of the impairment if the receiving water is impaired on the CWA 303(d) list, if a TMDL has been completed for the receiving waterbody, and the TMDL ID and pollutants for which there is a TMDL may be outdated and inaccurate. It is recommended that you consult with your state's guidance for discharges into impaired waters to determine the correct pollutants and TMDLS and update the causes for the impairment and TMDL information accordingly.

Is the receiving water listed as impaired on the 303(d) list and in need of a TMDL? Yes

Cause of Impairment Group	Pollutant
---------------------------	-----------

METALS (OTHER THAN MERCURY) Aluminum, total recoverable METALS (OTHER THAN MERCURY) Copper, dissolved [as Cu]	POLYCHLORINATED BIPHENYLS (PCBS)	Poly chlorinated bipheny Is [PCBs]
METALS (OTHER THAN MERCURY) Copper, dissolved [as Cu]	METALS (OTHER THAN MERCURY)	Aluminum, total recoverable
	METALS (OTHER THAN MERCURY)	Copper, dissolved [as Cu]

Has a TMDL been completed for this receiving waterbody? No

Discharge Point 037: TA-60 Roads and Grounds

Applicable Sectors

Select the Sectors/Subsector(s) that apply to this discharge point.

	Sector	Subsector	SIC/Activity Code
	D - ASPHALT PAVING AND ROOFING MATERIALS AND LUBRICANTS	D1 - Asphalt Paving and Roofing Materials	2951
	N - SCRAP RECYCLING FACILITIES	N2 - Source-separated Recycling Facility	5093
¥	P - LAND TRANSPORTATION AND WAREHOUSING	P1 - Railroad Transportation; Local and Highway Passenger Transportation; Motor Freight Transportation and Warehousing; United States Postal Service; Petroleum Bulk Stations and Terminals	4212
	AA - FABRICATED METAL PRODUCTS	AA1 - Fabricated Metal Products, Except Machinery and Transportation Equipment, and Coating, Engraving, and Allied Services; Jewelry, Silverware, and Plated Ware	3499

Latitude/Longitude: 35.867859°N, 106.292992°W

□ This discharge point is Substantially Identical to an existing discharge point.

Receiving Water

GNIS Name:

Waterbody Name: SANDIA CANYON (SIGMA CANYON TO NPDES OUTFALL 001) Listed Water ID: NM-9000.A_047

Is this receiving water saltwater or freshwater? Freshwater

Is this receiving water designated by the state or tribal authority under its antidegradation policy as a Tier 2 (or Tier 2.5) water (water quality exceeds levels necessary to support propagation of fish, shellfish, and wildlife and recreation in and on the water)?

No

Will you have stormwater discharges from paved surfaces that will be initially sealed or re-sealed with coal-tar sealcoat where industrial activities are located during coverage under this permit?

No

Benchmark Monitoring

Are you subject to benchmark monitoring requirements for a hardness-dependent metal? No

Impaired Waters Monitoring

NOTE: The information automatically populated in this section for determining if the receiving water is listed as impaired on the 303(d) list and in need of a TMDL, the cause(s) of the impairment if the receiving water is impaired on the CWA 303(d) list, if a TMDL has been completed for the receiving waterbody, and the TMDL ID and pollutants for which there is a TMDL may be outdated and inaccurate. It is recommended that you consult with your state's guidance for discharges into impaired waters to determine the correct pollutants and TMDLS and update the causes for the impairment and TMDL information accordingly.

Is the receiving water listed as impaired on the 303(d) list and in need of a TMDL? Yes

Cause of Impairment Group	Pollutant
METALS (OTHER THAN MERCURY)	Aluminum, total recoverable
POLYCHLORINATED BIPHENYLS (PCBS)	Poly chlorinated bipheny Is [PCBs]
METALS (OTHER THAN MERCURY)	Copper, dissolved [as Cu]

Has a TMDL been completed for this receiving waterbody? No

Discharge Point 076: TA-3-38 Metals Fab Shop

Applicable Sectors

Select the Sectors/Subsector(s) that apply to this discharge point.

	Sector	Subsector	SIC/Activity Code
	D - ASPHALT PAVING AND ROOFING MATERIALS AND LUBRICANTS	D1 - Asphalt Paving and Roofing Materials	2951
	N - SCRAP RECYCLING FACILITIES	N2 - Source-separated Recy cling Facility	5093
¥	AA - FABRICATED METAL PRODUCTS	AA1 - Fabricated Metal Products, Except Machinery and Transportation Equipment, and Coating, Engraving, and Allied Services; Jewelry, Silverware, and Plated Ware	3499
D	P - LAND TRANSPORTATION AND WAREHOUSING	P1 - Railroad Transportation; Local and Highway Passenger Transportation; Motor Freight Transportation and Warehousing; United States Postal Service; Petroleum Bulk Stations and Terminals	4212

Latitude/Longitude: 35.875851°N, 106.327924°W

□ This discharge point is *Substantially Identical* to an existing discharge point.

Receiving Water

GNIS Name:

Waterbody Name: SANDIA CANYON (SIGMA CANYON TO NPDES OUTFALL 001) Listed Water ID: NM-9000.A_047

Is this receiving water saltwater or freshwater? Freshwater

Is this receiving water designated by the state or tribal authority under its antidegradation policy as a Tier 2 (or Tier 2.5) water (water quality exceeds levels necessary to support propagation of fish, shellfish, and wildlife and recreation in and on the water)? No

Will you have stormwater discharges from paved surfaces that will be initially sealed or re-sealed with coal-tar sealcoat where industrial activities are located during coverage under this permit?

Benchmark Monitoring

Are you subject to benchmark monitoring requirements for a hardness-dependent metal? Yes

✤ What is the hardness of your receiving water(s)? 61

(mg/L)

Impaired Waters Monitoring

NOTE: The information automatically populated in this section for determining if the receiving water is listed as impaired on the 303(d) list and in need of a TMDL, the cause(s) of the impairment if the receiving water is impaired on the CWA 303(d) list, if a TMDL has been completed for the receiving waterbody, and the TMDL ID and pollutants for which there is a TMDL may be outdated and inaccurate. It is recommended that you consult with your state's guidance for discharges into impaired waters to determine the correct pollutants and TMDLS and update the causes for the impairment and TMDL information accordingly.

Is the receiving water listed as impaired on the 303(d) list and in need of a TMDL? Yes

Cause of Impairment Group	Pollutant						
POLYCHLORINATED BIPHENYLS (PCBS)	Poly chlorinated bipheny Is [PCBs]						
METALS (OTHER THAN MERCURY)	Aluminum, total recoverable						
METALS (OTHER THAN MERCURY)	Copper, dissolved [as Cu]						

Has a TMDL been completed for this receiving waterbody? No

Discharge Point 077: TA-3-38 Metals Fab Shop

Applicable Sectors

Select the Sectors/Subsector(s) that apply to this discharge point.

	Sector	Subsector	SIC/Activity Code
	D - ASPHALT PAVING AND ROOFING MATERIALS AND LUBRICANTS	D1 - Asphalt Paving and Roofing Materials	2951
	N - SCRAP RECYCLING FACILITIES	N2 - Source-separated Recycling Facility	5093
¥	AA - FABRICATED METAL PRODUCTS	AA1 - Fabricated Metal Products, Except Machinery and Transportation Equipment, and Coating, Engraving, and Allied Services; Jewelry, Silverware, and Plated Ware	3499
	P - LAND TRANSPORTATION AND WAREHOUSING	P1 - Railroad Transportation; Local and Highway Passenger Transportation; Motor Freight Transportation and Warehousing; United States Postal Service; Petroleum Bulk Stations and Terminals	4212

Latitude/Longitude: 35.869722°N, 106.300833°W

□ This discharge point is Substantially Identical to an existing discharge point.

Receiving Water

GNIS Name:

Waterbody Name: SANDIA CANYON (SIGMA CANYON TO NPDES OUTFALL 001) Listed Water ID: NM-9000.A_047

Is this receiving water saltwater or freshwater? Freshwater

Is this receiving water designated by the state or tribal authority under its antidegradation policy as a Tier 2 (or Tier 2.5) water (water quality exceeds levels necessary to support propagation of fish, shellfish, and wildlife and recreation in and on the water)? No

Will you have stormwater discharges from paved surfaces that will be initially sealed or re-sealed with coal-tar sealcoat where industrial activities are located during coverage under this permit?

No

Benchmark Monitoring

Are you subject to benchmark monitoring requirements for a hardness-dependent metal? Yes

What is the hardness of your receiving water(s)? 61

(mg/L)

Impaired Waters Monitoring

NOTE: The information automatically populated in this section for determining if the receiving water is listed as impaired on the 303(d) list and in need of a TMDL, the cause(s) of the impairment if the receiving water is impaired on the CWA 303(d) list, if a TMDL has been completed for the receiving waterbody, and the TMDL ID and pollutants for which there is a TMDL may be outdated and inaccurate. It is recommended that you consult with your state's guidance for discharges into impaired waters to determine the correct pollutants and TMDLS and update the causes for the impairment and TMDL information accordingly.

Is the receiving water listed as impaired on the 303(d) list and in need of a TMDL? Yes

Cause of Impairment Group	Pollutant						
POLYCHLORINATED BIPHENYLS (PCBS)	Poly chlorinated bipheny Is [PCBs]						
METALS (OTHER THAN MERCURY)	Aluminum, total recoverable						
METALS (OTHER THAN MERCURY)	Copper, dissolved [as Cu]						

Has a TMDL been completed for this receiving waterbody? No

Discharge Point 078: TA-16 Stockpile Yard

Applicable Sectors

Select the Sectors/Subsector(s) that apply to this discharge point.

SIC/Activity

	Sector	Subsector	Code
	D - ASPHALT PAVING AND ROOFING MATERIALS AND LUBRICANTS	D1 - Asphalt Paving and Roofing Materials	2951
	N - SCRAP RECYCLING FACILITIES	N2 - Source-separated Recycling Facility	5093
	AA - FABRICATED METAL PRODUCTS	AA1 - Fabricated Metal Products, Except Machinery and Transportation Equipment, and Coating, Engraving, and Allied Services; Jewelry, Silverware, and Plated Ware	3499
⊻	P - LAND TRANSPORTATION AND WAREHOUSING	P1 - Railroad Transportation; Local and Highway Passenger Transportation; Motor Freight Transportation and Warehousing; United States Postal Service; Petroleum Bulk Stations and Terminals	4212

Latitude/Longitude: 35.846944°N, 106.344722°W

□ This discharge point is Substantially Identical to an existing discharge point.

Receiving Water

GNIS Name:

Waterbody Name: CAOON DE VALLE (BELOW LANL GAGE E256)

Listed Water ID: NM-128.A_01

Is this receiving water saltwater or freshwater? Freshwater

Is this receiving water designated by the state or tribal authority under its antidegradation policy as a Tier 2 (or Tier 2.5) water (water quality exceeds levels necessary to support propagation of fish, shellfish, and wildlife and recreation in and on the water)? No

Will you have stormwater discharges from paved surfaces that will be initially sealed or re-sealed with coal-tar sealcoat where industrial activities are located during coverage under this permit?

No

Benchmark Monitoring

Are you subject to benchmark monitoring requirements for a hardness-dependent metal? No

Impaired Waters Monitoring

NOTE: The information automatically populated in this section for determining if the receiving water is listed as impaired on the 303(d) list and in need of a TMDL, the cause(s) of the impairment if the receiving water is impaired on the CWA 303(d) list, if a TMDL has been completed for the receiving waterbody, and the TMDL ID and pollutants for which there is a TMDL may be outdated and inaccurate. It is recommended that you consult with your state's guidance for discharges into impaired waters to determine the correct pollutants and TMDLS and update the causes for the impairment and TMDL information accordingly.

Is the receiving water listed as impaired on the 303(d) list and in need of a TMDL? Yes

Cause of Impairment Group	ļi.	Pollutant
RADIATION		Alpha, gross adjusted

Has a TMDL been completed for this receiving waterbody? No

Applicable Sectors

Select the Sectors/Subsector(s) that apply to this discharge point.

	Sector	Subsector	SIC/Activity Code
	D - ASPHALT PAVING AND ROOFING MATERIALS AND LUBRICANTS	D1 - Asphalt Paving and Roofing Materials	2951
	N - SCRAP RECYCLING FACILITIES	N2 - Source-separated Recycling Facility	5093
¥	AA - FABRICATED METAL PRODUCTS	AA1 - Fabricated Metal Products, Except Machinery and Transportation Equipment, and Coating, Engraving, and Allied Services; Jewelry, Silverware, and Plated Ware	3499
	P - LAND TRANSPORTATION AND WAREHOUSING	P1 - Railroad Transportation; Local and Highway Passenger Transportation; Motor Freight Transportation and Warehousing; United States Postal Service; Petroleum Bulk Stations and Terminals	4212

Latitude/Longitude: 35.85678°N, 106.345631°W

□ This discharge point is Substantially Identical to an existing discharge point.

Receiving Water

GNIS Name:

Waterbody Name: ARROYO DE LA DELFE (PAJARITO CANYON TO HEADWATERS) Listed Water ID: NM-128.A_16

Is this receiving water saltwater or freshwater? Freshwater

Is this receiving water designated by the state or tribal authority under its antidegradation policy as a Tier 2 (or Tier 2.5) water (water quality exceeds levels necessary to support propagation of fish, shellfish, and wildlife and recreation in and on the water)? No

Will you have stormwater discharges from paved surfaces that will be initially sealed or re-sealed with coal-tar sealcoat where industrial activities are located during coverage under this permit?

No

Benchmark Monitoring

Are you subject to benchmark monitoring requirements for a hardness-dependent metal? Yes

✤ What is the hardness of your receiving water(s)? 28

(mg/L)

Impaired Waters Monitoring

NOTE: The information automatically populated in this section for determining if the receiving water is listed as impaired on the 303(d) list and in need of a TMDL, the cause(s) of the impairment if the receiving water is impaired on the CWA 303(d) list, if a TMDL has been completed for the receiving waterbody, and the TMDL ID and pollutants for which there is a TMDL may be outdated and inaccurate. It is recommended that you consult with your state's guidance for discharges into impaired waters to determine the correct pollutants and TMDLS and update the causes for the impairment and TMDL information accordingly.

Cause of Impairment Group	Pollutant								
POLYCHLORINATED BIPHENYLS (PCBS)	Poly chlorinated bipheny Is [PCBs]								
METALS (OTHER THAN MERCURY)	Aluminum, total recoverable								
METALS (OTHER THAN MERCURY)	Copper, dissolved [as Cu]								
RADIATION Alpha, gross adjusted									
Has a TMDL been completed for this receiving waterbody? <u>No</u>									
SWPPP Information									
Has the SWPPP been prepared in advance of filing this NOI, as requir	ed? Yes								
SWPPP Contact Information:									
First Name Middle Initial Last Name: Holly Wheeler									
Phone: 5056671312 Ext.:									
Email: hbenson@lanl.gov									
SWPPP Availability:									
Your current SWPPP or certain information from your SWPPP must be mad options and provide the required information.	e available through one of the following three options. Select one of the								
Note: you are not required to post any confidential business informat (https://www.epa.gov/sites/production/files/2021-01/documents/2021_n redacted), but you must clearly identify those portions of the SWPPP	nsgpappendix_adefinitions.pdf)) (such information may be								
□ Option 1: Attach a current copy of your SWPPP to this NOI.									
☑ Option 2: Maintain a Current Copy of your SWPPP on an Internet pa	age (Universal Resource Locator or URL).								
Provide the web address URL (e.g. http://www.example.com): https://e	prr.lanl.gov								
□ Option 3: Provide the following information from your SWPPP:									
Endangered Species Protection Worksheet: Criterion D									
The following questions will help you determine your eligibility under Species Act (ESA) species and critical habitat(s). Please refer to Append 01/documents/2021_msgpappendix_eprocedures_relating_to_en- information regarding your obligations under this permit concerning	dix E (https://www.epa.gov/sites/production/files/2021- dangered_species_protection.pdf) of the 2021 MSGP for important								
Determine ESA Eligibility Criterion									

Are your industrial activities already addressed in another operator's valid certification of eligibility for your "action area" under eligibility criteria A, C, D, or E of the 2021 MSGP?

Has consultation between you, a Federal Agency, and the USFWS and/or the NMFS under section 7 of the Endangered Species Act (ESA) concluded?

Consultations can be either formal or informal, and would have occurred only as a result of a separate federal action (e.g., during application for an individual wastewater discharge permit or the issuance of a wetlands dredge and fill permit), and the consultation must have addressed the effects of your industrial activity's discharges and discharge-related activities on ESA-listed species and/or critical habitat under the jurisdiction of USFWS and/or NMFS in your action area.

Yes

- The result of the consultation was either:
 - i. A biological opinion and/or conference opinion that concludes that the action in question (taking into account the effects of your facility's discharges and discharge-related activities) is not likely to jeopardize the continued existence of ESA-listed species or result in the destruction or adverse modification of critical habitat. The biological opinion and/or conference opinion must have included the effects of your facility's discharges and discharge-related activities on all the listed species and critical habitat in your action area. To be eligible under (i), any reasonable and prudent measures specified in the incidental take statement must be implemented;
 - ii. Written concurrence (e.g., letter of concurrence) from the applicable Service(s) with a finding that your facility's discharges and discharge-related activities are not likely to adversely affect ESA-listed species or critical habitat. The concurrence letter must have included the effects of your facility's discharges and discharge-related activities on all the ESA-listed species and/or critical habitat on your species list(s) acquired from the USFWS and/or the NMFS as part of this worksheet.

True

The consultation does not warrant reinitiation under 50 CFR §402.16; or, if reinitiation of consultation is required (e.g., due to a new species listing or critical habitat designation; new information), you have reinitiated the consultation and the result of the consultation is consistent with the statements above.

True

You are eligible under Criterion D

Identify the federal action agency(ies) involved:

☑ U.S. Fish and Wildlife Services

□ National Marine Fisheries Service

Provide the field office/regional office(s) providing that consultation and any tracking numbers of identifiers associated with that consultation (e.g., IPaC number, ECO number):

New Mexico Ecological Services Field Office, Cons. # 2-22-98-I-336, Cons. # 2-22-95-I-10 8, Cons. # 02ENNM00-2014-I-0014, Cons. # 02ENNM00-2015-I-0538

Provide the date the consultation was completed: 08/06/2015

You must attach copies of any letters or other communications with the USFWS or NMFS:

Name	Uploaded Date	Size
▲ 1999 HMP Concurrence Letter USFWS to DOE.pdf (attachment/712061)	05/19/2021	276.65 KB
2015-0538_USFWS Concurrence Letter_8-2015.pdf (attachment/712062)	05/19/2021	94.97 KB
Concurrence_8DEC2013_Biological Assessment of Jemez Mtn Salamander site Plan (2).pdf (attachment/712063)	05/19/2021	239.87 KB

Historic Preservation: Criterion B

The following questions will help you determine your eligibility under Part 1.1.5 of the permit with respect to preservation of historic properties. You may still use the paper instructions in Appendix F (https://www.epa.gov/sites/production/files/2021-01/documents/2021_msgp_-appendix_f_-procedures_relating_to_historic_properties_preservation.pdf) of the MSGP in advance or in conjunction with answering the questions in this section of the form. For more information about your State Historic Preservation Office (SHPO) or Tribal Historic Preservation Office (THPO), please visit the National Park Service (NPS) websites at:

- State Historic Preservation Office (SHPO) (https://www.nps.gov/subjects/nationalregister/state-historic-preservation-offices.htm)
- Tribal Historic Preservation Office (THPO) (https://www.nps.gov/history/tribes/Tribal_Historic_Preservation_Officers_Program.htm)

Are you an existing facility that is resubmitting for certification under the 2021 MSGP? Yes

If you are an existing facility you should have already addressed National Historic Preservation Act (NHPA) issues. To gain coverage under the 2015 MSGP, you were required to certify that you were either not affecting historic properties or had obtained written agreement from the relevant SHPO or THPO regarding methods of mitigating potential impacts.

Will you be constructing or installing any <u>new</u> stormwater control measures? Yes

✤ Will the stormwater control measures you are constructing or installing disturb subsurface less than one (1) acre? Yes

Have prior earth disturbances determined that historic properties do not exist, or have prior disturbances precluded the existence of historic properties?

Yes

You are eligible under Criterion B.

Certification Information

I certify under penalty of law that this document and all attachments were prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gathered and evaluated the information submitted. Based on my inquiry of the person or persons who manage the system, or those persons directly responsible for gathering the information, the information submitted is, to the best of my knowledge and belief, true, accurate, and complete. I have no personal knowledge that the information submitted is other than true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment for knowing violations. Signing an electronic document on behalf of another person is subject to criminal, civil, administrative, or other lawful action.

Certified By: Jennifer payne

Certifier Title: Division Leader

Certifier Email: jpay ne@lanl.gov

Certified On: 05/26/2021 5:41 PM ET



United States Department of the Interior

FISH AND WILDLIFE SERVICE

New Mexico Ecological Services Field Office 2105 Osuna NE Albuquerque, New Mexico 87113 Phone: (505) 346-2525 Fax: (505) 346-2542

February 12, 1999

Cons. #2-22-98-I-336 Cons. #2-22-95-I-108

David A. Gurule, Acting Area Manager Department of Energy Albuquerque Operations Office Los Alamos Area Office Los Alamos, New Mexico 87545

Dear Mr. Gurule:

This responds to your letter dated August 6, 1998, requesting our review and concurrence with the Threatened and Endangered Species Habitat Management Plan (HMP) for Los Alamos National Laboratory (LANL). The HMP was prepared by the LANL Ecology Group for the Department of Energy (DOE) as part of the Dual-Axis Radiographic Hydrodynamics Test Facility (DAHRT) Mitigation Action Plan. The U.S. Fish and Wildlife Service (Service) has worked closely with LANL in the development of the HMP. As a result of discussions and meetings following the August 6, 1998, submittal, additional information/clarification was provided via letters, updated Biological Evaluations/HMPs, and e-mail messages, dated September 8, October 20, November 25, and December 9, 1998, and January 4, January 22, and January 29, 1999. The purpose of the HMP is to provide for the protection of threatened and endangered species and their habitats on LANL. The HMP consists of three components that must be used together to assure proper management of the threatened and endangered species: an Overview Document, Site Plans, and Monitoring Plans. It was determined that if all the restrictions and protective measures outlined in the HMP are strictly followed, the implementation of this HMP may affect, but is not likely to adversely affect the Mexican spotted owl (owl), peregrine falcon (falcon), bald eagle (eagle), and southwestern willow flycatcher (flycatcher). The Biological Evaluation (BE) also considered potential impacts on the black-footed ferret, arctic peregrine falcon, and whooping crane. It was determined that there would be no effect on these species because of a lack of habitat.

Property at LANL varies from remote isolation to heavily developed and/or industrialized. The Service agrees, as stated in the Overview document, that a number of activities at LANL have the potential to adversely impact threatened and endangered species. Many of the industrial processes used at LANL have involved hazardous and radioactive materials. These materials as well as remediation of potential release sites may disturb

David A. Gurule, Acting Area Manager

or reduce population viability of threatened and endangered species. In addition, other potential sources of disturbance or habitat alterations are possible as a result of the residential and commercial development in the LANL area. While the HMP identifies potential sources of adverse effects, this consultation does not necessarily cover all of those impacts. The Service does not anticipate that DOE will be able to plan all of its operations at LANL in accordance with this plan. The direct effects of most actions can be minimized through implementation of the HMP; however, a more thorough assessment is necessary to adequately evaluate the indirect and cumulative impacts of all actions that are funded, authorized, and permitted by DOE, as well as potential impacts from interrelated and interdependent actions. It was agreed (by Service, DOE, and LANL personnel) that consultation concerning ongoing LANL operations would be handled separately from the HMP, under the consultation on the Site-Wide EIS.

The Site Plans identify the particular areas of LANL where operations might impact known occupied or potential habitat for the flycatcher, eagle, falcon, and owl. Suitable habitat for these species, along with protective buffer areas surrounding their habitat, have been designated as Areas of Environmental Interest (AEIs). For the flycatcher, one AEI was established based on an observation of a migrant male flycatcher in 1997. The AEI is located in the Pajarito wetland area and includes the best available riparian habitat. For eagles, one AEI has been identified for wintering habitat that exists along the Rio Grande on the eastern edge of LANL. It is based on the locations of known and potential roost sites. For the falcon, four AEIs have been identified. They consist of the habitat previously identified under the 1985 interagency agreement. These areas are centered on deep canyons on the eastern side of LANL or on adjacent lands. LANL has agreed to implement the recommended management guidelines, which utilize four management zones (A through D) to protect nesting peregrine falcons from disturbance. For the owl, six AEIs have been identified, but only one of these sites is known to be occupied. These AEIs are based on and located in canyons that have been defined as suitable nest/roost habitat.

The AEI management section of each Site Plan provides guidelines for LANL operations to reduce or eliminate threats to each species. The primary threats on LANL property are (1) impacts on habitat quality from LANL operations and (2) disturbance of nesting or roosting birds. The site plans provide information on their location and guidelines for their management. The AEI Site Plans consist of a species description, descriptions of the AEIs for the species, descriptions of current impacts in the AEIs, management plans that describe allowable activities within core and buffer areas under the guidelines of the sites plan and protective measures. Activities discussed in the site plans include day to day activities, such as access into an AEI, as well as long-term projects, such as levels of habitat alteration in the buffer area of an AEI. Restrictions will be implemented on activities that could cause disturbance (people, vehicles and machinery, aircraft, light production, and noise) within occupied AEIs. The location of a potential disturbance activity within the AEI, the occupancy status of the AEI, and the type of activity all affect whether or not an activity is allowable. Habitat alterations are always restricted in core areas, but a limited amount of future development is allowed in currently undeveloped DOE-controlled buffer areas under the guidelines of this site plan as long

David A. Gurule, Acting Area Manager

as it does not alter habitat in the undeveloped AEI (including light and noise guidelines). The purpose of buffer areas is to protect core areas from undue disturbance or habitat alteration or habitat degradation. Each AEI is specific to the situation or circumstances of the site it covers. According to the HMP, development beyond the cap established for each AEI, or greater than 2 hectares in size, including the developed-area border, requires independent review for ESA compliance.

Varying amounts of development and/or ongoing activities exist in the cores and buffers of each AEI. These developments may include residential, commercial, and light industrial areas, as well as roads and utility corridors. Existing/ongoing activities may include periodic scientific surveys, power line maintenance, recreational use, residential development, ER Program activities, and possible use of a firing site. Potential disturbance may be associated with automobile and truck traffic, construction activities, a live-fire range, explosives testing, and aircraft traffic at the County airport. Ongoing activities in developed areas constitute a baseline condition for the AEIs and are not restricted. New activities including further development within already existing developed areas are not restricted unless they impact undeveloped portions of an AEI core. If a proposed action within a developed area does not meet site plan guidelines, it must be individually reviewed for ESA compliance.

Some activities such as utility corridor maintenance, fuels management, and a limited amount of development are allowed in each AEI (as described in the HMP). The potential impacts of these activities are considered to be insignificant or discountable because they will occur in habitat that has been previously disturbed or is of poor quality due to its size or proximity to already developed areas. It is our understanding (based on the January 22, 1999, e-mail response from Terry Foxx) that the fuels management activities within the owl AEIs will only consist of ongoing and proposed fire protection activities around existing facilities (e.g. thinning around buildings) or those activities that are already covered under the Dome Fire Emergency BA. The other fire management activities mentioned in the HMP will go through the ESH-ID process and further consultation with the Service when a fire management plan is completed in the future.

In general, activities that detrimentally alter habitat in an AEI or would cause unacceptable disturbance to the species inhabiting the AEI are not allowed under the guidelines of a Site Plan. The Site Plans are designed to minimize impacts to threatened and endangered species and their habitat. The protective measures and restrictions outlined in the Site Plans were developed using the best available data, in cooperation with Service biologists.

The U.S. Fish and Wildlife Service concurs with DOE's determination that implementation of LANL's HMP may affect, but is not likely to adversely affect the Mexican spotted owl, American peregrine falcon, bald eagle, and southwestern willow flycatcher based on the protective measures described in the BA and HMP. If all the restrictions and protective measures outlined in the HMP are strictly followed, potential impacts on owls, falcons, eagles, and flycatchers are expected to be insignificant or

David A. Gurule, Acting Area Manager

discountable for the following reasons: 1) appropriate seasonal restrictions will be implemented to avoid disturbance to potentially breeding flycatchers, peregrines, and owls and wintering eagles; 2) no nest or roost habitat for any listed species will be altered; 3) the total amount of potential foraging habitat that could be impacted within each species home ranges is expected to be insignificant compared to the amount of available foraging habitat throughout the area; 4) monitoring plans have been developed as an integral part of the HMP; and 5) a mechanism for incorporating necessary technical and regulatory changes and updating the HMP has been included (page 32 of the Overview Document).

In future communications regarding this project, please refer to Consultation #2-22-98-I-336. If we can be of further assistance, please contact Carol Torrez of my staff at (505) 346-2525, ext. 115.

Sincerely,

lennifer Fowler-Props Field Supervisor

cc:

Teralene Foxx, Project Manager, Ecology Group, Los Alamos National Laboratory, P.O. Box 1663, Mail Stop M887, Los Alamos, New Mexico 87545

Elizabeth Withers, U.S. Department of Energy, Los Alamos Area Office, 35th Street, Los Alamos, New Mexico

Field Supervisor, Ecological Services, U.S. Fish and Wildlife Service, Phoenix, Arizona



United States Department of the Interior

FISH AND WILDLIFE SERVICE New Mexico Ecological Services Field Office 2105 Osuna NE Albuquerque, New Mexico 87113 Phone: (505) 346-2525 Fax: (505) 346-2542

December 9, 2013

Cons. #02ENNM00-2014-I-0014

Geoffrey L. Beausoleil, Acting Manager National Nuclear Security Administration, Los Alamos Field Office Department of Energy Los Alamos, New Mexico 87544

Dear Mr. Beausoleil:

Thank you for your biological assessment entitled, "Biological Assessment of the Effects of Implementing the Jemez Mountains Salamander Site Plan on Federally Listed Threatened and Endangered Species at Los Alamos National Laboratory" (BA); the request for informal consultation and conferencing received on July 25, 2013 and supplemental information supplied in the "Jemez Mountains Salamander (Plethodon neomexicanus) Los Alamos National Laboratory (LANL) Site Plan" (Site Plan); and emails dated November 19 and December 3, 2013. The Department of Energy (DOE) requested concurrence with the determination of effects for the endangered Jemez Mountains salamander (Plethodon neomexicanus) (salamander) pursuant to Section 7(a)(2) of the Endangered Species Act of 1973 (ESA), as amended (16 U.S.C. § 1531 et seq.). Your proposed action consists of implementing the Site Plan, and includes of the incorporation of this Site Plan into LANL's Habitat Management Plan (HMP). The HMP was consulted upon in 1999 (Consultation #2-22-981-336) as the primary mechanism to ensure compliance with the ESA at LANL. The actions described in the Site Plan and analyzed in the BA, and supplemental emails are hereby incorporated by reference. You determined that implementing the Site Plan "may affect, is not likely to adversely affect" the salamander, and includes placing restrictions on certain types of work in areas identified as core habitat for the salamander on LANL property with the purpose of ensuring that effects to the salamander from those actions identified in the Site Plan are insignificant and discountable.

The Site Plan does not include any areas within designated salamander critical habitat, indicating that no critical habitat will be affected. The Site Plan has modeled and field validated the model to identify the areas on LANL property with the highest potential to be occupied by salamanders based on habitat features for the salamander. Each area identified by the modeling is termed "Area of Environmental Interest" (AEI) and consists of a "core area" and a "buffer area". The core area habitat is defined as suitable habitat where the salamander occurs or may occur at LANL. The core area habitat consists of sections of north-facing slope that contain the required

Geoffrey L. Beausoleil, Acting Manager

micro-habitat to support salamanders. The buffer area is 328 feet (100 meters) wide extending outward from the edge of the core area. Only the Los Alamos Canyon AEI is known to be occupied based on surveys. Surveys for the salamander are known to have a very low detection rate for occupied areas and DOE has assumed that all AEIs at LANL are occupied at all times by the salamander.

Within the Site Plan, DOE has assessed activities that could cause habitat alteration and includes any action that alters the soil structure, vegetative components necessary to the species, water quality, or hydrology in undeveloped areas of an AEI. If an activity were to take place outside of the AEI the activity will be assessed if it will have effects inside the AEI core. Within the core areas, only activities specified within the Site Plan and those that have no effect in the core areas (e.g. no habitat alterations or effects within the core areas) will be conducted without further consultation with the Service. Habitat alterations also include soil pits for soil samples deeper than 6 inches (15.2 centimeters) using either hand or mechanized augers. Within the Site Plan, DOE is proposing fuels management practices to reduce wildfire risk and maintenance of utility corridors within the AEIs. The likelihood that salamanders may be affected by the actions in the Site Plan is very low. To ensure that effects to the salamander are insignificant and discountable, the Site Plan incorporates the following conservation measures as restrictions to the identified work:

Fuels Management Practices to Reduce Wildfire Risk

- a. Within undeveloped core areas, thinning trees to a level of 80% canopy cover or higher may occur; tree thinning below 80% canopy cover is not part of the action under this consultation.
- b. Large logs on the ground will be left in place and not chipped.
- c. Large trees that are felled will be left as large logs on the ground
- d. When appropriate, smaller trees and understory shrubs that may be thinned will be dispersed and left on-site to aid in soil moisture retention.
- e. In buffer areas, thinning of trees may occur to the current LANL-approved prescription level; clear-cutting will not occur.
- f. Thinning activities will not occur during the rainy season when salamanders are surface active, between July 1 – October 31. Thinning activities may occur earlier in October if freezing temperatures are present.
- g. In the unlikely event that a salamander is observed surface active during thinning activities, all activities shall cease, and the Service will be notified.

Utility Corridors

- a. Cutting trees that threaten power lines may occur within 26 feet (8 meters) of either side of an existing utility line at LANL
- b. New utility lines and utility lines requiring clearance of a right-of-way greater than 52 feet (16 meters) total in core habitat is not part of the action under this consultation.

Geoffrey L. Beausoleil, Acting Manager

Habitat alterations other than the fuels management practices and utility corridor maintenance described above will not occur in undeveloped core areas under the guidelines of the Site Plan or this consultation. The Service concurs with DOE's determination regarding the salamander for the following reasons:

Within the Site Plan, DOE has placed the above detailed restrictions to ensure that any effects to the salamander and its habitat remain insignificant and discountable. Canopy cover will remain at 80% or greater in undeveloped core areas and fire management actions will occur outside of the salamander surface activity period. Maintaining utility line corridors in areas with existing infrastructure (the utility lines) by removing individual hazard trees is not expected to have any measurable effect on salamanders or their potential habitat. Consequently, we concur that potential effects to the salamander from the proposed action will be insignificant and discountable.

This concludes section 7 consultation regarding the proposed action. If monitoring or other information results in modification or the inability to complete all aspects of the proposed action, consultation should be reinitiated. Please contact the Service if: 1) future surveys detect listed, proposed or candidate species in habitats where they have not been previously observed; 2) the proposed action changes or new information reveals effects of the proposal to listed species that have not been considered in this analysis; or 3) a new species is listed or critical habitat designated that may be affected by the action.

Thank you for your concern for endangered and threatened species and New Mexico's wildlife habitats. In future correspondence regarding this project, please refer to consultation #02ENNM00-2014-I-0014. If you have any questions, please contact Michelle Christman of my staff at (505) 761-4715.

Sincerely,

Wally Murphy Field Supervisor

cc:

Wildlife Biologist, Cuba Ranger District, Cuba, NM (Attn: Ramon Borrego) Director, New Mexico Department of Game and Fish, Santa Fe, New Mexico



United States Department of the Interior



FISH AND WILDLIFE SERVICE

New Mexico Ecological Services Field Office 2105 Osuna Road NE Albuquerque, New Mexico 87113 Telephone 505-346-2525 Fax 505-346-2542 www.fws.gov/southwest/es/newmexico/

August 6, 2015

Cons. # 02ENNM00-2015-I-0538

Kimberly Davis Lebak, Manager Department of Energy National Nuclear Security Administration Los Alamos Field Office Los Alamos, New Mexico 87544

Dear Ms. Lebak:

This responds to your July 9, 2015, cover letter and biological assessment (BA) requesting informal consultation for the addition of the Western distinct population segment of the yellowbilled cuckoo (*Coccyzus americanus occidentalis*) (cuckoo) and the New Mexico meadow jumping mouse (*Zapus hudsonius luteus*) (jumping mouse) to the Los Alamos National Laboratory Habitat Management Plan, Los Alamos, New Mexico. As documented in your BA, which is hereby incorporated by reference, we find that your proposed action will have insignificant and discountable effects to the cuckoo and the jumping mouse. Therefore, the Service concurs with your determination of "may affect, is not likely to adversely affect" for the cuckoo and the jumping mouse.

This concludes section 7 consultation regarding the proposed action. If monitoring or other information results in modification or the inability to complete all aspects of the proposed action, consultation should be reinitiated. Please contact the Service if: 1) future surveys detect listed, proposed or candidate species in habitats where they have not been previously observed; 2) the proposed action changes or new information reveals effects of the proposal to listed species that have not been considered in this analysis; or 3) a new species is listed or critical habitat designated that may be affected by the action.

Kimberly Davis Lebak, Manager

Thank you for your concern for endangered species and New Mexico's wildlife habitats. If you have any questions, please contact Eric Hein of my staff at the letterhead address or at (505) 761-4735.

Sincerely,

for Wally Murphy Field Supervisor

cc:

Director, New Mexico Department of Game and Fish, Santa Fe, New Mexico

Date	Plan Section	Reason for Amendment	Amendment
Jan 2019	All	MSGP Plan for new industrial	New MSGP Plan for Triad, LLC
		facility at TA-16.	regarding the TA-16 Stockpile
			Area.
May 2021	All	The 2021 MSGP was published on January 15, 2021, and became effective on March 1, 2021. The new permit requires a SWPPP update.	Plan was revised to reflect new permit requirements."
December 2021	2.2, 2.5 and 4.5	Annual review	Updated the spill table and history, in addition to employee training.

ATTACHMENT 2: SWPPP AMENDMENTS

ATTACHMENT 3: CERTIFICATION OF NO UNAUTHORIZED STORMWATER DISCHARGES

Laboratory
National
s Alamos
Los

ATTACHMENT 4: DULY AUTHORIZED SIGNATORY MEMORANDUM



Environmental Protection & Compliance

Division

Los Alamos National Laboratory PO Box 1663, K490 Los Alamos, NM 87545 505-667-0666

Symbol: EPC-DO: 18-453 LAUR: 18-31574 Date: DEC 1 1 2018

Ms. Anne L. Idsal, Regional Administrator U.S. Environmental Protection Agency, Region 6 1445 Ross Avenue, Suite 1200 Mail Code: 6RA Dallas, TX 75202-2733

Subject: Notification of Triad National Security, LLC, Signatory Officials and Authorized Representatives for NPDES Permits

Dear Ms. Idsal:

The purpose of this letter is to provide an update to the U. S. Environmental Protection Agency (EPA) Region 6 on the Triad National Security, LLC delegation of authority for signature of documents associated with the various Los Alamos National Laboratory (LANL) NPDES Permits, pursuant to 40 CFR 122.22(c). This letter supersedes and replaces the signatory authority letter dated March 14, 2018 (ADESH: 18-017).

The positions of Associate Laboratory Director of Environment, Safety, Health & Quality and Safeguards & Security (ESHQSS), and Division Leader of the Environmental Protection & Compliance Division (EPC-DO) are identified as Triad's primary signatory officials under 40 CFR 122.22(a) for certifying and signing permit applications (including Notice of Intents (NOIs)) required under the LANL NPDES Industrial Point Source Outfall Permit (Permit No. NM0028355), the NPDES Storm Water Construction General Permit, the NPDES Multi-Sector General Permit (Permit No. NMR050013), and the NPDES Pesticide General Permit (Permit No. NMG87B113).

The following positions are hereby designated as authorized representatives under 40 CFR 122.22(b) to sign reports, Storm Water Pollution Prevention Plans, Discharge Monitoring Reports, Pesticide Discharge Management Plans, and any other compliance documentation required by the permits:



DEC 1 1 2018

Page 2

NPDES Industrial Point Source Outfall Permit (No. NM0028355)

- Positions listed as primary signatory officials above.
- Group Leader or Team Leaders within the Environmental Compliance Programs Group.
- Responsible Facility Operations Director (FOD).

NPDES Construction General Permit:

- Positions listed as primary signatory officials above.
- Group Leader or Team Leaders within the Environmental Compliance Programs Group.
- Cognizant Project Manager, Construction Manager, or Subcontractor Technical Representative for the regulated construction activity.

NPDES Multi-Sector General Permit (ID No. NMR053195)

- Positions listed as primary signatory officials above.
- Group Leader or Team Leaders within the Environmental Compliance Programs Group.
- Division Leader, Deputy Division Leader, or Group Leader of the LANL division responsible for the overall operation of the regulated facility or activity.
- Responsible FOD; Deputy FOD, Operations Manager; or Deployed Environment, Safety, & Health Manager responsible for the overall operation of the regulated facility or activity.

NPDES Pesticide General Permit (No. NM687A041)

- Positions listed as primary signatory officials above.
- Group Leader or Team Leaders within the Environmental Compliance Programs Group,

If you have questions, please contact me at (505) 667-7269 or at etorres@lanl.gov.

Sincerely

Enrique Torres Division Leader Environmental Protection & Compliance Division

ET/TWL/MTS:jdm



Page 3

Attachment(s): None.

Copy: Nancy Williams, USEPA, Region 6, williams.nancy@epa.gov, (E-File) Brent E. Larsen, USEPA, Region 6, Larsen.brent@epa.gov, (E-File) Robert Houston, USEPA, Region 6, Houston.robert@epa.gov, (E-File) Sarah Holcomb, NMED, sarah.holcomb@state.nm.us, (E-File) Karen E. Armijo, LASO-MA-LS, Karen.armijo@nnsa.doe.gov, (E-File) Jody Pugh, NA-LA, jody.pugh@nnsa.doe.gov, (E-File) Michael W. Hazen, ESHQSS, mhazen@lanl.gov, (E-File) William R. Mairson, ESHQSS, wrmairson@lanl.gov, (E-File) Enrique Torres, EPC-DO, etorres@lanl.gov, (E-File) Taunia Van Valkenburg, EPC-CP, tauniav@lanl.gov, (E-File) Michael T. Saladen, EPC-CP, saladen@lanl.gov, (E-File) Terrill W. Lemke, EPC-CP, tlemke@lanl.gov, (E-File) Tim Dolan, GC-ESH, tdolan@lanl.gov, (E-File) emla.docs@em.doe.gov, (E-File) locatesteam@lanl.gov, (E-File) epc-correspondence@lanl.gov, (E-File) adesh-records@lanl.gov, (E-File)

ATTACHMENT 5: DISCHARGE MONITORING REPORTS

DMR Copy of Record

Permit														_							
Permit #: NMR050013				P	Permittee:			TRIAD NATIONAL SECURITY LLC					F	Facility: LOS			OS ALAMOS NATIONAL LABORATORY				
Major: No I							PO BOX 1663 MS K490 LOS ALAMOS, NM 87545					F				PO BOX 1663 LOS ALAMOS, NM 87545					
Permitted Feature: 078 External Outfall				D				078-IW Impaired Water													
Report	Dates & Status																				
Monitor	ring Period:	Fron	n 12/01/19 to 11/3	0/20	D	OMR Due Da	ate:	0 1	/31/21					5	Status:			NetDMR Validated			
Conside	erations for Form (Comp	letion																		
Principa	al Executive Office	r																			
First Na	ame:				т	Fitle:								٦	Telepho	one:					
Last Na	ime:													-							
No Data	a Indicator (NODI)																				
Form N	ODI:																				
	Parameter		Monitoring Location	Season #	Param. N	ODI			ity or Loadi	_						Concentra			# of Ex	c. Frequency of Analys	is Sample Type
Code	Name					Sample		1 Value '	Qualifier 2	2 Value 2 U	Jnits	Qualifier 1	Value 1	Qualifier 2	Value 2	Qualifier 3	Value 3	Units			
51931	Alpha, gross adjust	bo	1 - Effluent Gross	0		Permit Re										<=	15.0 MAXIMUM	17 - pCi/L		01/YR - Annual	GR - GRAB
51551	Alpha, gross aujust	cu		U		Value NC	וסמ										C - No Discharg				
Submis	sion Note																1			1	
If a para	meter row does not	conta	ain any values for t	the Samr	ple nor E	ffluent Trad	ing, then n	one of th	ne followin	g fields	will b	be submit	ted for t	that row: I	Jnits, N	lumber of	Excursions, Fre	quency of /	Analysi	is, and Sample Type	э.
	eck Errors						-														
No error	rs.																				
Comme	ents																				
LA-UR-2	20-30426																				
Attachn	nents																				
No attachn																					
-	Last Saved By																				
TRIAD I	NATIONAL SECUR	ITY L	LC																		
User:			I	leslie@la	anl.gov																
Name:			l	Leslie [Dale																
E-Mail:			I	leslie@la	anl.gov																
Date/Tin	ne:		2	2020-12-	-22 16:0	00 (Time Zo	one: -06:00)													
Report	Last Signed By																				
User:			7	TERRILL	LLEMKE																
Name:			-	Terrill L	Lemke																
E-Mail:			t	tlemke@	lanl.gov																
Date/Tin	me:		2	2020-12-	-22 16:4	4 (Time Zo	one: -06:00)													

ATTACHMENT 6: ANNUAL REPORTS

ATTACHMENT 7: ROUTINE FACILITY INSPECTIONS

Los Alamos National Laboratory

Work Order MSGP-RI-65269

MSGP Routine Inspection Printed 11/16/2021 - 12:09 PM (Duplicate Copy)

Maintenance Details

Last PM: 6/18/2021 Phone: 6	anar, Alethea 99-5836
Project: Routine Facility Inspections October 2021 (P-MSGP- RI-5524)	

Tasks

Weather Information Describe the weather at time of inspection and document the temperature (F*). 20 Comments: Partly cloudy 72 degrees Within the Facility Boundary Is the facility free of previously unidentified discharges from and/or pollutants that have 0 occurred since the last inspection If "No" describe. 50 If "No" has a CAR been previously initiated for this new discharge? 60 Is the facility free of evidence of, or the potential for, pollutants entering the drainage 70 system. If "No" describe. Outfall Inspection of corrective actions in relevant task comment) 90 Monitored Outfall [078] Free of Evidence of Pollutants in Discharges and/or 100 describe. 110 describe. 120 "No" describe. 120 "No", describe. 120 Monitored Outfall [078] Free of Evidence of Pollutants in Discharges and/or 120 Receiving Water? If "No", describe. 120 "No" describe. 120 Monitored Outfall [078] Free of any unauthorized non-stormwater discharges? If 120 "No" describe. 120 Tho" describe. 120 "No" describe. 120	#	Description	Meas.	No	N/A	Yes
20 Comments: Partly cloudy 72 degrees Image: Comments: Partly cloudy 72 degrees Within the Facility Boundary Is the facility free of previously unidentified discharges from and/or pollutants that have 00 occurred since the last inspection If "No" describe. Image: Comments: Partly Cloudy 72 degrees 50 If "No" has a CAR been previously initiated for this new discharge? Image: Comments: Partly Cloudy 72 degrees 60 Is the facility free of discharge of pollutants at the time of inspection? If "No" describe. Image: Comments: Partly Cloudy 72 degrees 60 Is the facility free of discharge of pollutants at the time of inspection? If "No" describe. Image: Comments: Partly Cloudy 72 degrees 60 Is the facility free of discharge of pollutants at the time of inspection? If "No" describe. Image: Comments: Partly Cloudy 72 degrees 60 Unfail Imspection (identify needed maintenance and repairs, failed control measures that need replacement, or a description of corrective actions in relevant task comment) Image: Common comments and comments and comments and comments and comments. 60 Monitored Outfail [078] Free of Evidence of Pollutants in Discharges and/or Image: Comments and comments and comments and comments and comments. 70 describe Control Measures (identify needed maintenance and repairs, failed control measures that need replacement, or a description of corrective actions in relevant task comments).	Weat	her Information				
Is the facility free of previously unidentified discharges from and/or pollutants that have occurred since the last inspection If "No" describe. Image: Control Reserves and the image of pollutants at the time of inspection? If "No" describe. 50 If "No" has a CAR been previously initiated for this new discharge? Image: Control Reserves and the image of pollutants at the time of inspection? If "No" describe. Image: Control Reserves and the image of pollutants at the time of inspection? If "No" describe. 70 Is the facility free of evidence of, or the potential for, pollutants entering the drainage system. If "No" describe. Image: Control Reserves and the image of pollutants entering the drainage of corrective actions in relevant task comment) 90 Monitored Outfall [078] Free of Evidence of Erosion? If "No", describe. Image: Control Reserves and the image of pollutants in Discharges and/or 100 describe. Image: Control Reserves and the image of the ima	20	Describe the weather at time of inspection and document the temperature (F°). Comments: Partly cloudy 72 degrees				1
Is the facility free of previously unidentified discharges from and/or pollutants that have 40 occurred since the last inspection If "No" describe. 50 If "No" has a CAR been previously initiated for this new discharge? 60 Is the facility free of discharge of pollutants at the time of inspection? If "No" describe. 61 Is the facility free of evidence of, or the potential for, pollutants entering the drainage 70 system. If "No" describe. 61 If the facility free of evidence and repairs, failed control measures that need replacement, or a 62 Monitored Outfall [078] Free of Evidence of Erosion? If "No", describe. 63 Monitored Outfall [078] Free of Evidence of Pollutants in Discharges and/or 70 gescribe. If "No", describe. 70 Monitored Outfall [078] Free of any unauthorized non-stormwater discharges? If If "No", describe. 70 describe. If "No" 710 Receiving Water? If "No", describe. If "No" 72	Withi	n the Facility Boundary				
60 Is the facility free of discharge of pollutants at the time of inspection? If "No" describe. Image: Control inspection in the polential for, pollutants entering the drainage system. If "No" describe. Outfall Inspection (identify needed maintenance and repairs, failed control measures that need replacement, or a description of corrective actions in relevant task comment) 90 Monitored Outfall [078] Free of Evidence of Erosion? If "No", describe. Monitored Outfall [078] Free of Evidence of Pollutants in Discharges and/or 100 describe. Monitored Outfall [078] Free of Evidence of Pollutants in Discharges and/or 110 Receiving Water? If "No", describe. Monitored Outfall [078] Free of any unauthorized non-stormwater discharges? If 120 "No" describe. Monitored Outfall [078] Free of any unauthorized non-stormwater discharges? If 120 "No" describe. Control Measures (identify needed maintenance and repairs, failed control measures that need replacment, or a description of corrective actions in relevant task comments). Earthen Berm [1600103010002] Control Measure is operating effectively? If "No" 140 describe condition & need for Maintenance, Repair, or Replacement. Earthen Berm [1600103010002] Control Measure is operating effectively? If "No" 160 describe condition & need for Maintenance, Repair, or Replacement. Earthen Ber		Is the facility free of previously unidentified discharges from and/or pollutants that have			Г	12
60 Is the facility free of discharge of pollutants at the time of inspection? If "No" describe. Image: Control inspection in the polential for, pollutants entering the drainage system. If "No" describe. 0 Outfall Inspection (identify needed maintenance and repairs, failed control measures that need replacement, or a description of corrective actions in relevant task comment) 90 Monitored Outfall [078] Free of Evidence of Erosion? If "No", describe. Monitored Outfall [078] Free of Evidence of Pollutants in Discharges and/or 100 describe. Monitored Outfall [078] Free of Evidence of Pollutants in Discharges and/or 110 Receiving Water? If "No", describe. Monitored Outfall [078] Free of any unauthorized non-stormwater discharges? If 120 "No" describe. Monitored Outfall [078] Free of any unauthorized non-stormwater discharges? If 120 "No" describe. Control Measures (identify needed maintenance and repairs, failed control measures that need replacment, or a description of corrective actions in relevant task comments). Earthen Berm [1600103010002] Control Measure is operating effectively? If "No" 140 describe condition & need for Maintenance, Repair, or Replacement. Earthen Berm [1600103010002] Control Measure is operating effectively? If "No" 160 describe condition & need for Maintenance, Repair, or Replacement.	50	If "No" has a CAR been previously initiated for this new discharge?		F	12	
70 system. If "No" describe. Image: Control Measures that need replacement, or a description of corrective actions in relevant task comment) 90 Monitored Outfall [078] Free of Evidence of Erosion? If "No", describe. Image: Control Measures (actions) 90 Monitored Outfall [078] Free of Evidence of Pollutants in Discharges and/or Image: Control Measures (identify needed maintenance and repairs, failed control measures that need replacement, or a describe. Monitored Outfall [078] Free of Evidence of Pollutants in Discharges and/or Image: Control Measures (identify needed maintenance and repairs, failed control measures that need replacement, or a describte. Monitored Outfall [078] Free of Evidence and repairs, failed control measures that need replacement, or a describte. Image: Control Measures (identify needed maintenance and repairs, failed control measures that need replacement, or a describte on of corrective actions in relevant task comments). Earthen Berm [1600103010001] Control Measure is operating effectively? If "No" describe condition & need for Maintenance, Repair, or Replacement. Image: Condition & need for Maintenance, Repair, or Replacement. Earthen Berm [1600103010003] Control Measure is operating effectively? If "No" describe condition & need for Maintenance, Repair, or Replacement. Image: Condition & need for Maintenance, Repair, or Replacement. Image: Condition & need for Maintenance, Repair, or Replacement. Image: Condition & need for Maintenance, Repair, or Replacement. Image: Co	60				Г	11
description of corrective actions in relevant task comment) 90 Monitored Outfall [078] Free of Evidence of Erosion? If "No", describe. Monitored Outfall [078] Free of Evidence of Pollutants in Discharges and/or 100 describe. Monitored Outfall [078] Free of Evidence of Pollutants in Discharges and/or 110 Receiving Water? If "No", describe. Monitored Outfall [078] Free of any unauthorized non-stormwater discharges? If 120 "No" describe. Control Measures (identify needed maintenance and repairs, failed control measures that need replacment, or a description of corrective actions in relevant task comments). Earthen Berm [1600103010001] Control Measure is operating effectively? If "No" 140 describe condition & need for Maintenance, Repair, or Replacement. 150 describe condition & need for Maintenance, Repair, or Replacement. 160 describe condition & need for Maintenance, Repair, or Replacement. 160 describe condition & need for Maintenance, Repair, or Replacement. 160 describe condition & need for Maintenance, Repair, or Replacement. 160 describe condition & need for Maintenance, Repair, or Replacement. 160 describe condition & need for Maintenance, Repair, or Replacement. 160 describe condition & need for Ma	70	Is the facility free of evidence of, or the potential for, pollutants entering the drainage system. If "No" describe.				14
Monitored Outfall [078] Flow Dissipation Devices Operating Effectively? If "No", 100 describe. Monitored Outfall [078] Free of Evidence of Pollutants in Discharges and/or 110 Receiving Water? If "No", describe. Monitored Outfall [078] Free of any unauthorized non-stormwater discharges? If 120 "No" describe. Monitored Outfall [078] Free of any unauthorized non-stormwater discharges? If 120 "No" describe. Control Measures (identify needed maintenance and repairs, failed control measures that need replacment, or a description of corrective actions in relevant task comments). Earthen Berm [1600103010001] Control Measure is operating effectively? If "No" 140 describe condition & need for Maintenance, Repair, or Replacement. 150 describe condition & need for Maintenance, Repair, or Replacement. 160 describe condition & need for Maintenance, Repair, or Replacement. 160 describe condition & need for Maintenance, Repair, or Replacement. 160 describe condition & need for Maintenance, Repair, or Replacement. 160 describe condition & need for Maintenance, Repair, or Replacement. 160 describe condition & need for Maintenance, Repair, or Replacement. 160 describe condition & need for Maintenance, Repair, or Replacemen	descr	iption of corrective actions in relevant task comment)	need repl	aceme	nt, or a	
100 describe. Image: Control Measures (identify needed maintenance, Repair, or Replacement. 110 Receiving Water? If "No", describe. Image: Control Measures (identify needed maintenance and repairs, failed control measures that need replacment, or a description of corrective actions in relevant task comments). Earthen Berm [1600103010001] Control Measure is operating effectively? If "No" 140 describe condition & need for Maintenance, Repair, or Replacement. Image: Earthen Berm [1600103010002] Control Measure is operating effectively? If "No" 150 describe condition & need for Maintenance, Repair, or Replacement. Image: Earthen Berm [1600103010002] Control Measure is operating effectively? If "No" 160 describe condition & need for Maintenance, Repair, or Replacement. Image: Earthen Berm [1600103010003] Control Measure is operating effectively? If "No" 160 describe condition & need for Maintenance, Repair, or Replacement. Image: Earthen Berm [1600103010003] Control Measure is operating effectively? If "No" 160 describe condition & need for Maintenance, Repair, or Replacement. Image: Earthen Berm [1600103010003] Control Measure is operating effectively? If "No" 160 describe condition & need for Maintenance, Repair, or Replacement. Image: Earthen Berm [1600103010003] Control Measure is operating effectively? If "No" 160 desc	90					14
110 Receiving Water? If "No", describe. Monitored Outfall [078] Free of any unauthorized non-stormwater discharges? If 120 "No" describe. Control Measures (identify needed maintenance and repairs, failed control measures that need replacment, or a description of corrective actions in relevant task comments). Earthen Berm [1600103010001] Control Measure is operating effectively? If "No" 140 describe condition & need for Maintenance, Repair, or Replacement. Earthen Berm [1600103010002] Control Measure is operating effectively? If "No" 150 describe condition & need for Maintenance, Repair, or Replacement. Earthen Berm [1600103010003] Control Measure is operating effectively? If "No" 160 describe condition & need for Maintenance, Repair, or Replacement. Earthen Berm [1600103010003] Control Measure is operating effectively? If "No" 160 describe condition & need for Maintenance, Repair, or Replacement. Area/Activity exposed to stormwater (identify needed mainteance or a description of corrective actions in relevant task comment). Material loading/unloading and storage areas: controls adequate (appropriate, effective, and operating)? If "No" describe. Transfer areas for substances in bulk: controls adequate (appropriate, effective, and operating)? If "No" describe.	100	describe.			IV.	
120 "No" describe. Control Measures (identify needed maintenance and repairs, failed control measures that need replacment, or a description of corrective actions in relevant task comments). Earthen Berm [1600103010001] Control Measure is operating effectively? If "No" 140 describe condition & need for Maintenance, Repair, or Replacement. Earthen Berm [1600103010002] Control Measure is operating effectively? If "No" 150 describe condition & need for Maintenance, Repair, or Replacement. Earthen Berm [1600103010002] Control Measure is operating effectively? If "No" 160 describe condition & need for Maintenance, Repair, or Replacement. Earthen Berm [1600103010003] Control Measure is operating effectively? If "No" 160 describe condition & need for Maintenance, Repair, or Replacement. Image: Maintenance is operating effectively? If "No" 160 describe condition & need for Maintenance, Repair, or Replacement. Image: Maintenance is operating effectively? If "No" 160 describe condition & need for Maintenance, Repair, or Replacement. Image: Maintenance is operating effectively? If "No" 160 describe condition & need for Maintenance, Repair, or Replacement. Image: Maintenance is operating effectively? If "No" 160 describe condition & need for Maintenance is operating effectively? If "No"	110	Monitored Outfall [078] Free of Evidence of Pollutants in Discharges and/or Receiving Water? If "No", describe.		Г	Г	14
description of corrective actions in relevant task comments). Earthen Berm [1600103010001] Control Measure is operating effectively? If "No" 140 describe condition & need for Maintenance, Repair, or Replacement. Earthen Berm [1600103010002] Control Measure is operating effectively? If "No" 150 describe condition & need for Maintenance, Repair, or Replacement. Earthen Berm [1600103010003] Control Measure is operating effectively? If "No" 160 describe condition & need for Maintenance, Repair, or Replacement. Earthen Berm [1600103010003] Control Measure is operating effectively? If "No" 160 describe condition & need for Maintenance, Repair, or Replacement. I60 describe condition & need for Maintenance, Repair, or Replacement. I60 describe condition & need for Maintenance, Repair, or Replacement. I60 describe condition & need for Maintenance, Repair, or Replacement. I60 describe condition and storage areas: controls adequate or a description of corrective actions in relevant task comment). Material loading/unloading and storage areas: controls adequate (appropriate, effective, and operating)? If "No" describe. Transfer areas for substances in bulk: controls adequate (appropriate, effective, and operating)? If "No" describe. Transfer areas for substances in bulk: controls adequate (appropriate, effective, and operating)? If "No" describe. <td>120</td> <td>Monitored Outfall [078] Free of any unauthorized non-stormwater discharges? If "No" describe.</td> <td></td> <td>Г</td> <td>Γ</td> <td>11</td>	120	Monitored Outfall [078] Free of any unauthorized non-stormwater discharges? If "No" describe.		Г	Γ	11
Earthen Berm [1600103010001] Control Measure is operating effectively? If "No" 140 describe condition & need for Maintenance, Repair, or Replacement. Earthen Berm [1600103010002] Control Measure is operating effectively? If "No" 150 describe condition & need for Maintenance, Repair, or Replacement. Earthen Berm [1600103010003] Control Measure is operating effectively? If "No" 160 describe condition & need for Maintenance, Repair, or Replacement. Earthen Berm [1600103010003] Control Measure is operating effectively? If "No" 160 describe condition & need for Maintenance, Repair, or Replacement. Area/Activity exposed to stormwater (identify needed mainteance or a description of corrective actions in relevant task comment). Material loading/unloading and storage areas: controls adequate (appropriate, effective, and operating)? If "No" describe. Transfer areas for substances in bulk: controls adequate (appropriate, effective, and operating)? If "No" describe. 190	Contr descr	ol Measures (identify needed maintenance and repairs, failed control measures that in the province of the prov	need repl	acmen	t, or a	
150 describe condition & need for Maintenance, Repair, or Replacement. Earthen Berm [1600103010003] Control Measure is operating effectively? If "No" 160 describe condition & need for Maintenance, Repair, or Replacement. 160 describe condition & need for Maintenance, Repair, or Replacement. Area/Activity exposed to stormwater (identify needed mainteance or a description of corrective actions in relevant task comment). Material loading/unloading and storage areas: controls adequate (appropriate, effective, and operating)? If "No" describe. Transfer areas for substances in bulk: controls adequate (appropriate, effective, and operating)? If "No" describe. 190	140	describe condition & need for Maintenance, Repair, or Replacement.				IV.
160 describe condition & need for Maintenance, Repair, or Replacement. Area/Activity exposed to stormwater (identify needed mainteance or a description of corrective actions in relevant task comment). Material loading/unloading and storage areas: controls adequate (appropriate, effective, and operating)? If "No" describe. Transfer areas for substances in bulk: controls adequate (appropriate, effective, and operating)? If "No" describe. 190	150	Earthen Berm [1600103010002] Control Measure is operating effectively? If "No" describe condition & need for Maintenance, Repair, or Replacement.		Г		R.
comment). Material loading/unloading and storage areas: controls adequate (appropriate, 180 effective, and operating)? If "No" describe. Transfer areas for substances in bulk: controls adequate (appropriate, effective, and 190 operating)? If "No"	160	Earthen Berm [1600103010003] Control Measure is operating effectively? If "No" describe condition & need for Maintenance, Repair, or Replacement.				14
180 effective, and operating)? If "No" describe. Transfer areas for substances in bulk: controls adequate (appropriate, effective, and 190 190	Area// comm	Activity exposed to stormwater (identify needed mainteance or a description of corre ent).	ctive acti	ons in	relevar	ıt task
190 operating)2 If "No" describe	180	Material loading/unloading and storage areas: controls adequate (appropriate,		Г		14
	190	Transfer areas for substances in bulk: controls adequate (appropriate, effective, and operating)? If "No" describe.		Г		1

200	Product/chemical storage areas (raw material): controls adequate (appropriate, effective, and operating)? If "No" describe.	
210	Liquid tank storage/secondary containment: controls adequate (appropriate, effective, and operating)? If "No" describe.	
220	Industrial processing and finished product storage areas: controls adequate (appropriate, effective, and operating)? If "No" describe.	
230	Equipment operation and maintenance areas: controls adequate (appropriate, effective, and operating)? If "No" describe.	
240	Fueling areas: controls adequate (appropriate, effective, and operating)? If "No" describe.	
250	Outdoor vehicle and equipment washing areas: controls adequate (appropriate, effective, and operating)? If "No" describe.	
260	Machinery: controls adequate (appropriate, effective, and operating)? If "No" describe.	
270	Waste handling and disposal areas: controls adequate (appropriate, effective, and operating)? If "No" describe.	
280	Erodible areas/construction: controls adequate (appropriate, effective, and operating)? If "No" describe.	
290	Locations and sources of run-on to the site: controls adequate (appropriate, effective, and operating)? If "No" describe.	
300	Salt storage piles or pile containing salt: controls adequate (appropriate, effective, and operating)? If "No" describe.	
310	Dust generation and vehicle tracking: controls adequate (appropriate, effective, and operating)? If "No" describe.	
320	Housekeeping (Industrial materials/residues/trash in contact with stormwater): controls adequate (appropriate, effective, and operating)? If "No" describe.	
330	Leaks and spills: controls adequate (appropriate, effective, and operating)? If "No" describe.	
340	Sector P [16001-P] Vehicle storage/maintenance areas: controls adequate (appropriate, effective, and operating)? If "No" describe.	
Non-C	ompliance	
360	Free of incidents of observed non-compliance not already identified above? If "No" describe.	
Additio	onal Control Measures	
380	Are permit requirements satisfied with existing control measure(s)? If "No" describe additional control measures needed.	
abor I	Report	
Compl	11/8/2021 eted: 3:30:00 PM	
Report	:: Kelkenny Bileen 11/13/2021 - 178009: No deficiency found.	

CERTIFICATION STATEMENT

"I certify under penalty of law that this document and all attachments were prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gathered and evaluated the information submitted. Based on my inquiry of the person or persons who manage the system, or those persons directly responsible for gathering information, the information submitted is, to the best of my knowledge and belief, true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment for jowing violations".

(Signatory must meet definition in Section B.11.A, eg. FOD, Ops Mgr, DESH Group Leader, EPC Group Leader)

Work Orders (No Grouping)	https://www.maintenanceconnection.com/mcv18/mapp_v80/modules/
Print name and title: John Branch	WFO-HE OM
"Signature: John Brank	Date: 11-16-2021

Los Alamos National Laboratory

Work Order MSGP-RI-65268

MSGP Routine Inspection Printed 10/4/2021 - 4:34 PM (Duplicate Copy)

Maintenance Details

Taken By:Banar, AletherProcedure:MSGP RoutiInspection (E2108 R0 ForLast PM:3/23/2021Project:Routine FaciInspections C		9/1/2021 11:20:00 AM Banar, Alethea MSGP Routine Facility Inspection (EPC-CP-QP- 2108 R0 Form 1) 3/23/2021 Routine Facility Inspections July 2021 (P- MSGP-RI-5500)	Target: Priority/Type: Department: Aug-Sept)	▲ MSGP ♣ RG253 ▲ TA-16 \$ Contact: B Phone: 6	Stockpile Banar, Ale	e Area ethea			
Tasks									
#	Descr	intion				Meas.	No	N/A	Yes
	her Inform	-				weas.	No	N/A	res
20		be the weather at time of in	spection and do	cument the temperature	(F°)				X
-		ility Boundary					•		
VVILIII		acility free of previously uni	dentified discha	rges from and/or pollutan	ts that have				
40	occurr	ed since the last inspection	If "No" describe			_	<u> </u>		X
50		o" has a CAR been previous						X	<u> </u>
60		acility free of discharge of p							
70		acility free of evidence of, o . If "No" describe.	or the potential to	or, pollutants entering the	drainage				X
descr 90 100	Monito	corrective actions in relev pred Outfall [078] Free of E pred Outfall [078] Flow Dis pe.	Evidence of Eros	sion? If "No", describe,	- "No",				
110		ored Outfall [078] Free of E If "No", describe.	Evidence of Pollu	utants in Discharges and/	or Receiving		Г		x
120	Monito	ored Outfall [078] Free of a	iny unauthorized	l non-stormwater dischar	ges? If "No"				R
Contr descr	iption of	res (identify needed main corrective actions in relev n Berm [1600103010001]	ant task comm	ients).		d replaci		r a	
140		e condition & need for Mair			II NO				X
150		n Berm [1600103010002] be condition & need for Mair			lf "No"				R
160		n Berm [1600103010003] e condition & need for Mair			lf "No"				R
Area// comm	Activity e	xposed to stormwater (ide	entify needed m	nainteance or a descrip	tion of correctiv	e action	s in rel	evant t	ask
comm	,	I loading/unloading and sto	rade areas: con	trols adequate (appropria	te effective				
180	and op	erating)? If "No" describe.							
190	operati	er areas for substances in b ng)? If "No" describe.							
200	and op	t/chemical storage areas (ra erating)? If "No" describe.				_			X
210		ank storage/secondary con erating)? If "No" describe.	tainment: contro	ols adequate (appropriate	, effective,			X	

220	Industrial processing and finished product storage areas: controls adequate (appropriate, effective, and operating)? If "No" describe.		X
230	Equipment operation and maintenance areas: controls adequate (appropriate, effective, and operating)? If "No" describe.		X
240	Fueling areas: controls adequate (appropriate, effective, and operating)? If "No" describe.	X	
250	Outdoor vehicle and equipment washing areas: controls adequate (appropriate, effective, and operating)? If "No" describe.	X	
260	Machinery: controls adequate (appropriate, effective, and operating)? If "No" describe.		R
270	Waste handling and disposal areas: controls adequate (appropriate, effective, and operating)? If "No" describe.		
280	Erodible areas/construction: controls adequate (appropriate, effective, and operating)? If "No" describe.		X
290	Locations and sources of run-on to the site: controls adequate (appropriate, effective, and operating)? If "No" describe.		X
300	Salt storage piles or pile containing salt: controls adequate (appropriate, effective, and operating)? If "No" describe.	X	
310	Dust generation and vehicle tracking: controls adequate (appropriate, effective, and operating)? If "No" describe.		X
320	Housekeeping (Industrial materials/residues/trash in contact with stormwater): controls adequate (appropriate, effective, and operating)? If "No" describe.		X
330	Leaks and spills: controls adequate (appropriate, effective, and operating)? If "No" describe.	 Г	X
340	Sector P [16001-P] Vehicle storage/maintenance areas: controls adequate (appropriate, effective, and operating)? If "No" describe.		
Non-C	ompliance	 	<u> </u>
	Free of incidents of observed non-compliance not already identified above? If "No"		
360	describe.		
Additi	onal Control Measures		
	Are permit requirements satisfied with existing control measure(s)? If "No" describe		
380	additional control measures needed.		X
abor	Report		
•	00/02/0004		
Comp	eted: <u>09/23/2021</u>		
Repor	: Kelkenny Bileen	 	
Kelke	enny Bileen Back of the state o		
	Signature / Name Date Signature / Name	 Date	
confir	m the information as recorded is true, accurate and complete.		

CERTIFICATION STATEMENT

"I certify under penalty of law that this document and all attachments were prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gathered and evaluated the information submitted. Based on my inquiry of the person or persons who manage the system, or those persons directly responsible for gathering information, the information submitted is, to the best of my knowledge and belief, true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment for knowing violations".

(Signatory must meet definition in Section B.11.A, eg. FOD, Ops Mgr, DESH Group Leader, EPC Group Leader)

It name and title:____

JOHN BRANCH (Affiliate) Digitally signed by JOHN BRANCH (Affiliate) Date: 2021.10.05 07:15:48 -06'00'

Date:

Signature:

Los Alamos National Laboratory

- Maintenance Details -

Work Order MSGP-RI-64979

MSGP Routine Inspection Printed 5/6/2021 - 3:44 PM

d: 5/6/2021 3:39:00 PM	Target:	6/30/2021	🔁 MSGP	Program			
e: MSGP Routine Facility	Priority/Type:	Normal / Inspection	击 RG253	U			
Inspection (EPC-CP-QP-2108 R0 Form 1)	Department:	Weapons Facilities Operations	📥 TA-16 S	tockpile /	Area		
3/23/2021			Contact:				
Routine Facility Inspections May 2021 (P-MSGP-RI-5498)			Phone:				
2021 Quarter 2 Inspection							
Description				Meas.	No	N/A	Yes
Information							
Describe the weather at time of ins	pection and doc	ument the temperature (F	°). 88 degrees.				X
e Facility Boundary			Partly Cloudy				
	dentified dischar	ges from and/or pollutants	s that have				
							X
		and the second				X	
	-						X
s the facility free of evidence of, or system. If "No" describe.	r the potential fo	r, pollutants entering the c	Irainage				X
spection (identify peoded maint	onanco and for	airs failed control mos	euroe that need	roplacom	ont or	o door	
tive actions in relevant task con	nment)	Jairs, Tailed Control mea	sures that heed	replacem	ent, or	a dest	cription
Monitored Outfall [078] Free of E	vidence of Erosi	on? If "No", describe.					X
Monitored Outfall [078] Flow Diss	sipation Devices	Operating Effectively? If '	'No", describe.				X
Monitored Outfall [078] Free of E Nater? If "No", describe.	vidence of Pollu	tants in Discharges and/o	r Receiving				X
fonitored Outfall [078] Free of an lescribe.	ny unauthorized	non-stormwater discharg	es? If "No"				X
		pairs, failed control mea	sures that need	replacme	nt, or a	a descr	ription
Earthen Berm [1600103010001]	Control Measure		f "No" describe				X
arthen Berm [1600103010002]	Control Measure	is operating effectively? I	f "No" describe				
			f "No" describe			Г	x
	ntify needed m	ainteance or a descripti	on of corrective	actions ir	n relev	ant tas	ik
/	rane areas: cont	rols adequate (appropriat	e effective				
nd operating)? If "No" describe.							X
perating)? If "No" describe.							X
Product/chemical storage areas (raind operating)? If "No" describe.	aw material): cor	ntrols adequate (appropria	ite, effective,				X
perating)? If "No" describe.				E.			X
ffective, and operating)? If "No" de	escribe.						X
	ance areas: cont	rols adequate (appropriat	e, effective, and				
	appropriate, effe	ctive, and operating)? If "	No" describe				
	e: MSGP Routine Facility Inspection (EPC-CP-QP-2108 R0 Form 1) 3/23/2021 Routine Facility Inspections May 2021 (P-MSGP-RI-5498) 2021 Quarter 2 Inspection Information Describe the weather at time of ins e Facility Boundary s the facility free of previously unid occurred since the last inspection I If "No" has a CAR been previous s the facility free of discharge of p s the facility free of discharge of p s the facility free of discharge of p s the facility free of evidence of, or system. If "No" describe. spection (identify needed maint tive actions in relevant task com Monitored Outfall [078] Free of E Monitored Outfall [078] Free of E Monitored Outfall [078] Free of a lescribe. Monitored Outfall [078] Free of a lescr	e: MSGP Routine Facility Priority/Type: Inspection (EPC-CP-QP-2108 Department: R0 Form 1) 3/23/2021 Routine Facility Inspections May 2021 (P-MSGP-RI-5498) 2021 Quarter 2 Inspection 2021 Quarter 2 Insp	e: MSGP Routine Facility Inspection (EPC-CP-QP-2108 R0 Form 1) 3/23/2021 Routine Facility Inspections May 2021 (P-MSGP-RI-5498) 2021 Quarter 2 Inspection Source the weather at time of inspection and document the temperature (f e Facility Boundary s the facility free of previously unidentified discharges from and/or pollutants cccurred since the last inspection If "No" describe. If "No" has a CAR been previously initiated for this new discharge? s the facility free of previously unidentified discharges from and/or pollutants cccurred since the last inspection If "No" describe. If "No" has a CAR been previously initiated for this new discharge? s the facility free of discharge of pollutants at the time of inspection? If "No" s the facility free of evidence of, or the potential for, pollutants entering the of ystem. If "No" describe. Spection (Identify needed maintenance and repairs, failed control mea tive actions in relevant task comment) Monitored Outfall [078] Free of Evidence of Erosion? If "No", describe. Monitored Outfall [078] Free of Evidence of Pollutants in Discharges and/or Vater? If "No", describe. Monitored Outfall [078] Free of any unauthorized non-stormwater discharge lescribe. Iteasures (identify needed maintenance and repairs, failed control mea tive actions in relevant task comments). Contiored Outfall [078] Free of any unauthorized non-stormwater discharge lescribe. Iteasures (identify needed maintenance and repairs, failed control mea tive actions in relevant task comments). Control Measure is operating effectively? I condition & need for Maintenance, Repair, or Replacement. Carthen Berm [1600103010002] Control Measure is operating effectively? I condition & need for Maintenance, Repair, or Replacement. Carthen Berm [1600103010002] Control Measure is operating effectively? I condition & need for Maintenance, Repair, or Replacement. Carthen Berm [1600103010002] Control Measure is operating effectively? I condition & need for Maintenance, Repair, or Replacem	e: MSGP Routine Facility Priorfty/Type: Normal / Inspection Inspection (EPC-OP-QP-2108 RO Form 1) Operations Generalities Operations 3/23/2021 Routine Facility Inspections May 2021 (P-MSGP-RI-5498) 2021 Quarter 2 Inspection Information Describe the weather at time of inspection and document the temperature (F [*]). <u>88 degrees.</u> Facility Boundary Party Cloudy s the facility free of previously unidentified discharges from and/or pollutants that have course dince the last inspection If No" describe. If 'No" has CAR been previously unidentified discharges from and/or pollutants that have coursed since the last inspection If 'No" describe. If 'No" has CAR been previously inidentified for this new discharge? s the facility free of evidence of, or the potential for, pollutants entering the drainage system. If 'No" describe. Sepection (Identify needed maintenance and repairs, failed control measures that need twe actions in relevant task comment) Aonitored Outfall [078] Free of Evidence of Erosion? If 'No", describe. Anontored Outfall [078] Free of Evidence of Pollutants in Discharges and/or Receiving Vater? If 'No", describe. Anontored Outfall [078] Free of Evidence of Pollutants in Discharges If 'No" describe. Anontored Outfall [078] Free of Evidence and repairs, failed control measures that need twe actions in relevant task comments). Anontored Outfall [078] Free of Evidence of Pollutants in Discharges If 'No", describe. Anontored Outfall [078] Free of Evidence of Pollutants in Discharges If 'No" describe. Anontored Outfall [078] Free of Evidence and repairs, failed control measures that need twe actions in relevant task comments). Anontored Outfall [078] Free of any unauthorized non-stormwater discharges? If 'No" describe condition & need for Maintenance, Repair, or Replacement. Arthen Berm [1600103010001] Control Measure is operating effectively? If 'No" describe condition & need for Maintenance, Repair, or Replacement. Anthen Berm [1600103010001] Control Measure is operating effectively? If 'No" describe. Anateri	E: MSOP Routine Facility Inspection (EPC-CP-QP-2108 Department: Weapons Facilities Qoerations S223/2021 Routine Facility Inspections May 2021 (P-MSGP-RI-5498) Contact: Phone: Contact: Phon: Contact: Phone: Contact: Phone: Contact: Phone: Contact: Phon:	2: MSGP Routine Facility Priority/Type: Normal / Inspection Inspection (EPC-CP-QP-2108 Department: Veepons Facilities Operations Veepons Facilities Veepon	

250	Outdoor vehicle and equipment washing areas: co and operating)? If "No" describe	ntrols adequate (approp	oriate, effective,			X	
260	Machinery: controls adequate (appropriate, effectiv	ve, and operating)? If "N	o" describe.		-		X
770	Waste handling and disposal areas: controls adequoted operating)? If "No" describe.					x	
280	Erodible areas/construction: controls adequate (ap "No" describe.	propriate, effective, and	operating)? If				
290	Locations and sources of run-on to the site: contro operating)? If "No" describe.	ls adequate (appropriate	e, effective, and				
300	Salt storage piles or pile containing salt: controls a operating)? If "No" describe.	dequate (appropriate, ef	ffective, and				
310	Dust generation and vehicle tracking: controls ade operating)? If "No" describe.	quate (appropriate, effec	ctive, and				
320	Housekeeping (Industrial materials/residues/trash adequate (appropriate, effective, and operating)? I		ter): controls				
330	Leaks and spills: controls adequate (appropriate, e describe.		? If "No"		·•_·		
340	Sector P [16001-P] Vehicle storage/maintenance a effective, and operating)? If "No" describe.	areas: controls adequate	e (appropriate,				
360 Additio 380	_describe. nal Control Measures Are permit requirements satisfied with existing con- additional control measures needed.	trol measure(s)? If "No"	describe				
.abor-							
abor		Assigned	Work Date		OT U-		
	y Bileen	5/1/2021 / 14		Reg Hrs			
abor F	Report						
Comple	eted:N/A						
Report: N/A							
-					_		_
-			1	0	-	-	
		1 2	9	-1/			
Kelkenn	y Bileen 06/18/21 Signature / Name Date			3C	06/1	2/2	1

CERTIFICATION STATEMENT

"I certify under penalty of law that this document and all attachments were prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gathered and evaluated the information submitted. Based on my inquiry of the person or persons who manage the system, or those persons directly responsible for gathering information, the information submitted is, to the best of my knowledge and belief, true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment for knowing violations".

(Signatory must meet definition in Section B.11.A, eg. FOD, Ops Mgr,	DESH Group Leader, EPC Group Leader)
Print name and title: John Branch, Operations Manager	12/5/
Signature:	Date: 6/17/2021

Los Alamos National Laboratory

Work Order MSGP-RI-64935

MSGP Routine Inspection Printed 1/5/2021 - 4:35 PM

	nce Details							
-	d: 1/5/2021 4:22:00 PM e: MSGP Routine Facility Inspection (EPC-CP-QP-2108 R0 Form 1) 12/3/2020	Target: Priority/Type: Department:	3/31/2021 Normal / Inspection Weapons Facilities Operations	MSGP 귦 RG253 ம TA-16 :		Area		
Project:	Routine Facility Inspections January 2021 (P-MSGP-RI- 5494)			Contact: Phone:				
Reason:	2021 Quarter 1 Inspection							
asks						_		
	Description nformation			Mix of clouds and some	Meas.	No	N/A	Yes
<u>20</u>	Describe the weather at time of ins	pection and doc	ument the temperature (F		60 degree	S T		<u></u>
- Is	e Facility Boundary s the facility free of previously unic occurred since the last inspection I	lentified discharg	ges from and/or pollutants	s that have		-	_	-
50	If "No" has a CAR been previous		s new discharge?					
60 ls	s the facility free of discharge of po			describe.				
ls	s the facility free of evidence of, or							
<u>70</u> s	ystem. If "No" describe.					X		1
of correct	spection (identify needed maint ive actions in relevant task com Ionitored Outfall [078] Free of E	iment)		sures that need	replaceme		a desc	ription
	Ionitored Outfall [078] Flow Diss			No" describe			<u> </u>	
N	Ionitored Outfall [078] Free of Ev					<u></u>		
120 d	Ionitored Outfall [078] Free of ar escribe.	y unauthorized	non-stormwater discharge	oc2 If "No"		,		
Control M	easures (identify needed mainte					X		
of correct	ive actions in relevant task corr	enance and rep	airs, failed control meas		replacmer			
E .		iments).		sures that need	replacmer		 descri	ption
	arthen Berm [1600103010001] C ondition & need for Maintenance,	i ments). Control Measure Repair, or Repla	is operating effectively? If cement.	sures that need f "No" describe	replacmer		 descri	iption
150 C	arthen Berm [1600103010001] C ondition & need for Maintenance, arthen Berm [1600103010002] C ondition & need for Maintenance,	i ments). Control Measure Repair, or Repla Control Measure Repair, or Repla	is operating effectively? If cement. is operating effectively? If cement.	sures that need f "No" describe f "No" describe	replacmer	it, or a	 descri	iption
150 CC E	arthen Berm [1600103010001] C ondition & need for Maintenance, arthen Berm [1600103010002] C	iments). Control Measure Repair, or Repla Control Measure Repair, or Repla Control Measure	is operating effectively? If cement. is operating effectively? If cement. is operating effectively? If	sures that need f "No" describe f "No" describe	replacmer	it, or a	 descri	iption
150 co 160 co	arthen Berm [1600103010001] C ondition & need for Maintenance, arthen Berm [1600103010002] C ondition & need for Maintenance, arthen Berm [1600103010003] C ondition & need for Maintenance, vity exposed to stormwater (ide	iments). Control Measure Repair, or Repla Control Measure Repair, or Repla Control Measure Repair, or Repla	is operating effectively? If cement. is operating effectively? If cement. is operating effectively? If cement.	sures that need f "No" describe f "No" describe f "No" describe		it, or a		
E 150 co E 160 co Area/Activ comment) 180 an	arthen Berm [1600103010001] C ondition & need for Maintenance, arthen Berm [1600103010002] C ondition & need for Maintenance, arthen Berm [1600103010003] C ondition & need for Maintenance, vity exposed to stormwater (ide laterial loading/unloading and stor nd operating)? If "No" describe,	iments). Control Measure Repair, or Repla Control Measure Repair, or Repla Control Measure Repair, or Repla ntify needed ma age areas: contr	is operating effectively? If cement. is operating effectively? If cement. is operating effectively? If cement. ainteance or a description rols adequate (appropriate	sures that need f "No" describe f "No" describe f "No" describe f "No" describe		it, or a		
E 150 Ca 160 Ca Area/Activ comment) 180 aa 180 Ti 190 op	arthen Berm [1600103010001] C ondition & need for Maintenance, arthen Berm [1600103010002] C ondition & need for Maintenance, arthen Berm [1600103010003] C ondition & need for Maintenance, vity exposed to stormwater (ide l. laterial loading/unloading and stor nd operating)? If "No" describe, ransfer areas for substances in bu perating)? If "No" describe.	iments). Control Measure Repair, or Repla Control Measure Repair, or Repla Control Measure Repair, or Repla ntify needed ma age areas: control ik: controls adec	is operating effectively? If cement. is operating effectively? If cement. is operating effectively? If cement. ainteance or a description rols adequate (appropriate quate (appropriate, effection	sures that need f "No" describe f "No" describe f "No" describe on of corrective e, effective, ve, and		it, or a		
E 150 cd 160 cd Area/Activ comment) 180 an 180 p 190 op 200 ar	arthen Berm [1600103010001] C ondition & need for Maintenance, arthen Berm [1600103010002] C ondition & need for Maintenance, arthen Berm [1600103010003] C ondition & need for Maintenance, vity exposed to stormwater (ideal laterial loading/unloading and stor nd operating)? If "No" describe, ransfer areas for substances in bu perating)? If "No" describe, roduct/chemical storage areas (ra nd operating)? If "No" describe,	iments). Control Measure Repair, or Repla Control Measure Repair, or Repla Control Measure Repair, or Repla ntify needed ma age areas: control ik: controls adec	is operating effectively? If cement. is operating effectively? If cement. is operating effectively? If cement. ainteance or a description rols adequate (appropriate quate (appropriate, effection trols adequate (appropriate)	sures that need f "No" describe f "No" describe f "No" describe f "No" describe on of corrective e, effective, ve, and te, effective,		it, or a		
E 150 ca 160 ca Area/Activ comment) 180 an 190 op 200 an Li 210 op	arthen Berm [1600103010001] C ondition & need for Maintenance, arthen Berm [1600103010002] C ondition & need for Maintenance, arthen Berm [1600103010003] C ondition & need for Maintenance, vity exposed to stormwater (idea laterial loading/unloading and stor nd operating)? If "No" describe, rransfer areas for substances in bu perating)? If "No" describe, roduct/chemical storage areas (ra nd operating)? If "No" describe, quid tank storage/secondary cont perating)? If "No" describe.	iments). Control Measure Repair, or Repla Control Measure Repair, or Repla Control Measure Repair, or Repla ntify needed ma age areas: control ik: controls adec w material): cont ainment: controls	is operating effectively? If cement. is operating effectively? If cement. is operating effectively? If cement. ainteance or a description rols adequate (appropriate quate (appropriate, effecti- trols adequate (appropriate, of s adequate (appropriate, of	sures that need f "No" describe f "No" describe f "No" describe f "No" describe on of corrective e, effective, ve, and te, effective, effective, and		it, or a		
E 150 ca 160 ca Area/Activ comment) 180 au 190 op 200 au Li 210 op In	arthen Berm [1600103010001] C ondition & need for Maintenance, arthen Berm [1600103010002] C ondition & need for Maintenance, arthen Berm [1600103010003] C ondition & need for Maintenance, vity exposed to stormwater (ide laterial loading/unloading and stor nd operating)? If "No" describe, rransfer areas for substances in bu perating)? If "No" describe, roduct/chemical storage areas (ra nd operating)? If "No" describe, quid tank storage/secondary cont	iments). Control Measure Repair, or Repla Control Measure Repair, or Repla Control Measure Repair, or Repla ntify needed ma age areas: control age areas: control ik: controls adec w material): controls ainment: controls	is operating effectively? If cement. is operating effectively? If cement. is operating effectively? If cement. ainteance or a description rols adequate (appropriate quate (appropriate, effecti- trols adequate (appropriate, of s adequate (appropriate, of	sures that need f "No" describe f "No" describe f "No" describe f "No" describe on of corrective e, effective, ve, and te, effective, effective, and		it, or a	 ant tasl 	

240 Fu	eling areas: controls adequate (appropriate, effective, and operating)? If "No" describ	e.		X	
Оц 250 an	utdoor vehicle and equipment washing areas: controls adequate (appropriate, effectiv d operating)? If "No" describe.	e,	[]		F .
	achinery: controls adequate (appropriate, effective, and operating)? If "No" describe.				
Wa	aste handling and disposal areas: controls adequate (appropriate, effective, and erating)? If "No" describe.				
Er 280 "N	odible areas/construction: controls adequate (appropriate, effective, and operating)? o" describe.	lf			
Lo 190 op	cations and sources of run-on to the site: controls adequate (appropriate, effective, a erating)? If "No" describe.	nd			
Sa 300 op	It storage piles or pile containing salt: controls adequate (appropriate, effective, and erating)? If "No" describe.				
	ist generation and vehicle tracking: controls adequate (appropriate, effective, and erating)? If "No" describe.			·	
Ho	ousekeeping (Industrial materials/residues/trash in contact with stormwater): controls equate (appropriate, effective, and operating)? If "No" describe.				
Le	aks and spills: controls adequate (appropriate, effective, and operating)? If "No" scribe.				
deitional	ee of incidents of observed non-compliance not already identified above? If "No" scribe. Control Measures		<u> </u>		_ <u>_</u>
	e permit requirements satisfied with existing control measure(s)? If "No" describe ditional control measures needed.		X		
abor .abor	Assigned Work Date	Reg Hrs	от н	rs Oth	er Hr
Kelkenny Bi	leen 1/1/2021 / 14			_	
abor Report Completed Report:	le Kelkenny Diben 02/23/21				
	Bignature / Name J Date Signature / Name	ne	-	Date	
	CERTIFICATION STATEMENT				

"I certify under penalty of law that this document and all attachments were prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gathered and evaluated the information submitted. Based on my inquiry of the person or persons who manage the system, or those persons directly responsible for gathering information, the

information submitted is, to the best of my knowledge and belief, true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment for knowing violations".

(Signatory must meet definition in Section B.11.A, eg. FOD, Ops Mgr, DESH Group Leader, EPC Group Leader)

Print name and title:_	John Branch	Operations Manager		
Signature:	h-13		Date: 4/21/2001	

Los Alamos National Laboratory

Work Order MSGP-RI-64702

MSGP Routine Inspection Printed 11/3/2020 - 10:56 AM (Duplicate Copy)

Mainte	nance Details							
-	ted: 10/5/2020 10:52:00 AM ure: MSGP Routine Facility Inspection (EPC-CP-QP- 2108 R0 Form 1)	Target: Priority/Type: Department:	12/31/2020 Normal / Inspection Weapons Facilities Operations	ឝ្ឋឹឝ RG25	P Program 3 Stockpile	Агеа		
.ast PN	1: 7/14/2020							
Project	Routine Facility Inspections October 2020 (P-MSGP-RI- 5477)			Contact: Phone:				
Reason	: 2020 Quarter 4 Inspection (Oct	-Nov-Dec)						
asks								
#	Description				Meas.	No	N/A	Yes
Weathe	er Information				Mostly			
20	Describe the weather at time of i	nspection and do	cument the temperature (F°). 31°F	Sunal			
Within	the Facility Boundary			211				
	Is the facility free of previously u	nidentified discha	rges from and/or pollutant	ts that have				
40	occurred since the last inspectio		See nem and of pendant					17
50	If "No" has a CAR been previo	usly initiated for th	nis new discharge?			Γ		Ē
60	Is the facility free of discharge of	pollutants at the t	time of inspection? If "No"	' describe			Г	X
70	Is the facility free of evidence of, system. If "No" describe.	or the potential fo	or, pollutants entering the	drainage				R
lescrip 00	Inspection (identify needed main otion of corrective actions in rele Monitored Outfall [078] Free of Monitored Outfall [078] Flow D	evant task comm Evidence of Eros	ent) ion? If "No", describe					
00	describe. Monitored Outfall [078] Free of						<u> </u>	R
110	Water? If "No", describe							X
120	Monitored Outfall [078] Free of describe.	any unauthorized	l non-stormwater discharg	ges? If "No"				X
Control	Measures (identify needed mai tion of corrective actions in rele	ntenance and re	pairs, failed control mea	sures that ne	ed replacn	nent, c	ora	
40	Earthen Berm [1600103010001 describe condition & need for Ma	Control Measure	e is operating effectively?	If "No"		Г		ĸ
50	Earthen Berm [1600103010002 describe condition & need for Ma	intenance, Repai	r, or Replacement.					K
60	Earthen Berm [1600103010003 describe condition & need for Ma			If "No"				
Area/Ac	ctivity exposed to stormwater (in nt).	tentify needed m	nainteance or a descript	ion of correct	ive actions	in rel	evant t	ask
80	Material loading/unloading and s and operating)? If "No" describe.							R
90	Transfer areas for substances in operating)? If "No" describe.						×	
:00	Product/chemical storage areas and operating)? If "No" describe.							
:10	Liquid tank storage/secondary co and operating)? If "No" describe.							
20	Industrial processing and finished effective, and operating)? If "No"		areas: controls adequate	(appropriate,		Г	Г	

230	Equipment operation and maintenance areas: controls adequate (appropriate, effective, and operating)? If "No" describe.		R	Г
240	Fueling areas: controls adequate (appropriate, effective, and operating)? If "No" describe.	Fi	R	
250	Outdoor vehicle and equipment washing areas: controls adequate (appropriate, effective, and operating)? If "No" describe.		x	
260	Machinery: controls adequate (appropriate, effective, and operating)? If "No" describe.			X
270	Waste handling and disposal areas: controls adequate (appropriate, effective, and operating)? If "No" describe.			X
280	Erodible areas/construction: controls adequate (appropriate, effective, and operating)? If "No" describe.			X
290	Locations and sources of run-on to the site: controls adequate (appropriate, effective, and operating)? If "No" describe.	Γ		R
300	Salt storage piles or pile containing salt: controls adequate (appropriate, effective, and operating)? If "No" describe.		R	Г
310	Dust generation and vehicle tracking: controls adequate (appropriate, effective, and operating)? If "No" describe.			R
320	Housekeeping (Industrial materials/residues/trash in contact with stormwater): controls adequate (appropriate, effective, and operating)? If "No" describe		Г	X
330	Leaks and spills: controls adequate (appropriate, effective, and operating)? If "No" describe.			R
Non-C	Compliance			
350	Free of incidents of observed non-compliance not already identified above? If "No" describe.		Г	×
additi	onal Control Measures			
370	Are permit requirements satisfied with existing control measure(s)? If "No" describe additional control measures needed.			X
abor	Report			
	leted: 12/03/20			
Jomp	leleu: <u></u>			
Repor	t: Kelkenny Bileen			
11	Plus			
12	Signature / Name / Date Signature / Name		Date	
confir	m the information as recorded is true, accurate and complete.		2010	

CERTIFICATION STATEMENT

"I certify under penalty of law that this document and all attachments were prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gathered and evaluated the information submitted. Based on my inquiry of the person or persons who manage the system, or those persons directly responsible for gathering information, the information submitted is, to the best of my knowledge and belief, true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment for knowing violations".

(Signatory must meet definition in Section B.11.A, eg. FOD, Ops Mgr, DESH Group Leader, EPC Group Leader)

Print name and title:

Signature:_

Date:

Los Alamos National Laboratory

Work Order MSGP-RI-64299

MSGP Routine Inspection Printed 6/29/2020 - 4:31 PM

Maintena	ance Details					_		
•	et: 5/28/2020 12:24:00 PM e: MSGP Routine Facility Inspection (EPC-CP-Form- 1020.2) 4/15/2020	Target: Priority/Type: Department:		제SGP 급급 RG253 삶 TA-16 5	-	Area		
	2020 Quarter 2 Inspections (July	-Aug-Sept)		Contact: Phone:				
1025011		, kug eoptij		Filone.				
Tasks								
#	Description				Meas.	No	N/A	Yes
Weather	Information							
20	Describe the weather at time of in	spection and doc	ument the temperature (F	°).	79°			x
Within th	e Facility Boundary							
	s the facility free of new discharge nspection? If "Failed" describe.	es of pollutants th	nat have occurred since th	e last				X
50	If "No" has a CAR been previous	sly initiated for thi	is new discharge?					X
60	s the facility free of discharge of p	collutants at the ti	me of inspection? If "No"	describe.		Γ		X
	s the facility free of evidence of, c system. If "No" describe.	or the potential for	r, pollutants entering the d	lrainage				Xi
of correct	spection (identify needed main tive actions in relevant task con Monitored Outfall [078] Free of E Monitored Outfall [078] Flow Dia	mment) Evidence of Erosi	on? If "No", describe.		replacem	ent, or	a desc	X
·,	Monitored Outfall [078] Flow Dis							x
110	Monitored Outfall [078] Free of E Water? If "No", describe.							<u> </u>
	Monitored Outfall [078] Free of a describe.	iny unauthorized	non-stormwater discharge	es? If "No"		_□_		X
	leasures (identify needed main		airs, failed control mea	sures that need	replacme	ent, or a	descri	iption
1	tive actions in relevant task con Earthen Berm [1600103010001] condition & need for Maintenance.	Control Measure		f "No" describe		6		X
Ĩ	Earthen Berm [1600103010002] condition & need for Maintenance,	Control Measure	is operating effectively? I	f "No" describe				
	Earthen Berm [1600103010003] condition & need for Maintenance.	Control Measure	is operating effectively? I	f "No" describe		<u>г</u>		
	vity exposed to stormwater (ide	entify needed m	ainteance or a description	on of corrective	actions i	n relev	ant tas	k k
comment	•		rele edeguate (energyist					
<u>180</u> a	Material loading/unloading and sto and operating)? If "No" describe.							X
190 0	Fransfer areas for substances in b operating)? If "No" describe.						X	
<u>200</u> a	Product/chemical storage areas (r and operating)? If "No" describe.						X	
<u>210 c</u>	.iquid tank storage/secondary con operating)? If "No" describe.						X	
<u>220</u>	ndustrial processing and finished affective, and operating)? If "No" d	escribe			_		X	
230 0	Equipment operation and mainten operating)? If "No" describe.						X	
	ueling areas: controls adequate (X	
	Dutdoor vehicle and equipment wa and operating)? If "No" describe.	ashing areas: cor	ntrols adequate (appropria	te, effective,			X	

260	Machinery: controls adequate (appropriate, effective, and operating)? If "No" describe.			1.13
270	Waste handling and disposal areas: controls adequate (appropriate, effective, and operating)? If "No" describe.		X	· 🔽
280	Erodible areas/construction: controls adequate (appropriate, effective, and operating)? If "No" describe.			X
290	Locations and sources of run-on to the site: controls adequate (appropriate, effective, and operating)? If "No" describe.			X
300	Salt storage piles or pile containing salt: controls adequate (appropriate, effective, and operating)? If "No" describe.	Г		Г
310	Dust generation and vehicle tracking: controls adequate (appropriate, effective, and operating)? If "No" describe.			
320	Housekeeping (Industrial materials/residues/trash in contact with stormwater): controls adequate (appropriate, effective, and operating)? If "No" describe. Plastic debris, metal banding, gravel bags	X	F	Г
№п-С	Leaks and spills: controls adequate (appropriate, effective, and operating)? If "No" describe. compliance Free of incidents of observed non-compliance not already identified above? If "No"			<u> </u>
Non-C 350 Additie	describe. compliance Free of incidents of observed non-compliance not already identified above? If "No" describe. conal Control Measures Are permit requirements satisfied with existing control measure(s)? If "No" describe			<u> </u>
Non-C 350 Additie 370	describe. ompliance Free of incidents of observed non-compliance not already identified above? If "No" describe. onal Control Measures			
350 Additid 370	describe. compliance Free of incidents of observed non-compliance not already identified above? If "No" describe. conal Control Measures Are permit requirements satisfied with existing control measure(s)? If "No" describe additional control measures needed. Report leted: 07/14/2020			<u>x</u>
Non-C 350 Additid 370 abor I	describe. compliance Free of incidents of observed non-compliance not already identified above? If "No" describe. conal Control Measures Are permit requirements satisfied with existing control measure(s)? If "No" describe additional control measures needed. Report eted: 07/14/2020 t: Remove extra TRM Matting and 11 gauge staples			<u> </u>

CERTIFICATION STATEMENT

"I certify under penalty of law that this document and all attachments were prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gathered and evaluated the information submitted. Based on my inquiry of the person or persons who manage the system, or those persons directly responsible for gathering information, the information submitted is, to the best of my knowledge and belief, true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment for knowing violations".

(Signatory must meet definition in Section B.11.A, eg. FOD, Ops Mgr, DESH Group Leader, EPC Group Leader)

Print name and titler	John Bo	anch	WFO OR	erations	Manager
Signature:	Dr.		Date:	9-29.	- 2020
0					

Los Alamos National Laboratory

Work Order MSGP-RI-64161

MSGP Routine Inspection Printed 4/8/2020 - 2:49 PM

Maintenai	nce Details							
	 3/17/2020 3:56:00 PM MSGP Routine Facility Inspection (EPC-CP-Form- 1020.2) 	Target: Priority/Type: Department:		🛁 MSGP 品 RG-TA 由 TA-16		Area		
Last PM:	N/A			Contact:				
Project:	Routine Facility Inspections April 2020 (P-MSGP-RI-5429)			Phone:				
Reason: 2	2020 April Inspections							
Tasks								
# D	escription				Meas.	No	N/A	Yes
Weather I	nformation			Clear,				
20 D	escribe the weather at time of ins	pection and doc	ument the temperature (F°).	1000	710		Г_	<u> </u>
ls	Facility Boundary	s of pollutants th	at have occurred since the la	ast				
	spection? If "Failed" describe.					<u> </u>		
50	If "No" has a CAR been previous					<u> </u>	<u>_R</u> _	
	the facility free of discharge of po the facility free of evidence of, or							<u>_K_</u>
	"No" describe.	the potential for	, pollutants entering the drai	nage system.			<u>_</u> X_	
Outfall Ins of correct	pection (identify needed maint ive actions in relevant task con	enance and rep nment)	airs, failed control measur	es that need	replaceme	ent, or	a desc	ription
90 M	onitored Outfall [078] Free of E	vidence of Erosi	on? If "No", describe.		_			
	Ionitored Outfall [078] Flow Diss	the second s		and the second se				R
	onitored Outfall [078] Free of E /ater? If "No", describe.	vidence of Pollut	ants in Discharges and/or Re	eceiving		п		_ <u>X</u>
	onitored Outfall [078] Free of a escribe.	ny unauthorized	non-stormwater discharges?	' If "No"			Г	<u> </u>
	easures (identify needed maint ive actions in relevant task con		airs, failed control measur	es that need	replacmer	nt, or a	descri	ption
140 co	arthen Berm [1600103010001] (andition & need for Maintenance,	Control Measure Repair, or Repla	is operating effectively? If "N icement.	lo" describe				X
	arthen Berm [1600103010002] (andition & need for Maintenance,			lo" describe		л.	Г.	<u></u>
	arthen Berm [1600103010003] (andition & need for Maintenance,			lo" describe				<u>x</u>
Area/Activ comment)	rity exposed to stormwater (ide	ntify needed m	ainteance or a description	of corrective	actions in	n releva	ant tasl	ĸ
M	aterial loading/unloading and sto perating)? If "No" describe.	rage areas: cont	rols adequate (appropriate, e	effective, and		E	Г	K
	ransfer areas for substances in bu perating)? If "No" describe.	ulk: controls adeo	quate (appropriate, effective,	and		Г	R	
	roduct/chemical storage areas (ra nd operating)? If "No" describe.	iw material): con	trols adequate (appropriate,	effective,		Г	X	
210 or	quid tank storage/secondary cont nerating)? If "No" describe.				_	Г.	<u></u>	
<u>220 ef</u>	dustrial processing and finished p fective, and operating)? If "No" de	escribe.				П		<u> </u>
<u>230 or</u>	quipment operation and maintena perating)? If "No" describe.					<u> </u>	<u>_</u>	K
240 Fi	ueling areas: controls adequate (a	appropriate, effe	ctive, and operating)? If "No'	' describe.		5	-14-	<u> </u>

260 Machinery: controls adequate (appropriate, effective, and operating)? If "No" describe. Γ K 280 Machinery: controls adequate (appropriate, effective, and operating)? If "No" describe. Γ K 280 "No" describe. Γ K Γ K 280 "No" describe. Γ Γ K K 280 "No" describe. Γ Γ K K 280 operating)? If "No" describe. Γ Γ K K 280 operating)? If "No" describe. Γ Γ K Γ Γ K 280 operating)? If "No" describe. Γ Γ K Γ K Γ 300 operating)? If "No" describe. Γ Γ K Γ K Γ 310 operating)? If "No" describe. Γ Γ K Γ K Γ K Γ K Γ K Γ K Γ K K Γ K K Γ K K Γ K K K K K K		ontrols adequate (appropriate, effective,		Г	×	П
Waste handling and disposal areas: controls adequate (appropriate, effective, and operating)? If "No" describe. Г R Г R Г R Г R Г R Г R Г R Г R Г R L <td></td> <td>ve, and operating)? If "No" describe.</td> <td></td> <td>—</td> <td>X</td> <td>F</td>		ve, and operating)? If "No" describe.		—	X	F
Erodible areas/construction: controls adequate (appropriate, effective, and operating)? If "No" describe. 280 "No" describe. 281 storage piles or pile containing salt: controls adequate (appropriate, effective, and 290 operating)? If "No" describe. 290 Dust generation and vehicle tracking: controls adequate (appropriate, effective, and 291 operating)? If "No" describe. 290 Dust generation and vehicle tracking: controls adequate (appropriate, effective, and 291 operating)? If "No" describe. 290 Dust generation and vehicle tracking: controls adequate (appropriate, effective, and 291 operating)? If "No" describe. 290 Dust generation and vehicle tracking: controls adequate (appropriate, effective, and 290 operating)? If "No" describe. 290 Dust generating? If "No" describe. 290 Housekeeping (Industrial materials/residues/trash in contact with stormwater): controls 290 adequate (appropriate, effective, and operating)? If "No" describe. 290 Dust generating? If "No" describe generating? I	Waste handling and disposal areas: controls adequ				- <u> </u>	
290 operating)? If "No" describe. <pre> F</pre> Salt storage piles or pile containing salt controls adequate (appropriate, effective, and operating)? If "No" describe. F Subscription and vehicle tracking: controls adequate (appropriate, effective, and operating)? If "No" describe. F		ppropriate, effective, and operating)? If				<u></u>
Salt storage piles or pile containing salt: controls adequate (appropriate, effective, and operating)? If "No" describe. Dust generation and vehicle tracking: controls adequate (appropriate, effective, and operating)? If "No" describe. Housekeeping (Industrial materials/residues/trash in contact with stormwater): controls adequate (appropriate, effective, and operating)? If "No" describe. Salt Leaks and spills: controls adequate (appropriate, effective, and operating)? If "No" describe. Non-Compliance Free of incidents of observed non-compliance not already identified above? If "No" describe. Additional Control Measures Are permit requirements satisfied with existing control measure(s)? If "No" describe additional control measures needed Labor Kelkenny Bileen Additional control measures needed Completed: Report: - Additional control Measure in place around spoils pite, Signature / Name Signature / Name Signature / Name Signature / Name Signature / Name Control Measure Signature / Name Control Measure Signature / Name Control Measure		ols adequate (appropriate, effective, and		Г	Г.	
Dust generation and vehicle tracking: controls adequate (appropriate, effective, and operating)? If "No" describe. Image: Controls adequate (appropriate, effective, and operating)? If "No" describe. 320 adequate (appropriate, effective, and operating)? If "No" describe. Image: Controls adequate (appropriate, effective, and operating)? If "No" describe. 330 Leaks and spills: controls adequate (appropriate, effective, and operating)? If "No" describe. Image: Controls adequate (appropriate, effective, and operating)? If "No" describe. 330 Leaks and spills: controls adequate (appropriate, effective, and operating)? If "No" describe. Image: Control is adequate (appropriate, effective, and operating)? If "No" describe. 340 Leaks and spills: controls adequate (appropriate, effective, and operating)? If "No" describe. Image: Control is adequate (appropriate, effective, and operating)? If "No" describe 350 describe. Image: Control is adequate (appropriate, effective, and operating)? If "No" describe 370 Additional control measures needed. Image: Control is adequate (appropriate, effective, and appropriate, additional control measures needed. 370 Additional control measures needed. Image: Control is additional control measures needed. 380 Regnot: Additional control measure in pluce around oposite pite, is abo		adequate (appropriate, effective, and		Γ	x	<u>г</u>
Housekeeping (Industrial materials/residues/trash in contact with stormwater): controls adequate (appropriate, effective, and operating)? If "No" describe. I		equate (appropriate, effective, and		Γ		
Non-Compliance Free of incidents of observed non-compliance not already identified above? If "No" 350 describe. Additional Control Measures Are permit requirements satisfied with existing control measure(s)? If "No" describe 370 additional control measures needed additional control measures needed abor Labor Labor Kelkenny Bileen 4/30/2020 / 14 Wheeler, Holly 4/30/2020 / 14 wheeler, Holly 4/30/2020 / 14 Additional control measure in place around specifs pile, See map updated in the SWPP. Date Date Signature/Name Date Date					Г Г	K
Free of incidents of observed non-compliance not already identified above? If "No" 350 describe. Additional Control Measures Are permit requirements satisfied with existing control measure(s)? If "No" describe 370 additional control measures needed. Image: Statistic of the existing control measure(s)? If "No" describe 370 additional control measures needed. Image: Statistic of the existing control measure(s)? If "No" describe 370 additional control measures needed. Image: Statistic of the existing control measure(s)? If "No" describe 370 additional control measures needed. Image: Statistic of the existing control measure(s)? If "No" describe 370 additional control measures needed. Image: Statistic of the existing control measure(s)? If "No" describe Image: Statistic of the existing control measure(s)? If "No" describe abor Assigned Work Date Reg Hrs OT Hrs Other Hrs abor A/30/2020 / 14 A/30/2020 / 14 wheeler, Holly 4/30/2020 / 14 A/30/2020 / 14 abor Additional control measure in place around sports pite, Statistic of the existing control measure in place around sports pite, Stepating: Statis of the existic of the existing control measure in plac	Leaks and spills: controls adequate (appropriate, e	effective, and operating)? If "No" describe.			Г	<u> </u>
Labor Assigned Work Date Reg Hrs OT Hrs Other Hrs Kelkenny Bileen 4/30/2020 / 14 Wheeler, Holly 4/30/2020 / 14 abor Report Completed:		ntrol measure(s)? If "No" describe		<u> </u>	<u>г_</u> _	<u>_</u>
Kelkenny Bileen 4/30/2020 / 14 Wheeler, Holly 4/30/2020 / 14 abor Report Completed:				-		
Wheeler, Holly 4/30/2020 / 14 abor Report Completed: Report: 	Pu Bilgen		Reg Hrs	OT Hrs	Othe	r Hrs
abor Report Completed: Report: - Additional control Measure in place around spoils pile, 					2-	
Completed: Report: - Additional control Measure in place around spoils pile, 	5, TONY	4730/2020 7 14				
Report: - Additional control measure in place around spoils pile, see map updated in the SWPAP. - Additional control measure in place around spoils pile, - Date Signature/Name Date Date	Report			- 7		-
Report: - Additional control measure in place around spoils pile, see map updated in the SWPAP. - Additional control measure in place around spoils pile, - Difference of the SWPAP. - Difference						
- Additional control Measure in place around spoils pile, see map updated in the SWPAP. Marker 04/15/20 Signature/Name Date Signature/Name Date	eted:					
see map updated in the SWPAP. When Diffed in the SWPAP. Signature / Name Date Date Date						
Signature / Name Date Signature / Name Date	" - Additional control Measure	in pluce around spoils	oile.			
Signature / Name Date Signature / Name Date	- Additional control Measure		pile,	5		
	- Additional control Measure		pile,	1		
	- Additional control Measure see map updated in t Ate 04/15/	he SWPPP.	pile,	1		
2		and operating)? If "No" describe. Machinery: controls adequate (appropriate, effecti Waste handling and disposal areas: controls adeq operating)? If "No" describe. Erodible areas/construction: controls adequate (ap "No" describe. Locations and sources of run-on to the site: control operating)? If "No" describe. Salt storage piles or pile containing salt: controls ade operating)? If "No" describe. Dust generation and vehicle tracking: controls ade operating)? If "No" describe. Housekeeping (Industrial materials/residues/trash adequate (appropriate, effective, and operating)? Leaks and spills: controls adequate (appropriate, of ompliance Free of incidents of observed non-compliance not describe. onal Control Measures Are permit requirements satisfied with existing cor additional control measures needed. ny Bileen er, Holly Report	Machinery: controls adequate (appropriate, effective, and operating)? If "No" describe. Waste handling and disposal areas: controls adequate (appropriate, effective, and operating)? If "No" describe. Erodible areas/construction: controls adequate (appropriate, effective, and operating)? If "No" describe. Locations and sources of run-on to the site: controls adequate (appropriate, effective, and operating)? If "No" describe. Salt storage piles or pile containing salt: controls adequate (appropriate, effective, and operating)? If "No" describe. Dust generation and vehicle tracking: controls adequate (appropriate, effective, and operating)? If "No" describe. Housekeeping (Industrial materials/residues/trash in contact with stormwater): controls adequate (appropriate, effective, and operating)? If "No" describe. Leaks and spills: controls adequate (appropriate, effective, and operating)? If "No" describe. Leaks and spills: controls adequate (appropriate, effective, and operating)? If "No" describe. Leaks and spills: controls adequate (appropriate, effective, and operating)? If "No" describe. Leaks and spills: controls adequate (appropriate, effective, and operating)? If "No" describe. onpliance Free of incidents of observed non-compliance not already identified above? If "No" describe additional control measures needed. my Bileen 4/30/2020 / 14 er, Holly 4/30/2020 / 14	and operating)? If "No" describe. Machinery: controls adequate (appropriate, effective, and operating)? If "No" describe. Waste handling and disposal areas: controls adequate (appropriate, effective, and operating)? If "No" describe. Erodible areas/construction: controls adequate (appropriate, effective, and operating)? If "No" describe. Locations and sources of run-on to the site: controls adequate (appropriate, effective, and operating)? If "No" describe. Salt storage piles or pile containing salt: controls adequate (appropriate, effective, and operating)? If "No" describe. Dust generation and vehicle tracking: controls adequate (appropriate, effective, and operating)? If "No" describe. Housekeeping (Industrial materials/residues/trash in contact with stormwater): controls adequate (appropriate, effective, and operating)? If "No" describe. Leaks and spills: controls adequate (appropriate, effective, and operating)? If "No" describe. Leaks and spills: controls adequate (appropriate, effective, and operating)? If "No" describe. Ompliance Free of incidents of observed non-compliance not already identified above? If "No" describe additional control measures needed No Bileen 4/30/2020 / 14 ar, Holly 4/30/2020 / 14 ar, Holly 4/30/2020 / 14	and operating)? If "No" describe. Machinery: controls adequate (appropriate, effective, and operating)? If "No" describe. Waste handling and disposal areas: controls adequate (appropriate, effective, and operating)? If "No" describe. Erodible areas/construction: controls adequate (appropriate, effective, and operating)? If "No" describe. Locations and sources of run-on to the site: controls adequate (appropriate, effective, and operating)? If "No" describe. Salt storage piles or pile containing salt: controls adequate (appropriate, effective, and operating)? If "No" describe. Dust generation and vehicle tracking: controls adequate (appropriate, effective, and operating)? If "No" describe. Housekeeping (Industrial materials/residues/trash in contact with stormwater): controls adequate (appropriate, effective, and operating)? If "No" describe. Leaks and spills: controls adequate (appropriate, effective, and operating)? If "No" describe. Leaks and spills: controls adequate (appropriate, effective, and operating)? If "No" describe. Impliance Free of incidents of observed non-compliance not already identified above? If "No" describe additional control measures needed my Bileen 4/30/2020 / 14 ar, Holly 4/30/2020 / 14	and operating)? If "No" describe. Machinery: controls adequate (appropriate, effective, and operating)? If "No" describe. Waste handling and disposal areas: controls adequate (appropriate, effective, and operating)? If "No" describe. Image: Control State (Control State)? Erodible areas/construction: controls adequate (appropriate, effective, and operating)? If "No" describe. Image: Control State (Control State)? Locations and sources of run-on to the site: controls adequate (appropriate, effective, and operating)? If "No" describe. Image: Control State (Control State)? Salt storage piles or pile containing salt: controls adequate (appropriate, effective, and operating)? If "No" describe. Image: Control State (Control State)? Dust generation and vehicle tracking: controls adequate (appropriate, effective, and operating)? If "No" describe. Image: Control State (Control State)? Housekeeping (Industrial materials/residues/trash in contact with stormwater): controls adequate (appropriate, effective, and operating)? If "No" describe. Image: Control State compliance Image: Control State (Control State)? If "No" describe. Image: Control State)? Free of incidents of observed non-compliance not already identified above? If "No" describe additional control measures needed. Image: Control State)? Mathematic control measures needed. Image: Control State)? Image: Control State)? Pree formit requirements satisfied with existing control measure(s)? If "No" describe additional control me

CERTIFICATION STATEMENT

"I certify under penalty of law that this document and all attachments were prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gathered and evaluated the information submitted. Based on my inquiry of the person or persons who manage the system, or those persons directly responsible for gathering information, the information submitted is, to the best of my knowledge and belief, true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment for knowing violations".

(Signatory must meet definition in Section B.11.A, eg. FOD, Ops Mgr, DESH Group Leader, EPC Group Leader)

Print name and title:	anch, WF	FO-HE OM	1
Signature: Jahn B	\mathcal{Q}'	Date: 4-15-20	20
0			1

ATTACHMENT 8: QUARTERLY VISUAL ASSESSMENTS

ATTACHMENT 9: CORRECTIVE ACTION DOCUMENTATION AND CERTIFICATION

ATTACHMENT 10: SCHEDULED MAINTENANCE LOG

Date	Control Measure or Equipment Description (include location where appropriate)	Action Taken/Comments	Action Taken By (printed name & Z no.)
2021	No maintenance required.		

ATTACHMENT 11: TRAINING DOCUMENTATION

Information on employees receiving training is available upon request.

June 10, 2020

AGENDA

For

TA-16 STOCKPILE AREA MSGP TRAINING

- 1. Brief overview of the National Pollutant Discharge Elimination System, Multi-Sector General Permit (MSGP)
 - a. The MSGP is a nation-wide general permit
 - b. It authorizes the discharge of stormwater from specific industrial activities to meet Clean Water Act provisions
 - c. EPA is the regulatory authority
 - i. NM Environment Department is delegated authority to conduct inspections for them.
- 2. Key Elements of the MSGP
 - a. Industrial sites must have a Stormwater Pollution Prevention Plan (SWPPP)
 - b. Stormwater discharge from the site is sampled and analytical monitoring conducted
 - c. Quarterly inspections are performed at the site
 - d. Conditions requiring corrective action are identified, documented, and addressed
- 3. Purpose of the MSGP is to MINIMIZE off-site migration of pollutants
 - a. Ensure controls are always adequate (not just after identification of a condition requiring corrective action)
- 4. (You all may be wondering why you are here) The permit requires personnel who implement requirements of the permit to be trained
 - a. You all are or will be managing industrial materials (sand, gravel, base course, clean fill) and conducting activities on an industrial site (TA-16 Stockpile Area)
- 5. SWPPP
 - a. Identifies a Pollution Prevention Team
 - i. This team consists of Bob Lechel, Kelkenny Bileen, John Branch, Holly Wheeler and Adam Martinez. This team is instrumental in ensuring implementation of the MSGP, SWPPP, and associated stormwater controls.
 - b. Identifies potential pollutant sources (Ask trainees what they think these sources are)
 - i. Spills of fuel, oil, grease, fluids (transmission and hydraulic), anti-freeze and associated heavy metals
 - ii. Dust from loading and unloading of materials
 - iii. Sediment
 - iv. (Ask Trainees how WFO prevents potential pollutants in potholing water from being accepted)
 - v. Describes stormwater controls used to reduce/eliminate pollutants in stormwater discharges
 - 1. Review SWPPP map and walk down controls at the site. Discuss their purpose and when they should be repaired or replaced.

- vi. Contains procedures the site uses to comply with the terms/conditions of the permit
 - 1. WFO-IWD-00016, Spill Response and Clean Up in Weapons Facilities Operations Areas
 - 2. Weapons Facilities Operations Clean Fill Acceptance and Reuse Process (Kelkenny to review process briefly)
 - 3. Procedures by EPC-CP specifically identifying how permit conditions are implemented
 - a. How to conduct inspections, visual assessments, document conditions requiring corrective actions, obtain samples, etc.
- 6. Spill response and clean up
 - a. (Ask Trainees what they would do if they noticed the truck, forklift, front-end loader or potholing machine, was leaking)
 - b. Call the EPC-CP spills pager at 505-664-7722
 - c. If trained, implement the requirements of WFO-IWD-00016, Spill Response and Clean Up in Weapons Facilities Operations Areas *immediately*
 - d. All complex/emergency spills or releases are reported to the Emergency Operations Support Center (EOSC) 667-2400
 - e. For fire or explosion call 911 or activate fire pull box
- 7. Good Housekeeping
 - a. Keep Stockpile Area in an orderly condition. (Ask Trainees what they would do if they noticed waste, trash, or debris in the Stockpile Area)
 - b. If sediment is tracked onto K-Site Road, sweeping will occur.
 - c. Maintain adequate capacity to accommodate precipitation events and prevent inadvertent discharge of pothole or culvert cleanout water.
 - d. Pick up garbage, debris, and floatables when observed on-site.
 - e. Check trucks, loaders, forklifts and other heavy equipment for leaks prior to using them to transport material to the TA-16 Stockpile Area. Only use well maintained trucks and heavy equipment for transfer operations.
- 8. Material Management
 - a. Keep materials (sand, gravel, rock, base course, soil and clean fill within the designated material storage area.
 - b. Disposition potholing washout and culvert cleanout water in the pothole staging area.
 - c. Contact Kelkenny Bileen and your Waste Management Coordinator if the pothole staging area starts getting full.



MSGP Training Overview

Presented by the EPC-CP Stormwater Permitting/Compliance Team

April 2020



Managed by Triad National Security, LLC for the U.S. Department of Energy's NNSA

LA-UR-YY-XXXXX



"GOSH, TOTO . . . WATER IN OZ MUST REALLY BE POLLUTED!"

Slide 2

LOS Alamos NATIONAL LABORATORY



What is the MSGP?

- A nation-wide general permit
- Authorizes the discharge of stormwater from specific industrial activities to meet Clean Water Act provisions
 - MSGP contains 30 industrial sectors
- EPA is the regulatory authority
 - NM Environment Department is delegated authority to conduct inspections



MSGP Industrial Sectors Within LANL

- LANL (Triad) has 8 of the 30 industrial sectors
 - Asphalt Paving Manufacturing (Sector D)
 - Fabricated Metal Products (Sector AA)
 - Primary Metals (Sector F)
 - Timber Products (Sector A)
 - Scrap Recycling (Sector N)
 - Steam Electric Generation (Sector O)
 - Land Transportation/Warehousing (Sector P)
 - Hazardous Waste Treatment, Storage, or Disposal (Sector K)

Slide 4

• UI FOD has facilities in 6 of these sectors.



What is the Purpose of the MSGP?

- Minimize off-site migration of pollutants!
 - Ensure controls are *always* adequate (not just after identification of condition requiring corrective action or exceedance of permit limit).



What are the Key Elements of the MSGP?

- Storm Water Pollution Prevention Plan (SWPPP)
- Storm Water Sampling
- Analytical Monitoring
- Inspections
- Corrective Actions





Key Elements of the MSGP

SWPPP

- Facility-specific document identifying how MSGP requirements will be met at the facility
 - All personnel implementing MSGP requirements must be trained to, and understand it
 - Identifies potential pollutant sources
 - Describes stormwater controls used to reduce/eliminate pollutants in discharges

- Contains procedures the facility uses to comply with terms/conditions of the permit
- Identifies the Pollution Prevention Team (PPT)



Pollution Prevention Team

- Typically consists of the FOD/Designee, DESH Group Leader, Operations Manager, DEP, and the MSGP Program Lead
- Provides expertise to evaluate changes to the design of controls and facilitates action to resolve identified issues/conditions <u>(i.e., Corrective Action)</u>
- Assists with Stormwater Control Implementation
 - Design, install, and implement control measures (including best management practices) to minimize pollutant discharges and meet effluent limits



Pollution Prevention Team (cont.)

- Stormwater Control Implementation (cont.)
 - Consider the following when selecting and designing control measures
 - Minimizing stormwater contact with potential pollutants
 - Using control measures in combination
 - Assessing the type and quantity of pollutants
 - Minimizing impervious areas and infiltrating runoff onsite
 - Attenuating flow using open vegetated swales and natural depressions
 - Conserving and/or restoring riparian buffers
 - Using treatment interceptors (e.g., vortex separators and sand filters)





MSGP Storm Water Sampling



Managed by Triad National Security, LLC for the U.S. Department of Energy's NNSA

LA-UR-YY-XXXXX

What triggers a sample?

- A measureable storm event
 - One that results in an actual discharge
 - Proceed an event by at least 72-hours

- EPC-CP Database
 - Rainfall Data/Rain gages
 - Flow intensities at facilities



How are samples collected?

- Automated Samplers
 - Avalanche (refrigerated)
 - Model 3700 (filtered)
- Grab Sample





Avalanche Sampler



- MSGP requires sample collection to follow 40 CFR Part 136
- Some constituents require refrigeration as preservation within 15 minutes



3700 Sampler



Other constituents require filtering within 15 minutes



Where are samples collected?

- Monitored Outfalls
 - Automated Samplers
- Substantially Identical Outfalls
 - Other outfalls that discharge substantially identical effluent





What types of samples are collected?

- Samples for analysis of monitored constituents
- Samples for field parameters
 - Visual Assessment
 - pH





Collection and Preservation

 Volume collected are based on 40 CFR 136 and identified in the SAP provided by EPC-CP

- Volumes from samplers are transferred to shipping containers (250mL, 500mL, 1L, etc.)
- Filter samples and add preservatives
- SMO ships to off-site analytical laboratory



Visual Assessments

- Examination includes:
 - Odor
 - Color
 - Clarity
 - Floating solids
 - Settled solids
 - Suspended solids
 - Foam
 - Oil sheen
 - Other obvious indicators of storm water pollution







MSGP Analytical Monitoring



Managed by Triad National Security, LLC for the U.S. Department of Energy's NNSA

LA-UR-YY-XXXXX

Monitoring Requirements

Why?

 To demonstrate that pollutants resulting from industrial activity are not being discharged from the site (or not exceeding numeric limits)

Slide 20

Show effectiveness of stormwater control measures

What? Analytical monitoring types

- Benchmark
- Impaired Waters
- Effluent Limitation Guidelines (ELG)
- 103 Analytical Samples planned for MY20



Monitoring Requirements

How?

- 40 CFR § 136

 Defines Clean Water Act analytical methods, sample containers, volumes, preservatives, holding times, and cool samples immediately after collection and store < 6°C (42° F)

Laboratories performing analyses for NPDES certified under

National Environmental Laboratory Accreditation Program (NELAP)

- DOE Consolidated Audit Program (DOECAP)
- 20.6.4 NMAC NM Water Quality Standards
 - Applies to Impaired Waters and some Benchmark parameters
 - Dissolved metals require 0.45 micron filtration
 - Total recoverable AI requires 10 micron filtration



Monitoring Frequency

When?

- Monitoring season April 1- Nov 30
 - 2-month quarters
 - Once per Quarter
 - Benchmark monitoring
 - Once per Year
 - Impaired Waters
 - Effluent Limitation Guidelines (ELG)



Benchmarks

Parameters are sector-specific – based on industrial activity

Sector	Industrial Activity	Parameter(s)	Facilities
А	Timber Products	COD, TSS	TA-3-38 Carpenter Shop
AA	Fabricated Metals	Al, Fe, Zn, NO2-+NO3-N	TA-3-38 Metals Fab Shop TA-60-1 Heavy Equipment Yard
D	Asphalt Paving	pH, TSS, Oil and Grease	TA-60 Asphalt Batch Plant
Ν	Scrap Recycling	N/A for subsector	TA-60 MRF
0	Steam Electric Power	Fe	TA-3-22 Power & Steam Plant
Ρ	Land Transportation/ Warehousing	N/A	TA-16 Stockpile Yard TA-60-1 Heavy Equipment Yard TA-60-2 Warehouse TA-60 Roads and Grounds

Slide 23



New for next permit:

- Universal benchmarks for <u>all</u> sectors: pH, TSS, COD
- Fe dropped from Sector AA, O
- Hg and Pb added to Sector P



Benchmark Limits

Benchmark limits provided in permit

• Superseded by NM WQS if different

Analyte	Field Prep Code	National Benchmark	Chronic Exposure Limit	Acute Exposure Limit	Units	Regulatory Source
Al*	F10U	750	1010	2520	ug/L	20.6.4.900 NMAC Subpart I
COD	UF	120	120	120	mg/L	NMR053195 Sect 9.6.2.1
Fe	UF	1000	1000	1000	ug/L	NMR053195 Sect 9.6.2.1
Hg	UF	1.4	0.77	0.77	ug/L	20.6.4.900 NMAC Subpart J
NO3+NO2-N	UF	0.68	0.68	0.68	mg/L	NMR053195 Sect 9.6.2.1
Pb‡*	UF	210	2	51	ug/L	20.6.4.900 NMAC Subpart I
pН	UF	6-9	6-9	6-9	SU	NMR053195 Sect 9.6.2.1
TSS	UF	100	100	100	mg/L	NMR053195 Sect 9.6.2.1
Zn*‡	F	110	76	101	ug/L	20.6.4.900 NMAC Subpart I

Slide 24

* NM water quality hardness-based values replace Appendix J as benchmarks.

+ National benchmark applies to total (unfiltered) result; NM water quality benchmark applies to dissolved (filtered) result.

NM WQS more stringent than benchmark

NM WQS is less stringent than benchmark



Data Evaluation - Benchmarks

- Evaluate the average of 4 quarterly results against the benchmark
- Exceedances: triggers corrective action process
 - average of 4 results > benchmark or
 - average of fewer than 4 results is mathematically certain to exceed benchmark
- If average of 4 < benchmark, discontinue monitoring</p>





Benchmark Exceedances

2016-2018 LANS permit data

Permitted Facility	Location ID	Analyte Name	Field Prep Code	QBM Sequence No.	Last Mon Sample Date	Actual Result Average	Minimum Possible Average	Report Units	Analysis Results Count	Maximum Adjusted Result	MSGP QBM Exceedance	MSGP QBM Level
TA-3-38 Metals Fab Shop	MSGP00201	Iron, total	UF	1	06/04/2016	2955.0	1477.5	ug/L	2	3640.0	Predicted	1000.0
TA-3-38 Metals Fab Shop	MSGP00201	Iron, total	UF	2	08/04/2016	4860.0	1215.0	ug/L	1	4860.0	Predicted	1000.0
TA-3-38 Metals Fab Shop	MSGP00201	Iron, total	UF	3	04/04/2017	3914.0	1957.0	ug/L	2	7370.0	Predicted	1000.0
TA-3-38 Metals Fab Shop	MSGP00201	Iron, total	UF	4	10/05/2017	1400.0	1050.0	ug/L	3	1520.0	Predicted	1000.0
TA-3-38 Metals Fab Shop	MSGP00201	Iron, total	UF	5	08/02/2018	771.0	385.5	ug/L	2	1330.0		1000.0
TA-3-38 Metals Fab Shop	MSGP00201	Aluminum, total recoverable	F10u	1	08/04/2016	1604.333	1203.25	ug/L	3	2770.0	Predicted	681.0
TA-3-38 Metals Fab Shop	MSGP00201	Aluminum, total recoverable	F10u	2	10/05/2017	799.75	799.75	ug/L	4	1280.0	True Value	681.0
TA-3-38 Metals Fab Shop	MSGP00201	Aluminum, total recoverable	F10u	3	08/02/2018	896.5	448.25	ug/L	2	1550.0		681.0
TA-3-38 Metals Fab Shop	MSGP00201	Zinc, dissolved	F	1	10/08/2016	140.075	140.075	ug/L	4	324.0	True Value	76.0
TA-3-38 Metals Fab Shop	MSGP00201	Zinc, dissolved	F	2	06/01/2017	, 194.5	97.25	ug/L	2	250.0	Predicted	76.0
TA-3-38 Metals Fab Shop	MSGP00201	Zinc, dissolved	F	3	07/05/2018	171.933	128.95	ug/L	3	285.0	Predicted	76.0
TA-3-38 Metals Fab Shop	MSGP00201	Zinc, dissolved	F	4	08/02/2018	78.0	19.5	ug/L	1	78.0		76.0
TA-3-39 & 102 Metal Shop	MSGP00401	Iron, total	UF	1	06/27/2016	4105.0	2052.5	ug/L	2	6620.0	Predicted	1000.0
TA-3-39 & 102 Metal Shop	MSGP00401	Iron, total	UF	2	05/09/2017	4035.0	2017.5	ug/L	2	6650.0	Predicted	1000.0
TA-3-39 & 102 Metal Shop	MSGP00401	Nitrate plus Nitrite Nitrogen	UF	1	08/03/2016	1.178	0.883	mg/L	3	2.66	Predicted	0.68
TA-3-39 & 102 Metal Shop	MSGP00401	Nitrate plus Nitrite Nitrogen	UF	2	05/09/2017	0.733	0.183	mg/L	1	0.733		0.68
TA-3-39 & 102 Metal Shop	MSGP00401	Aluminum, total recoverable	F10u	1	04/18/2016		2265.0	ug/L	1	9060.0	Predicted	1699.0
TA-3-39 & 102 Metal Shop	MSGP00401	Aluminum, total recoverable	F10u	2	05/09/2017	2822.667	2117.0	ug/L	3	6570.0	Predicted	1699.0
TA-3-39 & 102 Metal Shop	MSGP00401	Zinc, dissolved	F	1	04/01/2017		13.45	ug/L	4	20.5		101.0
TA-3-22 Power & Steam Plant	MSGP00501	Iron, total	UF	1	07/01/2016	9980.0	2495.0	ug/L	1	9980.0	Predicted	1000.0
TA-3-22 Power & Steam Plant	MSGP00501	Iron, total	UF	2	07/15/2016	4450.0	1112.5	ug/L	1	4450.0	Predicted	1000.0
TA-3-22 Power & Steam Plant	MSGP00501	Iron, total	UF	3	04/04/2017		5674.5	ug/L	3	20700.0	Predicted	1000.0
TA-3-22 Power & Steam Plant	MSGP00501	Iron, total	UF	4	08/07/2017	3010.0	1505.0	ug/L	2	3270.0	Predicted	1000.0
TA-3-22 Power & Steam Plant	MSGP00501	Iron, total	UF	5	05/21/2018		2310.0	ug/L	2	6410.0	Predicted	1000.0
TA-3-22 Power & Steam Plant	MSGP00501	Iron, total	UF	6	08/03/2018		134.5	ug/L	2	367.0		1000.0
TA-3-22 Power & Steam Plant	MSGP00901	Iron, total	UF	1	06/07/2016		2007.5	ug/L	2	5240.0	Predicted	1000.0
TA-3-22 Power & Steam Plant	MSGP00901	Iron, total	UF	2	04/01/2017		1329.25	ug/L	3	3600.0	Predicted	1000.0
TA-3-22 Power & Steam Plant	MSGP00901	Iron, total	UF	3	10/05/2017		1180.0	ug/L	3	2390.0	Predicted	1000.0
TA-3-22 Power & Steam Plant	MSGP00901	Iron, total	UF	4	08/03/2018		541.25	ug/L	2	1800.0		1000.0
TA-60 Asphalt Batch Plant	MSGP04301	Total Suspended Solids (TSS)	UF	1	10/05/2017		6.85		1	27.4		100.0
TA-3-38 Carpenter Shop	MSGP07302	Chemical Oxygen Demand (COD)	UF	1	07/26/2017				2	463.0	Predicted	120.0
TA-3-38 Carpenter Shop	MSGP07302	Chemical Oxygen Demand (COD)	UF	2	08/16/2018		50.5		2	202.0		120.0
TA-3-38 Carpenter Shop	MSGP07302	Total Suspended Solids (TSS)	UF	1	08/16/2018		92.763		3	188.0		100.0





New: Additional Implementation Measures – Tiered Corrective Action Levels

based on nature and magnitude of benchmark exceedances

- Tier 1
 - a. One Annual Average > benchmark (same as current permit)
 - Average of 4 results exceeds benchmark
 - Average of fewer than 4 results is mathematically certain to exceed benchmark
 - b. One single result > 4X benchmark
- Tier 2
 - a. Two Annual Averages > benchmark
 - b. Two single results > 4x benchmark in 2 year period
 - C. One single result > 8x benchmark
- Tier 3
 - a. Three Annual Averages > benchmark
 - b. Three single results > 4x benchmark in 3 year period
 - C. Two single results > 8x benchmark in 3 year period
 - d. 4 consecutive results are each > benchmark and the average is > 2 times benchmark

Slide 27

 Can discontinue monitoring if the average of 4 results < benchmark (does <u>not</u> apply to new Universal benchmarks)



Preview of Corrective Action Status with Tiered Corrective Action Levels

2019 Triad permit data

	MSGP Station	Report		Field Prep		Last Mon	Adjusted Result		Report	Results	Adjusted		•	MSGP QBM	Maximum Adjusted Result >	
Permitted Facility	Number	Туре	Analyte Name	Code UF		Sample Date		- U	Units	Count			Exceedance		QBM	Tier
	MSGP00501 MSGP00501	MSGP QBM	,	UF	1	06/15/2019 08/07/2019			0,	2	916.0 54900.0		Predicted	1000.0 1000.0	Y Y	1b
				UF	2					1	4610.0			1000.0	Y	2c 3b
	MSGP00501 MSGP00901			UF	3 1	10/04/2019 04/23/2019	4610.0 5290.0		0,	1	5290.0		Predicted Predicted	1000.0	Y Y	1b
		MSGP QBM		UF	2	08/08/2019	3345.0			2	3290.0		Predicted	1000.0	Y	2b
		MSGP QBM	,	UF	3	10/04/2019			0,	1	3620.0		redicted	1000.0	Y	20
			,	UF	1	10/04/2019			- <u></u> ,	4	0.0			120.0	N	
			Total Suspended Solids (TSS)	UF	1	10/04/2019			-	4	21.2			100.0	Y	+
TA-3-38 Metals Fab Shop			1 ()	F10u	1	04/22/2019			ug/L	1	222.0	222.0		1010.0	N	
		MSGP QBM	,	UF	1	04/22/2019				1	7550.0	7550.0 F	Predicted	1000.0	Y	1b
TA-3-38 Metals Fab Shop	MSGP00201	MSGP QBM	Nitrate plus Nitrite Nitrogen	UF	1	04/22/2019	1.12		mg/L	1	1.12	1.12		0.68	Y	
TA-3-38 Metals Fab Shop	MSGP00201	MSGP QBM	Zinc, dissolved	F	1	04/22/2019	387.0	96.75	ug/L	1	387.0	387.0		99.0	Y	
TA-3-38 Metals Fab Shop	MSGP07601	MSGP QBM	Aluminum, total recoverable	F10u	1	10/04/2019	81128.667	60846.5	ug/L	3	896.0	241000.0 F	Predicted	1010.0	Y	2c
TA-3-38 Metals Fab Shop	MSGP07601	MSGP QBM	Iron, total	UF	1	08/06/2019	2365.0	1182.5	ug/L	2	1390.0	3340.0 F	Predicted	1000.0	Y	1a
TA-3-38 Metals Fab Shop	MSGP07601	MSGP QBM	Iron, total	UF	2	10/04/2019	7400.0	1850.0	ug/L	1	7400.0	7400.0 F	Predicted	1000.0	Y	1b
TA-3-38 Metals Fab Shop	MSGP07601	MSGP QBM	Nitrate plus Nitrite Nitrogen	UF	1	10/04/2019	0.656	0.492	mg/L	3	0.393	0.82		0.68	Y	
TA-3-38 Metals Fab Shop	MSGP07601	MSGP QBM	Zinc, dissolved	F	1	10/04/2019	470.333	352.75	ug/L	3	135.0	1110.0 F	Predicted	99.0	Y	2c
TA-60 Asphalt Batch Plant	MSGP04301	MSGP QBM	Total Suspended Solids (TSS)	UF	1	08/07/2019	101.0	50.5	mg/L	2	61.0	141.0		100.0	Y	
TA-60-1 Heavy Equipment Yard	MSGP02201	MSGP QBM	Aluminum, total recoverable	F10u	1	04/22/2019	14900.0	3725.0	ug/L	1	14900.0	14900.0 F	Predicted	1010.0	Y	2c
TA-60-1 Heavy Equipment Yard	MSGP02201	MSGP QBM	Aluminum, total recoverable	F10u	2	10/04/2019	1596.667	1197.5	ug/L	3	1430.0	1860.0 F	Predicted	1010.0	Y	1a
TA-60-1 Heavy Equipment Yard	MSGP02201	MSGP QBM	Iron, total	UF	1	07/02/2019	4910.0	2455.0	ug/L	2	1300.0	8520.0 F	Predicted	1000.0	Y	2c
TA-60-1 Heavy Equipment Yard	MSGP02201	MSGP QBM	Iron, total	UF	2	10/04/2019	1090.0	545.0	ug/L	2	1080.0	1100.0		1000.0	Y	
TA-60-1 Heavy Equipment Yard	MSGP02201	MSGP QBM	Nitrate plus Nitrite Nitrogen	UF	1	08/06/2019	1.131	0.848	mg/L	3	0.742	1.48 F	Predicted	0.68	Y	1a
TA-60-1 Heavy Equipment Yard	MSGP02201	MSGP QBM	Nitrate plus Nitrite Nitrogen	UF	2	10/04/2019	0.642		0,	1	0.642	0.642		0.68	N	
TA-60-1 Heavy Equipment Yard				F	1	04/22/2019		164.25	ug/L	1	657.0	657.0F	Predicted	99.0	Y	1b
TA-60-1 Heavy Equipment Yard	MSGP02201	MSGP QBM	Zinc, dissolved	F	2	10/04/2019	114.533	85.9	ug/L	3	82.6	148.0		99.0	Y	

Tier 1	
Tier 2	
Tier 3	



Impaired Waters

Parameters and limits are receiving-water specific

 – CWA 303d/305b Integrated Report is revised by NMED biennially (next revision due late 2020)

Assessment Unit	Description	Parameter(s)	Facility
NM-9000.A_047 (perennial flow - chronic exposure risk)	Sandia Canyon (Sigma Canyon to NPDES outfall 001)	Al, Cu, PCBs	TA-3-22 Power & Steam Plant TA-3-38 Carpenter Shop TA-3-38 Metals Fab Shop TA-60 MRF TA-60-1 Heavy Equipment Yard TA-60-2 Warehouse TA-60 Roads and Grounds
NM-9000.A_042 (ephemeral flow – acute exposure risk)	Mortandad Canyon (within LANL)	Cu, Hg, PCBs, Adjusted Gross Alpha	TA-60-Asphalt Batch Plant TA-60 Roads and Grounds
NM-128.A_01 (ephemeral flow - acute exposure risk)	Canon de Valle (below LANL gage E256)	Adjusted Gross Alpha	TA-16 Stockpile Yard



Impaired Waters Limits

20.6.4 NMAC – Water Quality Standards Limits are risk-based by exposure type

Parameter	Field Prep Code	Chronic Exposure Limit	Acute Exposure Limit	Units	Regulatory Source
AI	F10U	1010	2520	ug/L	20.6.4.900 NMAC Subpart I
Cu	F	7	11	ug/L	20.6.4.900 NMAC Subpart I
Hg	UF	0.77	0.77	ug/L	20.6.4.900 NMAC Subpart J
Pb	F	2	51	ug/L	20.6.4.900 NMAC Subpart I
GROSSA-Adj	UF	15	15	pCi/L	20.6.4.900 NMAC Subpart J
Tot Aroclor	UF	0.2	0.2	ug/L	20.6.4.900 NMAC Subpart J/ 20.6.4.12 Subpart E

Lower WQS limit for chronic exposure

Higher WQS limit for acute exposure

• Any WQS exceedance is a permit violation and triggers the corrective action process

- Current permit if the parameter is not detected, monitoring may be discontinued
 - New: parameter must not be detected <u>for three consecutive years</u> for monitoring to be discontinued



Exceedances– Impaired Waters

2019 Triad permit data

	MSGP Station				Field Prep	Current Mon	Last Mon	~	Analysis Results	Detected Results	Minimum Adjusted	Maximum		Maximum Adjusted
Permitted Facility	Number	Report Type	Level Type	Analyte Name	Code	Status	Sample Date	Report Units	Count	Count	Result	Adjusted Result	MSGP I Level	Result > I
TA-3-22 Power & Steam Plant	MSGP00501	MSGP I	NM 2010 Aqu Chronic 80 mg	Aluminum, total recoverable	F10u	Mon	4/22/2019	ug/L	1	1	18300	18300	1010	Y
TA-3-22 Power & Steam Plant	MSGP00501	MSGP I	2007 EPA R6 MQL	Aroclor, total	UF	NMM	4/22/2019	ug/L	1	0	(0 0	0.2	N
TA-3-22 Power & Steam Plant	MSGP00501	MSGP I	NM 2010 Aqu Chronic 80 mg	Copper, dissolved	F	Mon	4/22/2019	ug/L	1	1	15.9	15.9	7	Y
TA-3-22 Power & Steam Plant	MSGP00901	MSGP I	NM 2010 Aqu Chronic 80 mg	Aluminum, total recoverable	F10u	Mon	4/23/2019	ug/L	1	1	6550	6550	1010	Y
TA-3-22 Power & Steam Plant	MSGP00901	MSGP I	2007 EPA R6 MQL	Aroclor, total	UF	NMM	4/23/2019	ug/L	1	0	() C	0.2	N
TA-3-22 Power & Steam Plant	MSGP00901	MSGP I	NM 2010 Aqu Chronic 80 mg	Copper, dissolved	F	Mon	4/23/2019	ug/L	1	1	11.9	11.9	7	Y
TA-3-22 Power & Steam Plant	MSGP01201	MSGP I	NM 2010 Aqu Chronic 80 mg	Copper, dissolved	F	Mon	7/25/2019	ug/L	1	1	13.5	i 13.5	7	Y
TA-3-38 Carpenter Shop	MSGP07401	MSGP I	NM 2010 Aqu Chronic 80 mg	Aluminum, total recoverable	F10u	Mon	5/10/2019	ug/L	1	1	728	728	1010	N
TA-3-38 Carpenter Shop	MSGP07401	MSGP I	2007 EPA R6 MQL	Aroclor, total	UF	NMM	5/10/2019	ug/L	1	0	() C	0.2	N
TA-3-38 Carpenter Shop	MSGP07401	MSGP I	NM 2010 Aqu Chronic 80 mg	Copper, dissolved	F	Mon	5/10/2019	ug/L	1	1	2.94	2.94	7	N
TA-3-38 Metals Fab Shop	MSGP00201	MSGP I	NM 2010 Aqu Chronic 80 mg	Aluminum, total recoverable	F10u	NoRpt	4/22/2019	ug/L	1	1	222	222	1010	N
TA-3-38 Metals Fab Shop	MSGP00201	MSGP I	NM 2010 Aqu Chronic 80 mg	Copper, dissolved	F	NoRpt	4/22/2019	ug/L	1	1	24.9	24.9	7	Y
TA-3-38 Metals Fab Shop	MSGP07601	MSGP I	NM 2010 Aqu Chronic 80 mg	Aluminum, total recoverable	F10u	Mon	6/17/2019	ug/L	1	1	1490	1490	1010	Y
TA-3-38 Metals Fab Shop	MSGP07601	MSGP I	2007 EPA R6 MQL	Aroclor, total	UF	NMM	6/17/2019	ug/L	1	0	() C	0.2	N
TA-60 Asphalt Batch Plant	MSGP04301	MSGP I	NM 2010 Lvstk Wtr	Adjusted Gross Alpha	UF	Mon	7/25/2019	pCi/L	1	1	3.96	3.96	15	N
TA-60 Asphalt Batch Plant	MSGP04301	MSGP I	2007 EPA R6 MQL	Aroclor, total	UF	NMM	7/25/2019	ug/L	1	0	() C	0.2	N
TA-60 Asphalt Batch Plant	MSGP04301	MSGP I	NM 2010 Aqu Acute 80 mg	Copper, dissolved	F	Mon	7/25/2019	ug/L	1	1	3.1	3.1	11	N
TA-60 Asphalt Batch Plant	MSGP04301	MSGP I	NM 2010 Widlf Hab	Mercury, total	UF	NMM	7/25/2019	ug/L	1	0	() C	0.77	N
TA-60 MRF	MSGP02901	MSGP I	NM 2010 Aqu Chronic 80 mg	Aluminum, total recoverable	F10u	Mon	4/22/2019	ug/L	1	1	816	816	1010	N
TA-60 MRF	MSGP02901	MSGP I	2007 EPA R6 MQL	Aroclor, total	UF	NMM	4/22/2019	ug/L	1	0	(o c	0.2	N
TA-60 MRF	MSGP02901	MSGP I	NM 2010 Aqu Chronic 80 mg	Copper, dissolved	F	Mon	4/22/2019	ug/L	1	1	41.8	41.8	7	Y
TA-60 Roads and Grounds	MSGP03101	MSGP I	NM 2010 Lvstk Wtr	Adjusted Gross Alpha	UF	Mon	7/25/2019	pCi/L	1	1	0.495	0.495	15	N
TA-60 Roads and Grounds	MSGP03101	MSGP I	2007 EPA R6 MQL	Aroclor, total	UF	NMM	7/25/2019	ug/L	1	0	(0 0	0.2	N
TA-60 Roads and Grounds	MSGP03101	MSGP I	NM 2010 Aqu Acute 80 mg	Copper, dissolved	F	Mon	7/25/2019	ug/L	1	1	8	8 8	11	N
TA-60 Roads and Grounds	MSGP03101	MSGP I	NM 2010 Widlf Hab	Mercury, total	UF	NMM	7/25/2019		1	0	(0 0	0.77	N
TA-60 Roads and Grounds	MSGP03201	MSGP I	NM 2010 Aqu Chronic 80 mg	Copper, dissolved	F	Mon	4/22/2019	ug/L	1	1	5.14	5.14	7	N
TA-60 Roads and Grounds	MSGP03201	MSGP I	NM 2010 Aqu Chronic 80 mg	Aluminum, total recoverable	F10u	Mon	4/30/2019	.	1	1	1380	1380	1010	Y
TA-60 Roads and Grounds	MSGP03201	MSGP I	2007 EPA R6 MQL	Aroclor, total	UF	NMM	4/30/2019	ug/L	1	0	() C	0.2	N
TA-60 Roads and Grounds	MSGP03701	MSGP I	NM 2010 Aqu Chronic 80 mg	Aluminum, total recoverable	F10u	Mon	7/26/2019	ug/L	1	1	6580	6580	1010	Y
TA-60 Roads and Grounds	MSGP03701	MSGP I	2007 EPA R6 MQL	Aroclor, total	UF	NMM	7/26/2019	ug/L	1	0	() C	0.2	N
TA-60 Roads and Grounds	MSGP03701	MSGP I	NM 2010 Aqu Chronic 80 mg	Copper, dissolved	F	Mon	7/26/2019		1	1	3.23		7	N
TA-60 Roads and Grounds	MSGP03901	MSGP I	NM 2010 Aqu Chronic 80 mg	Copper, dissolved	F	Mon	7/25/2019		1	1	7.74		7	Y
TA-60 Roads and Grounds	MSGP04201	MSGP I	NM 2010 Aqu Chronic 80 mg	Aluminum, total recoverable	F10u	Mon	4/23/2019	ug/L	1	1	2050	2050	1010	Y
TA-60 Roads and Grounds	MSGP04201	MSGP I	2007 EPA R6 MQL	Aroclor, total	UF	NMM	4/23/2019		1	0	() C	0.2	N
TA-60 Roads and Grounds	MSGP04201	MSGP I	NM 2010 Aqu Chronic 80 mg	Copper, dissolved	F	Mon	4/23/2019	ug/L	1	1	4.75	4.75	7	N
TA-60-1 Heavy Equipment Yard	MSGP02201	MSGP I	NM 2010 Aqu Chronic 80 mg	Aluminum, total recoverable	F10u	Mon	4/22/2019	.	1	1	14900	14900	1010	Y
TA-60-1 Heavy Equipment Yard	MSGP02201	MSGP I	2007 EPA R6 MQL	Aroclor, total	UF	NMM	4/22/2019	о.	1	0	(o c	0.2	N
TA-60-1 Heavy Equipment Yard	MSGP02201	MSGP I	NM 2010 Aqu Chronic 80 mg	Copper, dissolved	F	Mon	4/22/2019	. 0,	1	1	13.4	13.4	7	Y
TA-60-2 Warehouse	MSGP02601	MSGP I	NM 2010 Aqu Chronic 80 mg	Aluminum, total recoverable	F10u	Mon	4/1/2019		1	1	2350	2350	1010	Y
TA-60-2 Warehouse	MSGP02601	MSGP I	2007 EPA R6 MQL	Aroclor, total	UF	NMM	4/1/2019		1	0	(0 0	0.2	N
TA-60-2 Warehouse	MSGP02601	MSGP I	NM 2010 Aqu Chronic 80 mg	Copper, dissolved	F	Mon	4/1/2019		1	1	9.67	9.67	7	Y
TA-60-2 Warehouse	MSGP07501	MSGP I	NM 2010 Aqu Chronic 80 mg	Aluminum, total recoverable	F10u	Mon	4/22/2019		1	1	5760	5760	1010	Y
TA-60-2 Warehouse	MSGP07501	MSGP I	2007 EPA R6 MQL	Aroclor, total	UF	NMM	4/22/2019	-	1	0	(0 0	0.2	N
TA-60-2 Warehouse	MSGP07501	MSGP I	NM 2010 Aqu Chronic 80 mg	Copper, dissolved	F	Mon	4/22/2019	ug/L	1	1	37	37	7	Y

Not-detected - discontinue monitoring

WQS Exceedance - violation and corrective action



Effluent Limitation Guidelines

Sector D – Asphalt Batch Plant

Analyte	Field Prep Code	Daily Min	Daily Max	30-Day Avg	Units
Oil and Grease	UF		15	10	mg/L
рН	UF	6	9		SU
TSS	UF		23	15	mg/L

- Any exceedance is a permit violation and triggers the corrective action process;
 - A follow-up sample must be collected within 30 days or during the next qualifying storm event.
- If follow-up result also exceeds, submit an ELG Exceedance Report to EPA and monitoring moves from annual to quarterly until results return to compliance.



Exceedances-ELG

2019 Triad permit data

	MSGP Station Number	Level Type			Last Mon	Actual Result Average	Report Units	Analysis Results Count	Results	Minimum Adjusted Result			MSGP ELG Daily Min Level			Result >	Day Avg Sequence	MSGP ELG 30- Day Avg	MSGP ELG 30- Day Avg Adjusted Result	MSGP 30- Day Avg Adjusted Result > ELG
TA-60 Asphalt Batch Plant	MSGP04301	MSGP ELG Daily Max, MSGP ELG 30- Day Avg	Oil and Grease	UF	07/25/2019	1.41	mg/L	1	0	0.0	0.0	N			15.0	N	1	10.0	0.0	D N
TA-60 Asphalt Batch Plant	MSGP04301	MSGP ELG Daily Max, MSGP ELG 30- Day Avg	Total Suspended Solids (TSS)	UF	07/25/2019	141.0	mg/L	1	1	141.0	141.0	Y			23.0	Y	1	15.0	141.0) Y
TA-60 Asphalt Batch Plant	MSGP04301	MSGP ELG Daily Max, MSGP ELG 30- Day Avg	Total Suspended Solids (TSS)	UF	08/07/2019	101.0	mg/L	2	2	61.0	141.0	Y			23.0	Y	2	15.0	101.0) Y
TA-60 Asphalt Batch Plant	MSGP04301	MSGP ELG Daily Max, MSGP ELG Daily Min	рН	UF	08/07/2019	9.03	SU	2	0	8.93	9.13	Y	6.0	N	9.0	Y				

TSS and pH - 2 exceedances in 2019

- Submitted Exceedance Report to EPA
- Now monitoring quarterly until results return to compliance

Every TSS result at Asphalt Batch Plant since 2011 has exceeded the ELG



Summary

- Consistent pattern of repeated exceedances for the same parameters at most locations
- Need to evaluate the appropriateness and effectiveness of corrective actions
- New AIM Tiered Corrective Action process requires increasingly more prescriptive and robust responses
 - Tier 1 Review existing controls, add new controls, continue monitoring (same as current requirement)
 - Tier 2 Implement Sector-specific stormwater controls
 - Tier 3 Install permanent controls
- LANL's environmental compliance data are published on EPA's Enforcement and Compliance History Online (ECHO) public website. Environmental groups and stakeholders review and assess facility data nationwide to advocate for more stringent permit conditions.





MSGP Routine Facility Inspections



Managed by Triad National Security, LLC for the U.S. Department of Energy's NNSA

LA-UR-YY-XXXXX

When Do I Perform A Routine Facility Inspection (RFI)?

At least <u>quarterly</u>

- <u>Monthly</u> for areas w/ significant activities and materials exposed to stormwater
- At least <u>once a calendar year</u> during stormwater discharge
- Once a calendar year for sites in No Exposure or Inactive status




Where Do I Find Information to Help Me Perform an RFI?



Psst! Look at the SWPPP







NISA

Slide 38

NATIONAL LABORATORY

0

What Does An RFI Cover?

- Weather at time of inspection
- Discharges or evidence of discharges from the site
 - New discharges?
 - Evidence of, or potential for pollutants to enter the drainage system?



- Evidence of erosion?
- Evidence of pollutants in discharge?
- Flow dissipation devices operating effectively?











What Does An RFI Cover?

- Stormwater Control Measures
 - Are they operating effectively?
 - Are then in need of maintenance, repair, replacement?









What Does An RFI Cover?

- Industrial areas/activities exposed to stormwater
 - Includes the site's MSGP Sector of Industrial Activity (e.g. TA-60-2 Warehouse is under Sector P: Land Transportation and Warehousing)
- Additional activities you must inspect for
 - Dust generation
 - Offsite tracking
 - Housekeeping
 - Leaks/spills
- Non-compliances not identified in the above sections
- Additional Control Measures
- Signed Certification Statement



Common Issues Found During Inspection

















Los Alamos National Laboratory

Work Order MSGP-RI-64155

MSGP Routine Inspection Printed 3/2/2020 - 11:02 AM

Mainten	ance Details						
		Target: 3/31/2020 Priority/Type: Normal / Inspe Department: Utilities and In			2		
	5427)						
Reason:	2020 March Inspections						
ľasks –				_	_	_	-
#	Description		1.1.1	Meas.	No	N/A	Yes
Weather	r Information		1				
20	Describe the weather at time of in	spection and document the temp	perature (F*).				
Within +	he Facility Boundary		100				
WILDHIN L	Is the facility free of new discharg	es of pollutants that have occurr	ed since the last				
40	inspection? If "Failed" describe.	er of pointaine inactione accord					
50	If "No" has a CAR been previou	sly initiated for this new discharg	e?				0
60	Is the facility free of discharge of	collutants at the time of inspectio	n? If "No" describe.				1
-	Is the facility free of evidence of,	or the potential for, pollutants ent	ering the drainage	-	-	-	_
70	system. If "No" describe.						
Outfall I	nspection (identify needed main	tenance and repairs, failed co	ntrol measures that need	replacemen	t, or	a desc	ription
of corre	ctive actions in relevant task co	mment)					0
90	Monitored Outfall [026] Free of						
100	Monitored Outfall [026] Flow Dis	ssipation Devices Operating Effe	ctively? If "No", describe.				
110	Monitored Outfall [026] Free of Water? If "No", describe				17	Π.	
120	Monitored Outfall [026] Free of describe.	any unauthorized non-stormwate	r discharges? If "No"		<u> </u>	п	
130	Monitored Outfall [075] Free of	Evidence of Erosion? If "No", des	scribe				
140	Monitored Outfall [075] Flow Dis	ssipation Devices Operating Effe	ctively? If "No", describe.				
150	Monitored Outfall [075] Free of Water? If "No", describe.	Evidence of Pollutants in Dischar	ges and/or Receiving		<u> </u>	п.	
	Monitored Outfall [075] Free of	any unauthorized non-stormwate	r discharges? If "No"		2.1	1	
160	describe.					- E	
170	Substantially Identical Outfall [the second s			Π.,	п.	
180	Substantially Identical Outfall ["No", describe.				Π_	п.	
190	Substantially Identical Outfall [Receiving Water? If "No", describ	e.					
200	Substantially Identical Outfall [discharges? If "No" describe.	027] Free of any unauthorized no	on-stormwater		-	-	-
210	Substantially Identical Outfall [0281 Free of Evidence of Erosion	2 If "No", describe		-	-	-
220	Substantially Identical Outfall ["No", describe.					-	-
230	Substantially Identical Outfall [Receiving Water? If "No", describ		its in Discharges and/or			E	
	Substantially Identical Outfall [on-stormwater			-	-
240	discharges? If "No" describe.	No. on the fair dealer	(V & W (1)) (1) (1)		Π.	17	
					-	-	

Control Measures (identify needed maintenance and repairs, failed control measures that need replacment, or a description of corrective actions in relevant task comments).

- This is an example of a printed inspection form.
- Forms may be completed electronically through software MC Express.
- Instructions for performing inspection and filling out form are in procedure EPC-CP-QP-023, MSGP Routine Facility Inspections





260	Gravel Bags [6000503100008] Control Measure is operating effectively? If "No" describe condition & need for Maintenance, Repair, or Replacement.	П		П
270	Concrete/Asphalt Channel/Swale [6000504020005] Control Measure is operating effectively? If "No" describe condition & need for Maintenance, Repair, or Replacement.	П	Π	D
280	Eco-Block [6000503110006] Control Measure is operating effectively? If "No" describe condition & need for Maintenance, Repair, or Replacement.	Π		Ē
200	Rip Rap (6000504060004) Control Measure is operating effectively? If "No" describe	-	-	-
290	condition & need for Maintenance, Repair. If you need more space, write Rip Rap [6000504060012] Control Measu condition & need for Maintenance, Repair. "See Labor Report" and	-		-
300	Rip Rap [6000504060019] Control Measu Continue notes at end of form	-11		
310	condition & need for Maintenance, Repair, or Replacement. Earthen Berm [6000503010007] Control Measure is operating effectively? If "No" describe			<u> </u>
320	condition & need for Maintenance, Repair, or Replacement.	Ē		
330	Straw Wattle [6000503060013] Control Measure is operating effectively? If "No" describe condition & need for Maintenance, Repair, or Replacement. Elk ate wattle. Need to replace			E.
340	Rock Check Dam [6000506010001] Control Measure Is operating effectively? If "No" describe condition & need for Maintenance, Repair, or Replacement.			
350	Rock Check Dam [6000506010002] Control Measure is operating effectively? If "No" describe condition & need for Maintenance, Repair, or Replacement.	-		
	Rock Check Dam [6000506010003] Control Measure is operating effectively? If "No"	-	-	-
360	describe condition & need for Maintenance, Repair, or Replacement. Trench Drain [6000509040011] Control Measure is operating effectively? If "No" describe	11	. <u>Id</u>	
370	condition & need for Maintenance, Repair, or Replacement. EnviroSoxx w/ MetalLoxx (6000503200016) Control Measure is operating effectively? If			
380	"No" describe condition & need for Maintenance, Repair, or Replacement	E	П	
-	EnviroSoxx w/ MetalLoxx (6000503200017) Control Measure is open if your site does not hav "No" describe condition & need for Maintenance, Repair, or Replacer an activity, check N/A	le	D	
390				
400 Area//	EnviroSoxx w/ MetalLoxx [6000503200018] Control Measure is operang encourtery in "No" describe condition & need for Maintenance, Repair, or Replacement Activity exposed to stormwater (identify needed mainteance or a description of corrective actions nent).	in relev	ant tas	sk
400	EnviroSoxx w/ MetalLoxx [6000503200018] Control Measure is operang encountry on "No" describe condition & need for Maintenance, Repair, or Replacement Activity exposed to stormwater (identify needed mainteance or a description of corrective actions		ant tas	sk
400 Area// comm	EnviroSoxx w/ MetalLoxx (6000503200018) Control Measure is operang encountry in "No" describe condition & need for Maintenance, Repair, or Replacement. Activity exposed to stormwater (identify needed mainteance or a description of corrective actions ient). Material loading/unloading and storage areas controls adequate (appropriate, effective,		V	sk
400 Areal/ comm 420 430	EnviroSoxx w/ MetalLoxx [6000503200018] Control Measure is operating circular in "No" describe condition & need for Maintenance, Repair, or Replacement Activity exposed to stormwater (identify needed mainteance or a description of corrective actions tent). Material loading/unloading and storage areas controls adequate (appropriate, effective, and operating)? If "No" describe. Transfer areas for substances in bulk controls adequate (appropriate, effective, and		V	sk
400 Area// comm 420 430 440	EnviroSoxx w/ MetalLoxx (6000503200018] Control Measure is operang circulary in "No" describe condition & need for Maintenance, Repair, or Replacement Activity exposed to stormwater (identify needed mainteance or a description of corrective actions itent). Material loading/unloading and storage areas controls adequate (appropriate, effective, and operating)? If "No" describe. Transfer areas for substances in bulk controls adequate (appropriate, effective, and operating)? If "No" describe. Product/chemical storage areas (raw material): controls adequate (appropriate, effective, and operating)? If "No" describe. Liquid tank storage/secondary containment. controls adequate (appropriate, effective, and product (appropriate, effective, and and operating)? If "No" describe.		V	п
400 Area// comm 420 430 440 450	EnviroSoxx w/ MetalLoxx (6000503200018] Control Measure is operand circontery in "No" describe condition & need for Maintenance, Repair, or Replacement Activity exposed to stormwater (identify needed mainteance or a description of corrective actions nent). Material loading/unloading and storage areas: controls adequate (appropriate, effective, and operating)? If "No" describe. Transfer areas for substances in bulk controls adequate (appropriate, effective, and operating)? If "No" describe. Product/chemical storage areas (raw material): controls adequate (appropriate, effective, and operating)? If "No" describe. Liquid tank storage/secondary containment. controls adequate (appropriate, effective, and operating)? If "No" describe. Liquid tank storage/secondary containment. controls adequate (appropriate, effective, and operating)? If "No" describe. Liquid tank storage/secondary containment. controls adequate (appropriate, effective, Industrial processing and finished product storage areas: controls adequate (appropriate, effective, and operating)? If "No" describe. Industrial processing and finished product storage areas: controls adequate (appropriate, effective, and operating)? If "No" describe. Industrial processing and finished product storage areas: controls adequate (appropriate, effective, and product) (appropriate, effective, and operating)? If "No" describe. Industrial processing and finished product storage areas: controls adequate (appropriate, appropriate,		V	п
400 Area// comm 420 430 440	EnviroSoxx w/ MetalLoxx (6000503200018) Control Measure is operang circulary in "No" describe condition & need for Maintenance, Repair, or Replacement Activity exposed to stormwater (identify needed mainteance or a description of corrective actions tent). Material loading/unloading and storage areas: controls adequate (appropriate, effective, and operating)? If "No" describe. Transfer areas for substances in bulk: controls adequate (appropriate, effective, and operating)? If "No" describe. Product/chemical storage areas (raw material): controls adequate (appropriate, effective, and operating)? If "No" describe. Liquid tank storage/secondary containment: controls adequate (appropriate, effective, and operating)? If "No" describe. Liquid tank storage/secondary containment: controls adequate (appropriate, effective, and operating)? If "No" describe. Liquid tank storage/secondary containment: controls adequate (appropriate, effective, and operating)? If "No" describe. Liquid tank storage/secondary containment: controls adequate (appropriate, effective, and operating)? If "No" describe. Liquid tank storage/secondary containment controls adequate (appropriate, effective, and operating)? If "No" describe. Liquid tank storage/secondary containment controls adequate (appropriate, effective, and operating)? If "No" describe. Liquid tank storage/secondary containment controls adequate (appropriate, effective, and operating)? If "No" describe. Liquid tank storage/secondary containment controls adequate (appropriate, effective, and operating)? If "No" describe. Liquid tank storage/secondary containment controls adequate (appropriate, effective, and operating)? If "No" describe. Liquid tank storage/secondary containment controls adequate (appropriate, effective, effective, and operating)? If "No" describe.		V	п
400 Area// comm 420 430 440 450 460 470	EnviroSoxx w/ MetalLoxx (6000503200018] Control Measure is operang creating on a second		V	п
400 Area// comm 420 430 440 450 460	EnviroSoxx w/ MetalLoxx (6000503200018] Control Measure is operang circulary on "No" describe condition & need for Maintenance, Repair, or Replacement Activity exposed to stormwater (identify needed mainteance or a description of corrective actions ient). Material loading/unloading and storage areas: controls adequate (appropriate, effective, and operating)? If "No" describe. Transfer areas for substances in bulk controls adequate (appropriate, effective, and operating)? If "No" describe. Product/chemical storage areas (raw material): controls adequate (appropriate, effective, and operating)? If "No" describe. Liquid tank storage/secondary containment: controls adequate (appropriate, effective, and operating)? If "No" describe. Industrial processing and finished product storage areas: controls adequate (appropriate, effective, and operating)? If "No" describe. Equipment operation and maintenance areas: controls adequate (appropriate, effective, and operating)? If "No" describe. Equipment operation and maintenance areas: controls adequate (appropriate, effective, and operating)? If "No" describe. Equipment operation and maintenance areas: controls adequate (appropriate, effective, and operating)? If "No" describe. Equipment operation and maintenance areas: controls adequate (appropriate, effective, and operating)? If "No" describe. Equipment operation adequate (appropriate, effective, and operating)? If "No" describe.		V	п
400 Area// comm 420 430 440 450 460 470 480	EnviroSoxx w/ MetalLoxx (6000503200018] Control Measure is operand circoartery in "No" describe condition & need for Maintenance, Repair, or Replacement Activity exposed to stormwater (identify needed mainteance or a description of corrective actions nent). Material loading/unloading and storage areas: controls adequate (appropriate, effective, and operating)? If "No" describe. Transfer areas for substances in bulk controls adequate (appropriate, effective, and operating)? If "No" describe. Product/chemical storage areas (raw material): controls adequate (appropriate, effective, and operating)? If "No" describe. Liquid tank storage/secondary containment. controls adequate (appropriate, effective, and operating)? If "No" describe. Industrial processing and finished product storage areas: controls adequate (appropriate, effective, and operating)? If "No" describe. Equipment operation and maintenance areas: controls adequate (appropriate, effective, and operating)? If "No" describe. Equipment operation and maintenance areas: controls adequate (appropriate, effective, and operating)? If "No" describe. Equipment operation and maintenance areas: controls adequate (appropriate, effective, and operating)? If "No" describe. Equipment operation and maintenance areas: controls adequate (appropriate, effective, and operating)? If "No" describe. Equipment operation and maintenance areas: controls adequate (appropriate, effective, and operating)? If "No" describe. Equipment operation and maintenance areas: controls adequate (appropriate, effective, and operating)? If "No" describe. Equipment operation and maintenance areas: controls adequate (appropriate, effective, and operating)? If "No" describe. Equipment operation and maintenance areas: controls adequate (appropriate, effective, and operating)? If "No" describe. Dutdoor vehicle and equipment washing areas: controls adequate (appropriate, effective, effective, and operating)? If "No" describe. Dutdoor vehicle and equipment washing areas: controls adequate (appropriate,		V	п
400 Area// comm 420 430 440 450 460 470	EnviroSoxx w/ MetalLoxx (6000503200018] Control Measure is operang circulary in "No" describe condition & need for Maintenance, Repair, or Replacement Activity exposed to stormwater (identify needed mainteance or a description of corrective actions tent). Material loading/unloading and storage areas: controls adequate (appropriate, effective, and operating)? If "No" describe. Transfer areas for substances in bulk: controls adequate (appropriate, effective, and operating)? If "No" describe. Product/chemical storage areas (raw material): controls adequate (appropriate, effective, and operating)? If "No" describe. Liquid tank storage/secondary containment: controls adequate (appropriate, effective, and operating)? If "No" describe. Liquid tank storage/secondary containment: controls adequate (appropriate, effective, and operating)? If "No" describe. Liquid tank storage/secondary containment: controls adequate (appropriate, effective, and operating)? If "No" describe. Equipment operation and maintenance areas: controls adequate (appropriate, effective, and operating)? If "No" describe. Equipment operation and maintenance areas: controls adequate (appropriate, effective, and operating)? If "No" describe. Equipment operation and maintenance areas: controls adequate (appropriate, effective, and operating)? If "No" describe. Fueling areas: controls adequate (appropriate, effective, and operating)? If "No" describe. Fueling areas: controls adequate (appropriate, effective, and operating)? If "No" describe. Outdoor vehicle and equipment washing areas: controls adequate (appropriate, effective, and operating)? If "No" describe.		V	п
400 Area/// comm 420 430 440 450 460 470 480 490 500	EnviroSoxx w/ MetalLoxx (6000503200018] Control Measure is operand circoartery in "No" describe condition & need for Maintenance, Repair, or Replacement Activity exposed to stormwater (identify needed mainteance or a description of corrective actions inent). Material loading/unloading and storage areas: controls adequate (appropriate, effective, and operating)? If "No" describe. Transfer areas for substances in bulk controls adequate (appropriate, effective, and operating)? If "No" describe. Product/chemical storage areas (raw material): controls adequate (appropriate, effective, and operating)? If "No" describe. Liquid tank storage/secondary containment: controls adequate (appropriate, effective, and operating)? If "No" describe. Industrial processing and finished product storage areas: controls adequate (appropriate, effective, and operating)? If "No" describe. Equipment operation and maintenance areas: controls adequate (appropriate, effective, and operating)? If "No" describe. Equipment operation and maintenance areas: controls adequate (appropriate, effective, and operating)? If "No" describe. Equipment operation and maintenance areas: controls adequate (appropriate, effective, and operating)? If "No" describe. Eucling areas: controls adequate (appropriate, effective, and operating)? If "No" describe. Eucling areas: controls adequate (appropriate, effective, and operating)? If "No" describe. Outdoor vehicle and equipment washing areas: controls adequate (appropriate, effective, and operating)? If "No" describe. Waste handling and disposal areas: controls adequate (appropriate, effective, and operating)? If "No" describe. Waste handling and disposal areas: controls adequate (appropriate, effective, and operating)? If "No" describe.		V	п
400 Areal/ comm 420 430 440 450 460 470 480 490 500 510	EnviroSoxx w/ MetalLoxx (6000503200018] Control Measure is operang circulary in "No" describe condition & need for Maintenance, Repair, or Replacement Activity exposed to stormwater (identify needed mainteance or a description of corrective actions tent). Material loading/unloading and storage areas: controls adequate (appropriate, effective, and operating)? If "No" describe. Transfer areas for substances in bulk controls adequate (appropriate, effective, and operating)? If "No" describe. Product/chemical storage areas (raw material): controls adequate (appropriate, effective, and operating)? If "No" describe. Liquid tank storage/secondary containment: controls adequate (appropriate, effective, and operating)? If "No" describe. Liquid tank storage/secondary containment: controls adequate (appropriate, effective, and operating)? If "No" describe. Liquid tank storage/secondary containment: controls adequate (appropriate, effective, and operating)? If "No" describe. Equipment operation and maintenance areas: controls adequate (appropriate, effective, and operating)? If "No" describe. Equipment operation and maintenance areas: controls adequate (appropriate, effective, and operating)? If "No" describe. Equipment operation and maintenance areas: controls adequate (appropriate, effective, and operating)? If "No" describe. Equipment operating and equate (appropriate, effective, and operating)? If "No" describe. Cutdoor vehicle and equipment washing areas: controls adequate (appropriate, effective, and operating)? If "No" describe. Machinery: controls adequate (appropriate, effective, and operating)? If "No" describe. Machinery: controls adequate (appropriate, effective, and operating)? If "No" describe. Machinery: controls adequate (appropriate, effective, and operating)? If "No" describe. Cutdoor vehicle and equipment washing areas: controls adequate (appropriate, effective, and operating)? If "No" describe. Machinery: controls adequate (appropriate, effective, and operating)? If "		V	п
400 Area/// comm 420 430 440 450 460 470 480 490 500	EnviroSoxx w/ MetalLoxx (6000503200018] Control Measure is opehang circulary in "No" describe condition & need for Maintenance, Repair, or Replacement Activity exposed to stormwater (identify needed mainteance or a description of corrective actions tent). Material loading/unloading and storage areas: controls adequate (appropriate, effective, and operating)? If "No" describe. Transfer areas for substances in bulk: controls adequate (appropriate, effective, and operating)? If "No" describe. Product/chemical storage areas (raw material): controls adequate (appropriate, effective, and operating)? If "No" describe. Liquid tank storage/secondary containment: controls adequate (appropriate, effective, and operating)? If "No" describe. Liquid tank storage/secondary containment: controls adequate (appropriate, effective, and operating)? If "No" describe. Liquid tank storage/secondary containment: controls adequate (appropriate, effective, and operating)? If "No" describe. Liquid tank storage/secondary containment: controls adequate (appropriate, effective, and operating)? If "No" describe. Equipment operation and maintenance areas: controls adequate (appropriate, effective, and operating)? If "No" describe. Equipment operation and maintenance areas: controls adequate (appropriate, effective, and operating)? If "No" describe. Fueling areas: controls adequate (appropriate, effective, and operating)? If "No" describe. Machinery: controls adequate (appropriate, effective, and operating)? If "No" describe. Waste handling and disposal areas: controls adequate (appropriate, effective, and operating)? If "No" describe. Erodible areas/construction: controls adequate (appropriate, effective, and operating)? If "No" describe. Erodible areas/construction: controls adequate (appropriate, effective, and operating)? If "No" describe. Erodible areas/construction: controls adequate (appropriate, effective, and operating)? If "No" describe. Erodible areas/construction: controls adequate (appropriate, eff		V	п
400 Area// comm 420 430 440 450 460 470 480 490 500 510 520	EnviroSoxx w/ MetalLoxx (6000503200018] Control Measure is operand circoartery in "No" describe condition & need for Maintenance, Repair, or Replacement Activity exposed to stormwater (identify needed mainteance or a description of corrective actions nent). Material loading/unloading and storage areas: controls adequate (appropriate, effective, and operating)? If "No" describe. Transfer areas for substances in bulk controls adequate (appropriate, effective, and operating)? If "No" describe. Product/chemical storage areas (raw material): controls adequate (appropriate, effective, and operating)? If "No" describe. Liquid tank storage/secondary containment: controls adequate (appropriate, effective, and operating)? If "No" describe. Industrial processing and finished product storage areas: controls adequate (appropriate, effective, and operating)? If "No" describe. Equipment operation and maintenance areas: controls adequate (appropriate, effective, and operating)? If "No" describe. Equipment operation and maintenance areas: controls adequate (appropriate, effective, and operating)? If "No" describe. Equipment operation and maintenance areas: controls adequate (appropriate, effective, and operating)? If "No" describe. Equipment operating)? If "No" describe. Equipment operating)? If "No" describe. Machinery: controls adequate (appropriate, effective, and operating)? If "No" describe. Waste handling and disposal areas: controls adequate (appropriate, effective, and operating)? If "No" describe. Ecodible areas/construction: controls adequate (appropriate, effective, and operating)? If "No" describe. Ecodible areas/construction: controls adequate (appropriate, effective, and operating)? If "No" describe. Ecodible areas/construction: controls adequate (appropriate, effective, and operating)? If "No" describe. Ecodible areas/construction: controls adequate (appropriate, effective, and operating)? If "No" describe.		V	п
400 Areal/ comm 420 430 440 450 460 470 480 490 500 510	EnviroSoxx w/ MetalLoxx (6000503200018] Control Measure is operand creation on "No" describe condition & need for Maintenance, Repair, or Replacement Activity exposed to stormwater (identify needed mainteance or a description of corrective actions nent). Material loading/unloading and storage areas controls adequate (appropriate, effective, and operating)? If "No" describe. Transfer areas for substances in bulk controls adequate (appropriate, effective, and operating)? If "No" describe. Droduct/chemical storage areas (raw material): controls adequate (appropriate, effective, and operating)? If "No" describe. Liquid task storage/secondary containment controls adequate (appropriate, effective, and operating)? If "No" describe. Industrial processing and finished product storage areas: controls adequate (appropriate, effective, and operating)? If "No" describe. Equipment operation and maintenance areas: controls adequate (appropriate, effective, and operating)? If "No" describe. Equipment operation and maintenance areas: controls adequate (appropriate, effective, and operating)? If "No" describe. Equipment operation and maintenance areas: controls adequate (appropriate, effective, and operating)? If "No" describe. Eucling areas: controls adequate (appropriate, effective, and operating)? If "No" describe. Outdoor vehicle and equipment washing areas: controls adequate (appropriate, effective, and operating)? If "No" describe. Waste handling and disposal areas: controls adequate (appropriate, effective, and operating)? If "No" describe. Waste handling and disposal areas: controls adequate (appropriate, effective, and operating)? If "No" describe. Waste handling and disposal areas: controls adequate (appropriate, effective, and operating)? If "No" describe. Locations and sources of run-on to the site: controls adequate (appropriate, effective, and operating)? If "No" describe.		V	п
400 Area// 420 430 440 450 460 470 480 490 500 510 520 530	EnviroSoxx w/ MetalLoxx (6000503200018] Control Measure is operang circulary in "No" describe condition & need for Maintenance, Repair, or Replacement Activity exposed to stormwater (identify needed mainteance or a description of corrective actions tent). Material loading/unloading and storage areas: controls adequate (appropriate, effective, and operating)? If "No" describe. Transfer areas for substances in bulk: controls adequate (appropriate, effective, and operating)? If "No" describe. Product/chemical storage areas (raw material): controls adequate (appropriate, effective, and operating)? If "No" describe. Liquid tank storage/secondary containment: controls adequate (appropriate, effective, and operating)? If "No" describe. Liquid tank storage/secondary containment: controls adequate (appropriate, effective, and operating)? If "No" describe. Liquid tank storage/secondary containment: controls adequate (appropriate, effective, and operating)? If "No" describe. Equipment operation and maintenance areas: controls adequate (appropriate, effective, and operating)? If "No" describe. Equipment operating and finished product storage areas: controls adequate (appropriate, effective, and operating)? If "No" describe. Equipment operating and storage areas: controls adequate (appropriate, effective, and operating)? If "No" describe. Equipment operating and equate (appropriate, effective, and operating)? If "No" describe. Cutdoor vehicle and equipment washing areas: controls adequate (appropriate, effective, and operating)? If "No" describe. Machinery: controls adequate (appropriate, effective, and operating)? If "No" describe. Controls adequate (appropriate, effective, and operating)? If "No" describe. Waste handling and disposal areas: controls adequate (appropriate, effective, and operating)? If "No" describe. Erodible areas/construction: controls adequate (appropriate, effective, and operating)? If "No" describe. Cocations and sources of run-on to the site: controls adequate (approp		V	п
400 Area// comm 420 430 440 450 460 460 470 480 490 500 510 520 520 530 540	EnviroSoxx w/ MetalLoxx (6000503200018] Control Measure is operang circulary in "No" describe condition & need for Maintenance, Repair, or Replacement Activity exposed to stormwater (identify needed mainteance or a description of corrective actions nent). Material loading/unloading and storage areas: controls adequate (appropriate, effective, and operating)? If "No" describe. Transfer areas for substances in bulk controls adequate (appropriate, effective, and operating)? If "No" describe. Product/chemical storage areas (raw material): controls adequate (appropriate, effective, and operating)? If "No" describe. Liquid tank storage/secondary containment controls adequate (appropriate, effective, and operating)? If "No" describe. Industrial processing and finished product storage areas: controls adequate (appropriate, effective, and operating)? If "No" describe. Equipment operation and maintenance areas: controls adequate (appropriate, effective, and operating)? If "No" describe. Equipment operation and maintenance areas: controls adequate (appropriate, effective, and operating)? If "No" describe. Equipment operation and maintenance areas: controls adequate (appropriate, effective, and operating)? If "No" describe. Equipment operation and maintenance areas: controls adequate (appropriate, effective, and operating)? If "No" describe. Equipment operating)? If "No" describe. Machinery: controls adequate (appropriate, effective, and operating)? If "No" describe. Waste handling and disposal areas: controls adequate (appropriate, effective, and operating)? If "No" describe. Erodible areas/construction: controls adequate (appropriate, effective, and operating)? If "No" describe. Ecodible areas/construction: controls adequate (appropriate, effective, and operating)? If "No" describe. Cocations and sources of run-on to the site: controls adequate (appropriate, effective, and operating)? If "No" describe. Salt storage piles or pile containing salt: controls adequate (appropriate, effective, and operating)? If "No" describ		V	п



Slide 44

LOS Alamos

— EST.1943 —

0

Meas. No N/A Yes



Meas.	No	N/A	Yes

		(neus.	140	THUR .	160
580	Sector P [60005-] Vehicle storage/maintenance areas: controls adequate (appropriate, effective, and operating)? If "No" describe.		п	п	П
Non-Co	ompliance				
600	Free of incidents of observed non-compliance not already identified above? If "No" describe.		Π.	п	
Additio	nal Control Measures				_
620	Are permit requirements satisfied with existing control measure(s)? If "No" describe additional control measures needed.				Ē.
					-
abor-					
Labor	Assigned Work Date	Reg Hrs	OTHM	s Oth	er Hrs
Admin	Jane 2/20/2020			2	
-					
abor P	Report				
Comple	eted:				
a a uniferr					
Report		P			
Report	The inspector prints	e			
Report	The inspector prints and signs his/her name Add the date an	d time th	ie		_
Report	and signs his/ber name		1 S S S S S S S S S S S S S S S S S S S		
Report	and signs his/her name Add the date an		1 S S S S S S S S S S S S S S S S S S S		

CERTIFICATION STATEMENT

"I certify under penalty of law that this document and all attachments were prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gathered and evaluated the information submitted. Based on my inquiry of the person or persons who manage the system, or those persons directly responsible for gathering information, the information submitted is, to the best of my knowledge and belief, true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment for knowing violations".

(Signatory must meet definition in Section B.11.A, eg. FOD, Ops Mgr, DESH Group Leader, EPC Group Leader)

Print name and title:	
Signature:	_Date:
	Have the Cert Statement signed
	no more than 14 days after completing the inspection





What Do I Do When I Complete the RFI?

- Check your work (especially the check boxes)
- Sign it....and date/time it
- Sign the Certification Statement (w/in 14 days of inspection)
- Give a copy to the MSGP Program (w/in 14 days of inspection)
- Add it to your SWPPP
- Enter any issues* (corrective actions) into the Corrective Action Response database

*<u>Anyone</u> can identify potential stormwater issue, not just DEPs or MSGP Program staff











Call the MSGP Program Team when you have questions









MSGP Corrective Actions



Managed by Triad National Security, LLC for the U.S. Department of Energy's NNSA

LA-UR-YY-XXXXX

Agenda

- Definition of corrective action
- Conditions requiring corrective action
- Immediate corrective action
- Subsequent corrective action
- 45-day extension
- Corrective action documentation





Corrective Action

Definition: Any action taken, or required to be taken, to

- (1) repair, modify, or replace any stormwater control used at the site;
- (2) clean up and dispose of spills, releases, or other deposits found on the site;
- (3) satisfy any permit condition or SWPPP requirement





Conditions Requiring Corrective Action

- Unauthorized release or discharge
- Impaired water quality standards are exceeded (e.g., control measures are inadequately managing stormwater discharges)
- The average of four quarterly sampling results exceeds an applicable benchmark
- Effluent limitation guidelines are exceeded at the Asphalt Batch Plant (Sector D)
- Control measures are not being properly operated and maintained



Conditions Requiring Corrective Action (cont.)

- Visual assessment that shows evidence of stormwater pollution (e.g., color, odor, floating solids, settled solids, suspended solids, foam)
- A regulator during an inspection determines control modification is necessary to meet non-numeric effluent limits
- Facility operations change resulting in an increase in the quantities of pollutants discharged
- Failure to meet any permit condition or those specified in the site specific SWPPP



Conditions Requiring Corrective Action











Conditions Requiring Corrective Action









Slide 55

05

am

LABORATORY

NATIONAL



Immediate Corrective Action

- Shall *Immediately* act upon identification of an issue
 - Immediately is the same day a condition is found
 - Solely calling or emailing personnel requesting action is not considered to be an immediate response
 - Minimize or prevent the discharge of pollutants until a permanent solution is installed (e.g., absorbents, micro blaze, gravel bags)



Immediate Corrective Action (cont.)

- Clean up all contaminated surfaces to prevent pollutant discharge during subsequent storm events
- Designated staff must be trained and available to provide immediate support
- Basic BMPs and cleanup materials must be readily available on site
- If found after 3:00 pm, action must be taken the next workday





Subsequent Corrective Action

- For minor conditions, immediate action is often sufficient, and no additional action is necessary
- An FSR may be required to initiate a follow up action or permanent solution after the immediate action is completed (e.g., procurement and installation of a new stormwater control measure or SCM)
- Complete the corrective action (e.g., install a new or modified control and make it operational or complete the repair) <u>before the next</u> <u>storm event or within 14 calendar days from the time of discovery</u>
- Any corrective action resulting in a change to a SCM or procedure documented in the SWPPP will require SWPPP modification within 14 days of completing the corrective action



Subsequent Corrective Action (cont.)

- If finalization of CA is *infeasible* within the 14-day timeline then:
 - Document reasoning in database (e.g., delays in procuring industrial stormwater controls, installation of enclosures, etc.)
 - Provide a schedule for completion of corrective action in database
 - If the completion of a corrective action is anticipated to take more than 45 days from the time of discovery, EPA must be provided a notification of the intention to exceed, rational for the extension and a completion date
 - These time intervals are not grace periods, but are schedules for documenting findings and for making repairs and improvements

Slide 59

The permit does not allow corrective actions to remain open indefinitely



45 Day Extension

- If a CA is expected to exceed the 45-day timeframe the DEP shall provide EPC-CP the following information:
 - Rationale for an extension (e.g. an engineered design and installation of an engineered control)
 - A description of the condition requiring corrective action along with a summary of the preliminary steps that have been taken to complete the corrective action
 - A realistic completion date along with a realistic and detailed schedule that includes all outstanding steps required to complete the corrective action
- EPC-CP MSGP staff will prepare and submit to EPA the 45day exceedance based on the information above



Corrective Action Documentation Recap

- Within 24 hours of discovery enter a description of the condition requiring corrective action and the date the condition was identified in the CAR database
- Document immediate actions taken to minimize or prevent the discharge of pollutants
- Document dates when each corrective action was initiated, completed, or is expected to be completed
- If the corrective action cannot be completed within 14-days, provide a schedule and justification why it is infeasible to complete the necessary installation

Slide 61



Corrective Action Documentation Recap (cont.)

- Spill documentation must describe:
 - Material, location, amount, date/time and the cause of the spill
 - Leaks, spills, or other releases that resulted in discharges of pollutants to waters of the U.S
 - Response actions, date/time cleanup was completed, notifications, staff involved, measures implemented to prevent reoccurrence

Slide 62



Additional Implementation Measures (AIM)

- EPA proposed revisions to the 2015 MSGP's provisions regarding benchmark monitoring exceedances
- There are three AIM levels: AIM Tier 1, Tier 2, and Tier 3
- Operators will be required to respond to different AIM levels with increasingly robust control measures depending on the nature and magnitude of the benchmark threshold exceedance



ATTACHMENT 12: MSGP (OR ACTIVE URL)

Attached is a copy of the2021 MSGP is kept of file with the SWPPP in hard copy. The active URL for the permit is https://www.epa.gov/npdes/stormwater-discharges-industrial-activities-epas-2021-msgp

ATTACHMENT 13: THREATENDED AND ENDANGERED SPECIES HABITAT MANAGEMENT PLAN FOR LOS ALAMOS NATIONAL LABORATORY

LA-UR-17-29454 Approved for public release; distribution is unlimited.

October2017

Threatened and Endangered Species Habitat Management Plan for Los Alamos National Laboratory





Cover photo: Mexican Spotted Owls at Los Alamos National Laboratory

Prepared by: Environmental Protection and Compliance Division Resources Management Team Los Alamos National Laboratory

Prepared for: U.S. Department of Energy, National Nuclear Security Administration, Los Alamos Field Office

An Affirmative Action/Equal Opportunity Employer

Los Alamos National Laboratory, an affirmative action/equal opportunity employer, is operated by the Los Alamos National Security, LLC, for the National Nuclear Security Administration of the U.S. Department of Energy under contract DE-AC52-06NA25396. By acceptance of this article, the publisher recognizes that the U.S. Government retains a nonexclusive, royalty-free license to publish or reproduce the published form of this contribution, or to allow others to do so, for U.S. Government purposes. Los Alamos National Laboratory requests that the publisher identify this article as work performed under the auspices of the U.S. Department of Energy. Los Alamos National Laboratory strongly supports academic freedom and a researcher's right to publish; as an institution, however, the Laboratory does not endorse the viewpoint of a publication or guarantee its technical correctness.

Contents

Ac	ronyms and Terms	.vi
I.	Threatened and Endangered Species Habitat Management Plan General Overview	1
	1.0 Introduction	1
	2.0 Role of Site Plans in the HMP	1
	3.0 Description of Areas of Environmental Interest	1
	3.1 Definition and Role of Developed Areas in AEI Management	2
	3.2 General Description of Buffer Areas and Allowable Buffer Area Development	2
	3.3 Emergency Actions	2
	4.0 Implementation of Site Plans	3
	4.1 Roles and Responsibilities	3
	4.2 If an Activity Does Not Meet Site Plan Guidelines	4
	4.3 Dissemination of Information	4
	5.0 Changes in the HMP since Implementation	
	6.0 Data Management	5
II.	Area of Environmental Interest Site Plan for the Mexican Spotted Owl	5
	1.0 Species Description—Mexican Spotted Owl	5
	1.1 Status	5
	1.2 General Biology	5
	1.3 Threats	6
	2.0 Impact of Human Activities	
	2.1 Introduction	
	2.2 Impacts on Habitat Quality	
	2.2.1 Development	6
	2.2.2 Ecological Risk	7
	2.2.3 Disturbance	
	2.2.3.1 Pedestrians and Vehicles	7
	2.2.3.2 Aircraft	
	2.2.3.3 Explosives 2.2.3.4 Other Sources of Noise	
	2.2.3.5 Artificially Produced Light	
	3.0 AEI General Description for Mexican Spotted Owl	
	3.1 Method for Identifying a Mexican Spotted Owl AEI	11
	3.2 Location and Number of Mexican Spotted Owl AEIs	
	4.0 AEI Management	12
	4.1 Overview	12
	4.2 Definition and Role of Occupancy in AEI Management	12
	4.3 Introduction to AEI Management Guidelines	12
	4.4 Definition of and Restrictions on Habitat Alterations	
	4.4.1 Definition of Habitat Alterations	13
	4.4.2 Fuels Management Practices to Reduce Wildfire Risk	13
	4.4.3 Utility Corridors	14

4.4.4 Restrictions on Habitat Alterations	14
4.5 Definition of and Restrictions on Disturbance Activities	15
4.5.1 Definitions of Disturbance Activities	15
4.5.2 Activity Table	17
4.6 Protective Measures	17
5.0 Levels of Development in AEI Core and Buffers	
5.1 Allowable Habitat Alteration in the Buffer Areas	
III. Area of Environmental Interest Site Plan for the Southwestern Willow Flycatcher	19
1.0 Species Description—Southwestern Willow Flycatcher	19
1.1 Status	19
1.2 General Biology	19
1.3 Threats	20
2.0 Impact of Human Activities	
2.1 Introduction	20
2.2 Impacts on Habitat Quality	21
2.2.1 Development	21
2.2.2 Ecological Risk	21
2.2.2.1 Ecorisk Assessment	21
2.2.3 Disturbance	
2.2.3.1 Pedestrians and Vehicles	
2.2.3.2 Aircraft	
2.2.3.3 Explosives 2.2.3.4 Other Sources of Noise	
2.2.3.4 Other Sources of Noise	
3.0 AEI General Description for the Southwestern Willow Flycatcher	
3.1 Method for Identifying the Southwestern Willow Flycatcher AEI	
3.2 Location of the Southwestern Willow Flycatcher AEI	
4.0 AEI Management	23
4.1 Overview	23
4.2 Definition and Role of Occupancy in AEI Management	23
4.3 Introduction to AEI Management Guidelines	24
4.4 Definition of and Restrictions on Habitat Alterations	24
4.4.1 Definition of Habitat Alterations	24
4.4.2 Fuels Management Practices to Reduce Wildfire Risk	24
4.4.3 Utility Corridors	24
4.4.4 Restrictions on Habitat Alterations	25
4.5 Definition of and Restrictions on Disturbance Activities	25
4.5.1 Definition of Disturbance Activities	25
4.5.2 Activity Table	26
4.6 Protective Measures	27
5.0 Southwestern Willow Flycatcher AEI Description	28
5.1 Pajarito Canyon Southwestern Willow Flycatcher AEI	28

5.1.1 Allowable Habitat Alteration in the Buffer Area	
IV. Area of Environmental Interest Site Plan for the Jemez Mountains Salamander	
1.0 Species Description—Jemez Mountains Salamander	
1.1 Status	
1.2 General Biology	
1.3 Threats	
2.0 Impact of Human Activities	
2.1 Introduction	
2.2 Impacts on Habitat Quality	29
2.2.1 Development	29
2.2.2 Pedestrians and Vehicles	
2.2.3 Severe Wildland Fire and Wildfire Suppression	
2.3 Impacts on Individual Salamanders	
2.3.1 Disease	
2.3.2 Destruction of Individual Salamanders	
3.0 AEI General Description for the Jemez Mountains Salamander	
3.1 Method for Identifying a Jemez Mountains Salamander AEI	
3.2 Location and Number of Jemez Mountains Salamander AEIs	
4.0 AEI Management	
4.1 Overview	
4.2 Definition and Role of Occupancy in AEI Management	
4.3 Definition and Role of Developed Areas in AEI Management	32
4.4 General Description of Core and Buffer Areas and Allowable Area Development	
4.5 Emergency Actions	
4.6 Introduction to AEI Management Guidelines	
4.7 Definition of and Restrictions on Habitat Alterations	
4.7.1 Definition of Habitat Alterations	
4.7.2 Fuels Management Practices to Reduce Wildfire Risk	
4.7.3 Utility Corridors	34
4.7.4 Restrictions on Habitat Alterations	
References Cited	
APPENDIX	

Figures

	Process flowchart for determining site plan requirements	
Figure A-1.	Most recent map of all AEIs at LANL	1

Tables

Table 1.	Restrictions on Activities in Undeveloped Occupied Mexican Spotted Owl AEIs17
Table 2.	Restrictions on Activities in Undeveloped Occupied Southwestern Willow Flycatcher AEI27
Table A-1.	The Percentage of each Food Type Found in Mexican Spotted Owl Food Remains at LANL40
Table A-2.	Preliminary Light Measurements in ftc for Mexican Spotted Owl Site Plan

ACRONYMS AND TERMS

AEI	area of environmental interest			
Bd	Batrachochytrium dendrobatidis (Chytrid Fungus)			
DARHT	Dual-Axis Radiographic Hydrodynamic Test (Facility)			
dB	decibel			
dB(A)	A-weighted decibel			
dB(C)	C-weighted decibel			
DDT	(dichloro-diphenyl-trichloroethane)			
DOE	U.S. Department of Energy			
ESA	Endangered Species Act of 1973			
fc	foot candles			
Field Office	U.S. Department of Energy Los Alamos Field Office			
FR	Federal Register			
GIS	geographic information system			
HMP	Threatened and Endangered Species Habitat Management Plan			
HVAC	heating, ventilation, and air conditioning			
LANL	Los Alamos National Laboratory			
LANS	Los Alamos National Security, LLC			
NEPA	National Environmental Policy Act of 1969			
PCBs	polychlorinated biphenyls			
TNT	trinitrotoluene(2,4,6-)			
USFWS	U.S. Fish and Wildlife Service			

I. THREATENED AND ENDANGERED SPECIES HABITAT MANAGEMENT PLAN GENERAL OVERVIEW

1.0 Introduction

Los Alamos National Laboratory's (LANL) Threatened and Endangered Species Habitat Management Plan (HMP) fulfills a commitment made to the U.S. Department of Energy (DOE) in the "Final Environmental Impact Statement for the Dual-Axis Radiographic Hydrodynamic Test Facility Mitigation Action Plan" (DOE 1996). The HMP received concurrence from the U.S. Fish and Wildlife Service (USFWS) in 1999 (USFWS consultation numbers 2-22-98-I-336 and 2-22-95-I-108). This 2017 update retains the management guidelines from the 1999 HMP for listed species, and updates some descriptive information.

2.0 Role of Site Plans in the HMP

The purpose of the HMP is to provide a management strategy for Endangered Species Act (ESA) compliance through the protection of threatened and endangered species and their habitats on LANL property. The HMP consists of site plans for federally listed threatened or endangered species with a moderate or high probability of occurring at LANL. The following federally listed threatened or endangered species currently have site plans at LANL: Mexican Spotted Owl (*Strix occidentalis lucida*), Southwestern Willow Flycatcher (*Empidonax trailii extimus*), and Jemez Mountains Salamander (*Plethodon neomexicanus*). Site plans provide guidance to ensure that LANL operations do not adversely affect threatened or endangered species or their habitats.

The Black-footed Ferret (*Mustela nigripes*) is federally listed as endangered. However, no sightings of Black-footed Ferrets have been reported in Los Alamos County for more than 50 years. In addition, no large prairie dog towns, prime habitat for Black-footed Ferrets, have been observed at LANL. Therefore, there is no site plan for this species.

The New Mexico Meadow Jumping Mouse (*Zapus hudsonius luteus*) and Yellow-billed Cuckoo (*Coccyzus americanus*) do not require a site plan because they do not have breeding habitat on LANL property. In Keller (2015), it was concluded that if any LANL work activities might affect habitat for these two species, those activities would be reviewed for impacts.

3.0 Description of Areas of Environmental Interest

Suitable habitats for federally listed threatened and endangered species have been designated as areas of environmental interest (AEIs). AEIs are geographical units at LANL that are managed for the protection of federally listed species and consist of core habitat areas and buffer areas. The purpose of the core habitat is to protect areas essential for the existence of the specific threatened or endangered species. This includes the appropriate habitat type for breeding, prey availability, and micro-climate conditions. The purpose of buffer areas is to protect core areas from undue disturbance and habitat degradation.

Site plans identify restrictions on activities within the AEIs. The USFWS reviewed allowable activities and provided concurrence that these activities are not likely to adversely affect federally listed species. Activities discussed in site plans include day-to-day activities causing

disturbance (hereafter referred to as "disturbance activities"), such as access into an AEI, and long-term impacts, such as habitat alteration.

3.1 Definition and Role of Developed Areas in AEI Management

Developed areas include all building structures, paved roads, improved gravel roads, paved and unpaved parking lots, and firing sites. The extent of developed areas in each AEI was determined using two methods. First, LANL geographic information system (GIS) analysts placed a 15-m (49-ft) border around all buildings and parking lots. For paved and improved gravel roads, the developed area was defined as the area to a roadside fence, if one exists within 9 m (30 ft) of the road, or 5 m (15 ft) on each side of the road if there is no fence within 9 m (30 ft). If an area of highly fragmented habitat was enclosed by roads, a security fence, or connected buildings, that area was also classified as developed. Developed areas at firing sites were defined as a circle with a 91-m (300-ft) radius from the most centrally located firing pad. Second, LANL GIS analysts overlaid scanned orthophotos onto a map of the Los Alamos area and digitized all areas that appeared developed. These two information sources were overlaid and combined, so that areas classified as developed by either method were considered developed in final maps and analyses. Some areas were confirmed by ground surveys, such as the firing sites.

Developed areas occur in the core and/or buffer of all AEIs. However, developed areas do not constitute suitable habitat for federally listed species. Current ongoing activities in developed areas constitute a baseline condition for the AEIs and are not restricted. New activities, including further development within already existing developed areas, are not restricted unless they impact undeveloped portions of an AEI core. For example, if light or noise from a new office building in a developed area were to raise levels in an undeveloped core area, those light and noise levels would be subject to the guidelines on habitat alterations.

3.2 General Description of Buffer Areas and Allowable Buffer Area Development

The purpose of buffer areas is to protect core areas from undue disturbance or habitat degradation. The current levels of development in buffer and core areas represent baseline conditions for this HMP. No further development is allowed in the core area under the guidelines of this HMP. A limited amount of development is allowed in buffer areas. Under the guidelines of this HMP, individual development projects are limited to 2 ha (5 ac) in size, including a 15-m (49-ft) developed-area border around structures and a 5-m (15-ft) developed-area border around paved and improved gravel roads. Projects greater than 2 ha (5 ac) in size require individual review for ESA compliance (see exceptions for fuels management activities and utility corridor maintenance). New development projects in AEI buffer areas must be reported to Los Alamos National Security, LLC (LANS) biologists for tracking

(http://int.lanl.gov/environment/bio/controls/index.shtml).

3.3 Emergency Actions

Managers may activate emergency actions if safety and/or property is immediately threatened by something occurring within an AEI (for example, wildfire, water line breakage, etc.). Contact a LANS biologist (<u>http://int.lanl.gov/environment/bio/controls/index.shtml</u>), the Environmental Stewardship Group (505-665-8855), or the DOE Los Alamos Field Office (Field Office; 505-667-6819) as soon as possible. If the emergency occurs outside of regular business hours, contact

the Emergency Management Office (505-667-6211); this office will then communicate with the appropriate LANL and DOE Field Office personnel.

4.0 Implementation of Site Plans

4.1 Roles and Responsibilities

LANL's facility managers and operational staff are responsible for ensuring that activities are reviewed for compliance with all applicable site plans. Figure 1 illustrates the process for utilizing site plans. If activities follow approved guidance, there is no requirement for additional ESA regulatory compliance. However, additional National Environmental Policy Act (NEPA), cultural resources, wetlands, or other regulatory compliance actions may be required.




Figure 1. Process flowchart for determining site plan requirements

If an activity or project occurs outside of all LANL AEIs and will not impact habitat within an AEI, it does not have to be reviewed for ESA compliance unless it is a large project. Projects that are larger than 2 ha (5 ac) or cost more than \$5 million require an individual ESA compliance review, even if they are not located within an AEI.

LANL's facility managers are responsible for determining if operations within their geographic and/or programmatic area of responsibility comply with the guidelines in these site plans. Submission of a project into the integrated review tool for a new or modified project is required under Program Description 400 (LANL 2016) and allows managers to identify the requirements within their project area. Deployed environmental professionals and core LANS biologists are available to support facility managers. If activities follow site plan guidelines, they do not require any additional ESA regulatory compliance action. However, NEPA, cultural resources, wetlands, or other regulatory compliance actions are not addressed in site plans and additional compliance actions may be required. It is the responsibility of the project leader or facility management staff to ensure that all requirements are satisfied. If you have questions, contact biological, cultural, NEPA, or other environmental subject matter experts. Contacts can be found at http://int.lanl.gov/environment/compliance/ier/index.shtml.

A single facility may have one or more AEIs within its boundary and the AEIs may be for different species. Some AEIs overlap. In areas where overlap occurs, project managers must follow the guidelines for AEIs of all involved species.

4.2 If an Activity Does Not Meet Site Plan Guidelines

If a project reviewer determines that an activity or project cannot meet the guidelines in applicable site plans, LANS biologists evaluate that activity individually for compliance with the ESA. Results of the evaluation of potential impacts allow LANS biologists to make recommendations to the DOE Field Office Biological Resources Program Manager regarding the need for USFWS consultation. An evaluation may result in 1) a DOE Field Office determination that there is no effect and the activity can proceed, 2) a DOE Field Office suggestion for modifications of the action to avoid adverse effects so that it can proceed, or 3) a DOE Field Office decision to prepare a biological assessment for the activity and submit it to the USFWS for concurrence. Fieldwork and preparation of a biological assessment can take a few months with an additional 2 to 12 months for DOE Field Office review and then final USFWS concurrence.

4.3 Dissemination of Information

Habitat locations of threatened and endangered species are not considered sensitive; however, it is in the best interest of threatened and endangered species to restrict specific knowledge about their locations.

5.0 Changes in the HMP since Implementation

The HMP received concurrence from USFWS and was first implemented in 1999. Since that time, both the Peregrine Falcon (*Falco peregrinus*) and the Bald Eagle (*Haliaeetus leucocephalus*) have been delisted. Site plans for those species have been removed from LANL's HMP. Both species are protected at LANL under the Migratory Bird Treaty Act, and the Bald Eagle is also protected under the Bald and Golden Eagle Protection Act.

In 2005, the USFWS concurred with DOE's proposal for updated Mexican Spotted Owl habitat boundaries based on a revised analysis of Mexican Spotted Owl habitat quality within DOE property around LANL (USFWS consultation number 22420-2006-I-0010).

In 2012, the USFWS concurred with DOE's proposal to modify the habitat boundaries for the Los Alamos Canyon Mexican Spotted Owl AEI due to changes from the fire response activities after the Las Conchas wildfire (USFWS consultation number 02ENNM00-2012-IE-0088).

In 2013, the USFWS concurred with the DOE's new site plan for the Jemez Mountains Salamander and its addition to LANL's HMP (USFWS consultation number 02ENNM00-2014-I-0014).

In 2015, the USFWS concurred with the DOE's addition of the New Mexico Meadow Jumping Mouse and Yellow-billed Cuckoo to LANL's HMP (USFWS consultation number 02ENNM00-2015-I-0538).

In 2017, the USFWS concurred with DOE's proposal to modify the habitat boundaries for the lower section of Water Canyon Mexican Spotted Owl AEI due to habitat degradation resulting from long-term drought and fire effects (USFWS consultation number 02ENNM00-2017-I-0255).

6.0 Data Management

The data used in the implementation of the HMP are stored in a geodatabase at LANL. The current map of all of the AEIs at LANL is in Figure A-1 in the appendix.

II. AREA OF ENVIRONMENTAL INTEREST SITE PLAN FOR THE MEXICAN SPOTTED OWL

1.0 Species Description—Mexican Spotted Owl

1.1 Status

In 1993, the USFWS determined the Mexican Spotted Owl to be a threatened species under the authority of the ESA, as amended (58 Federal Register [FR] 14248). In 1995, the USFWS released its final recovery plan for the owl (USFWS 1995), which was revised in 2012 (USFWS 2012). The USFWS most recently designated critical habitat for Mexican Spotted Owl in 2004 (69 FR 53181).

1.2 General Biology

The Mexican Spotted Owl is found in northern Arizona, southeastern Utah, and southwestern Colorado south through New Mexico, west Texas, and into Mexico. It is the only subspecies of Spotted Owl recognized in New Mexico (USFWS 1995).

The Mexican Spotted Owl generally inhabits mixed conifer and ponderosa pine- (*Pinus ponderosa;* Lawson & C. Lawson) Gambel oak (*Quercus gambelli;* Nutt.) forests in mountains and canyons. High canopy closure, high stand diversity, multilayered canopy resulting from an uneven-aged stand, large mature trees, downed logs, snags, and stand decadence as indicated by the presence of mistletoe are characteristics of Mexican Spotted Owl habitat. Some owls have been found in second-growth forests (i.e., younger forests that have been logged); however, these areas were found to contain characteristics typical of old-growth forests. Mexican Spotted Owls in the Jemez Mountains prefer cliff faces in canyons for their nest sites (Johnson and Johnson 1985). The recovery plan for the Mexican Spotted Owl recommends that mixed conifer and pine-oak woodland types on slopes greater than 40 percent be protected for the conservation of this owl.

A mated pair of adult Spotted Owls may use the same home range and general nesting areas throughout their lives. A pair of owls requires approximately 800 ha (1,976 ac) of suitable nesting and foraging habitat to ensure reproductive success. Incubation is carried out by the female. The incubation period is approximately 30 days and most eggs hatch by the end of May. Most owlets fledge in June, 34 to 36 days after hatching (USFWS 1995). The owlets are "semi-independent" by late August or early September, although juvenile begging calls have been heard as late as September 30. Young are fully independent by early October. The non-breeding season runs from September 1 through February 28. Although seasonal movements vary among owls, most adults remain within their summer home ranges throughout the year.

The diet of Mexican Spotted Owls nesting in canyons consists primarily of woodrats (*Neotoma* spp.) and deermice (*Peromyscus* spp.) with lesser amounts of rabbits, birds, reptiles, and arthropods (Willey 2013). The relative abundance of prey types in Mexican Spotted Owl pellets collected at LANL are listed in Table A-1 in the appendix. Ganey and Balda (1994) found core areas of individuals (i.e., where owls spent 60 percent of their time) averaged 134 ha (331 ac), and core areas for pairs averaged 160 ha (395 ac).

1.3 Threats

The Mexican Spotted Owl was listed as threatened because of destruction and modification of habitat caused by timber harvest, wildfires, increased predation on owls associated with habitat fragmentation, and a lack of adequate protective regulations.

2.0 Impact of Human Activities

2.1 Introduction

The primary threats to Mexican Spotted Owls on LANL property are 1) impacts to habitat quality from LANL operations and 2) disturbance of nesting owls. This section provides a review and summary of scientific knowledge of the effects of various types of human activities on the Mexican Spotted Owl and provides an overview of the current levels of activities at LANL.

2.2 Impacts on Habitat Quality

2.2.1 Development

The type of habitat used by Mexican Spotted Owls, late seral stage forests with large trees, is usually not found in large quantities near developed areas or near areas that have had recent agricultural or forest product extraction land uses. Therefore, Mexican Spotted Owls are generally not found near developments. Whether it is the development or a lack of suitable habitat that discourages colonization of these areas by Mexican Spotted Owls is unknown.

Areas of LANL vary from remote, undeveloped areas to heavily developed and/or industrialized facilities. Most LANL facilities are situated atop mesas, primarily in the northern and western portion of the DOE property. LANL is bounded by developed residential, industrial, and retail areas along its northern boundary (the town of Los Alamos) and by residential and retail development along a portion of its eastern boundary (the town of White Rock). Three major paved roads traverse LANL from northeast to southwest. Sandia, Pajarito, and Los Alamos canyons have paved roads within AEIs, and several AEIs have dirt roads along at least a portion

of the canyon bottom. AEIs containing paved or dirt roads in the canyon bottoms have not been occupied at LANL (Hathcock et al. 2010).

2.2.2 Ecological Risk

There is no specific information on the impact of chemicals on the Mexican Spotted Owl, although experience with other raptor species suggests that exposure to polychlorinated biphenyls (PCBs), dichloro-diphenyl-trichloroethane (DDT) and its derivatives, and other organophosphate or organochlorine pesticides would probably be harmful. Exposure to other chemicals could also be harmful (Cain 1988).

LANS subject matter experts completed three ecological risk assessments that included the Mexican Spotted Owl between 1997 and 2009. The ecological risk assessment process involves using computer modeling to assess potential effects to animals from chemicals of potential concern that have been detected in the environment. All of the following ecological risk assessments concluded that, on average, no appreciable impact is expected to Mexican Spotted Owls from chemicals of potential concern (Gallegos et al. 1997; Gonzales et al. 2004; Gonzales et al. 2009).

2.2.3 Disturbance

2.2.3.1 Pedestrians and Vehicles

Based on work with other raptors, LANS biologists assume that Mexican Spotted Owls would likely be disturbed by the approach of either pedestrians or vehicles. At an equal distance, pedestrians are frequently more disturbing to raptors than vehicles (Grubb and King 1991). Brown and Stevens (1997) reported that during surveys in Grand Canyon National Park, 22 times more Bald Eagles were found in canyon reaches with low human recreational use compared to reaches with moderate to high human recreational use. Human activity 100 m (328 ft) from Bald Eagle nests in Alaska caused clear and consistent changes in behavior of breeding eagles (Steidl and Anthony 2000).

Swarthout and Steidl (2001) found that both juvenile and adult roosting Mexican Spotted Owls were unlikely to alter their behavior in the presence of a single hiker at distances greater than 55 m (180 ft). Swarthout and Steidl (2003) concluded that cumulative effects of high levels of short-duration recreational hiking near Mexican Spotted Owl nests may be detrimental.

Many canyon bottoms and mesa tops at LANL have dirt roads traversing them. Most of these roads are gated; however, these roads are accessible to LANL employees and some of them are accessible to the public on foot or by bike. LANS biologists found that AEIs are occupied less often if there is recreational access into a canyon (Hathcock et al. 2010).

2.2.3.2 Aircraft

Ground-based disturbances appear to impact raptor reproductive success more than aerial disturbances (Grubb and King 1991). Grubb and Bowerman (1997) concluded that an exclusion of aircraft within 600 m (1,968 ft) of Bald Eagle nest sites would limit Bald Eagle response frequency to 19 percent.

Delaney et al. (1999) found that for Mexican Spotted Owls, chainsaws consistently elicited higher response rates than helicopters at similar distances. Owl flush rates did not differ between nesting and non-nesting seasons. No owls flushed when noise stimuli (helicopter or chainsaws) were at distances greater than 105 m (344 ft). Distance was generally a better predictor of owl response to helicopter overflights than sound level.

LANL is restricted airspace and planes infrequently fly less than 609 m (2,000 ft) above ground level. The County of Los Alamos operates an airport along the northern edge of LANL. The airport is located on the southern rim of Pueblo Canyon. Most flights approach and depart to the east of the airport, over the Rio Grande.

2.2.3.3 Explosives

There is currently no specific information available on the reaction of Mexican Spotted Owls to explosives detonation. Explosive blasts set off 120 to 140 m (393 to 459 ft) from active Prairie Falcon (*Falco mexicanus*) nests caused perched Prairie Falcons to flush from perches 79 percent of the time, and, in 26 percent of the cases, caused incubating Prairie Falcons to flush from nests. Measured sound levels at aerie entrances during blasts ranged from 129 to 141 decibel (dB) (Holthuijzen et al. 1990). Explosives blasting for dam construction 560 to 1,000 m (1,837 to 3,280 ft) from active Prairie Falcon nests caused a change in behavior 26 percent of the time, and birds flushed in 17 percent of all cases. No incubating birds flushed (Holthuijzen et al. 1990). Brown et al. (1999) found little activity change in roosting or nesting Bald Eagles and no population-level impacts from weapons detonations at the Aberdeen Proving Ground. Holthuijzen et al. (1990) found that a 167-g (5.89-oz) charge of Kinestik produced noise levels between 138 and 141 dB at 100 m (328 ft), and that a 500-g (17.6-oz) charge of trinitrotoluene(2,4,6-) (TNT) produced noise levels between 144 and 146 dB at 100 m (328 ft). A 20-kg (44-lb) charge of TNT produced noise levels that measured 163 dB at 100 m (328 ft) (Paakkonen 1991).

Measurements of noise levels during explosives testing were conducted at three locations at LANL using quantities of high explosives ranging from 4.5 to 67.5 kg (10 to 148 lb) of TNT during six shots. Noise levels increased during the test from a background level of 31 A-weighted decibel [dB(A)]¹ to a range between 64 and 71 dB(A) during shots at a distance of 1.8 km (1.1 mi). At a distance of 4.3 km (2.67 mi), noise levels rose from a background range of 35 to 64 dB(A) to a range of 60 to 63 dB(A) (Vigil 1995). At a distance of 6.7 km (4.16 mi), noise levels rose from a background range of 38 to 51 dB(A) to a range of 60 to 71 dB(A) (Burns 1995). LANS biologists estimated that the noise from a shot at the Dual-Axis Radiographic Hydrodynamic Test (DARHT) Facility would be 150 dB(A) at the source and 80 dB(A) at 400 m (1,312 ft) (Keller and Risberg 1995). LANS biologists found that Mexican Spotted Owl AEIs located within the explosives testing buffer area were occupied more frequently than AEIs in other locations (Hathcock et al. 2010). This is likely due to the strict access control in explosives areas that limit human activity and development in the canyon bottoms.

¹Sound can be measured as decibels (dB), C-weighted dB [dB(C)], or A-weighted dB [dB(A)]. The dB(A) measurement best resembles the response of the human ear by filtering out lower and higher frequency sound not normally heard by the human ear.

2.2.3.4 Other Sources of Noise

Major noise-producing activities at LANL include automobile and truck traffic and noise associated with office buildings, construction activities, a live-fire range, and explosives testing. Noise is also associated with aircraft traffic at the Los Alamos County airport. Construction and maintenance activities involved with operations at LANL are fairly common. In addition, implementation of the 2016 Compliance Order on Consent issued by the New Mexico Environmental Department has resulted in an increased frequency of drilling groundwater monitoring wells in protected habitat at LANL. Also, forest fuels management operations use chainsaws, chippers, and other noise-generating equipment. The 2010 National Pollutant Discharge Elimination System Individual Permit (EPA 2010) issued by the Environmental Protection Agency requires sediment control features such as berms and small rock check dams to be installed at various sites with stormwater runoff; these are sometimes installed in protected habitat. LANS biologists conducted a study of noise levels in canyons and found that the primary sources of noise exceeding 55 dB(A) were cars and trucks. Readings taken near flowing water were up to 11 dB(A) higher than readings taken elsewhere. The average dB(A) in canyons near paved roads ranged from 41 to 62, with maximum values ranging from 62 to 74. Away from paved roads 1.6 km (1 mi) or more, average dB(A) in canyons ranged from 37 to 50, with all but one average below 45. Maximum dB(A) away from paved roads ranged from 38 to 76, 76 dB(A) was measured during a thunder clap (Huchton et al. 1997).

In December 1997, LANS biologists conducted noise measurements at the Los Alamos County airport and in Bayo and Pueblo canyons, including the Los Alamos County Sewage Treatment Facility. Sound levels near the airport runway during the maximum use time (6:30 to 7:30 am) had background values averaging 54 dB(A). Noise during plane arrivals ranged from 47 to 63 dB(A). No measurements were collected during plane take-off. Sound measurements conducted in the bottoms of Pueblo and Bayo canyons ranged from 37 to 40 dB(A) in most areas of the canyon. At the sewage treatment facility parking lot during a working day, the average dB(A) during a 3-minute period was 46 (range 45 to 49). At the intersection of the road going into Pueblo Canyon with State Road 502, the average dB(A) during a 3-minute period was 60 (range 41 to 70).

LANS biologists conducted sound measurements at successive distances from an industrial area near a canyon rim, into the canyon, and to the opposite rim, using a C-weighted decibel (dB(C) scale (Keller and Foxx 1997). Measurements of noise levels using the dB(C) scale are greater than if measured using the dB(A) scale. The average background noise on the mesa was 65.8 dB(C) [with a range of 43–81 dB(C)]. The average background noise in the canyon bottom was 62.3 dB(C) [with a range of 54–78 dB(C)]. The average background noise at the bottom of the north-facing slope was 53.8 dB(C) [with a range of 48–64 dB(C)]. Measurements were taken mid-day.

LANS biologists measured sound levels from various pieces of construction equipment used at LANL project sites over 5-minute intervals at distances of 6 to 31 m (20 to 100 ft) (Knight and Vrooman 1999). Average values ranged from 58.5 to 80.9 dB(A). Peak values ranged from 75.7 to 155.4 dB(A). Additional data were collected by other LANL operators on specific pieces of construction equipment and on the Security Computer Complex construction site fence perimeter at Technical Area 3 before and during construction (Knight and Vrooman 1999). The average

noise level before construction began was 56.6 dB(A), and the average during construction was 82.1 dB(A).

LANS biologists conducted a series of sound measurements at LANL to investigate background noise levels around AEIs (Vrooman et al. 2000). Background noise levels were significantly higher in daytime than in nighttime. AEIs with greater than a 10 percent developed area in their buffers had significantly higher levels of background noise than undeveloped AEIs. The mean background sound level was 51.3 dB(A) in developed AEIs and 39.6 dB(A) in undeveloped AEIs. The LANL biological resources project review process uses the individual AEI background measurements from Vrooman et al. (2000) to screen project activities for increases more than 6 dB(A) above background.

LANS biologists took sound level measurements of heavy equipment use associated with concrete recycling on Sigma Mesa at LANL in 2004 (Hansen 2004). At this location, background noise levels at two different locations were 55.2 and 58.8 dB(A). Operation of a dump truck hauling and dumping concrete increased noise levels above background by a mean of 22.7 dB(A) at 30 m (98 ft) and 2.4 dB(A) at 80 m (262 ft). Additional sound level measurements were taken in the same general area on Sigma Mesa in 2005 as part of a biological assessment for the operation of an asphalt batch plant (Hansen 2005). Measurements were taken on the north rim of Mortandad Canyon (south of the asphalt batch plant at distances of approximately 30 to 122 m (100 to 400 ft), at the bottom of Mortandad Canyon approximately 183 to 244 m (600 to 800 ft) from the asphalt batch plant, and on the south rim of Mortandad Canyon approximately 305 m (1,000 ft) from the asphalt batch plant. Background noise levels at the various locations ranged from 41.1 to 48.7 dB(A). The only locations with increases greater than 3 dB(A) during operation of the asphalt batch plant. Noise from the operation of the asphalt batch plant were the locations on the north rim of Mortandad Canyon, within 122 m (400 ft) of the asphalt batch plant. Noise from the operation of the asphalt batch plant at Canyon or on the south rim.

LANS biologists took sound level measurements around the LANL Biosafety Level 3 laboratory with the heating, ventilation, and air conditioning (HVAC) system on and with it off (Hansen 2009). The area to the north of the Biosafety Level 3 laboratory is developed, the area to the south is not. Background noise levels north of the facility ranged from 53.6 to 57.6 dB(A). Background noise levels south of the facility ranged from 41.6 to 49.7 dB(A). Noise from the HVAC system was detected at 25 m (82 ft) from the facility on both sides, but was not detected at 81 m (266 ft) on the north side, or at 107 m (351 ft) on the south side.

Overall, these studies appear to show that areas adjacent to or within developed areas or paved roads are likely to have daytime average background noise levels between 45 and 63 dB(A). Less disturbed areas are likely to have average background noise levels between 37 and 50 dB(A).

2.2.3.5 Artificially Produced Light

There is no information available on the effects of artificially produced light on Mexican Spotted Owls. Under the Los Alamos County Code, commercial site development plans are reviewed to ensure that lighting serves the intended use of the site while minimizing adverse impacts to adjacent residential property (Section 16-276). Section 16-276 of the County Code includes light source measurement limitations by zoning district. The code allows off-site light to be 0.5 foot candles (fc) in residential areas. By comparison, full moonlight measures 0.1 fc, and a crescent

moon was measured at 0.01 fc. Table A-2 in the appendix presents preliminary light measurements in fc.

Preliminary surveys were conducted for light levels within Los Alamos Canyon at the Omega Reactor (Keller and Foxx 1997). The Omega Reactor was brightly lit for purposes of security; therefore, total light intensity was greater than the average street lighting. Measurements were conducted at a light pole in an open parking lot at the reactor as the source. Trees did not obscure the area. Using the relationship of light intensity reducing as a square of the distance, calculations using the field data indicated that at 30 m (98 ft) from the source, the light levels would be equivalent or nearly equivalent to full moonlight.

3.0 AEI General Description for Mexican Spotted Owl

An AEI consists of two areas—a core and a buffer. The core of the habitat is defined as suitable canyon habitat from rim to rim and 100 m (328 ft) out from the top of the canyon rim. The buffer area is 400 m (1,312 ft) wide extending outward from the edge of the core area. Although adult Mexican Spotted Owls may be found within their home range anytime throughout the year, the primary threat from disturbance to the owls is during the breeding season when owl pairs are tied to their nest sites. Therefore, management of disturbance in Mexican Spotted Owl AEIs is concentrated on the breeding season.

3.1 Method for Identifying a Mexican Spotted Owl AEI

The original location of each Mexican Spotted Owl AEI was identified using a habitat model developed by Johnson (1998) that classified nesting and roosting habitat for Mexican Spotted Owls using topographic characteristics and vegetative diversity. LANS biologists compared the results from the Johnson (1998) model to a different model identifying slopes >40 percent in mixed conifer and ponderosa pine cover types at LANL. Areas identified from the Johnson (1998) model application to LANL that were over five contiguous 30×30 m (97×98 ft) pixels in size, were above 1,980 m (6,496 ft) in elevation, and that had mixed conifer or ponderosa pine forest cover, were considered suitable Mexican Spotted Owl habitat. Where suitable habitat was identified, AEI core area boundaries were established to include the canyons and 100 m (328 ft) outward from the canyon rims.

An updated Mexican Spotted Owl habitat model was developed and refined for application on LANL property following the Cerro Grande wildfire (Hathcock and Haarmann 2008). This model incorporated finer-scale vegetation characteristics into the Mexican Spotted Owl habitat quality assessment. This model was used to redelineate the boundaries of the Mexican Spotted Owl AEIs at LANL in 2005 following wildfire, drought, and a regional bark beetle outbreak (USFWS consultation number 22420-2006-I-0010).

The new core boundaries were delineated with an area approximately 0.4 km (0.25 mi) from the edge of the nearest suitable habitat, up and down canyon. Core boundaries were established along readily recognizable geologic features or anthropogenic features in the terrain wherever possible to facilitate the ease of identification of core boundaries when in the field.

3.2 Location and Number of Mexican Spotted Owl AEIs

There are currently five Mexican Spotted Owl AEIs on LANL property, each encompassing one or more canyons. In general, the AEI cores are centered in canyons on the western side of LANL. The canyons with AEIs are Cañon de Valle, Water, Pajarito, Los Alamos, Sandia, Mortandad, and Three-Mile.

4.0 AEI Management

4.1 Overview

This AEI management section provides guidelines for LANL operations to reduce or eliminate the threats to Mexican Spotted Owls from 1) habitat alterations that reduce habitat quality and 2) disturbance of breeding or potentially breeding owls. Habitat alterations are considered for all AEIs and for both core and buffer areas. Disturbance activities to owls are considered only for occupied AEIs and only for impacts on core areas. Developed areas (see Part I, Section 3.1) that have ongoing baseline levels of activities and are not suitable habitat for Mexican Spotted Owls have different restrictions than undeveloped core or buffer areas. Therefore, the location of the disturbance activity within the AEI, the occupancy status of the AEI, and the type of activity all affect whether or not the activity is allowable. AEIs for different species may overlap, and an activity must meet the guidelines of all applicable site plans to be allowable.

4.2 Definition and Role of Occupancy in AEI Management

Occupancy simply refers to whether or not an AEI is occupied during a species' period of sensitivity. For Mexican Spotted Owls, the primary concern is to protect the owls from disturbance during the breeding season. Because individuals may colonize suitable habitat, all Mexican Spotted Owl AEIs are treated as though they are occupied from March 1 through August 31 or until surveys show an AEI to be unoccupied. Mexican Spotted Owl surveys are conducted from late March through June. In general, surveys in areas with ongoing or proposed projects are completed by May 15. If a nest is located during surveys, then the AEI can be treated as unoccupied except for the area within a 400 m (1,312 ft) radius of the nest site. Because owls are not as sensitive to disturbance during the non-breeding season, Mexican Spotted Owl AEIs are treated as unoccupied from September 1 to February 28.

The occupancy status of an AEI affects what activities are allowable in the AEI. Although activities causing habitat alterations are restricted in all AEIs, disturbance activities are restricted only in occupied AEIs. The Activity Table (Table 1, Section 4.5.2) provides dates and levels of allowable disturbance activities within occupied Mexican Spotted Owl AEIs under the guidelines of this site plan. Contact a LANS biologist to find out the current occupancy status of an AEI (http://int.lanl.gov/environment/bio/controls/index.shtml).

4.3 Introduction to AEI Management Guidelines

Sections 4.4 and 4.5 provide the guidelines for habitat alterations and allowable activities in AEI core and buffer areas. Section 4.4 describes what and where habitat alterations are allowed under the guidelines of this site plan. Section 4.5 describes what, when, and where disturbance activities are allowed in occupied AEIs under the guidelines of this site plan. If an activity does not meet the restrictions given in the guidelines, the activity must be individually reviewed for

ESA compliance. This site plan only provides guidelines for Mexican Spotted Owl AEIs. If an activity is desired in an area with overlapping AEIs, all applicable site plans must be consulted. AEI maps show the location of all AEIs in an area. Section 4.6 describes management practices that should be applied when working or considering work in an AEI. LANS biologists are available to answer questions and provide advice

(http://int.lanl.gov/environment/bio/controls/index.shtml).

4.4 Definition of and Restrictions on Habitat Alterations

4.4.1 Definition of Habitat Alterations

Habitat alteration includes any action that alters the soil structure, vegetative components necessary to the species, prey quality and quantity, water quality, hydrology, or noise or light levels in undeveloped areas of an AEI. Long term means the alteration lasts for more than one year. For physical disturbances, in general, any activity that can be accomplished by one person with a hand tool is generally not considered habitat alteration; any activity that requires mechanized equipment on a landscape is habitat alteration. An actual activity may take place outside of the AEI and will be considered habitat alteration if consequences of the activity have effects inside the AEI core.

The habitat components most important to Mexican Spotted Owls include vegetative structure, food quality and quantity, and disturbance levels, including noise and light. The forest structure within a canyon designated as a Mexican Spotted Owl AEI is important because it provides roost sites and a suitable habitat for nesting and foraging. Trees along the canyon rim are used for foraging and territorial calling, and they shelter the canyon interior from light and noise disturbances.

A long-term change in light or noise levels within the undeveloped core of an AEI is considered to be a habitat alteration if it increases average noise levels by $\geq 6 \text{ dB}(A)$ during any portion of the 24-hour day, or it increases average light levels by ≥ 0.05 fc at night. Changes in noise and light levels are measured at the core area boundary if the source is outside the core area, or at 10 m (33 ft) from the source if the source is inside the undeveloped core area. Impacts of changes in developed areas on undeveloped cores are measured at the developed area boundary if it is within the core, or at the core area boundary if the developed area is outside of the core.

4.4.2 Fuels Management Practices to Reduce Wildfire Risk

The recovery plan for the Mexican Spotted Owl lists stand-replacing wildfires as a primary threat to their habitat and encourages land managers to reduce fuel levels and abate fire risks in ways compatible with owl presence on the landscape (USFWS 1995). Within undeveloped core areas, on slopes >40 percent, in the bottoms of steep canyons, and within 30 m (100 ft) of a canyon rim, thinning of trees <22 cm (9 in) diameter at breast height, treatment of fuels, and prescribed and natural prescribed fires are allowed. Exceptions allowing trees >22 cm (9 in) to be thinned within 30 m (100 ft) of buildings are granted to protect facilities. Large logs (>30 cm [11.8 in] midpoint diameter) and snags should be retained. Thinning within core areas not meeting the characteristics listed above, and in buffer areas, may include trees of any size to achieve 8 m (25 ft) spacing between tree crowns. However, clear cutting is not allowed in undeveloped core areas.

For health and safety reasons, any trees within 30 m (100 ft) of buildings, but outside a developed area, may be thinned to achieve 8 m (25 ft) spacing between crowns. Habitat alterations including thinning are not restricted in developed areas. However, LANS biologists encourage the retention of trees and snags along canyon rims if the rim is in a developed area. Because of the extreme fire danger associated with firing sites and the potential impact of a fire on Mexican Spotted Owl habitat, firing sites and burn areas are treated separately for the purposes of fuels management. Trees within 380 m (1,246 ft) of firing sites and burn areas in both core and buffer areas may be thinned to a 15 m (49 ft) spacing between trees everywhere except on slopes >40 percent or in the bottoms of steep canyons. Any tree over 22 cm (9 in) diameter at breast height within 380 m (1,246 ft) of a firing site may be delimbed to a height of 2 m (6 ft) to help prevent crown fires.

In historically occupied core areas, fuels treatment may not exceed 10 percent of the undeveloped core area and is not allowed within 400 m (1,312 ft) of nesting areas. In occupied core areas, forest management activities must take place during the nonbreeding season (September 1 to February 28) (USFWS 1995). Fuels management activities that are allowable in core areas must be reported to LANS biologists for tracking (http://int.lanl.gov/environment/bio/controls/index.shtml).

4.4.3 Utility Corridors

Habitat alterations such as cutting down trees that threaten power lines are allowed within 8 m (26 ft) of either side of an existing utility line in all areas of an AEI (Trujillo and Racinez 1995). New utility lines and utility lines requiring clearance of a right-of-way greater than 16 m (52 ft) total must be individually reviewed for ESA compliance. Disturbance activities must follow the guidelines given in the Activities Table (Table 1, Section 4.5.2) for occupied AEIs.

4.4.4 Restrictions on Habitat Alterations

Habitat alterations other than the fuels management practices and utility corridor maintenance described above are not allowed in undeveloped core areas under the guidelines of this site plan. If a project or activity is planned that would alter habitat in an undeveloped core area, it must be individually evaluated for ESA compliance. Habitat alterations in undeveloped buffer areas other than the fuels management activities and utility corridor maintenance described above are restricted to 2 ha (5 ac) in area per project and are subject to other restrictions including light and noise effects in the core (see Section 2.2.3). Projects in the buffer area over 2 ha (5 ac) in size will require individual ESA compliance review.

Habitat alterations in a buffer area other than the fuels management and utility corridor maintenance described above must be reported to LANS biologists for tracking (<u>http://int.lanl.gov/environment/bio/controls/index.shtml</u>). There is a cumulative maximum area that can be developed in each AEI's buffer. Once that cumulative area is reached, all habitat alterations in a buffer will require individual ESA reviews for compliance.

4.5 Definition of and Restrictions on Disturbance Activities

4.5.1 Definitions of Disturbance Activities

LANS biologists considered six categories of activities that might cause disturbance in an AEI. Most of the categories were first identified in the document "Peregrine Falcon Habitat Management in the National Forests of New Mexico," prepared for the United States Forest Service (Johnson 1994). LANS biologists added explosives detonation, other light production, and other noise production to provide the most comprehensive list of activities possible, thereby reducing the need for individual review of activities for ESA compliance. The categories of activities are people, vehicles, aircraft, other light production, other noise production, and explosives detonation. LANS biologists defined low, medium, and high levels of impact for these activities except for explosives detonation. Activity levels for explosives detonation have been designed to follow the guidelines agreed upon by LANL, DOE, and USFWS in the DARHT biological assessment (Keller and Risberg 1995). Restrictions on explosives detonation are described in the definition of the activity, but are not included in the Activity Table (Table 1, Section 4.5.2). These six categories of activities are restricted only in AEIs that are classified as occupied.

People—includes any entry of people into an AEI on foot.

- Low impact is the presence of three or fewer people per project and duration of one day or less during a breeding season.
- Medium impact is the exceedance of either the number of people or the duration criteria.
- High impact is the exceedance of both the number of people and the duration criteria.

Vehicles—includes the entry of any two-axle highway vehicle, all-terrain vehicle, or motorized machinery into an AEI by any route other than a paved road or an improved gravel road.

- Low impact is the presence of two or fewer vehicles per project and duration of one day or less during a breeding season.
- Medium impact is the exceedance of either the number of vehicles or the duration criteria.
- High impact is the exceedance of both the number of vehicles and the duration criteria.

Aircraft—includes the operation of any aircraft below an elevation of 600 m (2,000 ft) above the highest ground level in the local vicinity.

- Low impact is the presence of one single-engine airplane and the duration of one day or less during a breeding season.
- Medium impact is the exceedance of either the number of aircraft or the duration criteria.
- High impact is the exceedance of both the number of aircraft and the duration criteria.

Any use of helicopters, jet airplanes, and propeller airplanes with two or more engines is classified as medium impact or above, depending on duration.

Other Light Production—includes any activity not previously listed that causes additional light to occur in an AEI core area. For example, plans for construction of a new building at the edge of a developed area may call for lighting at night to facilitate nighttime work that impacts an undeveloped core area.

- Low impact is the increase of light intensity by ≤0.05 fc and a duration of one night or less per project per breeding season.
- Medium impact is the exceedance of either the intensity or duration criteria.
- High impact is the exceedance of both the intensity and duration criteria.

Measurements for increases in light are taken at the AEI core area boundary closest to the light source if the source is outside the core and at 10 m (33 ft) from the source if the source is inside the core. Light measurements for developed areas are taken at the edge of the developed area if the developed area is within an AEI core or at the closest core boundary if the developed area is outside of an AEI core.

Other Noise Production—includes any activity not previously listed except for explosives detonation that causes additional noise to occur in an AEI. For example, operation of machinery creates noise.

- Low impact is increasing noise levels in an AEI core by 6 dB(A) or less for one day or less per project per breeding season.
- Medium impact is the exceedance of either the level or the duration criteria.
- High impact is the exceedance of both the level and the duration criteria.

Measurements for increases in noise are taken at the AEI core boundary closest to the noise source if the source is outside the core and at 10 m (33 ft) from the source if the source is inside the core. Noise measurements for developed areas are taken at the edge of the developed area if the developed area is within an AEI core or at the closest core boundary if the developed area is outside of an AEI core.

Explosives Detonation—includes the use of high explosives for any purpose. LANS biologists did not define low, medium, and high levels of this activity because of the difficulty of determining levels for a shot before actually doing the shot. For the purpose of explosives detonation near Mexican Spotted Owl AEIs, occupied habitat is defined as the area within 400 m (1,312 ft) of the current year's nest/roost sites or the previous year's nest site if a current site has not been identified. No explosives detonation will take place within 400 m (1,312 ft) of nest/roost sites in occupied habitat between March 1 and August 31. Explosives detonation at night at sites within 400 to 800 m (1,312 to 2,624 ft) of a nest site in occupied habitat is restricted to once a month from March 1 and August 31.There are no restrictions on daytime explosives testing between 400 and 800 m (1,312 to 2,624 ft). There are no restrictions between September 1 and February 28 or in unoccupied habitat. Explosives detonation adjacent to AEIs that have not previously been recorded by LANS biologists as occupied will have no restrictions unless surveys detect Mexican Spotted Owls. Explosives tests not allowed under the guidelines of this site plan must be individually reviewed for ESA compliance.

4.5.2 Activity Table

The dates shown in the Activity Table (Table 1) are the dates between which the activity in the row is restricted under the guidelines of this site plan. All AEIs are considered occupied from March 1 to August 31 or until surveys show an AEI to be unoccupied. If owls are detected, AEIs are considered occupied until August 31 within 400 m (1,312 ft) of the nest site. Consult with LANS biologists to find out occupancy status of AEIs and what locations are within 400 m (1,312 ft) of nest sites (http://int.lanl.gov/environment/bio/controls/index.shtml).

	Levels of Impact	Core	Buffer
People			
	Low	No Restrictions*	No Restrictions
	Medium	March 1 to August 31	No Restrictions
	High	March 1 to August 31	No Restrictions
Vehicles			
	Low	No Restrictions	No Restrictions
	Medium	March 1 to August 31	No Restrictions
	High	March 1 to August 31	No Restrictions
Aircraft			
	Low	March 1 to August 31	No Restrictions
	Medium	March 1 to August 31	March 1 to May 15
	High	March 1 to August 31	March 1 to August 31
Other Light Production			
	Low	March 1 to August 31	No Restrictions**
	Medium	March 1 to August 31	No Restrictions**
	High	March 1 to August 31	No Restrictions**
Other Noise Production			
	Low	March 1 to August 31	No Restrictions**
	Medium	March 1 to August 31	No Restrictions**
	High	March 1 to August 31	No Restrictions**
Explosives Detonation (se	e text in Section 4.5.	1)	

Table 1.	Restrictions on	Activities in U	Undeveloped	Occupied Mexic	an Spotted Owl AEIs
----------	------------------------	------------------------	-------------	-----------------------	---------------------

onation (see text in Section 4.5.1)

Entry is restricted in core areas that are occupied within 400 m (1,312 ft) of the nest site from March 1 to August 31. If the current nest has not been located, entry is restricted within 400 m (1,312 ft) of the previous year's nest site.

** Noise or light production in the buffer is restricted if the activity would violate core area restrictions on noise or light.

4.6 Protective Measures

This section provides a list of management practices to apply in Mexican Spotted Owl AEIs.

• Timing of projects must take into account that projects in core areas or projects that violate restrictions for occupied buffer areas must stop on February 28 each year until occupancy status of the AEI is determined.

- Make every reasonable effort to reduce the noise from explosives testing within 800 m (2,624 ft) of occupied habitat. Methods to reduce noise could include contained shots, noise shields in the direction of AEI cores, etc. For night shots, every reasonable effort should be made to limit the amount of light directed into AEI core areas.
- Install signs on dirt roads and trails leading into AEIs labeling them as restricted access areas and provide a contact number for access restrictions.
- Keep disturbance and noise to a minimum.
- Avoid unnecessary disturbance to vegetation (e.g., excessive parking areas or equipment storage areas, off-road travel, materials storage areas, crossing of streams or washes).
- Avoid removal of vegetation along drainage systems and stream channels.
- Avoid all vegetation removals not absolutely necessary.
- Employ appropriate erosion and runoff controls to reduce soil loss. The controls must be put in place and periodically checked throughout the life of projects.
- Revegetate all exposed soils as soon as feasible after construction to minimize erosion.
- Focus development away from undeveloped areas on the western end of the Los Alamos Canyon AEI.

5.0 Levels of Development in AEI Core and Buffers

5.1 Allowable Habitat Alteration in the Buffer Areas

The following quantifications of development and guidance for allowable habitat alteration in buffer areas were published and consulted on in the 1999 version of the HMP. Most AEIs changed in dimensions during the 2005 redelineation of the habitats, and many have experienced additional development under past consultations. Many projects were reviewed and received USFWS concurrence between 1999 and 2017.

The current development status for each of the AEIs is at the end of each AEI description.

Cañon de Valle—In 1999, 16.3 ha (40.3 ac) of the core was developed and 52.2 ha (129 ac) of the buffer was developed. For this AEI, it was recommended that only an additional 25.30 ha (62.5 ac) of the AEI buffer be developed. The 1999 HMP stated that once this cap is reached or a large-scale project is proposed, additional consultation with USFWS would be required. By 2011, 28 ha (69.2 ac) of the core and 84 ha (207.5 ac) of the buffer was developed, with most of the changes due to consultations. The 2017 redelineation of the lower Water Canyon AEI resulted in another reduction of 69 ha (170 ac). The current size of this AEI is 277 ha (685 ac) of core and 524 ha (1295 ac) of buffer habitat. Of that, 21 ha (52 ac) of the current core is developed and 71 ha (176 ac) of the current buffer is developed.

Pajarito—In 1999, 6.7 ha (16.5 ac) of the core was developed and 75.1 ha (186.5 ac) of the buffer was developed. For this AEI, it was recommended that only an additional 35 ha (86.4 ac) of the buffer be developed. The 1999 HMP stated that once the cap is reached or a single large-scale project is proposed, additional consultation with the USFWS would be required. By 2011,

27 ha (66.7 ac) of the core and 89 ha (220 ac) of the buffer was developed, with most of the changes due to consultations. The current size of this AEI is 236 ha (585 ac) of core and 449 ha (1,111 ac) of buffer habitat. Of that, 27 ha (67 ac) of the current core is developed and 89 ha (220 ac) of the current buffer is developed.

Los Alamos—In 1999, 77.16 ha (190 ac) of the core was developed and 167.2 ha (413.1 ac) of the buffer was developed. Because this AEI is heavily developed, additional development was restricted to a few selected areas within the buffer. By 2011, 94 ha (232.2 ac) of the core and 181 ha (447.3 ac) of the buffer was developed, with most of the changes due to consultations. The current size of this AEI is 325 ha (805 ac) of core and 535 ha (1,323 ac) of buffer habitat. Of that, 64 ha (158 ac) of the current core is developed and 129 ha (319 ac) of the current buffer is developed.

Sandia-Mortandad—In 1999, 29 ha (71.7 ac) of the core was developed and 75.1 ha (185.6 ac) of the buffer was developed. For this AEI, LANS biologists recommended only an additional 38.1 ha (94.1 ac) of the buffer be developed before additional USFWS consultations take place. By 2011, 45 ha (111.2 ac) of the core and 83 ha (205.1 ac) of the buffer was developed, with most of the changes due to consultations. The current size of this AEI is 270 ha (669 ac) of core and 371 ha (918 ac) of buffer habitat. Of that, 44 ha (110 ac) of the current core is developed and 83 ha (206 ac) of the current buffer is developed.

Three Mile—In 1999, 3.8 ha (9.4 ac) of the core was developed and 21.5 ha (51.1 ac) of the buffer was developed. For this AEI, LANS biologists recommended only 64.3 ha (158.8 ac) additional area of buffer be developed before additional USFWS consultations take place. By 2011, 12 ha (29.6 ac) of the core and 37 ha (91.4 ac) of the buffer was developed, with most of the changes due to consultations. The current size of this AEI is 131 ha (325 ac) of core and 295 ha (730 ac) of buffer habitat. Of that, 11 ha (29 ac) of the current core is developed and 36 ha (91 ac) of the current buffer is developed.

III. AREA OF ENVIRONMENTAL INTEREST SITE PLAN FOR THE SOUTHWESTERN WILLOW FLYCATCHER

1.0 Species Description—Southwestern Willow Flycatcher

1.1 Status

In 1995, the USFWS designated the Southwestern Willow Flycatcher as a federally endangered species (60 FR 10693). The USFWS most recently designated critical habitat for the Southwestern Willow Flycatcher in 2013 (78 FR 343). The most recent recovery plan for the Southwestern Willow Flycatcher was published in 2002 (USFWS 2002).

1.2 General Biology

The Southwestern Willow Flycatcher is one of four subspecies of the Willow Flycatcher. The historic range of the Southwestern Willow Flycatcher included Arizona, California, Colorado, New Mexico, Texas, Utah, and Mexico. Currently, this flycatcher breeds in riparian habitats from southern California to Arizona and New Mexico, plus southern Colorado, Utah, Nevada,

and far western Texas. In winter it is found in southern Mexico, Central America, and northern South America (USFWS 2002).

Southwestern Willow Flycatchers are present in New Mexico from early May through mid-September and breed from late May through late July (Finch and Kelly 1999; USFWS 2002; Yong and Finch 1997). The flycatcher's nesting cycle is approximately 28 days. Three or four eggs are laid at one-day intervals, and incubation begins when the clutch is complete. The female incubates eggs for approximately 12 days, and the young fledge about 13 days after hatching. Southwestern Willow Flycatchers typically raise one brood per year (USFWS 2002). Because arrival dates vary, northbound migrant Willow Flycatchers (of all subspecies) pass through areas where Southwestern Willow Flycatchers have already begun nesting. Similarly, southbound migrants (of all subspecies) in late July and August may occur where Southwestern Willow Flycatchers are still breeding. Therefore, it is only during a short period of the breeding season (approximately June15 through July 20) that a Willow Flycatcher seen within Southwestern Willow Flycatcher range is probably of that subspecies (USFWS 2002).

The Southwestern Willow Flycatcher only nests along rivers, streams, and other wetlands. It is found in close association with dense stands of willows (*Salix* spp.), arrowweed (*Pluchea* spp.), buttonbush (*Cephalanthus* spp.), tamarisk (*Tamarix* spp.), Russian olive (*Eleagnus angustifolia* L.), and other riparian vegetation, often with a scattered overstory of cottonwood (*Populus* spp.) (USFWS 2002). The size of vegetation patches or habitat mosaics used by Southwestern Willow Flycatchers varies considerably and ranges from as small as 0.8 ha (1.9 ac) to several hundred hectares (Hatten and Paradzick 2003). The Southwestern Willow Flycatcher nests in thickets of trees and shrubs approximately 2 to 15 m (6 to 49 ft) tall, with a high percentage of canopy cover and dense foliage from 0 to 4 m (0 to 13 ft) above ground. Regardless of the plant species composition or height, occupied sites always have dense vegetation in the patch interior (Allison et al. 2003; USFWS 2002).

The Southwestern Willow Flycatcher is an insectivore. It forages within and occasionally above dense riparian vegetation, taking insects on the wing and gleaning them from foliage. The flycatcher's prey includes flies, bees, wasps, ants, beetles, moths, butterflies, grasshoppers, crickets, dragonflies, damselflies, and spiders (Durst et al. 2008; Wiesenborn and Heydon 2007).

1.3 Threats

The current population of Southwestern Willow Flycatchers in the United States occupies an estimated 1,214 territories (Durst et al. 2006). The distribution of breeding groups is highly fragmented, with groups often separated by considerable distances. This subspecies has suffered declines attributed to extensive loss of its cottonwood-willow habitat and to poor productivity resulting from brood parasitism by Brown-headed Cowbirds (*Molothrus ater*) (USFWS 2002).

2.0 Impact of Human Activities

2.1 Introduction

The primary threats to the Southwestern Willow Flycatcher on LANL property are 1) impacts on habitat quality from LANL operations and 2) disturbance of nesting flycatchers. This section includes a review and summary of the known effects of various types of human activities to the

Southwestern Willow Flycatcher and an overview of the current levels of activities at LANL within species habitat.

2.2 Impacts on Habitat Quality

2.2.1 Development

Throughout the Southwest, riparian habitats are rare and tend to be small and separated by vast expanses of arid lands. The Southwestern Willow Flycatcher has experienced extensive habitat loss and modification resulting from urban and agricultural development, water diversion and impoundment, channelization of waterways, livestock grazing, off-road vehicle and other recreational uses, and hydrological changes resulting from these and other land uses (USFWS 2002). River and stream impoundments, groundwater pumping, and overuse of riparian areas have altered as much as 90 percent of the Southwestern Willow Flycatcher's habitat (USFWS 2002). Loss of cottonwood-willow riparian forests has had widespread impact on the distribution and abundance of bird species associated with that forest. Development may be tolerated if the habitat is left intact.

Because watercourses at LANL tend to be intermittent to ephemeral, riparian habitat is uncommon. There has been extensive degradation of the riparian zone along the Rio Grande caused by feral cattle grazing and flood control operations at Cochiti Lake. There are other riparian/wetland areas on LANL property associated with canyon bottoms, the most significant being the Pajarito wetlands in the lower end of Pajarito Canyon. A major paved road parallels the wetlands area in Pajarito Canyon.

2.2.2 Ecological Risk

There is no specific information on the impact of chemicals on the Southwestern Willow Flycatcher.

2.2.2.1 Ecorisk Assessment

LANS subject matter experts completed two ecological risk assessments between 1997 and 2009 that included the Southwestern Willow Flycatcher. The ecological risk assessment process involves using computer modeling to assess potential effects to animals from chemicals of potential concern that have been detected in the environment. The ecological risk assessments concluded that, in general, there is a small potential for effects to Southwestern Willow Flycatcher from chemicals of potential concern (Gonzales et al. 1998; Gonzales et al. 2009).

An ecotoxicological risk assessment for the Southwestern Willow Flycatcher, centered on the Pajarito wetlands, found that between 7 and 16 percent of 100 hypothetical nest sites examined had hazard indices >1.0 and <10.0, depending on the foraging scenario (Gonzales et al. 1998). This indicates a small potential for impacts from chemicals. The primary chemicals driving the risk scenario were pentachlorophenol, aluminum, radium-226, calcium, and thorium-228. Aluminum, radium, and thorium are naturally occurring substances in northern New Mexico.

2.2.3 Disturbance

2.2.3.1 Pedestrians and Vehicles

There is no specific information available on the reactions of Southwestern Willow Flycatchers to pedestrians and vehicles. The recovery plan for the Southwestern Willow Flycatcher recommends providing protected areas, reducing unpredictable activities, providing visual barriers, and reducing noise disturbance (USFWS 2002).

2.2.3.2 Aircraft

There is no specific information available on the reaction of Southwestern Willow Flycatchers to aircraft.

LANL lies within restricted airspace and planes infrequently fly less than 609 m (2,000 ft) above ground level. The County of Los Alamos operates an airport along the northern edge of LANL. The airport is located on the southern rim of Pueblo Canyon. Most flights approach and depart to the east of the airport, over the Rio Grande.

2.2.3.3 Explosives

There is no specific information available on the reaction of Southwestern Willow Flycatchers to explosives detonation. The Southwestern Willow Flycatcher AEI is not located close to any explosives testing sites at LANL.

2.2.3.4 Other Sources of Noise

LANS biologists do not have good information on the effects of noise, including machinery operation, on Southwestern Willow Flycatchers. However, Southwestern Willow Flycatchers are probably not as sensitive to disturbance as some other threatened or endangered species (USFWS 2002). For a description of noise levels at LANL, see Part I, Section 2.2.3.

2.2.3.5 Artificially Produced Light

There is no information available on the effects of artificially produced light on Southwestern Willow Flycatchers. Under the Los Alamos County Code, commercial site development plans are reviewed to ensure that lighting serves the intended use of the site while minimizing adverse impacts to adjacent residential property (Section 16-276). Section 16-276 of the County Code includes light source measurement limitations by zoning district. The code allows off-site light to be 0.5 fc in residential areas. By comparison, full moonlight measures 0.1 fc, and a crescent moon was measured at 0.01 fc.

3.0 AEI General Description for the Southwestern Willow Flycatcher

The AEI consists of two types of areas—core and buffer. Core areas represent wetland areas with suitable vegetation for nesting, primarily dense willows. The buffer area is the area within 100 m (328 ft) of core areas. The Southwestern Willow Flycatcher AEI on LANL property consists of two separate core areas. For purposes of this site plan, both core areas and associated buffers are considered one AEI unit.

3.1 Method for Identifying the Southwestern Willow Flycatcher AEI

The core areas were defined by the presence of riparian habitat and suitable wetland vegetation. These areas were identified in 1994 during a survey of wetlands at LANL and mapped using a global positioning system receiver. Wetlands without stands of dense willows at least 2 m (7 ft) tall and 30 m (98 ft) wide were not included in the AEI. The buffer area is the area within 100 m (328 ft) of the core areas.

3.2 Location of the Southwestern Willow Flycatcher AEI

There is one Southwestern Willow Flycatcher AEI on LANL property. It is composed of two core areas with associated buffers. The AEI core areas are located in the bottom of Pajarito Canyon, on the eastern side of LANL adjacent to Pajarito Road and State Road 4.

4.0 AEI Management

4.1 Overview

This AEI management section provides guidelines for LANL operations to reduce or eliminate the threats to the Southwestern Willow Flycatcher from 1) habitat alterations that reduce habitat quality and 2) disturbance of breeding or potentially breeding flycatchers. Habitat alterations are considered for all AEIs and for both core and buffer areas. Disturbance activities to flycatchers are considered only for occupied AEIs and only for impacts on core areas. Developed areas (see Part I, Section 2.3) that have ongoing baseline levels of activities and are not suitable habitat for Southwestern Willow Flycatchers have different restrictions than undeveloped core or buffer areas. Therefore, the location of the disturbance activity within the AEI, the occupancy status of the AEI, and the type of activity all affect whether or not the activity is allowable. AEIs for different species may overlap, and an activity must meet the guidelines of all applicable site plans to be allowable. Protective measures are described as management practices that should be followed when working in AEIs.

4.2 Definition and Role of Occupancy in AEI Management

Occupancy simply refers to whether or not an AEI is occupied during a species' period of sensitivity. For Southwestern Willow Flycatchers, LANS biologists are primarily concerned with protecting the birds from disturbance during the breeding season. Because individuals may colonize suitable habitat, the Southwestern Willow Flycatcher AEI is treated as though it is occupied from May 15 through September 15 or until surveys show an AEI to be unoccupied. Southwestern Willow Flycatcher surveys are conducted during May, June, and July. Because Southwestern Willow Flycatchers migrate south for the winter, the AEI is treated as unoccupied from September 16 to May 14.

The occupancy status of an AEI affects what activities are allowable in the AEI. Although activities causing habitat alterations are always restricted, disturbance activities are restricted only in occupied AEIs. The Activity Table (Table 2, Section 4.5.2) provides dates and levels of disturbance activities allowable in the occupied Southwestern Willow Flycatcher AEI under the guidelines of this site plan. The dates in Table 2 indicate the time period during which the activity is restricted. Contact a LANS biologist to find out the current occupancy status of an AEI (http://int.lanl.gov/environment/bio/controls/index.shtml).

4.3 Introduction to AEI Management Guidelines

Sections 4.4 and 4.5 provide the guidelines for habitat alterations and allowable activities in AEI core and buffer areas. The flowchart (see Figure 1) provides a quick reference that should be used to determine if a project or activity will affect an AEI and what sections of the site plan need to be consulted. The section on habitat alterations (Section 4.4) describes what and where habitat alterations are allowed under the guidelines of this site plan. The section and table on allowable activities (Section 4.5 and Table 2) describe what, when, and where disturbance activities are allowed in occupied AEIs under the guidelines of this site plan. If an activity does not meet the restrictions given in the guidelines, the activity must be individually reviewed for ESA compliance. This site plan only provides guidelines for the Southwestern Willow Flycatcher AEI. If an activity is desired in an area with overlapping AEIs, all applicable site plans must be consulted. Section 4.6 describes management practices that should be applied when working or considering work in an AEI. LANS biologists are available to help interpret site plans and answer questions (<u>http://int.lanl.gov/environment/bio/controls/index.shtml</u>).

4.4 Definition of and Restrictions on Habitat Alterations

4.4.1 Definition of Habitat Alterations

Habitat alteration includes any action that over the long term alters the soil structure, vegetative components necessary to the species, prey quality and quantity, water quality, hydrology, or noise or light levels in undeveloped areas of an AEI. Long term means the alteration lasts for more than one year. Habitat alteration includes any activity that removes vegetative components important to the Southwestern Willow Flycatcher (primarily trees and shrubs). An actual activity may take place outside of the AEI and will be considered habitat alteration if consequences of the activity have effects inside the AEI core.

The habitat components most important to flycatchers include vegetative structure, food quality and quantity, and disturbance levels, including noise and light. The thickets of certain trees and shrubs along wetlands are important because they provide roost sites and a suitable habitat for nesting and foraging.

4.4.2 Fuels Management Practices to Reduce Wildfire Risk

Thinning within undeveloped buffer areas may include trees of any size to achieve 7.6 m (25 ft) spacing between tree crowns. However, clear cutting is not allowed in undeveloped buffer areas. No fuels management practices are allowed in core areas. Habitat alterations including thinning are not restricted in developed areas.

4.4.3 Utility Corridors

Habitat alterations such as cutting down trees that threaten power lines are allowed within 8 m (26 ft) of either side of an existing utility line in all areas of an AEI (Trujillo and Racinez 1995). New utility lines and utility lines requiring clearance of a right-of-way greater than 16 m (52 ft) total must be individually reviewed for ESA compliance. Disturbance activities must follow the guidelines given in the Activities Table (Table 2, Section 4.5.2) for occupied AEIs.

4.4.4 Restrictions on Habitat Alterations

Habitat alterations other than the utility corridor maintenance described above are not allowed in undeveloped core areas under the guidelines of this site plan. Habitat alteration in buffers is limited. If a project or activity is planned that would alter habitat in an undeveloped core area, it must be individually evaluated for ESA compliance. Habitat alterations in a buffer area other than fuels management activities or utility corridor maintenance must be reported to a LANS biologist for tracking (http://int.lanl.gov/environment/bio/controls/index.shtml).

4.5 Definition of and Restrictions on Disturbance Activities

4.5.1 Definition of Disturbance Activities

LANS biologists considered five categories of activities that might cause disturbance in an AEI. Most of the categories were first identified in the document "Peregrine Falcon Habitat Management in the National Forests of New Mexico" prepared for the United States Forest Service (Johnson 1994). Other light production and other noise production were included to provide the most comprehensive list of activities possible, reducing the need for individual review of activities for ESA compliance. The categories of activities are people, vehicles, aircraft, other light production, and other noise production. The impact of explosives detonation on this species is not considered here because there are no explosives testing sites within 2 km (1.25 mi) of potential nesting habitat. Low, medium, and high levels of impact for these activities are considered here. The following categories of activities are restricted only in AEIs that are classified as occupied.

People—includes any entry of people into an AEI on foot.

- Low impact is the presence of three or fewer people per project and duration of one day or less during a breeding season.
- Medium impact is the exceedance of either the number of people or the duration criteria.
- High impact is the exceedance of both the number of people and the duration criteria.

Vehicles—includes the entry of any two-axle highway vehicle, all-terrain vehicle, or motorized machinery into an AEI by any route other than a paved road or an improved gravel road.

- Low impact is the presence of two or fewer vehicles per project and duration of one day or less during a breeding season.
- Medium impact is the exceedance of either the number of vehicles or the duration criteria.
- High impact is the exceedance of both the number of vehicles and the duration criteria.

Aircraft—includes the operation of any aircraft below an elevation of 600 m (2,000 ft) above the highest ground level in the local vicinity.

- Low impact is the presence of one single-engine airplane and duration of one day or less during a breeding season.
- Medium impact is the exceedance of either the number of aircraft or the duration criteria.

• High impact is the exceedance of both the number of aircraft and the duration criteria.

Any use of helicopters, jet airplanes, and propeller airplanes with two or more engines is classified as medium impact or above, depending on duration.

Other Light Production—includes any activity not previously listed that causes additional light to occur in an AEI core area (e.g., plans for construction of a new building at the edge of a developed area may call for lighting at night to facilitate nighttime work that impacts an undeveloped core area).

- Low impact is the increase of light intensity by up to 0.05 fc and a duration of one night or less per project per breeding season.
- Medium impact is the exceedance of either the intensity or duration criteria.
- High impact is the exceedance of both the intensity and duration criteria.

Measurements for increases in light are taken at the AEI core area boundary closest to the light source if the source is outside the core, and at 10 m (33 ft) from the source if the source is inside the core. Light measurements for developed areas are taken at the edge of the developed area if the developed area is within an AEI core, or at the closest core boundary, if the developed area is outside of an AEI core.

Other Noise Production—includes any activity not previously listed except for explosives detonation that causes additional noise to occur in an AEI. For example, operation of machinery causes noise.

- Low impact is increasing noise levels in an AEI core by 6 dB(A) or less for one day or less per project per breeding season.
- Medium impact is the exceedance of either the level or the duration criteria.
- High impact is the exceedance of both the level and the duration criteria.

Measurements for increases in noise are taken at the AEI core boundary closest to the noise source if the source is outside the core, and at 10 m (33 ft) from the source if the source is inside the core. Noise measurements for developed areas are taken at the edge of the developed area if the developed area is within an AEI core, or at the closest core boundary if the developed area is outside of an AEI core.

4.5.2 Activity Table

The dates shown in the Activity Table (Table 2) are the dates between which the activity in the row is restricted under the guidelines of this site plan. Disturbance activities are of concern only when Southwestern Willow Flycatchers occupy an AEI. The AEI is always considered occupied between May 15 and September 15, or until surveys show the AEI to be unoccupied. The Southwestern Willow Flycatcher AEI is always considered unoccupied between September 16 and May 14, when flycatchers have migrated for the winter. For occupancy status of an AEI after completion of surveys, contact a LANS biologist

(http://int.lanl.gov/environment/bio/controls/index.shtml).

	Levels of Impact	Core	Buffer
People			
	Low	No Restrictions	No Restrictions
	Medium	May 15 to August 15	No Restrictions
	High	May 15 to September 15	No Restrictions
Vehicles			
	Low	May 15 to September 15	No Restrictions
	Medium	May 15 to September 15	No Restrictions
	High	May 15 to September 15	No Restrictions
Aircraft			
	Low	No Restrictions	No Restrictions
	Medium	May 15 to August 15	May 15 to August 15
	High	May 15 to September 15	May 15 to August 15
Other Light/Noise Production			
	Low	May 15 to September 15	No Restrictions*
	Medium	May 15 to September 15	No Restrictions*
	High	May 15 to September 15	No Restrictions*

Table 2. Restrictions on Activities in Undeveloped OccupiedSouthwestern Willow Flycatcher AEI

* Noise or light production in the buffer is restricted if the activity would violate core area restriction on noise or light.

4.6 **Protective Measures**

This section provides a list of management practices to apply in the AEI.

- No wetland vegetation will be removed outside of developed areas.
- Employ appropriate erosion and runoff controls to reduce soil loss.
- Avoid unnecessary disturbance to vegetation (e.g., excessive parking areas or equipment storage areas, off-road travel, materials storage areas, crossing of streams or washes).
- Avoid removal of vegetation along drainage systems and stream channels.
- Avoid all vegetation removals not absolutely necessary.
- Appropriate erosion controls must be put in place and periodically checked throughout the life of any projects.
- Revegetate all exposed soils as soon as feasible after disturbance to minimize erosion.

5.0 Southwestern Willow Flycatcher AEI Description

5.1 Pajarito Canyon Southwestern Willow Flycatcher AEI

5.1.1 Allowable Habitat Alteration in the Buffer Area

Since the purpose of the buffer area is to help maintain the core area as suitable Southwestern Willow Flycatcher habitat, habitat alteration in the buffer area will be extremely limited. There are two areas in which restrictions on habitat alteration are relaxed.

- 1. The mesa top of Mesita del Buey. This mesa top can be developed as long as restrictions on impacts to the core area are met.
- 2. Pajarito Road within the AEI. Mowing of upland vegetation is allowed up to 5 m (15 ft) from Pajarito Road, or to the fence, if the fence is within 9 m (30 ft). Vegetation must cover the roadsides to prevent sediment runoff, so mowed plants should be at least 5 cm (2 in) high. LANS biologists encourage the growth of willow throughout the AEI—even the area along Pajarito Road—to enhance habitat. If, within this area, it is absolutely necessary to remove new willow growth (i.e., to improve visibility for human safety), LANS biologists recommend that only willows at or above the level of the roadway surface be mowed.

IV. AREA OF ENVIRONMENTAL INTEREST SITE PLAN FOR THE JEMEZ MOUNTAINS SALAMANDER

1.0 Species Description—Jemez Mountains Salamander

1.1 Status

The Jemez Mountains Salamander was listed in New Mexico as endangered under the Wildlife Conservation Act of New Mexico in 2006 (NMDGF 2006). In September 2012 the USFWS proposed the Jemez Mountains Salamander as endangered under the ESA (77 FR 56481) and the final listing as endangered was on September 10, 2013 (78 FR 55599).

1.2 General Biology

The Jemez Mountains Salamander is endemic to the Jemez Mountains of north-central New Mexico and is found in Los Alamos, Rio Arriba, and Sandoval counties (Stebbins and Riemer 1950). It is one of two endemic plethodontid salamanders that occur in New Mexico. It occurs predominantly at elevations between 2,130 to 3,430 m (6,988 to 11,254 ft) in mixed-conifer forest with greater than 50 percent canopy cover consisting mainly of Douglas fir (*Pseudotsuga menziesii* [Mirb.] Franco), blue spruce (*Picea pungens* Engelm.), Engelmann spruce (*Picea engelmannii* Parry ex Engelm.), white fir (*Abies concolor* [Gord. & Glend.] Lindl. ex Hildebr.), limber pine (*Pinus flexilis* James), ponderosa pine, and quaking aspen (*Populus tremuloides* Michx.). The ground surface in forest areas has (a) moderate to high volumes of large fallen trees and other woody debris, especially coniferous logs at least 25 cm (10 in) in diameter, particularly Douglas fir, which are in contact with the soil in varying stages of decay from freshly fallen to nearly fully decomposed; or (b) structural features, such as rocks, bark, and

moss mats that provide the species with food and cover. Underground habitat in forest or meadow areas contains interstitial spaces provided by (a) igneous rock with fractures or loose rocky soils, (b) rotted tree root channels, or (c) burrows of rodents or large invertebrates (Degenhardt et al. 1996; 78 FR 9876).

Plethodontid salamanders, which lack both lungs and gills, breathe through the mucous membranes in their mouth and throat and through their moist skin. The Jemez Mountains Salamander is completely terrestrial and does not use standing surface water for any life stage (77 FR 56481). Present in its habitat year-round, the Jemez Mountains Salamander spends most of its life underground, but can be found on the surface when conditions are warm and wet, approximately July through October. During this time, the Jemez Mountains Salamander can be found under rocks, bark, and moss mats, and inside and under logs (Ramotnik 1986, Everett 2003). The Jemez Mountains Salamander eats invertebrates, including ants, mites, and beetles, and is thought to lay its eggs underground (78 FR 9876).

1.3 Threats

Principal threats to habitat include historical fire exclusion and suppression and severe wildland fires; forest composition and structure conversions; post-fire rehabilitation; forest and fire management; roads, trails, and habitat fragmentation; recreation; and disease (77 FR 56482).

2.0 Impact of Human Activities

2.1 Introduction

Primary threats to the Jemez Mountains Salamander on LANL property are impacts to habitat quality or destruction of individual salamanders caused by LANL or Los Alamos County operations. Forested LANL property is also subject to impacts from severe wildland fire and wildfire suppression.

2.2 Impacts on Habitat Quality

2.2.1 Development

Property at LANL varies from remote isolated land to heavily developed and/or industrialized. Most of the large developed areas at LANL are found on mesa tops, generally in the northern and western portion of LANL. The areas of Jemez Mountains Salamander habitat currently most impacted by development occur in Los Alamos Canyon. There is a secondary paved road (West Road) in the bottom of the canyon that exits the canyon on the north-facing slope through Jemez Mountains Salamander habitat. The canyon bottom also contains a recreational ice rink operated by Los Alamos County on an inholding owned by Los Alamos County. Development that reduces the occurrence of primary constituent elements of Jemez Mountains Salamander in core habitat would likely have a negative impact on the species.

2.2.2 Pedestrians and Vehicles

Many canyon bottoms and mesa tops at LANL have dirt roads traversing them. Most of these roads are gated; however, many of these roads are accessible to LANL employees and the public on foot or by bike. Some areas, such as Los Alamos Canyon, are frequently used by hikers and dog owners on active and historic trails that traverse the canyon, through Jemez Mountains

Salamander habitat in places. Maintenance of roads and trails in the habitat may have a negative impact on the species.

2.2.3 Severe Wildland Fire and Wildfire Suppression

Stand-replacing wildfires significantly change forest composition and structure, and reduce canopy cover. Even ground wildfires may reduce the volume of fallen logs and large woody debris. Large areas of historic Jemez Mountains Salamander habitat have been impacted by stand-replacing wildfires associated with current forest stocking conditions, drought, and high temperatures (77 FR 56482). Forested habitats on LANL property are also subject to severe wildland fires. To mitigate wildfire risks, some areas of LANL have been treated for fuels reduction and creation of fuel breaks both pre-emptively and during active wildfire suppression. Both wildfires and wildfire suppression activities can negatively impact the primary constituent elements of Jemez Mountains Salamander core habitat.

2.3 Impacts on Individual Salamanders

2.3.1 Disease

The amphibian pathogenic fungus *Batrachochytrium dendrobatidis* (Bd) was found in a wildcaught Jemez Mountains Salamander in 2003 (Cummer et al. 2005) on the east side of the species' range and again in another Jemez Mountains Salamander in 2010 on the west side of the species' range (77 FR 56482). Bd causes the disease chytridiomycosis, whereby the Bd fungus attacks keratin in amphibians. In adult amphibians, keratin primarily occurs in the skin. The symptoms of chytridiomycosis can include sloughing of skin, lethargy, morbidity, and death. Chytridiomycosis has been linked with worldwide amphibian declines, die-offs, and extinctions, possibly in association with climate change (Pounds et al. 2006). Chytridiomycosis may be a threat to the Jemez Mountains Salamander because this disease is a threat to many other species of amphibians and the pathogen has been detected in the Jemez Mountains Salamander (77 FR 56482).

As part of a cooperative study with the New Mexico Department of Game and Fish between 2007 and 2013, various amphibian species, including the canyon tree frog (*Hyla arenicolor*), western chorus frog (*Pseudacris triseriata*), Woodhouse's toad (*Anaxyrus woodhousii*), tiger salamander (*Ambystoma tigrinum*), and Jemez Mountains Salamander were tested for Bd infection at LANL. To date, all sampling has been negative for Bd infection (Fresquez et al. 2013).

2.3.2 Destruction of Individual Salamanders

During periods of the year when Jemez Mountains Salamanders are on the soil surface, when conditions are warm and wet (generally July to October), they are vulnerable to injury and mortality from soil-disturbing activities, including operation of heavy equipment in core habitat. They also are at risk to be found and collected by people.

3.0 AEI General Description for the Jemez Mountains Salamander

The AEI consists of two areas—a core area and a buffer area. The core habitat is defined as suitable habitat where the Jemez Mountains Salamander occurs or may occur at LANL. The core habitat consists of sections of north-facing slope that contain the required micro-habitat to

support Jemez Mountains Salamander. The buffer area is 100 m (328 ft) wide extending outward from the edge of the core area.

3.1 Method for Identifying a Jemez Mountains Salamander AEI

The first step in identifying potential Jemez Mountains Salamander AEIs at LANL was to use a GIS to model habitat. Early modeling efforts by Hathcock (2008) identified areas of potential habitat and that model was further refined. The following parameters were modeled in the GIS:

- Elevation: 2,150 m (7,000 ft) and above
- Slope: Greater than 20 degrees
- Aspect: north-facing +/- 20 degrees
- Land cover: Mixed conifer
- Land use: Undeveloped
- Modeled habitat is only selected if it is greater than five contiguous 30 × 30 m (98 × 98 ft) pixels in size

Once this habitat layer was developed, a second layer was modeled that examined the level of shade in the habitat, also known as an illumination index. Since the Jemez Mountains Salamander needs cool moist conditions, an illumination index model would further highlight areas where this habitat type may occur or further reinforce the areas selected by the GIS modeling. The illumination index describes the amount and extent of solar radiation reaching the Earth's surface at a given point. This takes into account the topography that may cast shadows. The illumination model was developed using the 5 m (16 ft) resolution digital elevation model hillshade and using the Surface toolbox in ArcToolbox (Environmental Science Research Institute, Redlands, California) using the highest height of the sun on June 21 at 1:00 pm, altitude of 74.4 and Azimuth of 178.4, when the sun would be at its maximum height. These procedures were based on work done by Reilly et al. (2009).

Once this modeling was complete, LANS biologists performed field validation to verify the suitability of the modeled habitat. The goal was to verify that mixed conifer was still the dominant cover class in the selected area. The GIS analysis used data from a landcover map created by McKown et al. (2003). There have been changes in habitat from fire and extreme drought effects since this landcover map was published. Since LANL is on the extreme edge of Jemez Mountains Salamander lower elevational range, a key component in this part of its range is soil moisture content. During field validation, evidence of a moist mixed conifer habitat versus a dry mixed conifer habitat was noted. One of the key indicators used to delimit areas of moist versus dry mixed conifer during the field validation was the presence of white fir (Evans et al. 2011) combined with a high canopy cover.

Field validation of the model occurred in May 2013, or decisions were based on earlier field visits to the sites from other projects. Each field validation consisted of LANS biologists walking down all of the modeled habitat polygons to look for the presence of indictor features. If a polygon of modeled habitat contained white fir, indicating a moist wet conifer type habitat, a high canopy closure, and other signs of high habitat quality such as dead logs, moss, or other

areas that could be used as cover by the Jemez Mountains Salamander, then the polygon was marked for retention in the final core habitat. Polygons that did not contain the necessary habitat requirements were omitted.

After the field validation was complete, the final core habitat boundaries were hand digitized using ArcGIS (Environmental Science Research Institute, Redlands, California) by LANS biologists in and around the validated modeled polygon and areas between polygons, if appropriate. The final identified core habitat at LANL occurs on the north-facing slopes of canyons. Toward the rim of the canyon, the core boundaries end where the mixed conifer ends. In the canyon bottoms, the core boundaries end where the mixed conifer ends. A buffer habitat was extended around the core to a distance of 100 m (328 ft) outward. The LANL Fenton Hill satellite facility in the Jemez Mountains off of New Mexico Highway 126 is on land leased to DOE by the Santa Fe National Forest. The entire footprint is considered to be developed core habitat for the Jemez Mountains Salamander, since proposed critical habitat is adjacent to the facility.

3.2 Location and Number of Jemez Mountains Salamander AEIs

The identified Jemez Mountains Salamander core habitats were grouped by canyon system into AEIs, which contain contiguous and noncontiguous habitat areas. The largest contiguous section of habitat at LANL is in Los Alamos Canyon. There are two noncontiguous areas of habitat in Two-mile Canyon, four in Pajarito Canyon, one contiguous area in Cañon de Valle, and the entire Fenton Hill footprint.

4.0 AEI Management

4.1 Overview

This AEI management section provides guidelines for LANL operations to reduce or eliminate the threats to the Jemez Mountains Salamander from habitat alterations that reduce habitat quality. Habitat alterations are considered for all AEIs and for both core and buffer areas. Developed areas that have ongoing baseline levels of activities and are not suitable habitat for Jemez Mountains Salamander have different restrictions than undeveloped core or buffer areas. AEIs for different species may overlap, and an activity must meet the guidelines of all applicable site plans to be allowable. Protective measures are described as management practices that should be followed when working in AEIs.

4.2 Definition and Role of Occupancy in AEI Management

Occupancy simply refers to whether or not an AEI is occupied by the Jemez Mountains Salamander. The Los Alamos Canyon AEI is known to be occupied based on past surveys. Surveys for the Jemez Mountains Salamander are known to have a very low detection rate for occupied areas, so at LANL, all AEIs are assumed to be occupied at all times. If needed, sitespecific surveys will be conducted by federally permitted LANS biologists.

4.3 Definition and Role of Developed Areas in AEI Management

Developed areas include all building structures, paved roads, improved gravel roads, and paved and unpaved parking lots. The majority of Jemez Mountains Salamander core habitat is in undeveloped areas, except for the satellite facility at Fenton Hill and a small amount of habitat in Los Alamos Canyon where West Road crosses the habitat. Generally, developed areas will not have restrictions; however, some of the undeveloped sections within the footprint of Fenton Hill may have restrictions because they may contain Jemez Mountains Salamanders when they move to the surface between July and October. Any project that occurs within developed core habitat will be evaluated by LANS biologists for ESA compliance.

4.4 General Description of Core and Buffer Areas and Allowable Area Development

The purpose of buffer areas is to protect core areas from habitat degradation. The current levels of development in buffer and core areas represent baseline conditions for this site plan. No further development is allowed in the core area under the guidelines of this site plan. Any development in a buffer area will be reviewed by LANS biologists to ensure that there are no impacts to the core habitat.

4.5 Emergency Actions

If safety and/or property are immediately threatened by something occurring within an AEI (for example, wildfire, water line breakage, etc.) please contact a LANS biologist (505-665-3366) as soon as possible. If the emergency occurs outside of regular business hours, contact the Emergency Management Office (505-667-6211). This office will then communicate with the appropriate LANS personnel.

4.6 Introduction to AEI Management Guidelines

Section 4.7 provides the guidelines for habitat alterations and allowable activities in AEI core and buffer areas. It describes what and where habitat alterations are allowed under the guidelines of this site plan. If an activity does not meet the restrictions given in the guidelines, the activity must be individually reviewed for ESA compliance. This site plan only provides guidelines for the Jemez Mountains Salamander AEIs. If an activity is desired in an area with overlapping AEIs, all applicable site plans must be consulted. AEI maps show the location of all AEIs in an area. LANS biologists are available to help interpret site plans and answer questions (http://int.lanl.gov/environment/bio/controls/index.shtml).

4.7 Definition of and Restrictions on Habitat Alterations

4.7.1 Definition of Habitat Alterations

Habitat alteration includes any action that alters the soil structure, vegetative components necessary to the species, water quality, or hydrology in undeveloped areas of an AEI. An actual activity may take place outside of the AEI and will be considered habitat alteration if consequences of the activity have effects inside the AEI core. Habitat alterations would also include soil pits for soil samples deeper than 15 cm (6 in) using either hand or mechanized augers. Any activity that might disturb the soil will need to be reviewed by LANS biologists.

The habitat components most important to the Jemez Mountains Salamander include soil structure and vegetative structure. The forest structure within an area designated as a Jemez Mountains Salamander AEI is important because it provides the necessary moist, cool microclimate.

4.7.2 Fuels Management Practices to Reduce Wildfire Risk

One of the primary threats to the Jemez Mountains Salamander is wildfire (77 FR 56482), but they also require habitat with a high canopy cover, which makes fuels reduction challenging. Within undeveloped core areas, thinning trees to a level of 80 percent canopy cover or higher is approved. Trees may not be thinned below 80 percent canopy cover without further ESA review by LANS biologists. Large logs on the ground should be left in place and not chipped. Understory thinning that does not reduce total canopy cover below 80 percent is permitted. Large trees that are felled should be left as large logs on the ground. Smaller trees and understory shrubs that may be thinned should be dispersed and left on-site to aid in soil moisture retention. Thinning activities should not occur during the rainy season between July to October (or when freezing temperatures begin, whichever comes first) when the Jemez Mountains Salamander is found on the surface.

In buffer areas, thinning of trees can occur to the current LANL-approved prescription level (LAAO 2000). LANS biologists are available to provide guidance and mark trees for thinning (http://int.lanl.gov/environment/bio/controls/index.shtml).

4.7.3 Utility Corridors

Habitat alterations such as cutting down trees that threaten power lines are allowed within 8 m (26 ft) of either side of an existing electrical utility line at LANL under existing guidelines and engineering controls (Hathcock 2013). This level is approved in all areas of an AEI. New utility lines and utility lines requiring clearance of a right-of-way greater than 16 m (52 ft) total in core habitat must be individually reviewed for ESA compliance.

4.7.4 Restrictions on Habitat Alterations

Habitat alterations other than the fuels management practices and utility corridor maintenance described above are not allowed in undeveloped core areas under the guidelines of this site plan. If a project or activity is planned that would alter habitat in an undeveloped core area, it must be individually evaluated for ESA compliance. Habitat alterations in buffer areas must be reviewed by LANS biologists to ensure that there are no impacts to core habitat.

REFERENCES CITED

- Allison, L.J., C.E. Paradzick, J.W. Rourke, and T.D. McCarthey. 2003. A characterization of vegetation in nesting and non-nesting plots for southwestern willow flycatchers in central Arizona. In *Ecology and Conservation of the Willow Flycatcher* (eds) M.K. Sogge, B.E. Kus, S.J. Sferra & M.J. Whitfield. *Studies In Avian Biology*: Cooper Ornithological Society.
- Brown, B.T., G.S. Mills, C. Powels, W.A. Russell, G.D. Therres, and J.J. Pottie. 1999. The influence of weapons-testing noise on bald eagle behavior. *Journal of Raptor Research* 33:227–32.
- Brown, B.T. and L.E. Stevens. 1997. Winter bald eagle distribution is inversely correlated with human activity along the Colorado River, Arizona. *Journal of Raptor Research* 31:7–10.
- Burns, M.J. 1995. White Rock noise measurements during PHERMEX tests, 11 March 1995. Los Alamos National Laboratory Memorandum DX-DO:DARHT-95-31 and 35.
- Cain, B.W. 1988. The impact of environmental contaminants on Southwestern USA raptors. *Proceedings of the Southwest Raptor Management Symposium and Workshop* (ed) by R.L. Glinski, B.G. Pendleton, M.B. Moss, M.N. LeFranc Jr., B.A. Millsap & S.W. Hoffman, 348–54. Tucson, AZ, USA, May 21–24, 1986: National Wildlife Federation, Washington, D.C., USA.
- Cummer, M. R., D. E. Green, and E. M. O'Neill. 2005. Aquatic chytrid pathogen detected in terrestrial plethodontid salamander. *Herpetological Review* 36(3):248–249.
- Degenhardt, W.G., C.W. Painter, and A.H. Price. 1996. Amphibians and Reptiles of New Mexico. University of New Mexico Press, Albuquerque, New Mexico.
- Delaney, D.K., T.G. Grubb, P. Beier, L.L. Pater, and M.H. Reiser. 1999. Effects of helicopter noise on Mexican spotted owls. *Journal of Wildlife Management* 63:60–76.
- Department of Energy (DOE). 1996. Final Environmental Impact Statement for the Dual-Axis Radiographic Hydrodynamic Test Facility Mitigation Action Plan. DOE/EIS-0228.
- Durst, S.L., M.K. Sogge, H.C. English, S.O. Williams, B.E. Kus, and S.J. Sferra. 2006. Southwestern Willow Flycatcher breeding site and territory summary – 2005. USGS Southwest Biological Science Center report to the U.S. Bureau of Reclamation.
- Durst, S.L., T.C. Theimer, E.H. Paxton, and M.K. Sogge. 2008. Age, habitat, and yearly variation in the diet of a generalist insectivore, the southwestern willow flycatcher. *Condor* 110:514–25.
- Environmental Protection Agency (EPA). 2010. National Pollutant Discharge Elimination System Storm Water Individual Permit number NM0030759.

- Evans, A.M., R.G. Everett, S.L. Stephens, and J.A. Youtz. 2011. Comprehensive Fuels Treatment Practices Guide for Mixed Conifer Forests: California, Central and Southern Rockies, and the Southwest. *Forest Guild* 106pp.
- Everett, E. 2003. Habitat Characterization and Environmental Influences of the Jemez Mountains Salamander (*Plethodon neomexicanus*). M.S. Thesis, New Mexico State University, Las Cruces, New Mexico, 55pp.
- Finch, D.M. and J.F. Kelly. 1999. Status and migration of the southwestern willow flycatcher in New Mexico. In *Rio Grande Ecosystems: Linking Land, Water, and People: Toward a Sustainable Future for the Middle Rio Grande Basin* (ed.) D.M. Finch, J.C. Whitney, J.F. Kelly & S.R. Loftin, 197–203, Albuquerque, New Mexico.
- Fresquez, P.R., C. Hathcock, D. Keller, and J. Fair. 2013. "Foodstuffs and Biota Monitoring," in the 2012 Annual Site Environmental Report 2012. Los Alamos National Laboratory report LA-UR-13-27065.
- Gallegos, A., G. Gonzales, K. Bennett, and L. Pratt. 1997. "Preliminary Risk Assessment of the Mexican Spotted Owl under a Spatially-weighted Foraging Regime at the Los Alamos National Laboratory." Los Alamos National Laboratory report LA-13259-MS.
- Ganey, J.L. and R.P. Balda. 1994. Habitat selection by Mexican spotted owls in northern Arizona. *Auk* 111:162–69.
- Gonzales, G.J., A.F. Gallegos, K.D. Bennett, M.A. Mullen, and T.S. Foxx. 1998. "Preliminary Risk Assessment of the Southwestern Willow Flycatcher (*Empidonax traillii extimus*) at the Los Alamos National Laboratory." Los Alamos National Laboratory report LA-13508-MS.
- Gonzales, G., R. Ryti, P. Newell, A. Gallegos, and S. Sherwood. 2004. "Modeled Ecological Risk to the Deer Mouse, Mexican Spotted Owl, and Western Bluebird at the Los Alamos National Laboratory using ECORSK.7." Los Alamos National Laboratory report LA-14118.
- Gonzales, G., P. Gallegos, A. Gallegos, and K. Bennett. 2009. "Site-wide Application of ECORSK.9 at the Los Alamos National Laboratory." Los Alamos National Laboratory report LA-UR-09-02833.
- Grubb, T.G. and R.M. King. 1991. Assessing human disturbance of breeding bald eagles with classification tree models. *Journal of Wildlife Management* 55:500–11.
- Grubb, T.G. and W.W. Bowerman. 1997. Variations in breeding bald eagle responses to jets, light planes, and helicopters. *Journal of Raptor Research* 31:213–22.
- Hansen, L.A. 2004. Sigma Mesa Construction Debris Recycling Project. Los Alamos National Laboratory Memorandum RRES/Ecol-04-0049.

- Hansen, L.A. 2005. "A Biological Assessment of the Potential Effects of the Operation of an Asphalt Batch Plant and a Rock Crusher at Sigma Mesa on Federally Listed Threatened and Endangered Species." Los Alamos National Laboratory report LA-CP-05-0293.
- Hansen, L.A. 2009. "Sound studies of the Biosafety Level 3 (BSL-3) Laboratory at TA-3, Building 1076." Los Alamos National Laboratory report LA-UR-09-05482.
- Hathcock, C. D. 2013. Email from C. D. Hathcock to S. Martinez on June 20, 2013, Los Alamos National Laboratory communication.
- Hathcock, C.D. and T.K. Haarmann. 2008. Development of a predictive model for habitat of the Mexican spotted owl in Northern New Mexico. *Southwestern Naturalist* 53:34–38.
- Hathcock, C.D., L.A. Hansen, and D.C. Keller. 2010. Occupancy of habitats by Mexican spotted owl in relation to explosives noise and recreational access at Los Alamos National Laboratory. *Western Birds* 41:102–06.
- Hatten, J.R. and C.E. Paradzick. 2003. A multiscaled model of southwestern willow flycatcher breeding habitat. *Journal of Wildlife Management* 67:774–88.
- Holthuijzen, A.M.A., W.G. Eastland, A.R. Ansell, M.N. Kochert, R.D. Williams, and L.S. Young. 1990. Effects of blasting on behavior and productivity of nesting prairie falcons. *Wildlife Society Bulletin* 18:270–81.
- Huchton, K., S.W. Koch, and R.J. Robinson. 1997. "An analysis of background noise in selected canyons of Los Alamos County." Los Alamos National Laboratory report LA-13372-MS.
- Johnson, J.A. and T.H. Johnson. 1985. "Timber type model of spotted owl habitat in northern New Mexico," New Mexico Department of Game and Fish report, Santa Fe, New Mexico.
- Johnson, T.H. 1994. "Peregrine falcon habitat management in the national forests of New Mexico." USDA Forest Service unpublished report.
- Johnson, T.H. 1998. "Topographic-Landsat model of suitable spotted owl habitat around Los Alamos National Laboratory." Los Alamos National Laboratory unpublished report.
- Keller, D.C. 2015. "Biological Assessment for the Addition of the Western Distinct Population Segment of the Yellow-billed Cuckoo and the New Mexico Meadow Jumping Mouse to the Los Alamos National Laboratory Habitat Management Plan." Los Alamos National Laboratory report LA-UR 15-23445.
- Keller, D.C. and D. Risberg. 1995. "Biological and floodplain/wetland assessment for the Dual-Axis Radiographic Hydrodynamics Test Facility (DARHT)." Los Alamos National Laboratory report LA-UR-95-647.

- Keller, D.C. and T.S. Foxx. 1997. "Biological assessment for threatened and endangered species at the DP Road Tract land transfer." Los Alamos National Laboratory unpublished report.
- Knight, J.L. and S.S. Vrooman. 1999. "A study of construction machinery noise levels at Los Alamos National Laboratory." Los Alamos National Laboratory report LA-UR-99-5740.
- Los Alamos Area Office (Department of Energy) (LAAO). 2000. "Environmental Assessment for the Wildfire Hazard Reduction and Forest Health Improvement Program at Los Alamos National Laboratory, Los Alamos, New Mexico." DOE-EA-1329.
- Los Alamos National Laboratory (LANL). 2016. "Environmental Protection. Los Alamos National Laboratory Program Description 400, Revision 2."
- McKown, B., S.W. Koch, R.G. Balice, and P. Neville. 2003. "Land Cover Classification Map for the Eastern Jemez Region." Los Alamos National Laboratory report LA-14029.
- New Mexico Department of Game and Fish (NMDGF), April 2006. Threatened and Endangered Species of New Mexico—2006 Draft Biennial Review and Recommendations. Authority: Wildlife Conservation Act (NMSA 17-2-37+B1 through 17-2-46, 1978).
- Paakkonen, R. 1991. Low-frequency noise impulses from explosions. *Journal of Low Frequency Noise & Vibration* 10:78–82.
- Pounds, J.A., M.R. Bustamante, L.A. Coloma, J.A. Consuegra, M.P.L. Fogden, P.N.Foter, E. La Marca, K.L. Masters, A. Merino-Viteri, R. Puschendorf, S.R. Ron, G.A. Sanchez-Azofeifa, C.J. Still, and B.E. Yound. 2006. Widespread amphibian extinctions from epidemic disease driven by global warming. *Nature* 439(7073):161-167.
- Ramotnik, C.A. 1986. "Status Report: *Plethodon neomexicanus* Jemez Mountains Salamander." U.S. Fish and Wildlife Service Report.
- Reilly, E.C., D. Clayton, R.S. Nauman, D.H. Olson, H.H. Welsh Jr, B. Devlin. 2009. Spatial Model of Optimal Habitat for the Siskiyou Mountains Salamander (*Plethodon stormi*) North of the Siskyou Crest. Chapter 2. In: Olson, D.H., D. Clayton, R.S. Nauman, and H.H. Welsh Jr (Editors). 2009. Conservation of the Siskiyou Mountains Salamander (*Plethodon stormi*). Northwest Fauna 6:1-73.
- Stebbins, R.C., and W.J. Riemer. 1950. A New Species of Plethodontid Salamander from the Jemez Mountains of New Mexico. *Copeia* 1950(2):73–80.
- Steidl, R.J. and R.G. Anthony. 2000. Experimental effects of human activity on breeding bald eagles. *Ecological Applications* 10:258–68.
- Swarthout, E.C.H. and R.J. Steidl. 2001. Flush responses of Mexican spotted owls to recreationists. *Journal of Wildlife Management* 65:312–17.

- Swarthout, E.C.H. and R.J. Steidl. 2003. Experimental effects of hiking on breeding Mexican spotted owls. *Conservation Biology* 17:307–15.
- Trujillo, C.T. and E. Racinez. 1995. Meeting notes on the 13.8-kV transmission line tree trimming. Los Alamos National Laboratory Memorandum FSS-8-95-114.
- U.S. Fish and Wildlife Service (USFWS). 1995. "Recovery plan for the Mexican spotted owl." Albuquerque, New Mexico.
- U.S. Fish and Wildlife Service (USFWS). 2002. "Southwestern willow flycatcher recovery plan." Albuquerque, New Mexico.
- U.S. Fish and Wildlife Service (USFWS). 2012. "Recovery plan for the Mexican Spotted Owl, First Revision." Albuquerque, New Mexico.
- Vigil, E.A. 1995. Noise measurements at State Road 4 and Bandelier turn-off at State Road 4 during PHERMEX test on March 11, 1995. Los Alamos National Laboratory Memorandum ESH-5:95-11825.
- Vrooman, S.S., S.W. Koch, and J.L. Knight. 2000. "Temporal and spatial variation in background noise levels at Los Alamos National Laboratory." Los Alamos National Laboratory report LA-13684-MS.
- Wiesenborn, W.D. and S.L. Heydon. 2007. Diets of breeding southwestern willow flycatchers in different habitats. *Wilson Journal of Ornithology* 119:547–57.
- Willey, D.W. 2013. Diet of Mexican Spotted Owls in Utah and Arizona. *The Wilson Journal of* Ornithology 125(4):775-781.
- Yong, W. and D.M. Finch. 1997. Migration of the willow flycatcher along the middle Rio Grande. *Wilson Bulletin* 109:253–68.

APPENDIX

Species	Relative Abundance
Neotoma spp.	26.22
Peromyscus spp.	10.22
Microtus spp.	4.44
Gophers	4.89
Bats	5.78
Chipmunks	0.89
Rabbits	12.89
Shrews	1.33
Small Mammal	1.33
Medium Mammal	1.78
Medium Bird	8.00
Small Bird	4.89
Nocturnal Birds	0.89
Reptiles	4.89
Arthropods	11.56

Table A-1.The Percentage of each Food Type Found in Mexican Spotted Owl
Food Remains at LANL

		Distance from Source				
	Source (street light)	5 m	10 m	15 m	20 m	
ftc	3.70	2.28	1.20	0.62	0.32	




Figure A-1. Most recent map of all AEIs at LANL

ATTACHMENT 14: MSGP IPAC TRUST RESOURCES REPORT

NOTE: The Permit requires this information. However, LANL EPC-ES has completed consultation with U.S. Fish and Wildlife Service. Letters of Consultation are contained in the NOI (see Attachment 1). Refer to Attachment 13 for the species habitat management plan.

IPaC Information for Planning and Consultation U.S. Fish & Wildlife Service

IPaC resource list

This report is an automatically generated list of species and other resources such as critical habitat (collectively referred to as *trust resources*) under the U.S. Fish and Wildlife Service's (USFWS) jurisdiction that are known or expected to be on or near the project area referenced below. The list may also include trust resources that occur outside of the project area, but that could potentially be directly or indirectly affected by activities in the project area. However, determining the likelihood and extent of effects a project may have on trust resources typically requires gathering additional site-specific (e.g., vegetation/species surveys) and project-specific (e.g., magnitude and timing of proposed activities) information.

Below is a summary of the project information you provided and contact information for the USFWS office(s) with jurisdiction in the defined project area. Please read the introduction to each section that follows (Endangered Species, Migratory Birds, USFWS Facilities, and NWI Wetlands) for additional information applicable to the trust resources addressed in that section.

Location

Los Alamos, Sandoval, and Santa Fe counties, New Mexico



Local office

New Mexico Ecological Services Field Office

६ (505) 346-2525 **(505) 346-2542**

2105 Osuna Road Ne Albuquerque, NM 87113-1001

<u>http://www.fws.gov/southwest/es/NewMexico/</u> <u>http://www.fws.gov/southwest/es/ES_Lists_Main2.html</u>

NOTFORCONSULTATION

Endangered species

This resource list is for informational purposes only and does not constitute an analysis of project level impacts.

The primary information used to generate this list is the known or expected range of each species. Additional areas of influence (AOI) for species are also considered. An AOI includes areas outside of the species range if the species could be indirectly affected by activities in that area (e.g., placing a dam upstream of a fish population even if that fish does not occur at the dam site, may indirectly impact the species by reducing or eliminating water flow downstream). Because species can move, and site conditions can change, the species on this list are not guaranteed to be found on or near the project area. To fully determine any potential effects to species, additional site-specific and project-specific information is often required.

Section 7 of the Endangered Species Act **requires** Federal agencies to "request of the Secretary information whether any species which is listed or proposed to be listed may be present in the area of such proposed action" for any project that is conducted, permitted, funded, or licensed by any Federal agency. A letter from the local office and a species list which fulfills this requirement can **only** be obtained by requesting an official species list from either the Regulatory Review section in IPaC (see directions below) or from the local field office directly.

For project evaluations that require USFWS concurrence/review, please return to the IPaC website and request an official species list by doing the following:

- 1. Draw the project location and click CONTINUE.
- 2. Click DEFINE PROJECT.
- 3. Log in (if directed to do so).
- 4. Provide a name and description for your project.
- 5. Click REQUEST SPECIES LIST.

Listed species¹ and their critical habitats are managed by the <u>Ecological Services Program</u> of the U.S. Fish and Wildlife Service (USFWS) and the fisheries division of the National Oceanic and Atmospheric Administration (NOAA Fisheries²).

Species and critical habitats under the sole responsibility of NOAA Fisheries are **not** shown on this list. Please contact <u>NOAA Fisheries</u> for <u>species under their jurisdiction</u>.

- Species listed under the <u>Endangered Species Act</u> are threatened or endangered; IPaC also shows species that are candidates, or proposed, for listing. See the <u>listing status</u> <u>page</u> for more information. IPaC only shows species that are regulated by USFWS (see FAQ).
- 2. NOAA Fisheries, also known as the National Marine Fisheries Service (NMFS), is an

office of the National Oceanic and Atmospheric Administration within the Department of Commerce.

The following species are potentially affected by activities in this location:

Mammals

NAME	STATUS
New Mexico Meadow Jumping Mouse Zapus hudsonius luteus Wherever found There is final critical habitat for this species. The location of the critical habitat is not available. https://ecos.fws.gov/ecp/species/7965	Endangered
Birds	STATUS
Mexican Spotted Owl Strix occidentalis lucida Wherever found There is final critical habitat for this species. Your location overlaps the critical habitat. https://ecos.fws.gov/ecp/species/8196	Threatened
Southwestern Willow Flycatcher Empidonax traillii extimus Wherever found There is final critical habitat for this species. The location of the critical habitat is not available. https://ecos.fws.gov/ecp/species/6749	Endangered
Yellow-billed Cuckoo Coccyzus americanus There is proposed critical habitat for this species. The location of the critical habitat is not available. https://ecos.fws.gov/ecp/species/3911	Threatened
Amphibians	
NAME	STATUS

Endangered

Jemez Mountains Salamander Plethodon neomexicanus Wherever found There is final critical habitat for this species. The location of the critical habitat is not available. <u>https://ecos.fws.gov/ecp/species/4095</u>

Fishes

NAME	STATUS
Rio Grande Silvery Minnow Hybognathus amarus There is final critical habitat for this species. The location of the critical habitat is not available. https://ecos.fws.gov/ecp/species/1391	Endangered

Critical habitats

Potential effects to critical habitat(s) in this location must be analyzed along with the endangered species themselves.

This location overlaps the critical habitat for the following species:

NAME

Mexican Spotted Owl Strix occidentalis lucida https://ecos.fws.gov/ecp/species/8196#crithab Final

TYPE

Migratory birds

Certain birds are protected under the Migratory Bird Treaty Act^1 and the Bald and Golden Eagle Protection Act^2 .

Any person or organization who plans or conducts activities that may result in impacts to migratory birds, eagles, and their habitats should follow appropriate regulations and consider implementing appropriate conservation measures, as described <u>below</u>.

- 1. The Migratory Birds Treaty Act of 1918.
- 2. The <u>Bald and Golden Eagle Protection Act</u> of 1940.

Additional information can be found using the following links:

• Birds of Conservation Concern http://www.fws.gov/birds/management/managed-

<u>species/</u>

birds-of-conservation-concern.php

- Measures for avoiding and minimizing impacts to birds <u>http://www.fws.gov/birds</u> /management/project-assessment-tools-and-guidance/ conservation-measures.php
- Nationwide conservation measures for birds <u>http://www.fws.gov/migratorybirds</u> /pdf/management/nationwidestandardconservationmeasures.pdf

The birds listed below are birds of particular concern either because they occur on the USFWS Birds of Conservation Concern (BCC) list or warrant special attention in your project location. To learn more about the levels of concern for birds on your list and how this list is generated, see the FAQ below. This is not a list of every bird you may find in this location, nor a guarantee that every bird on this list will be found in your project area. To see exact locations of where birders and the general public have sighted birds in and around your project area, visit the <u>E-bird data mapping tool</u> (Tip: enter your location, desired date range and a species on your list). For projects that occur off the Atlantic Coast, additional maps and models detailing the relative occurrence and abundance of bird species on your list are available. Links to additional information about Atlantic Coast birds, and other important information about your migratory bird list, including how to properly interpret and use your migratory bird report, can be found <u>below</u>.

For guidance on when to schedule activities or implement avoidance and minimization measures to reduce impacts to migratory birds on your list, click on the PROBABILITY OF PRESENCE SUMMARY at the top of your list to see when these birds are most likely to be present and breeding in your project area.

NAME

BREEDING SEASON (IF A BREEDING SEASON IS INDICATED FOR A BIRD ON YOUR LIST, THE BIRD MAY BREED IN YOUR PROJECT AREA SOMETIME WITHIN THE TIMEFRAME SPECIFIED, WHICH IS A VERY LIBERAL ESTIMATE OF THE DATES INSIDE WHICH THE BIRD BREEDS ACROSS ITS ENTIRE RANGE. "BREEDS ELSEWHERE" INDICATES THAT THE BIRD DOES NOT LIKELY BREED IN YOUR PROJECT AREA.) Bald Eagle Haliaeetus leucocephalus Breeds Dec 1 to Aug 31 This is not a Bird of Conservation Concern (BCC) in this area, but warrants attention because of the Eagle Act or for potential susceptibilities in offshore areas from certain types of development or activities. https://ecos.fws.gov/ecp/species/1626 Black-chinned Sparrow Spizella atrogularis Breeds Apr 15 to Jul 31 This is a Bird of Conservation Concern (BCC) throughout its range in the continental USA and Alaska. https://ecos.fws.gov/ecp/species/9447 Breeds May 15 to Aug 10 Brewer's Sparrow Spizella breweri This is a Bird of Conservation Concern (BCC) only in particular Bird Conservation Regions (BCRs) in the continental USA https://ecos.fws.gov/ecp/species/9291 Golden Eagle Aquila chrysaetos Breeds Jan 1 to Aug 31 This is a Bird of Conservation Concern (BCC) only in particular Bird Conservation Regions (BCRs) in the continental USA https://ecos.fws.gov/ecp/species/1680 Grace's Warbler Dendroica graciae Breeds May 20 to Jul 20 This is a Bird of Conservation Concern (BCC) only in particular Bird Conservation Regions (BCRs) in the continental USA Gray Vireo Vireo vicinior Breeds May 10 to Aug 20 This is a Bird of Conservation Concern (BCC) throughout its range in the continental USA and Alaska. https://ecos.fws.gov/ecp/species/8680 Breeds elsewhere Lesser Yellowlegs Tringa flavipes This is a Bird of Conservation Concern (BCC) throughout its range in the continental USA and Alaska. https://ecos.fws.gov/ecp/species/9679 Lewis's Woodpecker Melanerpes lewis Breeds Apr 20 to Sep 30 This is a Bird of Conservation Concern (BCC) throughout its range in the continental USA and Alaska. https://ecos.fws.gov/ecp/species/9408

Long-billed Curlew Numenius americanus Breeds Apr 1 to Jul 31 This is a Bird of Conservation Concern (BCC) throughout its range in the continental USA and Alaska. https://ecos.fws.gov/ecp/species/5511 Long-eared Owl asio otus Breeds Mar 1 to Jul 15 This is a Bird of Conservation Concern (BCC) throughout its range in the continental USA and Alaska. https://ecos.fws.gov/ecp/species/3631 Olive-sided Flycatcher Contopus cooperi Breeds May 20 to Aug 31 This is a Bird of Conservation Concern (BCC) throughout its range in the continental USA and Alaska. https://ecos.fws.gov/ecp/species/3914 Breeds Feb 15 to Jul 15 Pinyon Jay Gymnorhinus cyanocephalus This is a Bird of Conservation Concern (BCC) throughout its range in the continental USA and Alaska. https://ecos.fws.gov/ecp/species/9420 Breeds elsewhere Rufous Hummingbird selasphorus rufus This is a Bird of Conservation Concern (BCC) throughout its range in the continental USA and Alaska. https://ecos.fws.gov/ecp/species/8002 Virginia's Warbler Vermivora virginiae Breeds May 1 to Jul 31 This is a Bird of Conservation Concern (BCC) throughout its range in the continental USA and Alaska. https://ecos.fws.gov/ecp/species/9441 Breeds elsewhere Willet Tringa semipalmata This is a Bird of Conservation Concern (BCC) throughout its range in the continental USA and Alaska. Willow Flycatcher Empidonax traillii Breeds May 20 to Aug 31 This is a Bird of Conservation Concern (BCC) only in particular Bird Conservation Regions (BCRs) in the continental USA https://ecos.fws.gov/ecp/species/3482 **Probability of Presence Summary**

The graphs below provide our best understanding of when birds of concern are most

likely to be present in your project area. This information can be used to tailor and schedule your project activities to avoid or minimize impacts to birds. Please make sure you read and understand the FAQ "Proper Interpretation and Use of Your Migratory Bird Report" before using or attempting to interpret this report.

Probability of Presence (

Each green bar represents the bird's relative probability of presence in the 10km grid cell(s) your project overlaps during a particular week of the year. (A year is represented as 12 4-week months.) A taller bar indicates a higher probability of species presence. The survey effort (see below) can be used to establish a level of confidence in the presence score. One can have higher confidence in the presence score if the corresponding survey effort is also high.

How is the probability of presence score calculated? The calculation is done in three steps:

- 1. The probability of presence for each week is calculated as the number of survey events in the week where the species was detected divided by the total number of survey events for that week. For example, if in week 12 there were 20 survey events and the Spotted Towhee was found in 5 of them, the probability of presence of the Spotted Towhee in week 12 is 0.25.
- 2. To properly present the pattern of presence across the year, the relative probability of presence is calculated. This is the probability of presence divided by the maximum probability of presence across all weeks. For example, imagine the probability of presence in week 20 for the Spotted Towhee is 0.05, and that the probability of presence at week 12 (0.25) is the maximum of any week of the year. The relative probability of presence on week 12 is 0.25/0.25 = 1; at week 20 it is 0.05/0.25 = 0.2.
- 3. The relative probability of presence calculated in the previous step undergoes a statistical conversion so that all possible values fall between 0 and 10, inclusive. This is the probability of presence score.

To see a bar's probability of presence score, simply hover your mouse cursor over the bar.

Breeding Season ()

Yellow bars denote a very liberal estimate of the time-frame inside which the bird breeds across its entire range. If there are no yellow bars shown for a bird, it does not breed in your project area.

Survey Effort ()

Vertical black lines superimposed on probability of presence bars indicate the number of surveys performed for that species in the 10km grid cell(s) your project area overlaps. The number of surveys is expressed as a range, for example, 33 to 64 surveys.

To see a bar's survey effort range, simply hover your mouse cursor over the bar.

No Data (–)

A week is marked as having no data if there were no survey events for that week.

Survey Timeframe

Surveys from only the last 10 years are used in order to ensure delivery of currently relevant information. The exception to this is areas off the Atlantic coast, where bird returns are based on all years of available data, since data in these areas is currently much more sparse.

Tell me more about conservation measures I can implement to avoid or minimize impacts to migratory birds.

<u>Nationwide Conservation Measures</u> describes measures that can help avoid and minimize impacts to all birds at any location year round. Implementation of these measures is particularly important when birds are most likely to occur in the project area. When birds may be breeding in the area, identifying the locations of any active nests and avoiding their destruction is a very helpful impact minimization measure. To see when birds are most likely to occur and be breeding in your project area, view the Probability of Presence Summary. <u>Additional measures</u> or <u>permits</u> may be advisable depending on the type of activity you are conducting and the type of infrastructure or bird species present on your project site.

What does IPaC use to generate the migratory birds potentially occurring in my specified location?

The Migratory Bird Resource List is comprised of USFWS <u>Birds of Conservation Concern (BCC)</u> and other species that may warrant special attention in your project location.

The migratory bird list generated for your project is derived from data provided by the <u>Avian Knowledge</u> <u>Network (AKN)</u>. The AKN data is based on a growing collection of <u>survey</u>, <u>banding</u>, <u>and citizen science</u> <u>datasets</u> and is queried and filtered to return a list of those birds reported as occurring in the 10km grid cell(s) which your project intersects, and that have been identified as warranting special attention because they are a BCC species in that area, an eagle (<u>Eagle Act</u> requirements may apply), or a species that has a particular vulnerability to offshore activities or development.

Again, the Migratory Bird Resource list includes only a subset of birds that may occur in your project area. It is not representative of all birds that may occur in your project area. To get a list of all birds potentially present in your project area, please visit the <u>AKN Phenology Tool</u>.

What does IPaC use to generate the probability of presence graphs for the migratory birds potentially occurring in my specified location?

The probability of presence graphs associated with your migratory bird list are based on data provided by the <u>Avian Knowledge Network (AKN</u>). This data is derived from a growing collection of <u>survey</u>, <u>banding</u>, and citizen science datasets.

Probability of presence data is continuously being updated as new and better information becomes available. To learn more about how the probability of presence graphs are produced and how to interpret them, go the Probability of Presence Summary and then click on the "Tell me about these graphs" link.

How do I know if a bird is breeding, wintering, migrating or present year-round in my project area?

To see what part of a particular bird's range your project area falls within (i.e. breeding, wintering, migrating or year-round), you may refer to the following resources: <u>The Cornell Lab of Ornithology All</u> <u>About Birds Bird Guide</u>, or (if you are unsuccessful in locating the bird of interest there), the <u>Cornell Lab</u> <u>of Ornithology Neotropical Birds guide</u>. If a bird on your migratory bird species list has a breeding season associated with it, if that bird does occur in your project area, there may be nests present at some point within the timeframe specified. If "Breeds elsewhere" is indicated, then the bird likely does not breed in your project area.

What are the levels of concern for migratory birds?

Migratory birds delivered through IPaC fall into the following distinct categories of concern:

- 1. "BCC Rangewide" birds are <u>Birds of Conservation Concern</u> (BCC) that are of concern throughout their range anywhere within the USA (including Hawaii, the Pacific Islands, Puerto Rico, and the Virgin Islands);
- 2. "BCC BCR" birds are BCCs that are of concern only in particular Bird Conservation Regions (BCRs) in the continental USA; and
- 3. "Non-BCC Vulnerable" birds are not BCC species in your project area, but appear on your list either because of the <u>Eagle Act</u> requirements (for eagles) or (for non-eagles) potential susceptibilities in offshore areas from certain types of development or activities (e.g. offshore energy development or longline fishing).

Although it is important to try to avoid and minimize impacts to all birds, efforts should be made, in particular, to avoid and minimize impacts to the birds on this list, especially eagles and BCC species of rangewide concern. For more information on conservation measures you can implement to help avoid and minimize migratory bird impacts and requirements for eagles, please see the FAQs for these topics.

Details about birds that are potentially affected by offshore projects

For additional details about the relative occurrence and abundance of both individual bird species and groups of bird species within your project area off the Atlantic Coast, please visit the <u>Northeast Ocean</u> <u>Data Portal</u>. The Portal also offers data and information about other taxa besides birds that may be helpful to you in your project review. Alternately, you may download the bird model results files underlying the portal maps through the <u>NOAA NCCOS Integrative Statistical Modeling and Predictive</u> <u>Mapping of Marine Bird Distributions and Abundance on the Atlantic Outer Continental Shelf</u> project webpage.

Bird tracking data can also provide additional details about occurrence and habitat use throughout the year, including migration. Models relying on survey data may not include this information. For additional information on marine bird tracking data, see the <u>Diving Bird Study</u> and the <u>nanotag studies</u> or contact <u>Caleb Spiegel</u> or <u>Pam Loring</u>.

What if I have eagles on my list?

If your project has the potential to disturb or kill eagles, you may need to <u>obtain a permit</u> to avoid violating the Eagle Act should such impacts occur.

Proper Interpretation and Use of Your Migratory Bird Report

The migratory bird list generated is not a list of all birds in your project area, only a subset of birds of priority concern. To learn more about how your list is generated, and see options for identifying what other birds may be in your project area, please see the FAQ "What does IPaC use to generate the migratory birds potentially occurring in my specified location". Please be aware this report provides the "probability of presence" of birds within the 10 km grid cell(s) that overlap your project; not your exact project footprint. On the graphs provided, please also look carefully at the survey effort (indicated by the black vertical bar) and for the existence of the "no data" indicator (a red horizontal bar). A high survey effort is the key component. If the survey effort is high, then the probability of presence score can be viewed as more dependable. In contrast, a low survey effort bar or no data bar means a lack of data and, therefore, a lack of certainty about presence of the species. This list is not perfect; it is simply a starting point for identifying what birds of concern have the potential to be in your project area, when they might be there, and if they might be breeding (which means nests might be present). The list helps you know what to look for to confirm presence, and helps guide you in knowing when to implement. conservation measures to avoid or minimize potential impacts from your project activities, should presence be confirmed. To learn more about conservation measures, visit the FAQ "Tell me about conservation measures I can implement to avoid or minimize impacts to migratory birds" at the bottom of your migratory bird trust resources page.

Facilities

National Wildlife Refuge lands

Any activity proposed on lands managed by the <u>National Wildlife Refuge</u> system must undergo a 'Compatibility Determination' conducted by the Refuge. Please contact the individual Refuges to discuss any questions or concerns.

THERE ARE NO REFUGE LANDS AT THIS LOCATION.

Fish hatcheries

THERE ARE NO FISH HATCHERIES AT THIS LOCATION.

Wetlands in the National Wetlands Inventory

ILTATIO

Impacts to <u>NWI wetlands</u> and other aquatic habitats may be subject to regulation under Section 404 of the Clean Water Act, or other State/Federal statutes.

For more information please contact the Regulatory Program of the local <u>U.S. Army Corps</u> <u>of Engineers District</u>.

Please note that the NWI data being shown may be out of date. We are currently working to update our NWI data set. We recommend you verify these results with a site visit to determine the actual extent of wetlands on site.

This location overlaps the following wetlands:

FRESHWATER EMERGENT WETLAND PEM1C

FRESHWATER FORESTED/SHRUB WETLAND

PSS1A

RIVERINE

R4SBA R4SBC

A full description for each wetland code can be found at the <u>National Wetlands Inventory</u> <u>website</u>

Data limitations

The Service's objective of mapping wetlands and deepwater habitats is to produce reconnaissance level information on the location, type and size of these resources. The maps are prepared from the analysis of high altitude imagery. Wetlands are identified based on vegetation, visible hydrology and geography. A margin of error is inherent in the use of imagery; thus, detailed on-the-ground inspection of any particular site may result in revision of the wetland boundaries or classification established through image analysis.

The accuracy of image interpretation depends on the quality of the imagery, the experience of the image analysts, the amount and quality of the collateral data and the amount of ground truth verification work conducted. Metadata should be consulted to determine the date of the source imagery used and any mapping problems.

Wetlands or other mapped features may have changed since the date of the imagery or field work. There may be occasional differences in polygon boundaries or classifications between the information depicted on the map and the actual conditions on site.

Data exclusions

Certain wetland habitats are excluded from the National mapping program because of the limitations of aerial imagery as the primary data source used to detect wetlands. These habitats include seagrasses or submerged aquatic vegetation that are found in the intertidal and subtidal zones of estuaries and

nearshore coastal waters. Some deepwater reef communities (coral or tuberficid worm reefs) have also been excluded from the inventory. These habitats, because of their depth, go undetected by aerial imagery.

Data precautions

Federal, state, and local regulatory agencies with jurisdiction over wetlands may define and describe wetlands in a different manner than that used in this inventory. There is no attempt, in either the design or products of this inventory, to define the limits of proprietary jurisdiction of any Federal, state, or local government or to establish the geographical scope of the regulatory programs of government agencies. Persons intending to engage in activities involving modifications within or adjacent to wetland areas NOTFORCONSULTATION should seek the advice of appropriate federal, state, or local agencies concerning specified agency

ATTACHMENT 15: EPC-CP-PIP-2101, NPDES MULTI-SECTOR GENERAL PERMIT



Effective Date: 10/20/2021

Environment, Safety, Health, Quality, Safeguards and Security Directorate

Environmental Protection and Compliance Division – Compliance Programs Group

Program Implementation Plan (PIP)

NPDES Multi-Sector General Permit

Name:	Organization:	Signature:	Date:		
Terrill W. Lemke	EPC-CP	Signature on File	10-19-21		
Derivative Classifier: 🔀 Unclassified or 🗌					
Name:	Organization:	Signature:	Date:		
Steven E. Wolfel	EPC-CP	Signature on File	10-20-21		
FPC-CP Reviewer:	Organization.	Signature:	Date [.]		
EPC-CP Reviewer:	Organization:	Signature on File	Date:		
Holly L. Wheeler	EPC-CP	Signature: Signature on File Signature:	Date: 10-20-21 Date:		
Holly L. Wheeler	0	Signature on File	10-20-21		
Holly L. Wheeler EPC-CP Team Leader:	EPC-CP Organization:	Signature on File Signature:	10-20-21 Date:		

To document a required read, Login to <u>UTrain</u>, and go to the Advanced Search.

Document Owner/Subject Matter Expert:

NPDES Multi-Sector General	No: EPC-CP-PIP-2101	Page 2 of 35
Permit	Revision: 1	Effective Date: 10/20/2021

REVISION HISTORY

Document Number and Revision	Effective Date	Description of Changes
ENV-RCRA-QAPP-MSGP, R0	06/03	New Document.
ENV-RCRA-QAPP-MSGP, R1	12/05	Annual review and revision.
ENV-RCRA-QAPP-MSGP, R2	07/07	Annual review, incorporated organizational restructure changes.
ENV-RCRA-QAPP-MSGP, R3	07/09	Biennial Review and Revision.
ENV-RCRA-QAPP-MSGP, R4	07/09	Biennial Review and Revision.
ENV-CP-QAPP-MSGP, R5	10/13	Biennial Review and Revision. New format implemented.
EPC-CP-PIP-2101, R0	01/19/2021	Initial issue under this document number. It supersedes/replaces ENV-CP-QAPP-MSGP, R5. Changes include revision to the document template, addition of MLs, software requirements, and detail to Section 4.5.
EPC-CP-PIP-2101 R1	10/20/2021	Update to procedure numbers and Attachment 2. Deletion of Appendices B, C and D with associated update to text in Section 3.3.2.

Revision: 1

Page 3 of 35

Table of Contents

	Table of Contents						
1.0	Purp	ose			5		
2.0	Auth	Authority and Applicability					
	2.1	1 Authority					
	2.2	Applica	bility		5		
3.0	Prog	ram Sco	pe		5		
	3.1	Require	ements		5		
	3.2	Descrip	otion of Wo	ork Activities	6		
	3.3	Gradeo	l Approach		6		
		3.3.1	Managen	nent Level Determination	6		
		3.3.2	Software	Risk Levels	6		
4.0	Prog	ram-Spe	cific Qualit	y Assurance Requirements and Implementing Work Activities	6		
	4.1 Criterion 1 – Management/Program				6		
		4.1.1	Program	Goals	6		
		4.1.2	Roles and	Responsibilities	7		
			4.1.2.1	Group Leader	7		
			4.1.2.2	Storm Water Permitting/Compliance Team Leader	7		
			4.1.2.3	MSGP Program Lead	8		
			4.1.2.4	Storm Water Tracking System/Discharge Monitoring Report Manager .	9		
			4.1.2.5	MSGP Personnel			
			4.1.2.6	EIM Database Administrator	10		
			4.1.2.7	Corrective Action Reporting Database Administrator	10		
			4.1.2.8	Maintenance Connection Database Administrator	10		
		4.1.3	Internal I	nterfaces	10		
			4.1.3.1	Facility Operations Directors	10		
			4.1.3.2	Permitted Industrial Activity Facility Owner/Operator	11		
			4.1.3.3	Deployed Environmental Professional	11		
			4.1.3.4	Sample Management Office (SMO)	11		
		4.1.4	External I	nterfaces			
			4.1.4.1	8-7			
			4.1.4.2	New Mexico Environmental Department			
			4.1.4.3	National Nuclear Safety Administration/Los Alamos Field Office			
				Analytical Laboratory Contractors			
	4.2		rion 2 – Management/Personnel Training and Qualification				
	4.3	Criterio	erion 3 – Management/Quality Improvement				
		4.3.1		nce Reporting			
		4.3.2		e Actions			
	4.4	Criterio		agement/Documents and Records			
		4.4.1		nt Control			
		4.4.2		es			
		4.4.3		c Media			
		4.4.4	Records I	Vanagement	15		

	4.5 Criterion 5 – Performance/Work Processes				
		4.5.1	Work Processes	17	
		4.5.2	Stormwater Pollution Prevention Plans		
	4.5.3 Inspections				
		4.5.4	Stormwater Corrective Actions	18	
			4.5.4.1 Responding to Water Quality Exceedances	18	
		4.5.5	Stormwater Monitoring	18	
			4.5.5.1 Quality Control Samples	20	
		4.5.6	Reporting	21	
			4.5.6.1 Discharge Monitoring Reports	21	
			4.5.6.2 Annual Reports	22	
	4.6	Criteric	on 6 – Performance/Design	22	
	4.7 Criterion 7 – Performance/Procurement				
	4.8 Criterion 8 – Performance/Inspection and Acceptance Testing				
	4.9 Criterion 9 – Assessment/Management Assessment			23	
	4.10 Criterion 10 – Assessment/Independent Assessment				
		•	ct/Counterfeit Items Prevention		
	4.12	Safety	Software Quality Assurance Requirements for Nuclear Facilities	24	
5.0	Imple	ementat	tion	24	
6.0	Train	ing		24	
7.0			and Records		
8.0	Defin	itions a	nd Acronyms	24	
9.0	Refer	rences		25	
10.0	Appe	ndicies.		27	
11.0	Attac	hments	5	27	
12.0	Conta	act Infor	rmation	27	
	Appendix A: NPDES Multi-Sector General Permit Program Management Level Determination, N			MLDS-	
			-324 Rev. 0		
			1: Summary of QA Requirements and Program-Level (Local) Work Practices		
	Attac	hment 2	2: MSGP Facilities Associated with Industrial Activities	35	

1.0 PURPOSE

This document describes the Program Implementation Plan (PIP) for the National Pollutant Discharge Elimination System (NPDES) Multi-Sector General Permit (MSGP) Program at Los Alamos National Laboratory (LANL or the Laboratory). Performance of the processes and procedures described herein, are in accordance with EPC-CP-QAP-001, *Environmental Compliance Programs Quality Assurance Plan*. This PIP provides detail and context regarding the implementation of those work activities generally described in EPC-CP-QAP-001. Work conducted under this program ensures compliance with the MSGP and the Clean Water Act.

2.0 AUTHORITY AND APPLICABILITY

2.1 Authority

This document is issued under the authority of the Environmental Protection and Compliance Division's Compliance Programs Group Leader to direct the management and operation of the MSGP Program.

2.2 Applicability

This PIP applies to personnel performing work by or for the MSGP Program, including but not limited to Triad National Security, LLC (Triad) employees, subcontractors and suppliers at all tiers (in accordance with subcontract documents), students, guests, and associates.

3.0 PROGRAM SCOPE

The MSGP Program is responsible for compliance oversight of Triad's NPDES MSGP, coordination and performance of institutional MSGP stormwater compliance activities, and developing and implementing institutional standards and policies regarding MSGP stormwater management. EPC-CP is the institutional point of contact regarding MSGP environmental compliance interactions with entities outside of LANL (i.e., regulatory agencies, stakeholders, and the public).

3.1 Requirements

The MSGP Program satisfies requirements contained in the following documents:

- EPC-CP-QAP-001, Section 3.3
- NPDES MSGP
- Title 40 of the Code of Federal Regulations (CFR) Part 136, *Guidelines Establishing Test Procedures for the Analysis of Pollutants*
- Title 20, Chapter 6, Part 4 of the New Mexico Administrative Code (NMAC), Standards for Interstate and Intrastate Surface Waters

3.2 Description of Work Activities

Triad will implement the monitoring requirements specified by the most current NPDES MSGP for industrial activities at LANL. The EPC-CP Storm Water Permitting/Compliance Team oversees institutional stormwater compliance related activities at the Laboratory.

3.3 Graded Approach

The following sections provide reference to the applicable Management Level Determinations and Software Risk Level forms.

3.3.1 Management Level Determination

The following Management Level Determinations are applicable to equipment and/or work activities for the MSGP Program (see Appendix A):

• ML-4, per MLDS No.: MLDS-TA-60-324, Revision 0.

3.3.2 Software Risk Levels

The Environmental Information Management (EIM), Maintenance Connection, and MSGP Corrective Action Oracle APEX software do not trigger any of the Reasonable Probability Criteria from P1040, Section 3.3.1. Therefore, the completion of a Safety/Non-Safety Determination, Categorization, and Software Risk Level (SRL) (Form 2033) is not required and the software is considered Non-Safety/Commercially Controlled.

4.0 PROGRAM-SPECIFIC QUALITY ASSURANCE REQUIREMENTS AND IMPLEMENTING WORK ACTIVITIES

Based on the Graded Approach results referenced above, this PIP is determined to be consistent with the work activity types covered by EPC-CP-QAP-001, Section 3.3. Attachment 1 presents a summary of the work practices (procedures, instructions, etc.,) that EPC-CP uses to meet the quality assurance (QA) requirements of SD300/Department of Energy (DOE) Order 414.1D, Chg. 2.

4.1 Criterion 1 – Management/Program

4.1.1 Program Goals

The MSGP Program supports EPC Division efforts to provide leadership in environmental protection and compliance services and compliance support to anticipate and manage environmental risk in support of Triad's mission.

Triad complies with the monitoring requirements, such as parameters, frequency of sampling, reporting, etc., set forth in the NPDES MSGP for industrial point source discharges through the Laboratory's MSGP Program. Compliance is demonstrated through the successful implementation of this PIP and applicable procedures.

4.1.2 Roles and Responsibilities

EPC-CP is responsible for the Laboratory's MSGP Program and a description of the group organization, levels of authority, and lines of communication are found within this PIP. EPC-CP group is organized by program teams under the line management direction of the Group Leader. Teams are cross-functional and focus on specific Program responsibilities, deliverables, or products. Program teams are guided by Team Leaders who have the responsibility to assure that the program is properly implemented. The following sections identify the roles and responsibilities for EPC-CP personnel, contractors, and program interfaces.

4.1.2.1 Group Leader

- Assure that the program has adequate resources (e.g., budget, staffing, etc.,) and that qualified staff properly gather and evaluate information submitted to the Environmental Protection Agency (EPA) as required by the MSGP Program.
- Sign Discharge Monitoring Reports (DMR), Annual Reports, Quarterly Visual Assessment Certifications, and change Notices of Intent (NOIs) prior to submittal to the EPA.
- Ensure that program personnel conduct procurements in accordance with P840-1, *Quality Assurance for Procurements*.
- Plan, conduct, and document periodic management assessments and Management Observation and Verifications (MOVs) of MSGP Program activities as required by P328-3 and P328-4.

4.1.2.2 Storm Water Permitting/Compliance Team Leader

- Ensure that program personnel perform work associated with the MSGP Program in accordance with the processes, procedures, and requirements specified in this plan.
- Ensure all MSGP Program personnel have the appropriate level of education, experience, and training to perform their job duties.
- Ensure that the most recent versions of the quality-related documents are used for all activities.
- Monitor and trend MSGP Program performance and track deficiencies.
- Support Facility Operations Directors (FODs) and Deployed Environmental Professionals (DEPs) with the implementation of corrective actions in a timely manner.
- Sign/submit DMRs, Annual Reports, Quarterly Visual Assessment Certifications, etc.
- Ensure PIP meets minimum specifications for documentation and records required by ADESH-QAP-001, ADESH Quality Assurance Plan.
- Conduct periodic reviews of records and documentation for accuracy, applicability, and compliance.

- Provide oversight and ensure that monitoring requirements are followed in accordance with the MSGP Program.
- Ensure that all required compliance documents are submitted to EPA in accordance with the MSGP.
- Recommend to Group Leader contracting items and services.
- Assist the Group Leader in planning and implementing management assessments and MOVs.
- Identify issues, concerns, or problems that warrant management assessment.
- Oversee resolution and correction of all problems found during management assessments.

4.1.2.3 MSGP Program Lead

- Perform MSGP Program related activities as assigned by the Storm Water Permitting/Compliance Team Leader.
- Engage other team members to support implementation of the MSGP Program.
- Support DEPs and permitted industrial facility owners with the implementation of corrective actions in a timely manner.
- Ensure analytical instruments used in the field are calibrated as per Institutional Procedure P330-2, *Control and Calibration of Measuring and Test Equipment (M&TE)*. Periodically review and update the calibration procedures to ensure permit requirements are met.
- Identify opportunities for process improvement, health and safety enhancement, environmenal protection, or other improvements of the program's operations.
- Ensure deficiencies are reported to the Storm Water Permitting/Compliance Team Leader in a timely manner.
- Implement a monitoring program as required by the MSGP.
- Ensure DMRs are prepared and submitted as required by the MSGP Program.
- Review documents for accuracy and completeness to assure that the requirements of the MSGP are met.
- Oversee data quality assessments prior to submittal of monthly, quarterly, and annual DMRs.
- Ensure procedures for sample handling and control during sample preparation, retrieval and analysis are followed.
- Identify issues, concerns, or problems that warrant management assessment.
- Periodically evaluate corrective actions to determine if there are issues that need to be entered into the Issues Management Tool.

- Oversee preparation, conduct quality review, and submit all required compliance documents (e.g., NOI/Notice of Termination (NOT), DMRs, Annual Reports, and correspondence) to EPA.
- Oversee preparation and conduct quality review of Stormwater Pollution Prevention Plans (SWPPP) coordinated with the responsible organization.

4.1.2.4 Storm Water Tracking System/Discharge Monitoring Report Manager

- Perform MSGP Program related activities as assigned by the Storm Water Permitting/Compliance Team Leader.
- Serve as database administrator for the Storm Water Tracking System (SWTS) and Discharge Monitoring Report modules in EIM.
- Maintain current MSGP station and monitoring requirement configuration content in SWTS.
- Ensure all results from sampling are returned and are eligible for reporting.
- Assist MSGP Program Lead in conducting data quality assurance review.
- Conduct data quality assessments prior to submittal of monthly, quarterly, and annual DMRs.
- Ensure compliance reports (NOI/NOT, DMRs, and Annual Reports) are prepared as required by the MSGP.
- Prepare stormwater DMRs for the MSGP Program.

4.1.2.5 MSGP Personnel

- Perform MSGP Program related activities as assigned by the Storm Water Permitting & Compliance Team Leader.
- Implement approved processes and procedures for any equipment and instrumentation used to collect field data (i.e., visual assessment parameters, temperature, and pH).
- Mentor and train new personnel, as needed.
- Conduct sampling activities in accordance with approved processes and procedures.
- Perform sample handling and control during sample preparation, retrieval, and analysis in accordance with approved processes and procedures.
- Notify the MSGP Program Lead immediately upon discovery of field parameter(s) (visual assessment parameters, temperature, and/or pH) exceedances.
- Conduct QA check of methods/equipment.
- Procure sampling equipment (i.e., bottles, standards, preservatives) in accordance with P840-1, *Quality Assurance for Procurements*. Order materials and supplies in accordance with LANL protocol.

4.1.2.6 EIM Database Administrator

- Coordinate with the Subcontract Technical Representative (STR) to ensure that formal contracts are in place to support MSGP Program compliance activities.
- Coordinate with the STR to oversee contract analytical laboratories and ensure they follow the DOE Analytical Services Program.
- Coordinate with the STR to ensure that the off-site laboratory participates in the DOE Consolidated Audit Program and that the analytical laboratory has been audited on an annual basis.
- Administer and maintain the database.
- Provide role-related database access.
- Maintain facility and personnel configuration content, permit-defined lists of limited values (LLVs), and e-mail notification distribution lists.
- Ship/transport samples to the correct off-site analytical laboratory for analysis.
- Administer and maintain sampling plans and sample documentation.
- Load analytical data into the EIM database and run auto-validation checks.
- Manage analytical laboratory data packages.

4.1.2.7 Corrective Action Reporting Database Administrator

- Administer and maintain the database.
- Provide role-related database access.
- Maintain facility and personnel configuration content, permit-defined LLVs, and e-mail notification distribution lists.

4.1.2.8 Maintenance Connection Database Administrator

- Administer and maintain the database.
- Provide role-related database access.
- Maintain facility and personnel configuration content.
- Extract data to support preparation of the MSGP Annual Report.

4.1.3 Internal Interfaces

4.1.3.1 Facility Operations Directors

The FOD provides organizational leadership to ensure that all facility and programmatic activities under their authority are performed in compliance with the MSGP. The FOD is also responsible for

NPDES Multi-Sector General	No: EPC-CP-PIP-2101	Page 11 of 35
Permit	Revision: 1	Effective Date: 10/20/2021

establishing an environmental compliance envelope. It is the FOD's responsibility to maintain trained and qualified DEPs and Waste Management Coordinators on staff under their authority.

4.1.3.2 Permitted Industrial Activity Facility Owner/Operator

The permitted industrial activity facility owner/operator is the organization or individual(s) designated by management to oversee the day-to-day operation and maintenance of each regulated facility and its associated stormwater control measures (SCMs) and outfalls. The designated owner/operator may be the FOD, Facility Operations Manager, Maintenance Manager, or Group Leader responsible for the buildings, facilities, and areas where the SCMs and outfalls are located. The MSGP Program interfaces with the owners/operators to assist in determining appropriate maintenance, corrective actions, inspections, site walks, and monitoring.

4.1.3.3 Deployed Environmental Professional

DEPs are embedded within FODs as assigned by the Deployed Environment Professionals Team Leader. DEPs provide daily environmental oversight, guidance, and support to the FOD and each designated permitted industrial activity facility owner/operator. The MSGP Program interfaces with DEPs regularly to coordinate outfall surveys, inspections, site walks, and monitoring. The DEPs perform the following MSGP activities.

- Act as a liaison between the permitted industrial activity operating facilities, the FOD, and EPC-CP.
- Write and update the facility-specific MSGP SWPPP.
- Conduct Routine Facility Inspections.
- Document, update, and coordinate correction of identified conditions requiring corrective actions.
- Identify personnel within industrial operating facilities requiring training.
- Update MSGP facility-specific training and present the training annually.

4.1.3.4 Sample Management Office (SMO)

The EPC-CP SMO is the central point for all analytical laboratory selection, evaluations, sample submittals, and data returns. The SMO performs the following activities.

- Evaluates potential analytical laboratories, prepares analytical statements of work that include requirements, and arrange contracts with selected laboratories for analysis of all samples.
- Accepts samples from sample collection personnel, prepares the sample for shipment, ships the samples to the off-site analytical laboratories, and receives the data packages from the laboratories.
- Analytical data is received from analytical laboratories in electronic format and uploaded into a database. Received data is checked for completeness and adherence to contract

requirements. After uploading, data undergoes verification and validation for evidence of laboratory contamination, improper analytical method, and other analytical issues, which could potentially affect data quality.

- Field data collected by sample collection personnel is verified and entered into EIM by SMO personnel when sample collection personnel deliver samples to the SMO.
- If significant verification and validation issues are identified, results are forwarded to, and discussed with, the responsible program lead.
- Data issues that result from procedural failures, personnel errors, or other failures to follow requirements are documented and corrected according to P322-4, *Issues Management*.

4.1.4 External Interfaces

4.1.4.1 Environmental Protection Agency

EPA Region 6 authorizes coverage under the MSGP in the State of New Mexico. The MSGP Program interfaces with the EPA, as needed, to submit public comment on draft permits, submit permit required reports, plans and other documentation, and to ensure compliance with the NPDES MSGP.

4.1.4.2 New Mexico Environmental Department

The New Mexico Environmental Department (NMED) Surface Water Quality Bureau assists the EPA with compliance evaluations, monitoring and Section 401, Clean Water Act certification through a joint federal and state agreement. Section 401 requires all federally issued permits to be certified by the state in which the discharge occurs and requires effluent limitations, other limitations and monitoring requirements set forth in the permit adhere to state water quality standards. The MSGP Program interfaces with the NMED as needed to ensure compliance with the Permit.

4.1.4.3 National Nuclear Safety Administration/Los Alamos Field Office

The National Nuclear Safety Administration (NNSA)/Los Alamos Field Office is the LANL facility owner and is responsible for providing oversight of LANL operations. It is the responsibility of the Los Alamos Field Office to ensure that LANL operates in compliance with all state and federal regulations. The MSGP Program interfaces with the Los Alamos Field Office as needed to ensure compliance with the Permit.

4.1.4.4 Analytical Laboratory Contractors

An independent off-site analytical laboratory performs analytical services for the MSGP Program. The analytical laboratory is required to participate in the DOE Consolidated Audit Program, maintain positive control of samples, perform analyses for samples received, and report sample results as specified in statements of work and internal procedures. The STR and SMO personnel interface with the off-site analytical laboratory. Interface between MSGP Program personnel and the analytical laboratory is conducted with STR and SMO oversight, as needed, to ensure that samples are handled correctly and that analytical results are received per the contract requirements.

NPDES Multi-Sector General	No: EPC-CP-PIP-2101	Page 13 of 35
Permit	Revision: 1	Effective Date: 10/20/2021

4.2 Criterion 2 – Management/Personnel Training and Qualification

The Storm Water Permitting/Compliance Team Leader shall determine skills, knowledge, and abilities required to perform MSGP Program work. Program personnel will be qualified and trained in accordance with P781-1, *Conduct of Training*. The Storm Water Permitting/Compliance Team Leader assigns minimum training requirements using a training plan. The Triad Human Resources Division maintains documentation of education qualification. Table 4.2 provides a summary of training and qualification requirements for MSGP Program personnel.

Table 4.2 Management/F		
Key Personnel/Role	Qualification Standard	Program Specific Training
Storm Water Permitting/Compliance Team Leader	 EPC-CP Manager Qualification Standard EPC-CP Group Qualification Standard EPC-CP-QS-2005, Stormwater Inspector Qualification Standard EPC-CP-QS-2006, Stormwater Pollution Prevention Plan Preparer Qualification Standard EPC-CP-QS-2007, Stormwater Design Reviewer Qualification Standard 	EPC-CP-PIP-2101
MSGP Program Lead, MSGP Personnel	 EPC-CP Group Qualification Standard EPC-CP-QS-2005, Stormwater Inspector Qualification Standard EPC-CP-QS-2006, Stormwater Pollution Prevention Plan Preparer Qualification Standard EPC-CP-QS-2007, Stormwater Design Reviewer Qualification Standard* 	
Discharge Monitoring Report Manager	EPC-CP Group Qualification Standard	-
Database Adminstrator	EPC-CP Group Qualification Standard	*

4.3 Criterion 3 – Management/Quality Improvement

The MSGP Program adheres to the EPC-CP-QAP-001 principles of problem prevention and continuous improvement. The MSGP Program Lead will evaluate improvement opportunities identified by trending and reporting.

4.3.1 Performance Reporting

Personnel involved in activities associated with the MSGP Program are encouraged to provide periodic updates, either verbal or written, to the MSGP Program Lead. The program uses these updates to determine areas that require attention and corrective actions.

4.3.2 Corrective Actions

Corrective actions for all EPC-CP programs and projects are initiated, tracked, corrected, and documented according to P330-6, *Nonconformance Control and Reporting*, P322-4, *Issues Management*, ADESH-QAP-001, *ADESH Quality Assurance Plan*, and Group procedures. A condition requiring corrective action that meets any of the following criteria is entered into the Issues Management Tool and will be screened as high, medium, or low.

- Corrective action was not completed by the expected completion date.
- A schedule is sent to the EPA Region 6 requesting an extension of the 45-day or 90-day timeframe to complete a corrective action and corrective action was not completed by the required completion date provided in the letter or as approved by EPA.
- All benchmark Additional Implementation Measure (AIM) level 2 or 3 exceedances.
- Repeat corrective actions or trends identified by EPC-CP personnel.
- Conditions requiring immediate action, where failure to take action would result in pollutants being released to a water body of the State or an immediate non-compliance with the MSGP.
- Violations identified by the regulatory authority.
- Other issues as deemed necessary by EPC-CP personnel.

4.4 Criterion 4 – Management/Documents and Records

4.4.1 Document Control

Procedures, permits, NOIs, NOTs, reports, and quality affecting correspondence are controlled by the organization's document control system (ESH-AP-007, *Document Control*). As a Best Management Practice (BMP), EPC-CP keeps an approved hard copy of the MSGP as well as all of the reapplication materials associated with the permit.

Controlled copies of EPC documents are located on the Internet:

• Electronic Document and Records Management System

Phone calls or emails are documented and controlled if the content provides direction or results in clarification of permit requirements or decisions.

4.4.2 Procedures

Procedures that implement the work scope identified in this PIP are developed and controlled, as needed, in accordance with ADESH-QAP-001, *ADESH Quality Assurance Plan*, ESH-AP-007, *Document Control*, and EPC-CP-QP-0901, *EPC-CP Quality Procedure to Supplement ESH-AP-007, Document Control*.

4.4.3 Electronic Media

The MSGP utilizes electronic means, as necessary, to maintain data. Databases used to hold data and generate reports used in demonstrating compliance are maintained on a common drive of a server or on a cloud-based platform. These databases are backed-up daily to minimize potential loss of data. The database administrator(s) control access to these databases, allowing only trained authorized personnel access to the databases.

EIM (<u>https://www.locusfocus.com/eim/eim.cfm</u>) is a cloud-based database information system designed in part to support the information management needs of the Laboratory's MSGP. MSGP support includes analytical data management, stormwater discharge monitoring reporting, Geographic Information System (GIS) development, and other information management activities as needed.

Maintenance Connection

(<u>https://www.maintenanceconnection.com/mcv18/online/mc_login_form.asp</u>) is a cloud-based computerized maintenance management system, or CMMS, used to manage MSGP field activities such as monitoring station installation and removal, inspections, maintenance, sample collection and retrieval, visual inspections, and information management change controls for data stored in Maintenance Connection and in the SWTS Module in EIM.

The MSGP Corrective Action Report (MSGP CAR) database (<u>https://epc.lanl.gov</u>) is a Laboratorymanaged Oracle APEX database and associated administration module that tracks corrective action data.

4.4.4 Records Management

Records are maintained and available for auditing in accordance with ESH-AP-006, *Records Management Plan*. The Storm Water Permitting/Compliance Team generates and retains records to ensure compliance with monitoring and recordkeeping requirements as specified by the Laboratory, DOE, and the EPA. Records kept by the MSGP Program include the following:

- Copy of the MSGP
- Annual Reports
- Discharge Monitoring Reports
- Corrective Action Reports
- NOIs and NOTs
- Reports and certifications required by the MSGP
- Data used for compliance purposes
- Inspection forms
- Logbook entries and/or field forms to document inspection and monitoring activity
- Equipment and instrument calibration and maintenance records

- QA documents
- General correspondence that affects the program (e.g., phone calls, emails, and log entries that provide directions or results in decisions)
- Applicable IWDs
- General MSGP compliance documents (correspondence with regulators and stakeholders, notice of change conditions, etc.)

Analytical data packages are stored in EDRMS and are available for public viewing on the Intellus New Mexico website.

The DEPs, assigned to the FOD in which a permitted industrial activity facility resides, keep the following records within the facility-specific Stormwater Pollution Prevention Plan.

- Reports and certifications required by the MSGP
- Routine Facility Inspection forms
- Visual Assessment forms
- Corrective Action Reports
- Discharge Monitoring Reports
- Annual Reports

All monitoring data is collected in accordance with the requirements specified in the MSGP. Triad submits monitoring results to EPA within 60 days of the end of the monitoring period, or in the case of no discharge (NODI) DMRs, within 30 days of the end of the monitoring period. The NOI or change NOIs, Annual Reports and DMRs are submitted electronically in accordance with the MSGP. These documents are submitted via EPA's electronic reporting site called the <u>Central Data Exchange</u> (CDX) website, unless the permit states otherwise or unless a waiver has been granted.

Triad keeps copies of the following documentation for a period of at least 3 years from the date its coverage under the MSGP expires or is terminated.

- SWPPP (including any modifications made during the term of the MSGP)
- Additional documentation requirements as identified in Section 6.5 of the MSGP
- All reports and certifications required by the MSGP
- Monitoring data
- Records of all information used to complete the NOI.

4.5 Criterion 5 – Performance/Work Processes

Work that contributes to achieving the quality specifications of the MSGP deliverables, is planned and documented, as described in this document and implementing procedures.

NPDES Multi-Sector General	No: EPC-CP-PIP-2101	Page 17 of 35
Permit	Revision: 1	Effective Date: 10/20/2021

Work is performed according to applicable plans and implementing procedures. The Program Lead provides first line supervision of personnel assigned to program tasks to ensure work is performed to achieve program quality specifications. Before changing a work process that affects the program quality specifications, the Program Lead ensures the same level of planning and review as used in the initial program planning steps.

4.5.1 Work Processes

All work should be regarded as a process. Each process consists of a series of actions and is planned and carried out by qualified workers using specified work processes and equipment under administrative, technical, and environmental controls established by management to achieve an end result. Workers are the best resource to contribute ideas for improving work processes and are involved in work process design, process evaluation, and providing the feedback necessary for improvement.

Work is planned and performed using the principles of Integrated Safety Management and is in compliance with P300, *Integrated Work Management for Work Activities*.

4.5.2 Stormwater Pollution Prevention Plans

SWPPP development and implementation by the permitted industrial activity facility is required for MSGP compliance (refer to Sections 6.0 and 8.0 of the MSGP for general SWPPP requirements and Sector-Specific Requirements for Industrial Activity, and Attachment 2, *MSGP Facilities Associated with Industrial Activity*). The SWPPP is intended to document the selection, design, and installation of SCMs. Additional documentation requirements are intended to document the implementation (including inspection, maintenance, monitoring, and corrective action) requirements identified in the MSGP. The SWPPP is a written assessment of potential sources of pollutants in stormwater runoff and it identifies SCMs implemented at the specific permitted industrial activity facility to minimize the discharge of pollutants in runoff from the site. These SCMs include site-specific stormwater controls, inspections, employee training, and reporting. The plans and procedures detailed in the SWPPP are implemented by the facility and updated as necessary, with a copy of the SWPPP kept on-site.

The SWPPP development process involves evaluating regulated industrial activities and requires FOD and Operational support for implementation, improvement, and revision of the plans. EPC-CP personnel follow guidance in EPC Division and Group documents including the most current revision of EPC-CP-QP-2110, *MSGP Stormwater Pollution Prevention Plan Preparation and Maintenance*.

4.5.3 Inspections

The MSGP requires periodic inspection of industrial processes and maintenance of SCMs to ensure their effectiveness. Triad has implemented a routine inspection process (e.g., monthly or quarterly) of industrial activity facilities permitted under the MSGP to support this determination. For information about how to perform a Routine Facility Inspection and how to complete the associated form, refer to the most current revision of EPC-CP-QP-2108, *MSGP Routine Facility Inspections.*

NPDES Multi-Sector General	No: EPC-CP-PIP-2101	Page 18 of 35
Permit	Revision: 1	Effective Date: 10/20/2021

Visual assessments are also required by the MSGP as an important tool for collecting information to determine the effectiveness of controls in preventing potential contaminants from migrating off Laboratory property. Accordingly, field personnel conduct visual assessments for stormwater collected at the monitoring stations or discharged through substantially identical outfalls associated with permitted industrial activity facilities located throughout the Laboratory. Information recorded documents all observations that are required by the MSGP. For information about how to perform a Visual Assessment and how to complete the associated form, refer to the most current revision of EPC-CP-QP-2105, *MSGP Stormwater Visual Assessments*.

4.5.4 Stormwater Corrective Actions

It is critical that Triad be able to effectively inspect and maintain the SCMs that have been installed at various locations. Quarterly inspections are completed and provided to the Program Lead for inclusion into the records system. In addition, the Program Lead accompanies the DEPs on the last Routine Facility Inspection of the year. All identified conditions requiring corrective action are summarized in an Annual Report submitted EPA each year. Triad management has made an investment in time and materials, in addition to a commitment to minimize potential migration of pollutants in stormwater. Report findings are evaluated, and in conjunction with facility personnel, SCMs are modified, installed, or removed as necessary. EPC-CP personnel follow guidance in EPC Division and Group level documents including EPC-CP-QP-2109, *MSGP Corrective Actions*.

4.5.4.1 Responding to Water Quality Exceedances

Federal stormwater regulations implemented under the Laboratory's MSGP require corrective action to be taken if exceedances of water quality standards or MSGP numeric effluent limits are identified. The identification of a pollutant source(s) contributing to a water quality exceedance is addressed through the creation of a condition requiring corrective action that is entered into the MSGP CAR database in accordance with EPC-CP-QP-2109, *MSGP Corrective Actions*. Corrective actions are typically accomplished by modifying, as appropriate, existing SCMs and SWPPPs or installing new SCMs.

When a water quality exceedance occurs, the MSGP EIM Database Administrator assures the analytical data is reviewed and submitted on the required DMR. The Program Lead enters the exceedance as a condition requiring corrective action in the MSGP CAR database. DEPs, and other SWPPP team members then investigate the occurrence, implement corrective action and document all corrective actions taken.

When an exceedance of the MSGP benchmark parameters is detected, the same process is followed as identified for a water quality exceedance above.

4.5.5 Stormwater Monitoring

The MSGP requires stormwater monitoring to address three separate criteria: Quarterly Benchmark, Effluent Limitations, and Impaired Waters. Refer to Attachment 2, *MSGP Facilities Associated with Industrial Activity* for a list of Laboratory permitted facilities that have monitoring requirements. Stormwater monitoring is conducted by EPC-CP personnel in accordance with the MSGP, EPC-CP

NPDES Multi-Sector General	No: EPC-CP-PIP-2101	Page 19 of 35
Permit	Revision: 1	Effective Date: 10/20/2021

procedures, and the current year MSGP Sampling and Analysis Plan. Considerations to be used for MSGP stormwater monitoring include, but may not be limited to, MSGP requirements, State water quality standards, and Administrative Authority requests.

Quarterly benchmark monitoring is used for determining the effectiveness of stormwater controls and, corrective actions for meeting the requirements of the MSGP. Four benchmark stormwater samples per year are required under the MSGP, but it is not necessary to collect them in consecutive quarters if climatic conditions preventing quarterly collection are documented (see *Adverse Weather Conditions* in Part 4.1.5 of the MSGP). Stormwater monitoring results are used to demonstrate compliance with water quality standards and to meet the requirement to evaluate results against benchmark parameter permit limits.

Annual Impaired Waters stormwater discharge monitoring of all pollutants for which a waterbody is impaired and for which a standard analytical method exists (see 40 CFR Part 136) is required. The canyons within and surrounding the Laboratory are declared as impaired waters by NMED. Impaired waters pollutants vary from canyon to canyon and are evaluated and published biannually by NMED in the Clean Water Act §303(d)/305(b) Integrated Report. The pollutants may be discontinued in subsequent annual monitoring if the concentration is below background levels in stormwater or if the constituent is not detected in year 1 or year 4 of the permit.

Effluent limitations monitoring is required annually where effluent limitation guidelines have been established for select regulated activities. Exceedance of an effluent limitation is a permit violation.

MSGP analytical methods applicable to LANL are consistent with the requirements of 40 CFR Part 136, *Guidelines Establishing Test Procedures for the Analysis of Pollutants.*

Triad monitors for four quarters as follows for each calendar year.

- January 1-March 31
- April 1-June 30
- July 1-September 30
- October 1-December 31

Documentation of the rationale for no monitoring or inspections due to adverse weather conditions must be included in the facility specific SWPPP. Adverse weather conditions are those that are dangerous or create inaccessibility for personnel, such as local flooding, high winds, or electrical storms, or situations that otherwise make sampling impractical, such as drought or extended frozen conditions.

Compliance is tracked by performing inspections of samplers and other associated equipment, and inspecting SCMs. Adequate records are maintained to demonstrate the operating history of essential instrumentation and equipment.

Triad operates and maintains systems of monitoring, control, and related equipment that are installed or used to achieve compliance with the MSGP and the SWPPP. Backup instrumentation and equipment will be timely deployed in the event of equipment failure.

NPDES Multi-Sector General	No: EPC-CP-PIP-2101	Page 20 of 35
Permit	Revision: 1	Effective Date: 10/20/2021

Instrument calibration is essential for documenting the quality of data obtained with the instrument. Technical work that depends upon the accuracy of data is performed using equipment for which the calibration status and limits of accuracy are known and controlled.

Field team personnel calibrate and perform maintenance procedures on all monitoring and analytical field instruments to ensure accuracy of measurements and maintain appropriate records of such activities. Calibrations are documented as prescribed by procedures or manufacturer's instructions.

Any person involved in the preparation, retrieval, and analysis will maintain positive control of samples at all times until sample disposal. Chain of custody responsibilities are provided in EPC-CP-QP-3020, *Sample Control and Field Documentation* and Table 4.5.5-1. EPC-CP personnel follow guidance in EPC Division documents including the most current revision of:

- EPC-CP-TP-2102, Installing, Setting Up, and Operating ISCO Samplers;
- EPC-CP-TP-2103, Inspecting Stormwater Runoff Samplers and Retrieving Samples for the MSGP;
- EPC-CP-QP-2104, Installing, Inspecting, and Maintaining MSGP Single Stage Samplers; and

Table 4.5.5-1 Chain of Custody		
Activity	Responsibility	
Sample collection and preparation	All persons (other than analytical personnel) performing sample preparation and collection are trained to sample collection procedures and adhere to the chain of custody requirements therein.	
Analysis	Analytical laboratories performing sample analysis maintain sufficient procedures to ensure positive control of samples as specified in the existing Statement of Work.	
Storage/Disposal	Analytical laboratories maintain/retained samples and/or sample portions under chain of custody until reanalysis, or ultimate disposal.	

• EPC-CP-QP-2106, Processing MSGP Stormwater Samples.

The EPC-CP SMO is the central point of contact for analytical laboratory selection, evaluations, sample submittal, and data return. See Section 4.1.3.4 for SMO roles and responsibilities.

4.5.5.1 Quality Control Samples

The planning and coordination of each sampling event and/or monitoring period may include the following quality control (QC) samples to detect potential sources of sample contamination or to track analytical laboratory performance:

- Equipment Rinsate Blank: A sample of analyte-free water that is prepared in the field using the appropriate sampling equipment with an aliquot of deionized (DI) or certified contaminant-free water that is processed using applicable field equipment in the same manner as the samples.
- Field Duplicates: Two samples taken from and representative of the same population and carried through all steps of the sampling and analytical procedures in an identical manner. Duplicate samples are used to assess variance of the total method including sampling and analysis.
- **Trip Blank:** Samples of analyte-free water that are prepared in the laboratory using DI or certified contaminant-free water and preserved as required. Trip blanks are used for volatile organic compound (VOC) samples only. Trip blanks are transported, unopened, to the field with other sample containers, handled like environmental samples and shipped to the analytical laboratory for analysis with the collected samples. VOC samples are not a requirement of the MSGP.
- **Field Blank:** A sample of analyte-free water that is prepared in the field using a clean samplecontainer.

The MSGP Program Lead shall consider and include, at a minimum, the collection of QC samples at the frequencies identified in Table 4.5.5.1-1.

Table 4.5.5.1-1 Quality Control Sampling Requirements		
Sample Type Analysis Frequency		
Field Blank and/or Field Duplicate	Includes all analytical groups	10% of samples or a minimum of one per calendar year.

All QC samples shall be collected in accordance with procedures provided in EPC-CP-QP-3027, *Sample Containers, Preservation, and Field Quality Control.*

4.5.6 Reporting

4.5.6.1 Discharge Monitoring Reports

DMRs are prepared in accordance with the most recent version of the procedure for generating DMRs using the DMR module in EIM. The DMR module is used to prepare the DMR in two formats: a paper form (EPA Form 3320-1) which may be printed as a hard copy or saved as a PDF, and an electronic comma-separated value file for import into the NetDMR electronic reporting system. The Laboratory is required to submit DMRs to EPA electronically using the NetDMR system and to keep a printed copy with the facility-specific SWPPP.

DMRs are due in the NetDMR system no later than 60 days following each monitoring period. NetDMR is accessed via EPA's CDX website (<u>https://cdx.epa.gov/</u>). The DMR manager may import DMRs into NetDMR; however, only a designated EPC Signatory Official or Authorized Representative

NPDES Multi-Sector General	No: EPC-CP-PIP-2101	Page 22 of 35
Permit	Revision: 1	Effective Date: 10/20/2021

may submit the DMRs for NPDES Permits. NetDMR roles and permissions for these functions are described on the NetDMR Support Portal (<u>https://netdmr.zendesk.com</u>/).

4.5.6.2 Annual Reports

The Laboratory is required to submit an annual report electronically to the EPA by January 30th for each year of permit coverage that includes a summary of the findings from inspections and corrective action documentation. The documentation includes the following:

- Information relative to whether a waiver was granted, by whom, and the date the waiver was approved;
- The NPDES Permit Tracking Number;
- A summary of the past year's routine facility inspection documentation (see Part 3.1.6 of the MSGP);
- A summary of your past years quarterly visual assessment documentation (see Part 3.2.3 of the MSGP);
- A summary of the corrective action and/or AIM documentation over the past year (see Parts 5.1.3 and 5.3 of the MSGP); and

The annual report is submitted electronically via the NetMSGP program service on EPA's CDX website. The annual report may be submitted on a paper form (EPA Form 6100-28) if the Laboratory has been granted a waiver from electronic reporting by the applicable EPA Regional Office.

4.6 Criterion 6 – Performance/Design

Design activities are conducted and reviewed in accordance with:

- PD340, Conduct of Engineering and Configuration Management for Facility Work;
- P341, Facility Engineering Processes Manual and;
- P342, Engineering Standards.

Design standards under this program include, but are not limited to temporary and permanent SCMs, conditions requiring corrective action, and stormwater monitoring support.

Design inputs are specified and approved on a timely basis for making design decisions. Inputs contain the level of detail required to permit the performance of design activities correctly.

Formal design reviews, including design verifications and evaluation of design changes, are conducted to ensure that the design input is correctly incorporated into the design output. Changes to design will undergo the same review as the original design. A Professional Engineer must stamp engineered designs.

NPDES Multi-Sector General	No: EPC-CP-PIP-2101	Page 23 of 35
Permit	Revision: 1	Effective Date: 10/20/2021

Verification and validation of the adequacy of designs are conducted before relying on the performance of the design function. Verification and validation are conducted in accordance with implementing procedures.

4.7 Criterion 7 – Performance/Procurement

Items and services required to perform the scope for the MSGP Program are commercial grade in nature and no special procurement requirements or needs are necessary. All procurements of equipment, supplies, and/or services are made in accordance with P840-1, *Quality Assurance for Procurements*.

4.8 Criterion 8 – Performance/Inspection and Acceptance Testing

Materials and services used in this program will be inspected and/or tested prior to acceptance in accordance with P330-8, *Inspection and Test* as applicable. Most supplies used during performance of program activities are commercial grade in nature and require no special acceptance practices or procedures.

4.9 Criterion 9 – Assessment/Management Assessment

The EPC-CP Group Leader conducts management assessments and/or MOV assessments of the MSGP Program in accordance with P328-3, *Management Assessment* and *P328-4, Management Observation and Verification*. Assessments are documented and filed as records in accordance with ESH-AP-006, *Records Management Procedure*. Violations of requirements and/or findings from management assessments and/or MOVs initiate a nonconformance report in accordance with P330-6 *Nonconformance Control and Reporting*. Corrective actions to resolve the nonconforming services or processes are tracked and documented in accordance with P322-4, *Issues Management*.

4.10 Criterion 10 – Assessment/Independent Assessment

Independent assessments are those assessments conducted by organizations external to EPC-CP. As required by the SD330, *Los Alamos National Laboratory Quality Assurance Program*, this program may be assessed by outside organizations in accordance with P328-2, *Independent Assessment*.

Annual audits/assessments will be conducted, with input from the Storm Water Permitting/Compliance Team Leader identifying one or more areas of the program to be audited each year. If a violation of requirements is found during an independent audit/assessment, a nonconformance report is initiated in accordance with P330-6, *Nonconformance Control and Reporting*. Corrective actions are tracked and documented in accordance with P322-4, *Issues Management*.

4.11 Suspect/Counterfeit Items Prevention

Suspect/Counterfeit items (S/CI) are prevented from being purchased by Triad at LANL. Potential S/CI are prevented, detected, reported and investigated in accordance with the procedures defined in the LANL procedure P330-9, *Suspect/Counterfeit Items (S/CI)*.

NPDES Multi-Sector General	No: EPC-CP-PIP-2101	Page 24 of 35
Permit	Revision: 1	Effective Date: 10/20/2021

4.12 Safety Software Quality Assurance Requirements for Nuclear Facilities

This section is only applicable for nuclear facilities in accordance with DOE Order 414.1D, Chg.2, Attachment 1 *Contractor Requirements Document* (CRD), Section 1.b. As such, this section is not applicable to the NPDES MSGP Program.

5.0 IMPLEMENTATION

The requirements of this document are effective on the date provided on the cover page.

6.0 TRAINING

Training for EPC-CP MSGP employees, DEPs, and subcontractors are assigned and tracked using UTrain, the institutional training management system. The required training associated with this document is as follows.

• Self-study of this procedure (required reading) is required for all MSGP Program employees, including subcontractors, and some DEPs depending on their assigned job duties.

7.0 DOCUMENTS AND RECORDS

The Environment, Safety, Health, Quality, Safeguards, and Security-Document Control and Records Management is the Office of Record for this document and maintains the administrative record. Documents and records are maintained in accordance with PD1020, *Document Control and Records Management;* ESH-AP-007, *Document Control;* P1020-1, *Laboratory Records Management,* and ESH-AP-006, *Records Management Procedure.*

8.0 DEFINITIONS AND ACRONYMS

Use the LANL Definition of Terms and those in SD330.

BMP	Best Management Practice
CDX	Central Data Exchange
CFR	Code of Federal Regulations
CRD	Contractor Requirements Document
DEP	Deployed Environmental Professional
DI	Deionized
DMR	Discharge Monitoring Report
DOE	Department of Energy
EIM	Environmental Information Management
EPA	Environmental Protection Agency
EPC-CP	Environmental Protection and Compliance-Compliance Programs
FOD	Facility Operations Director
LANL	Los Alamos National Laboratory

Use the LANL Acronym Master List.

NPDES Multi-Sector General	No: EPC-CP-PIP-2101	Page 25 of 35
Permit	Revision: 1	Effective Date: 10/20/2021

LLV	List of Limited Value
MOV	Management Observation and Verification
MSGP	Multi-Sector General Program
NeT	NPDES eReporting Tool
NMED	New Mexico Environmental Department
NNSA	National Nuclear Safety Administration
NOI	Notice of Intent
NOT	Notice of Termination
NPDES	National Pollutant Discharge Elimination System
PIP	Program Implementation Plan
QA	Quality Assurance
S/CI	Suspect/Counterfeit Items
SCM	Stormwater Control Measure
SMO	Sample Management Office
STR	Subcontract Technical Representative
SWPPP	Stormwater Pollution Prevention Plan
SWTS	Storm Water Tracking System Module
VOC	Volatile organic compound

9.0 **REFERENCES**

The latest document revision, available through Triad's Electronic Document and Records Management System, shall be used unless otherwise specified.

Prime Contract

DOE Order 414.1D, Chg. 2, Quality Assurance

NPDES MSGP

40 CFR Part 136, Guidelines Establishing Test Procedures for the Analysis of Pollutants

Clean Water Act, Title 33 U.S.C. 1251

20.6 Part 4 NMAC, Standards for Interstate Surface Waters

LANL Documents:

SD330, Los Alamos National Laboratory Quality Assurance Program

P101-17, Excavation/Fill/Soil Disturbance

P300, Integrated Work Management

P322-4, Issues Management

P328-2, Independent Assessment

- P328-3, Management Assessment
- P328-4, Management Observation and Verification
- P330-2, Control and Calibration of Measuring and Test Equipment (M&TE)
- P330-6, Nonconformance Control and Reporting
- P330-8, Inspection and Test
- P330-9, Suspect/Counterfeit Items (S/CI)
- P340, Conduct of Engineering and Configuration Management for Facility Work
- P341, Facility Engineering Processes Manual
- P342, Engineering Standards
- EPC-ES-FSD-001, Implementing Environmental Requirements
- EPC-CP-FSD-001, Water Quality
- P781-1 Conduct of Training
- P840-1, Quality Assurance for Procurements
- P1040, Software Quality Management
- PD1020, Document Control and Records Management
- P1020-1, Laboratory Records Management

EPC Documents:

- ESH-AP-006, Records Management Procedure
- ESH-AP-007, Document Control
- ADESH-QAP-001, ADESH Quality Assurance Plan
- EPC-DO-QP-100, General Field Safety
- EPC-CP-QAP-001, Environmental Compliance Programs Quality Assurance Plan
- EPC-CP-QP-0901, EPC-CP Quality Procedure to Supplement ESH-AP-007, Document Control
- EPC-DO-TP-120, Project Review Process
- EPC-CP-QP-2109, MSGP Corrective Actions
- EPC-CP-QP-2104, Installing, Inspecting, and Maintaining MSGP Single Stage Samplers
- EPC-CP-QP-2105, MSGP Stormwater Visual Assessments
- EPC-CP-QP-2106, Processing MSGP Stormwater Samples
- EPC-CP-QP-2107, Preparing Discharge Monitoring Reports for the NPDES Multi-Sector General Permit

NPDES Multi-Sector General	No: EPC-CP-PIP-2101	Page 27 of 35
Permit	Revision: 1	Effective Date: 10/20/2021

EPC-CP-QP-2108, MSGP Routine Facility Inspections

EPC-CP-QP-2110, MSGP Stormwater Pollution Prevention Plan Preparation and Maintenance

EPC-CP-TP-2102, Installing, Setting Up, and Operating ISCO Samplers

EPC-CP-TP-2103, Inspecting Stormwater Runoff Samplers and Retrieving Samples for the MSGP

10.0 APPENDICIES

Appendix A: NPDES Multi-Sector General Permit Program Management Level Determination, MLDS-TA-60-324 Rev. 0

11.0 ATTACHMENTS

Attachment 1: Summary of QA Requirements and Program-Level (Local) Work Practices

Attachment 2: MSGP Facilities Associated with Industrial Activity

12.0 CONTACT INFORMATION

Entity: EPC-CP Storm Water Permitting/Compliance Team Leader Name: Terrill W. Lemke Telephone: (505) 665-2397 E-mail: tlemke@lanl.gov Website: <u>https://int.lanl.gov/org/ddops/aldeshqss/environmental-waste-programs/compliance-programs/index.shtml</u>

NPDES Multi-Sector General	No: EPC-CP-PIP-2101	Page 28 of 35
Permit	Revision: 1	Effective Date: 10/20/2021

Appendix A: NPDES Multi-Sector General Permit Program Management Level Determination, MLDS-TA-60-324 Rev. 0

(Page 1 of 4)

		RATORY		Managem			
MLD	S No.: MLDS-	TA-60-324		Rev.: 0			Page 1 o
105	YSTEM INFO	PHATION					
	A No.: All	1.2 Facility	No: All	1.3 Facility Name: /		_	-
-	acility Hazard	1		ar Facility			Feelling
1.000	HC-2	outegory.	-	emical High-PSM		Nonnuclear I Accelerator	Facility
	HC-3		12.00	emical High-non-PSM	la l	Firing Range	
	Less than HC-	-3		emical Moderate	1	Biological	
				emical Low		Explosive	
1.5 O	perating Syste	em ID:		ating System Name: Wa			
1.7 S							
2.0 SE 2.1 Se 2.2 DC Taunia	curity Classifi C/RO: <i>(Name,</i> a Van Valkenb	ASSIFICATIO cation: Unclas <i>Z Number, O</i> burg, 145666,	Program N REVIEW ssified rganization EPC-CP	m Name: Storm Water -	- Multi-S	ector General	1
2.0 SE 2.1 Se 2.2 DC Taunia	ECURITY CLA Ecurity Classifi C/RO: (Name, a Van Valkent	ASSIFICATIO cation: Unclas <i>Z Number, O</i> burg, 145666,	Program N REVIEW ssified rganization EPC-CP		- Multi-S		
2.0 SE 2.1 Se 2.2 DC Taunia 3.0 SY 3.1 Do	CURITY CLA curity Classifi C/RO: (Name, a Van Valkent 'STEM MANA res this system	ASSIFICATIO cation: Unclar <i>Z Number, O</i> purg, 145666, AGEMENT LE	Program N REVIEW ssified rganization EPC-CP VEL DETER the criteria	Signature Date		12 12	114 19
2.0 SE 2.1 Se 2.2 DC Taunia 3.0 SY 3.1 Do applica	CURITY CLA curity Classifi C/RO: (Name, a Van Valkent STEM MANA es this system able criteria, in	ASSIFICATIO cation: Unclas Z Number, O burg, 145666, AGEMENT LE n meet one of nsert the safet	Program N REVIEW ssified rganization, EPC-CP VEL DETER the criteria b y function(s)	Signature Date		12 12	114 19
2.0 SE 2.1 Se 2.2 DC Taunia 3.0 SY 3.1 Do applica and go • The	CURITY CLA accurity Classifi C/RO: (Name, a Van Valkent STEM MANA es this system able criteria, in to Section 4. system is an	ASSIFICATIO cation: Unclas Z Number, O burg, 145666, AGEMENT LE n meet one of sert the safet 0 and designa SSC of a Haz	Program N REVIEW ssified rganization, EPC-CP VEL DETER the criteria by function(s) ate the syste card Categor	Signature Date	that ner	<u>12</u> , , forms	114 19
2.0 SE 2.1 Se 2.2 DC Taunia 3.0 SY 3.1 Do applica and go • The Doc	CURITY CLA accurity Classifi C/RO: (Name, a Van Valkent STEM MANA STEM MANA Ses this system able criteria, ir to Section 4. system is an umented Safe	ASSIFICATIO cation: Unclas Z Number, O burg, 145666, AGEMENT LE n meet one of sert the safet 0 and designs SSC of a Haz aty Analysis (I	Program N REVIEW ssified rganization, EPC-CP the criteria by function(s) ate the syste card Categor DSA) designa	Signature Date	ck the rence(s	/ 12), forms s).	le 19 № ⊠
2.0 SE 2.1 Se 2.2 DC Taunia 3.0 SY 3.1 Do applica and go • The Doc • The Doc	CURITY CLA accurity Classifi C/RO: (Name, a Van Valkenb /STEM MANA res this system able criteria, ir to Section 4. system is an umented Safe system is an ument (SAD)	ASSIFICATIO cation: Unclas Z Number, O burg, 145666, AGEMENT LE n meet one of hsert the safet 0 and designa SSC of a Haz sty Analysis (I SSC of an Ac designated pu	Program N REVIEW ssified rganization EPC-CP VELDETER the criteria b y function(s) ate the syste card Categor DSA) designa ccelerator Fa ublic protecti	Signature Date MINATION ANALYSIS Delow? If "Yes", then che and safety analysis refe m as ML-1. y 2 or 3 Nuclear Facility ated Safety Class (SC) ff cility that performs Safet on function(s).	ck the rence(s that per unction(y Asses	Yes), forms s). isment	l4]9 No⊠
2.0 SE 2.1 Se 2.2 DC Taunia 3.0 SY 3.1 Do applica and go • The Doc • The Doc	CURITY CLA acurity Classifi C/RO: (Name, a Van Valkent STEM MANA es this system able criteria, in to Section 4. system is an umented Safe system is an	ASSIFICATIO cation: Unclar Z Number, O burg, 145666, AGEMENT LE n meet one of nsert the safet 0 and designa SSC of a Haz SSC of a Haz SSC of an Ac designated pu SSC of a Hig	Program N REVIEW ssified rganizatos EPC-CP VEL DETER the criteria to y function(s) ate the syste card Categor DSA) designa scelerator Fa balloic protection h Hazard No	Signature Date MINATION ANALYSIS below? If "Yes", then che and safety analysis refe m as ML-1. y 2 or 3 Nuclear Facility ated Safety Class (SC) fr cility that performs Safet on function(s). nnuclear Facility that periors	ick the rence(s that per unction(y Asses	Yes), forms s). isment	llue 19 I № ⊠ □
2.0 SE 2.1 Se 2.2 DC Taunia 3.0 SY 3.1 Do applica and go • The Doc • The Doc • The iden	CURITY CLA acurity Classifi C/RO: (Name, a Van Valkent STEM MANA es this system able criteria, in to Section 4. system is an umented Safe system is an ument (SAD) system is an tified in the Fe	ASSIFICATIO cation: Unclas Z Number, O burg, 145666, AGEMENT LE n meet one of nsert the safet 0 and designa SSC of a Hag SSC of a Hag SSC of a Ad designated pu SSC of a Hig acility Safety /	Program N REVIEW ssified rganization EPC-CP VELDETER the criteria by y function(s) ate the syste card Categor DSA) designa ccelerator Fa ublic protecti h Hazard No Analysis (FS)	Signature Date MINATION ANALYSIS Delow? If "Yes", then che and safety analysis refe m as ML-1. y 2 or 3 Nuclear Facility ated Safety Class (SC) ff cility that performs Safet on function(s).	ick the rence(s that per unction(y Asses	Yes), forms s). isment	lee 19 1 № ⊠
2.0 SE 2.1 Se 2.2 DC Taunia 3.0 SY 3.1 Do applica and go • The Doc • The Doc • The iden	CURITY CLA accurity Classifi C/RO: (Name, a Van Valkent STEM MANA es this system able criteria, ir b to Section 4. system is an umented Safe system is an ument (SAD) system is an tified in the Fa	ASSIFICATIO cation: Unclas Z Number, O burg, 145666, AGEMENT LE n meet one of sert the safet 0 and designa SSC of a Haz aty Analysis (I SSC of a Haz designated pu SSC of a High acility Safety / en go to Field	Program N REVIEW ssified rganization EPC-CP the criteria b y function(s) ate the syste card Categor SA) designa ccelerator Fa ublic protecti h Hazard No Analysis (FS) 3.2	Signature Date MINATION ANALYSIS below? If "Yes", then che and safety analysis refe m as ML-1. y 2 or 3 Nuclear Facility ated Safety Class (SC) fr cility that performs Safet on function(s). nnuclear Facility that periors	that per unction(y Asses	Yes), forms s). isment	li(e)]9 □ □
2.0 SE 2.1 Se 2.2 DC Taunia 3.0 SY 3.1 Do applica and go • The Doc • The iden If "No"	CURITY CLA curity Classifi C/RO: (Name, a Van Valkent STEM MANA es this system able criteria, in to Section 4. system is an umented Safe system is an ument (SAD) system is an tified in the Fa is checked the SC or publi	ASSIFICATIO cation: Unclas Z Number, O burg, 145666, AGEMENT LE n meet one of sert the safet 0 and designa SSC of a Haz aty Analysis (I SSC of a Haz designated pu SSC of a High acility Safety / en go to Field	Program N REVIEW ssified rganization EPC-CP the criteria b y function(s) ate the syste card Categor SA) designa ccelerator Fa ublic protecti h Hazard No Analysis (FS) 3.2	Signature Date MINATION ANALYSIS Delow? If "Yes", then che and safety analysis refe m as ML-1. Y 2 or 3 Nuclear Facility ated Safety Class (SC) ff cility that performs Safet on function(s). nnuclear Facility that per A) for protection of the p	that per unction(y Asses	Yes □), forms s). isment unction(s)	llue] 19 □ □
2.0 SE 2.1 Se 2.2 DC Taunia 3.0 SY 3.1 Do applicas and go • The Doc • The Doc • The iden If "No" No.	CURITY CLA accurity Classifi C/RO: (Name, a Van Valkent STEM MANA es this system able criteria, ir to Section 4. system is an umented Safe system is an ument (SAD) system is an ument (SAD) system is an tified in the Fa is checked the SC or publi Analysis	ASSIFICATIO cation: Unclas Z Number, O burg, 145666, AGEMENT LE n meet one of sert the safet 0 and designa SSC of a Haz aty Analysis (I SSC of a Haz designated pu SSC of a High acility Safety / en go to Field	Program N REVIEW ssified rganization EPC-CP the criteria b y function(s) ate the syste card Categor SA) designa ccelerator Fa ublic protecti h Hazard No Analysis (FS) 3.2	Signature Date MINATION ANALYSIS Delow? If "Yes", then che and safety analysis refe m as ML-1. Y 2 or 3 Nuclear Facility ated Safety Class (SC) ff cility that performs Safet on function(s). nnuclear Facility that per A) for protection of the p	that per unction(y Asses	Yes □), forms s). isment unction(s)	llue] 19 □ □

Form No: AP-341-502-FM01, Rev. 6 Form Effective Date: 02/07/18

ES-DO-20-032

NPDES Multi-Sector General	No: EPC-CP-PIP-2101	Page 29 of 35
Permit	Revision: 1	Effective Date: 10/20/2021

Appendix A: NPDES Multi-Sector General Permit Program Management Level Determination, MLDS-TA-60-324 Rev. 0 (cont.)

(Page 2 of 4)

	Los Alamos	NPDES Gonstruction	Conduct of En General Perminent Level Dete	it Program
MLDS	No.: MLDS-TA-60-324	Rev.: 0		Page 2 of
• The desi	system is an SSC of a Ha gnated Safety Significant	izard Category 2 or 3 Nuclear Facili (SS) function(s).	ty that performs DSA	
The protection	system is an SSC of an A ection function(s).	ccelerator Facility that performs SA	D designated worker	
- The iden	system is an SSC of a High	gh Hazard Nonnuclear Facility that stion of the uninvolved or noninvolve d 3.3.	performs function(s) ed worker.	
No.	SS functions or worker Safety Analysis	protection functions as defined by	DSA, SAD, or F	SA Reference
3.2-1	N/A		N/A	
3.2-2	N/A		N/A	
3.2-3	N/A		N/A	
applicat	ole criteria, insert the func	f the criteria below? If "Yes", then cl tion(s) and safety analysis or Facilit o to Section 4.0 and designate the s	v	🗌 No 🖾

LANL Form No: AP-341-502-FM01, Rev. 6 Form Effective Date: 02/07/18

NPDES Multi-Sector General	No: EPC-CP-PIP-2101	Page 30 of 35
Permit	Revision: 1	Effective Date: 10/20/2021

Appendix A: NPDES Multi-Sector General Permit Program Management Level Determination, MLDS-TA-60-324 Rev. 0 (cont.)

(Page 3 of 4)

	LOS Alamos	NPDES Gonstruction	Conduct of Eng General Permit nent Level Dete	Program
MLDS	No.: MLDS-TA-60-324	Rev.: 0		Page 3 of
· Th Oth	e system is an SSC of a H her Hazard Control (OHC) i	azard Category 2 or 3 Nuclear Facil n the DSA.	lity that is designated	
• The Nu	e system is an SSC that pe clear Material (SNM) or Cla	rforms function(s) for protection of C assified Matter as determined by the	Category I or II Special Facility Management.	
fun the	ction(s) identified in the FS	oderate Hazard Nonnuclear Facility A for protection of uninvolved or nor ires enhanced engineering, quality, ndards requirements.	ninvolved worker and	t II
Acc	e system is an SSC that pe ceptance Criteria (WAC) for nagement.	rforms important function(s) for com r a Waste Receiving Site and as det	pliance with Waste ermined by the Facility	
cov	ered in the Radiation Prote	rforms function(s) for radiation prote action Safety Management Program al, abnormal, or emergency respons	(SMP) and are	
call	ed out in a permit or used t	rforms function(s) for environmental o demonstrate environmental comp acility Management. (See discussion	liance that are	\boxtimes
Evalu	letermined by the Facility N ation. This MLDS is for the IL. which is responsible for	forms function(s) that are essential Management. overall Multi-Sector General Permit monitoring the storm water dischar . The MSGP Program is responsible	t (MSGP) Program at	
•		quirements, how often to conduct th		
	Evaluates sample results	and compares those results to esta	blished effluent limits;	
•	Provides storm water disc agencies at a predetermin	charge summary reports to the asso ned reporting frequency;	ciated enforcement	
	Works with the enforcement	ent agencies to address identified is	sues.	
in th on e	e program that would requi quipment to support permi	ociated with a program and not equi ire it to be elevated to ML-3. While t t requirements, the equipment (as a program to determine the appropriat	he program may rely	
If "No" i	s checked then go to Field	3.4		_
No.	OHC Functions defined functions as determined	by Safety Analysis or other ML-3 by Facility Management	DSA or Facility Ma Reference	anagement
3.3-1	Obtain permit coverage	(NOI) and modification	N/A	
3.3-2	Permit implementation		N/A	
3.3-3	Compliance inspections		N/A	
3.3-4	Data management		N/A	

LANL

Form No: AP-341-502-FM01, Rev. 6 Form Effective Date: 02/07/18

NPDES Multi-Sector General	No: EPC-CP-PIP-2101	Page 31 of 35
Permit	Revision: 1	Effective Date: 10/20/2021

Appendix A: NPDES Multi-Sector General Permit Program Management Level Determination, MLDS-TA-60-324 Rev. 0 (cont.)

(Page 4 of 4)

	S No.: MLDS-TA-60-324	Rev.: 0		
	and a state of the state of the	Nev U		
3.3-5	Reporting			N/A
3.4 If desig	the System does not meet nate the system as ML-4 in	t any of the criteria in fields 3 n Section 4.0.	1.1, 3.2, or 3.3,	then
4.0 S	YSTEM MANAGEMENT L	EVEL DESIGNATION		
ML-1	□ ML-2	□ ML-3 [ML-4 🖂
_				
5.0 A	PPROVALS			
5.1 R		ne, Z Number, Organization,	Signature, and	-gate)
5.1 R Terrill 5.2 Ve	esponsible Engineer <i>(Nam</i> Lemke, 120092, EPC-CP	Drganization, Signature, and	with	
5.1 R Terrill 5.2 Ve Tauni 5.3 Fa	esponsible Engineer (Nam Lemke, 120092, EPC-CP erifier (Name, Z Number, C a Van Valkenburg, 145666	Drganization, Signature, and B, EPC-CP	Date)	Jul 25,
5.1 R Terrill 5.2 V Tauni 5.3 Fa Jason	esponsible Engineer (Nam Lemke, 120092, EPC-CP arifier (Name, Z Number, C a Van Valkenburg, 145666 acility Design Authority Rep	Drganization, Signature, and B, EPC-CP	Date)	on, Signature, an
5.1 R Terrill 5.2 V Tauni 5.3 Fa Jason	esponsible Engineer (Nam Lemke, 120092, EPC-CP erifier (Name, Z Number, C a Van Valkenburg, 145666 acility Design Authority Rep Apperson, 222827, ES-DO	Drganization, Signature, and B, EPC-CP	Date)	on, Signature, an

LANL Form No: AP-341-502-FM01, Rev. 6 Form Effective Date: 02/07/18

NPDES Multi-Sector General	No: EPC-CP-PIP-2101	Page 32 of 35
Permit	Revision: 1	Effective Date: 10/20/2021

Attachment 1: Summary of QA Requirements and Program-Level (Local) Work Practices

Summary of QA Requirements and Program-Level (Local) Work Practices			
DOE Order 414.1D/SD 330 Requirements	LANL Work Practice	Local Implementing Procedure or QAP section (if applicable)	
CRD Attach. 2, 1. Criterion 1 – Management/Program	LANL organization chart; SD100, Integrated Safety Management System Description; PD100, DOE/NNSA Approved Los Alamos National Laboratory; 10 CFR 851, Worker Safety and Health Program	EPC-CP organization chart; EPC-DO-QP-100; EPC-CP-IWD-2102	
CRD Attach. 2, 2. Criterion 2 – Management/Personnel Training and Qualification	PD781, Training Program Management; P1040, Software Quality Management	EPC-CP-QAP-001; EPC-CP Manager Qualification Standard EPC-CP Group Qualification Standard EPC-CP-QS-2005; EPC-CP-QS-2006; EPC-CP-QS-2007	
CRD Attach. 2, 3. Criterion 3 – Management/Quality Improvement	P101-18, Procedure for Pause/Stop Work; PD322-4, Issues Management; PD324, LANL Metrics Program; P330-6, Nonconformance Control and Reporting	EPC-CP-QAP-001	
CRD Attach. 2, 4. Criterion 4 – Management/Document and Records	PD1020, Document Control and Records Management	ADESH-QAP-001; ESH-AP-006; ESH-AP-007; EPC-CP-QP-0901	
CRD Attach. 2, 5. Criterion 5 – Performance/Work Processes	 SD100, Integrated Safety Management System Description Document with embedded 10 CFR 851 Worker Safety and Health Program; PD100, DOE/NNSA Approved Los Alamos National Laboratory; 10 CFR 851 Worker Safety and Health Program Description; P151-1, LANL Packaging and Transportation Program Procedure; PD311, Requirements System and Hierarchy; 	EPC-CP-PIP-2101, NPDES Multi-Sector General Permit Program Implementation Plan; EPC-CP-TP-2102, Installing, Setting Up, and Operating ISCO Samplers; EPC-CP-TP-2103, Inspecting ISCO Stormwater Runoff Samplers and Retrieving Samples; EPC-CP-QP-2104, Installing, Inspecting, and Maintaining MSGP Single Stage Samplers	

Summary of QA Requirements and Program-Level (Local) Work Practices			
DOE Order 414.1D / SD 330 Requirements	LANL Work Practice	Local Implementing Procedure or QAP section (if applicable)	
	SD330, Los Alamos National Laboratory Quality Assurance Program;	EPC-CP-QP-2105, MSGP Stormwater Visual Assessments;	
	PD340, Conduct of Engineering for Facility Work;	EPC-CP-QP-2106, Processing MSGP Stormwater Samples;	
	P315, Conduct of Operations Manual; P330-2, Control and Calibration of Measuring and Test Equipment (M&TE);	EPC-CP-QP-2107, Preparing Discharge Monitoring Reports for the NPDES Multi- Sector General Permit;	
	SD601, Conduct of Research and Development;	EPC-CP-QP-2108, <i>MSGP</i> Routine Facility Inspections;	
	PD781, Training Program Management P1040, Software Quality Management	EPC-CP-QP-2109, <i>MSGP Corrective Actions</i> ;	
		EPC-CP-QP-2110, MSGP Stormwater Pollution Prevention Plan Preparation and Maintenance	
CRD Attach. 2, 6. Criterion 6 – Performance/Design	For Facility Work: PD340, Conduct of Engineering and Configuration Management for Facility Work;	No local implementing procedures, LANL Work Practices apply.	
	P341, Facility Engineering Processes Manual;		
	P342, <i>Engineering Standards;</i> Engineering Standards Manual; Functional Series documents; Engineering Administrative Procedures		
	<u>For R&D:</u> PD370, Conduct of Engineering for Research and Development (R&D)		
CRD Attach. 2, 7. Criterion 7 – Performance/Procurement	P840-1, Quality Assurance for Procurements ¹	No local implementing procedures, LANL Work Practices apply.	
CRD Attach. 2, 8. Criterion 8 – Performance/Inspection and Acceptance Testing	P330-8, Inspection and Test ³ ; P330-2, Control and Calibration of Measuring and Test Equipment (M&TE)	No local implementing procedures, LANL Work Practices apply.	

Summary of QA Requirements and Program-Level (Local) Work Practices				
DOE Order 414.1D / SD 330 Requirements LANL Work Practice		Local Implementing Procedure or QAP section (if applicable)		
CRD Attach. 2, 9.	PD328, LANL Assessment Program;	ADESH-QAP-001		
Criterion 9 –	P328-3, Management Assessment;	EPC-CP-QAP-001		
Assessment/Management Assessment	P328-4, Management Observation and Verification			
CRD Attach. 2, 10.	PD328, LANL Assessment Program;	No local implementing procedures, LANL		
Criterion 10 –	P328-2, Independent Assessment;	Work Practices apply.		
Assessment/Independent Assessment	P328-4, Management Observation and Verification			
CRD Attach. 3, Suspect/Counterfeit Items Prevention	P330-9, Suspect/Counterfeit Items (S/CI) ¹	No local implementing procedures, LANL Work Practices apply.		
CRD Attach. 4, Safety	P1040, Software Quality Management ² ;	No local implementing procedures, LANL		
Software Quality Assurance Requirements for Nuclear Facilities ²	Form 2033, Safety Non-Safety Software Determination, Categorization, and Software Risk Level	Work Practices apply.		
¹ S/CI prevention is also integrated into other listed work processes. Application of the S/CI oversight and prevention process is commensurate with the facility/activity hazards and mission impact. The extent of applicability of S/CI prevention for ML-4 items is as described in P840-1, <i>Quality Assurance for Procurements</i> , and P330-9, <i>Suspect/Counterfeit Items (S/CI)</i> .				
² DOE Order 414.1D, Chg 1, <i>Quality Assurance</i> , Attachment 1 requires that all software meet the applicable quality assurance requirements in Attachment 2 of DOE Order 414.1D, Chg 1, using a graded approach. LANL uses risk levels to grade safety software and risk significant non-safety software. See P1040, Software Quality Management, for additional detail.				
³ For ML-4 items and activities, inspections and tests are performed to extent required by the applicable codes and/or standards.				

⁴ Core work practices applicable to R&D are described in SD601, *Conduct of Research and Development*.

NPDES Multi-Sector General	No: EPC-CP-PIP-2101	Page 35 of 35
Permit	Revision: 1	Effective Date: 10/20/2021

Attachment 2: MSGP Facilities Associated with Industrial Activities

(Page 1 of 1)

MSGP Facilities Associated with Industrial Activities						
PermittedPermittedAssessmentLocationFacilityOperationActivitySectorUnitCany						Canyon
TA-3-38	TA-3-38 Metals Fab Shop	Metal Shop	Fabricated metal products	AA1	NM-9000.A_047	Sandia
TA-09- 0214	TA-09-0214 Metal Fabrication Shop	Metal Shop	Fabricated metal products	AA1	NM-128.A_16	Arroyo de la Delfe
TA-16	Stockpile Area	Materials Storage	Materials storage	P1	NM-128.A_01	Canyon de Valle
TA-60	TA-60 Asphalt Batch Plant	Asphalt Batch Plant	Asphalt paving	D1	NM-9000.A_042	Mortandad
TA-60	TA-60 MRF	Materials Recycling Facility	Scrap recycling	N2	NM-9000.A_047	Sandia
TA-60	TA-60 Roads and Grounds	Roads and Grounds Facility	Vehicle maintenance and storage	P1	NM-9000.A_042 NM-9000.A_047	Mortandad Sandia
TA-60-1	TA-60-1 Heavy Equipment Yard	Motor Pool and Metal Shop	Vehicle maintenance and fabricated metal products	P1 and AA1	NM-9000.A_047	Sandia
TA-60-2	TA-60-2 Warehouse	Warehousing	Vehicle fueling	P1	NM-9000.A_047	Sandia

ATTACHMENT 16: EPC-CP-QP-2108, MSGP ROUTINE FACILITY INSPECTIONS

EPC-CP-QP-2108		Revision: 0		
Effective Date: 07/0	Effective Date: 07/09/2020 Next Rev		Date: 07/09/2023	EST.1943
Environment, Safety, Health, Quality, Safeguards, and Security Directorate				
Environment Protection and Compliance – Compliance Programs Group				
Quality Proce	edure			
	MSGI	P Routine	Facility Inspecti	ons
Hazard Grading:	🛛 Low [Moderate	High/Complex	
Usage Level:	Reference [UET	Mixed: UET Sections:	
Status:	 □ New [Major Revision	Minor Revision	
	Review w/No C	Review w/No Changes		at & numbering system
Safety Basis:		Jusq		
·			r/Subject Matter Expert:	
Name:		Organization:	Signature:	Date:
Holly L. Wheeler		EPC-CP	Signature on File	07-08-20
	Derivative	Classifier:	Unclassified or 🗌	
Name:		Organization:	Signature:	Date:
Steven E. Wolfel		EPC-CP	Signature on File	07-08-20
		Approv	al Signatures:	
EPC-CP Reviewer:		Organization:	Signature:	Date:
Alethea Banar		EPC-CP	Signature on File	07-08-20
EPC-CP RLM:		Organization:	Signature:	Date:
Terrill W. Lemke, Te	am Leader	EPC-CP	Signature on File	07-08-20
EPC-CP RLM:		Organization:	Signature:	Date:
Taunia Van Valkenb	urg, Group Leader	EPC-CP	Signature on File	07-09-20
This copy is uncontrolled. Users are responsible for ensuring they work to the latest approved version. To document a required read, Login to <u>UTrain</u> , and go to the Advanced Search.				

MSGP Routine Facility	No: EPC-CP-QP-2108	Page 2 of 21
Inspections	Revision: 0	Effective Date: 07/09/2020

REVISION HISTORY

Document Number and Revision [Include revision number, beginning with Revision 0]	Effective Date [Document Control Coordinator inserts effective date]	Description of Changes [List specific changes made since the previous revision]
EPC-CP-QP-023 R0	05/17/2018	New Document. Process formerly part of procedure ENV-RCRA-QP-022 R2, <i>MSGP Corrective Actions</i> .
EPC-CP-QP-023 R1	03/07/2019	Added question to inspection form, associated text to document, and renumbered steps. Removed reference to Los Alamos National Security, LLC. Added reference to LANL BMP Manual. Minor edits made.
EPC-CP-QP-2108, R0	07/09/2020	Supersedes EPC-CP-QP-023 R1. Reformat to new EPC-CP template, re-number procedure and forms to new EPC-CP procedure numbering system, and other edits.

MSGP Routine Facility	No: EPC-CP-QP-2108	Page 3 of 21
Inspections	Revision: 0	Effective Date: 07/09/2020

Table of Contents

Revis	ion Hi	story	2
1.0	Intro	duction	4
	1.1	Purpose	4
	1.2	Scope	4
	1.3	Applicability	4
2.0	Roles	s and Responsibilities	4
	2.1	EPC-CP MSGP Stormwater Permitting and Compliance Team	5
	2.2	Deployed Environmental Professionals	
	2.3	EPC-CP Stormwater Permitting and Compliance Team Leader	6
	2.4	EPC-CP Group Leader	6
	2.5	DESH Manager	6
3.0	Preca	autions and Limitations	7
	3.1	Precautions	7
	3.2	Limitations	7
4.0	Prere	equisite Actions	8
	4.1	Planning and Coordination	8
	4.2	Special Tools, Equipment, Parts, and Supplies	8
5.0	MSG	P Routine Facility Inspections	9
	5.1	Conducting the Inspection	. 10
	5.2	Completing the Inspection Form	. 12
	5.3	Completing the Certification Statement	. 13
6.0	Train	ing	. 14
7.0	Reco	rds	. 14
8.0	Defir	nitions and Acronyms	. 15
	8.1	Definitions	. 15
	8.2	Acronyms	. 15
9.0	Refe	rences	.15
10.0	Atta	chments	. 15
	Atta	chment 1: Screenshot Examples of EPC-CP-QP-2108 R0 Form 1, MSGP Routine Facility Inspection	on in
		MC Express	. 16
	Atta	chment 2: MSGP Routine Facility Inspection Hard Copy Example, EPC-CP-QP-2108 R0 Form 1	.19

MSGP Routine Facility	No: EPC-CP-QP-2108	Page 4 of 21
Inspections	Revision: 0	Effective Date: 07/09/2020

1.0 INTRODUCTION

The National Pollutant Discharge Elimination System (NPDES) Multi-Sector General Permit (MSGP), also referred to as the permit, contains specific environmental requirements for inspecting areas of Los Alamos National Laboratory (LANL) covered by the permit. This includes areas where industrial materials or activities are exposed to stormwater, areas identified as potential pollutant sources, areas where leaks and spills have occurred in the past three years, discharge points, and control measures used to comply with the effluent limits of the MSGP.

LANL inspectors and facility personnel are required to perform routine facility inspections for industrial stormwater discharge on LANL areas covered by the MSGP at least quarterly and document observations. Conditions (as described by the MSGP) found during an inspection, requiring a corrective action(s), are managed through EPC-CP-QP-022, *MSGP Corrective Actions*.

1.1 Purpose

Part 3.1 of the MSGP contains specific requirements for conducting and documenting periodic industrial routine facility inspections. This procedure governs the activities of personnel involved in conducting industrial routine facility inspections. It also contains information and specific steps to be used for identifying and documenting conditions in order to meet the permit requirements.

1.2 Scope

Requirements set forth in this document apply to personnel responsible for meeting the permit conditions on behalf of LANL industrial facilities covered by the MSGP. The MSGP requires periodic inspection of facilities and identification, documentation, and reporting of conditions, including those requiring corrective actions.

Inspections conducted under this procedure are documented using the Maintenance Connection Express[™] (MC Express) web application on a tablet or notebook style computer. (In the event of electronic hardware or web application failure, personnel may use a printed hard copy to conduct the inspection.)

1.3 Applicability

This procedure applies to Environmental Protection and Compliance–Compliance Programs (EPC-CP) technical staff, Deployed Environmental Professionals (DEPs), and other LANL staff who conduct inspections and monitoring activities at MSGP regulated LANL facilities.

2.0 ROLES AND RESPONSIBILITIES

Specific roles and responsibilities for implementation of requirements contained in this procedure are provided below.

MSGP Routine Facility	No: EPC-CP-QP-2108	Page 5 of 21
Inspections	Revision: 0	Effective Date: 07/09/2020

2.1 EPC-CP MSGP Stormwater Permitting and Compliance Team

EPC-CP MSGP Stormwater Permitting and Compliance personnel are fully knowledgeable of the specific regulatory requirements identified in the MSGP and are responsible for the following:

- Implementing this procedure;
- Performing routine facility inspections the last month or quarter of the year at regulated sites [depending on inspection frequency identified in site-specific Stormwater Pollution Prevention Plans (SWPPPs)];
- Performing "no exposure" site inspections once a year to ensure conditions of the "no exposure" exclusion are met;
- Performing routine facility inspections at inactive sites once a year;
- Identifying issues requiring a corrective action during any of the above inspections or assessments;
- Determining a condition of non-compliance;
- Notifying managers or legal counsel of non-compliances;
- Modifying the site-specific MSGP Routine Facility Inspection Forms (e.g., add or remove Best Management Practices (BMPs));
- Training personnel to use MC Express;
- Performing a quality review of routine facility inspections and "no exposure" site inspections; and
- Assisting customers with issues associated with MC Express.

2.2 Deployed Environmental Professionals

DEPs are responsible for the following:

- Implementing this procedure;
- Knowledgeable of the requirements contained in site-specific SWPPPs within their assigned Facility Operations Directorate (FOD);
- Meeting qualification requirements identified in the Quality Assurance Project Plan EPC-CP-PIP-2101, NPDES *Multi-Sector General Permit Program Implementation Plan*;
- Being trained on EPC-CP-QP-022, *MSGP Corrective Actions;*
- Being trained to MSGP Routine Inspections OJT;
- Being familiar with industrial site and facility operations assigned to them so that they minimize sources of pollutants and pro-actively maintain controls to prevent issues that require corrective action;

MSGP Routine Facility	No: EPC-CP-QP-2108	Page 6 of 21
Inspections	Revision: 0	Effective Date: 07/09/2020

- Performing routine facility inspections throughout the year at regulated sites within their FOD (depending on inspection frequency identified in site-specific SWPPPs) and documenting results accurately;
- Acting as liaison between the FOD, Deployed Environment, Safety, and Health (DESH) Manager and facility/operations personnel to ensure corrective actions are addressed appropriately by overseeing maintenance and/or installation of additional controls;
- Educating appropriate facility/operations personnel on the MSGP and site-specific SWPPPs so they successfully implement the conditions of the permit; and
- Notifying EPC-CP MSGP stormwater personnel when additional or substitute BMPs have been installed or old BMPs have been removed so the site-specific MSGP Routine Facility Inspection Form can be modified.

2.3 EPC-CP Stormwater Permitting and Compliance Team Leader

The EPC-CP Stormwater Permitting and Compliance Team Leader is responsible for compliance oversight relative to the MSGP. The Team Leader works with the EPC-CP Group Leader to ensure adequate resources needed to implement the regulatory requirements identified in the MSGP are identified and environmental risks are assessed. The Team Leader will notify upper management of these required resources or environmental risks, as deemed necessary. In the event there is a dispute regarding the regulatory requirements contained in the MSGP, the Team Leader makes the final determination of the required action. The Team Leader notifies upper management of instances of non-compliance with the permit.

2.4 EPC-CP Group Leader

The EPC-CP Group Leader or designee is responsible for ensuring there are adequate resources to implement the regulatory requirements identified in the MSGP. The Group Leader or Team Lead also acts as the duly authorized signatory that certifies the Annual Report and MSGP Routine Facility Inspections conducted by EPC-CP personnel. The Group Leader notifies upper management of instances of non-compliance with the permit or other identified environmental risk.

2.5 DESH Manager

The DESH manager works with programmatic entities and the FOD to identify adequate resources for their industrial facilities to ensure permit requirements can be implemented. The DESH Manager is responsible for the performance of DEPs under their management and to ensure DEPs are trained and qualified. They also provide oversight by ensuring that industrial facilities complying with the MSGP and will notify upper management of instances of non-compliance with the permit or other identified environmental risk.

3.0 PRECAUTIONS AND LIMITATIONS

3.1 Precautions

The hazard rating for the activities described in this procedure is <u>LOW</u> and therefore, does not require an Integrated Work Document (IWD).

Personnel must wear appropriate clothing (e.g., boots, long pants, etc.) to perform work in the field.

Work may be discontinued during periods or conditions that make sites dangerous for worker safety or prevent personnel from safely accessing sites (e.g., weather-related events such as flash floods, flooding, lightning, wildfires, hail, icy roads, deep snow, or LANL operations such as firing shots or burns).

If conditions prevent fieldwork, document the conditions on the work order. Multiple attempts can be documented on the original form. If the target date cannot be met, the field personnel must contact the Program Lead no less than 24 hours before the target date for guidance.

3.2 Limitations

In MC Express, document responses to each question on a work order by clicking the expand arrow located on the right side of the task line and changing the "Complete" or "Failed" line to "Yes." When using a hard copy form, mark the appropriate "Yes" or "No" check box.

Throughout this process, the field personnel will document comments and notations in the "Comments" field of the associated task line. If field personnel need more space, additional comments can be entered in the "Labor Report Update" field (see Section 5.2) when the work order is updated to "Complete" status. When using a hard copy form, document comments on the corresponding task line. If additional space is needed, comments can be entered in the "Labor Report" section at the bottom of the form.

Some terminology varies between the MC Express software and the Maintenance Connection (MC) desktop software.

- The "Reading" field in MC Express is the same field as "Reading Final" in MC desktop and "Meas." on a hard copy (printed) work order.
- The "Complete" option in MC Express is the same as a "Yes" answer; the "Failed" option in MC Express is the same as a "No" answer. MC desktop and hard copy (printed) work orders use "Yes" and "No" terminology.

Click the "Save" bar after all entries for a task line question have been completed and before proceeding to the next task line question. Failure to "Save" results in lost data entries.

4.0 PREREQUISITE ACTIONS

4.1 Planning and Coordination

- 1. Schedule work to be completed by the target date appearing on the inspection form or as requested by the MSGP Program Lead if an inspection form is not issued.
- 2. Inform (e.g., by e-mail) facility contacts (as needed) of the schedule for facility inspection work and locations up to a week (preferred) before but no later than the day before (for minor changes) to be added to the appropriate plan of the day (as necessary).
- 3. Gather the necessary equipment (see Section 4.2) for the work to be done.
- 4. Using the Safari or Chrome web browser on a tablet or notebook style computer, log into the MC Express application (http://express.maintenanceconnection.com) and confirm that the work order list displayed matches your sites. If the work order lists do not match, contact EPC-CP Data Management personnel for clarification.
- 5. In MC Express, click on the appropriate work order number to open the work order. The work order will open in the display to the Work Order Summary page.
- 6. Click on the "Tasks" bar to navigate to the work order Tasks page. See MC Express screen shot examples in Attachment 1.
- 7. Always log out of MC Express when you have finished work OR if work is interrupted.

4.2 Special Tools, Equipment, Parts, and Supplies

Ensure the following equipment is available.

- Sturdy hiking boots or steel-toed shoes with soles that grip.
- Facility-specific PPE as required by IWD Part II.
- Cell phone (Only government cell phones are allowed in secure areas. See https://int.lanl.gov/policy/documents/P217.pdf for requirements for using portable electronic devices on Laboratory property.)
- Copy of this procedure.
- Copy of facility specific SWPPP and map(s) (as needed).
- Current electronic or paper inspection form EPC-CP-QP-2108 R0 Form 1, *MSGP Routine Facility Inspection*.
- LANL issued tablet or notebook style computer with Safari web browser and Blackberry UEM[™] app (see <u>https://int.lanl.gov/policy/documents/P217.pdf</u> for requirements for using portable electronic devices on Laboratory property).
- Necessary access keys.

MSGP Routine Facility	No: EPC-CP-QP-2108	Page 9 of 21
Inspections	Revision: 0	Effective Date: 07/09/2020

5.0 MSGP ROUTINE FACILITY INSPECTIONS

MSGP routine facility inspections are conducted by the DEP or other qualified facility personnel (as defined in the MSGP or as determined by MSGP Program Lead) during periods when the facility is in operation and during standard operating hours. Results of visual and analytical monitoring for the past year must be considered when planning and conducting an inspection. The inspections are performed on the following facility areas:

- Areas where industrial materials or activities are exposed to stormwater;
- Areas identified in the SWPPP and those that are potential pollutant sources;
- Areas where spills and leaks have occurred in the past;
- Discharge points; and
- Control measures used to comply with the effluent limits contained in the MSGP.

Routine facility inspections are conducted at least quarterly; however, some facilities may conduct monthly inspections (as specified in the facility specific SWPPP). At least once each calendar year, the routine facility inspections must be conducted during a period when stormwater discharge (either rain or snow) is occurring. During the inspection, you must look for the following:

- Industrial materials, residue or trash that may have or could come into contact with stormwater;
- Leaks or spills from industrial equipment, drums, tanks and other containers;
- Offsite tracking of industrial or waste materials, or sediment where vehicles enter or exit the site;
- Tracking or blowing of raw, final or waste materials from areas of "no exposure" to exposed areas; and
- Control measures that need replacement, maintenance or repair.

Conditions requiring corrective action identified during an inspection, monitoring, or other means must be entered into the MSGP Corrective Action Report database by the DEP(s), EPC-CP stormwater personnel and/or other qualified facility personnel (as defined in the MSGP or as determined by MSGP Program Lead). Follow the process in EPC-CP-QP-022, *MSGP Corrective Actions* to address issues found during an inspection.

If the industrial facility is inactive and unstaffed and there are no industrial materials or activities exposed to stormwater, routine inspections may not be required. A determination of whether a facility is inactive or unstaffed is made in coordination with stormwater personnel from EPC-CP, as there are specific documentation and certification requirements that have to be met prior to discontinuing routine inspections. Such a facility is only required to conduct an annual site inspection.

If the industrial facility is eligible for a "no exposure" exclusion, routine inspections are no longer required. A condition of "no exposure" exists when all industrial materials and activities are

MSGP Routine Facility	No: EPC-CP-QP-2108	Page 10 of 21
Inspections	Revision: 0	Effective Date: 07/09/2020

protected by a storm resistant shelter (e.g., moved to an indoor location) to prevent exposure to rain, snow, snowmelt, and/or runoff. A determination of whether a facility is eligible for "no exposure" status is made in coordination with stormwater personnel from EPC-CP, as there are specific documentation and certification requirements that have to be met prior to discontinuing routine inspections. Such a facility is only required to conduct an annual site evaluation and recertification every five years.

5.1 Conducting the Inspection

See Attachment 1 for screen shot examples of EPC-CP-QP-2108 R0 Form 1, *MSGP Routine Facility Inspection* in MC Express. See Attachment 2 for an example of the inspection form in hard copy format. **Questions will be answered "Yes/Complete" or "No/Failed" unless the instructions specify "N/A" may also be used.**

- **NOTE:** Each item number listed in red font below corresponds to a red numbered box on both screenshots and hard copy format.
 - [1] **ITEM 1**: Observe the weather at time of inspection. Document the weather and temperature in the "Comments" field of the task line (e.g., Temp. 78°F, sunny, wind less than 5mph).
 - ITEM 2: Observe and document the facility is free of previously unidentified discharges from and/or pollutants that have occurred since the last inspection. Describe any new discharges and the specific location in the "Comments" field of the task line.
 - [3] **ITEM 3**:

<u>IF</u> the response to ITEM 2 is "Yes", <u>THEN</u> answer this task line as "N/A".

OR

IF the response to ITEM 2 is "No",

<u>THEN</u> answer this task line as "Yes" and document the corrective action previously initiated for the discharge.

- [4] **ITEM 4**: Check the facility is free of discharges of pollutants at the time of inspection. Describe any pollutant discharge and the specific location in the "Comments" field of the task line.
- [5] **ITEM 5**: Check the facility is free of evidence of pollutants entering the drainage system OR the potential for pollutants entering the drainage system. Describe any discharge or potential discharge and the specific location in the "Comments" field of the task line.
- [6] **ITEM 6**: Check the outfall does not have any **new** evidence of erosion **since the last inspection**. Describe any erosion observed in the "Comments" field of the task line.

MSGP Routine Facility	No: EPC-CP-QP-2108	Page 11 of 21
Inspections	Revision: 0	Effective Date: 07/09/2020

- [7] **ITEM 7**: Check all flow dissipation devices are operating effectively and are not in need of repair. Describe any non-functional status of devices in the "Comments" field of the task line (e.g., repair berm, replace rip rap, etc.).
- [8] **ITEM 8**: Check the outfall is free of evidence of pollutants in the discharge and/or the receiving water. Describe any pollutants observed in the "Comments" field of the task line (e.g., sediment from nearby erosion, etc.).
- [9] **ITEM 9**: Check the outfall is free of unauthorized non-stormwater discharges. Describe any unauthorized discharges observed in the "Comments" field of the task line (e.g., street sweeper emptied contents at Outfall 001, etc.).
- [10] Repeat Steps 6 through 9 for each outfall shown on the work order, if the location has more than one outfall.
- [11] **ITEM 10**: Check each control measure is operating effectively. Describe any nonoperational condition of the control measure (e.g., erosion, damage, etc.,) and if the control measure needs maintenance, repair, or replacement in the "Comments" field of the task line.
 - [a] Determine if additional controls are necessary, or that existing controls are insufficient and require replacement with a different type of control.
 - [b] The DEPs are responsible for the selection and oversight of proper installation of appropriate control measures per guidance provided in the LANL Stormwater BMP Manual.
- [12] Repeat Step 11 for each control measure shown on the work order, if the location has more than one control measure.
- [13] **ITEM 11**: Check each sector of NPDES specified industrial area/activity is inspected for exposure to stormwater (e.g., metal fabrication; foundry operations; power generation; asphalt production; fabricating timber products; material recycling; warehouse and transportation activity; treatment and storage of hazardous waste).
 - [a] Determine if the control measures associated with each industrial area/activity are appropriate for the activity, effectively controlling stormwater exposure, and operating.
 - [b] Describe any non-operational condition of the control(s) and needed maintenance or a description of corrective actions in the "Comments" field of the task line.
 - [c] For industrial activities that do not occur at the facility, select "N/A" on that task line.
- [14] Repeat Step 13 for each industrial area/activity shown on the work order, if the facility has more than one sector of NPDES specified industrial area/activity.

MSGP Routine Facility	No: EPC-CP-QP-2108	Page 12 of 21
Inspections	Revision: 0	Effective Date: 07/09/2020

- [15] **ITEM 12**: Check the facility is free of any incidence of non-compliance not documented elsewhere on the inspection form. Describe any additional incidences of non-compliance in the "Comments" field of the task line.
- [16] **ITEM 13**: Check the facility meets the MSGP requirements with existing control measures. Describe any additional control measures needed to comply with the Permit.
- [17] After all task lines have been completed, make sure you have clicked the "Save" bar at the bottom of the page.

5.2 Completing the Inspection Form

See Attachment 1 for completing EPC-CP-QP-2108 R0 Form 1 in MC Express and Attachment 2 for a hard copy example.

- [1] Ensure the inspection form has been filled out completely.
- [2] Click the "Back" arrow button in the upper left hand corner to exit the work order Tasks page and return to the Work Order Summary page.
- [3] Click the checkered flag A in the upper right corner of the work order Summary page to open the Work Order Status Update page. MC Express auto-populates the date and time fields.

CAUTION

MC Express automatically changes the work order status to "Closed."

- [4] **ITEM 14**: Click on the expand arrow located on the right side of the "New Status" field and select "Completed" from the available dropdown menu.
 - [a] Ensure the date and time that is auto-populated are the date and time that the work was completed and *not* the date/time the form was filled out.
 - [b] <u>IF</u> work needs to be performed over multiple days, <u>THEN</u> note the date and time the work began in the Labor Report field.
 - [c] To update the date or time, click the "Date" field and make necessary adjustments using the available timestamp application. Click "Set" to apply changes.
 - [d] <u>IF</u> using a hard copy form, <u>THEN</u> write the date and time the work was completed.
- [5] **ITEM 15**: The field personnel must type or write his/her name in the "Labor Report Update" field.
- [6] Additional notes, observations, or site conditions not documented in a task line "Comments" field can be documented in the "Labor Report Update" field.

MSGP Routine Facility	No: EPC-CP-QP-2108	Page 13 of 21
Inspections	Revision: 0	Effective Date: 07/09/2020

- [7] Scroll down the page to the "Signature" bar and click the expand arrow on the left side of the bar to open the "Signature" field.
 - [a] **ITEM 16**: Capture an electronic signature by drawing with a finger on the tablet screen.
 - **NOTE:** The mouse must be used to sign electronically when using MC Express on a desktop screen (not a tablet).
 - [b] If using a hard copy form, the field personnel will sign his/her name and write in the date of when the form was signed.
 - [c] By electronically signing the work order, field personnel certifies that the information submitted is "true, accurate, and complete."
- [8] Click on the "Save" bar at the bottom of the page to close the "Signature" field.

5.3 Completing the Certification Statement

Follow Steps 1 through 5 in this section if the inspection form was completed electronically (see Attachment 1). If the inspection form was completed on a hard copy form, skip to Step 6.

- Using the Chrome web browser on a desktop computer, navigate to <u>http://www.maintenanceconnection.com</u>. Log into the MC desktop application using your login credentials.
- [2] Click "Open" in the tool bar at the top of the page to open the MC module selections. Click on the "Work Orders" module.
- [3] Click on the "Search" tab at the top left of the page.
 - [a] Enter the work order number in the "Search Value" field.
 - [b] Click the arrow to the right of the "Search Value" field to open the work order in the right split screen.
- [4] Click on the "Report" tab at the top of the page and click the "Work Order Statement" sub-tab.
- [5] Click the Tools drop down menu in the top right corner of the page.
 - [a] Select "Print" from the options.
 - [b] When the print dialog box opens, select the print options as appropriate for your local printer.
- [6] **ITEM 17**: Obtain a printed name and title, signature, and date on the certification statement.

The certification statement will be signed no more than 14 days after completion of the inspection and a copy sent to the EPC-CP Program Lead or designee.

MSGP Routine Facility	No: EPC-CP-QP-2108	Page 14 of 21
Inspections	Revision: 0	Effective Date: 07/09/2020

- [a] The routine facility inspection form must be certified with a signature from a manager that meets the definition of a signatory in MSGP Permit Section
 B.11.A (e.g., FOD, Operations Manager, DSESH Group Leader, EPC-CP Group Leader, EPC-CP Team Lead).
- [b] The manager is certifying the information submitted is "true, accurate, and complete" by signing the inspection form.
- [7] Attach the completed, signed, and certified inspection form to the facility SWPPP.
- [8] Submit a copy of the completed form to the MSGP Program Lead.

6.0 TRAINING

The following personnel require training before implementing this procedure.

- DESH Group and Team Leaders
- EPC-CP MSGP stormwater compliance personnel
- DEPs
- Other personnel identified as being required to conduct stormwater assessments as part of their job duties

All EPC-CP personnel that execute the activities specified in this procedure must meet the minimum qualification and training requirements for their position as identified EPC-CP-PIP-2101, NPDES *Multi-Sector General Permit Program Implementation Plan*. This will include "self-study" (required reading) for this procedure as assigned and documented in accordance with ADSH-TPP-301, *ADESH Training Program Plan*.

Contract personnel that execute the activities specified in this procedure will be qualified and trained as required by the Exhibit D and Exhibit F. In addition, contract personnel will be required to complete "self-study" (required reading) of this procedure.

7.0 RECORDS

MSGP Routine Facility Inspection forms are signed and certified by individual LANL facilities. These completed forms are maintained in the facility's SWPPP and managed by the facility's document management system. The MSGP team may retain a copy for reference purposes.

Below are records generated as a result of implementing this procedure. Records generated are identified by title and type.

Record Title	QA Record	Non-QA Record
EPC-CP-QP-2108 R0 Form 1, MSGP Routine Facility Inspection	\boxtimes	

8.0 DEFINITIONS AND ACRONYMS

8.1 Definitions

See LANL <u>Definition of Terms</u>.

Best Management Practice (BMP) – Schedules of activities, prohibitions of practices, maintenance procedures, and other management practices to prevent or reduce the pollution of "waters of the United States." BMPs also include treatment requirements, operating procedures, and practices to control plant site runoff, spillage or leaks, sludge or waste disposal, or drainage from raw material storage (*40 CFR Part 122.2*).

Control Measure – Any BMP or other method (including effluent limitations) used to prevent or reduce the discharge of pollutants to waters of the United States.

8.2 Acronyms

See LANL Acronym Master List.

BMP	Best Management Practice
EPC-CP	Environmental Protection and Compliance – Compliance Programs
DEP	Deployed Environmental Professional
DESH	Deployed Environment, Safety, and Health
FOD	Facility Operations Director
LANL	Los Alamos National Laboratory
MC	Maintenance Connection
MC Express	Maintenance Connection Express
MSGP	Multi-Sector General Permit
NPDES	National Pollutant Discharge Elimination System
SWPPP	Stormwater Pollution Prevention Plan

9.0 REFERENCES

Federal Register, Final National Pollutant Discharge Elimination System (NPDES) General Permit for Stormwater Discharges from Industrial Activities. Federal Register: June 16, 2015, Volume 80, Number 115.

Los Alamos National Laboratory Storm Water BMP Manual

10.0 ATTACHMENTS

Attachment 1: Screenshot Examples of EPC-CP-QP-2108 R0 Form 1, MSGP Routine Facility Inspection in MC Express

Attachment 2: EPC-CP-QP-2108 R0 Form 1, MSGP Routine Facility Inspection Hard Copy Example

MSGP Routine Facility	No: EPC-CP-QP-2108	Page 16 of 21
Inspections	Revision: 0	Effective Date: 07/09/2020

Attachment 1: Screenshot Examples of EPC-CP-QP-2108 R0 Form 1, *MSGP Routine Facility Inspection* in MC Express

(Page 1 of 3)

Work Order Tasks Page (Section 5.1, Steps 1-5)

-		MC Express		
WORK ORDER: MSG Tasks	P-RI-52112		Pa	•
Tasks 🕥 🤇			Q	
Weather Informat	tion			
20 Describe the v	weather at time of inspection and	d document the temperature (F°).		*
Within the Facilit	y Boundary			
40 2 Is the facility	free of previously unidentified d	ischarges from and/or pollutants that have occurr	ed since the last inspection if "No" describe.	*
50 3 If "No" has a C	AR been previously initiated for	this new discharge?		*
60 4 Is the facility	free of discharge of pollutants at	t the time of inspection? If "No" describe.		*
70 Is the facility	free of evidence of, or the poter	ntial for, pollutants entering the drainage system.	If "No" describe.	+
0	Refresh	1 <u>0</u>	List	

Work Order Tasks Page (Section 5.1, Steps 6-9)

-		MC Express		
WORK ORDE	R: MSGP-RI-52112		1950	•
		maintenance and repairs, failed control mea ption of corrective actions in relevant task c		nt)
	of Evidence of Erosion? If "No", :: [074] Monitored Outfall	, describe.		4
	Dissipation Devices Operating :: [074] Monitored Outfall	Effectively? If "No", describe.		4
	of Evidence of Pollutants in Di :: [074] Monitored Outfall	scharges and/or Receiving Water? If "No", describe.		4
	of any unauthorized non-storm :: [074] Monitored Outfall	water discharges? If "No" describe.		4
	of Evidence of Erosion? If "No", :: [073] Substantially Identical			4
	Dissipation Devices Operating :: [073] Substantially Identical			ł
	of Evidence of Pollutants in Di :: [073] Substantially Identical	scharges and/or Receiving Water? If "No", describe. Outfall		4
	of any unauthorized non-storm 1: [073] Substantially identical	water discharges? If "No" describe. Outfall		4
	Refresh	List		

MSGP Routine Facility	No: EPC-CP-QP-2108	Page 17 of 21
Inspections	Revision: 0	Effective Date: 07/09/2020

Attachment 1: Screenshot Examples of EPC-CP-QP-2108 R0 Form 1, *MSGP Routine Facility Inspection* in MC Express (cont.)

(Page 2 of 3)

Work Order Tasks Page (Section 5.1, Step 11)

()		MC Express		
WORK ORDER: MSGP-	RI-52112		A	•
		tenance and repairs, failed cor evant task comments).	ntrol measures that need replacmen	nt, or
180 Control Measure Asset: [03005030	is operating effectively? I 040002] Asphalt Berm	f "No" describe condition & need for /	Maintenance, Repair, or Replacement.	*
190 Control Measure Asset: [03005040		f "No" describe condition & need for $\ensuremath{\boldsymbol{\lambda}}$	Maintenance, Repair, or Replacement.	*
	is operating effectively? I 200004] EnviroSoxx w/ Me		Maintenance, Repair, or Replacement.	+
0	Refresh		List	

Work Order Tasks Page (Section 5.1, Step 13)

\leftarrow		MC Express		
WORK ORDER	R: MSGP-RI-52112		P	\odot
	ty exposed to stormwater (ide sk comment).	ntify needed mainteance or a de	escription of corrective actions in	
220 11 Materia	al loading/unloading and storage area	as: controls adequate (appropriate, effe	ective, and operating)? If "No" describe.	*
230 Transfe	er areas for substances in bulk: contr	ols adequate (appropriate, effective, a	nd operating)? If "No" describe.	<u>+</u>
240 Produc	t/chemical storage areas (raw mater	rial): controls adequate (appropriate, el	ffective, and operating)? If "No" describe	. <u>+</u>
250 Liquid	tank storage/secondary containment	:: controls adequate (appropriate, effec	tive, and operating)? If "No" describe.	+
i	Refresh		List	

MSGP Routine Facility	No: EPC-CP-QP-2108	Page 18 of 21
Inspections	Revision: 0	Effective Date: 07/09/2020

Attachment 1: Screenshot Examples of EPC-CP-QP-2108 R0 Form 1, *MSGP Routine Facility Inspection* in MC Express (cont.)

(Page 3 of 3)

Work Order Tasks Page (Section 5.1, Steps 15 and 16)

-		MC Express		
WORK ORDER: Tasks	MSGP-RI-52112		P	•
Non-Complia	nce			
400 12 Free of 1	incidents of observed non-complianc	e not already identified above? If "No"	describe.	*
Additional Co	ontrol Measures			
420 13 Are per	nit requirements satisfied with exist	ing control measure(s)? If "No" describe	additional control measures needed.	*
6	Refresh		List	

Work Order Status Update Page (Section 5.2, Steps 4-6)

(MC Express	
ORK ORDER: MSGP atus Update	-RI-52112	
Issued /	Completed	
New Status 1	4	
Completed		0
Date		
1/23/2019 10:39	AM	
Percent Comple	ete 100%	
Labor Report U	pdate 15	~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~
Select Comments		0
Jane Doe		
) c	ancel 🛷	Save

Work Order Status Update Page (Section 5.2, Step 7)

+	B	MC Express	
WORK OF Status Upd	RDER: MSGP-RI-	52112	
C Sig	nature 16		
(Remo	<u>2/(8)</u>		
	Jane	Dл	
5	Cancel		Save

MSGP Routine Facility	No: EPC-CP-QP-2108	Page 19 of 21
Inspections	Revision: 0	Effective Date: 07/09/2020

Attachment 2: MSGP Routine Facility Inspection Hard Copy Example, EPC-CP-QP-2108 R0 Form 1

(Page 1 of 3)

Work Order MSGP-RI-52112 Los Alamos National Laboratory MSGP Routine Inspection Printed 1/23/2019 - 12:45 PM (Duplicate Copy) Maintenance Details Requested By: Admin, Jane on Target: 12/31/2020 MSGP Program 1/23/2019 12:30:00 PM Priority/Type: / Inspection - RG121.9 Taken By: Banar, Alethea Department: Utilities and Infrastructure A-3-38 Carpenter Shop Procedure: MSGP Routine Facility Inspection (EPC-CP-Contact: Admin, Jane QP-2108 R0 Form 1) Phone: 123-4567 Last PM: N/A Reason: Example MSGP Routine Facility Inspection Tasks ŧť. Description Meas. No N/A Yes Weather Information 1 20 Describe the weather at time of inspection and document the temperature (F1) Within the Facility Boundary Is the facility free of previously unidentified discharges from and/or pollutants that have occurred 2 40 since the last inspection? If "No" describe. • 3 50 If "No" has a CAR been previously initiated for this new discharge? г 4 60 Is the facility free of discharge of pollutants at the time of inspection? If "No" describe Is the facility free of evidence of, or the potential for, pollutants entering the drainage 5 70 system. If "No" describe. Outfall Inspection (identify needed maintenance and repairs, failed control measures that need replacement, or a description of corrective actions in relevant task comment) 6 Monitored Outfall [074] Free of Evidence of Erosion? If "No", describe 90 E Monitored Outfall [074] Flow Dissipation Devices Operating Effectively? If "No", 7 100 describe Monitored Outfall [074] Free of Evidence of Pollutants in Discharges and/or Receiving 8 110 Water? If "No", describe Monitored Outfall [074] Free of any unauthorized non-stormwater discharges? If "No" 9 120 describe Substantially Identical Outfall [073] Free of Evidence of Erosion? If "No", describe 130 Substantially Identical Outfall [073] Flow Dissipation Devices Operating Effectively? If 140 "No", describe Substantially Identical Outfall [073] Free of Evidence of Pollutants in Discharges and/or Receiving Water? If "No", describe. 150 Substantially Identical Outfall [073] Free of any unauthorized non-stormwater 160 discharges? If "No" describe. п. Control Measures (identify needed maintenance and repairs, failed control measures that need replacment, or a 10 description of corrective actions in relevant task comments). Asphalt Berm [0300503040002] Control Measure is operating effectively? If "No" 180 describe condition & need for Maintenance, Repair, or Replacement Rip Rap [0300504060001] Control Measure is operating effectively? If "No" describe 190 condition & need for Maintenance, Repair, or Replacement. EnviroSoxx w/ MetalLoxx [0300503200004] Control Measure is operating effectively? If 200 "No" describe condition & need for Maintenance. Repair, or Replacement **D** Area/Activity exposed to stormwater (identify needed mainteance or a description of corrective actions in relevant task 11 comment). Material loading/unloading and storage areas: controls adequate (appropriate, effective, 220 and operating)? If "No" describe. Transfer areas for substances in bulk: controls adequate (appropriate, effective, and operating)? If "No" describe 230 E. EPC-CP-QP-2108 R0 Form 1

MSGP Routine Facility	No: EPC-CP-QP-2108	Page 20 of 21
Inspections	Revision: 0	Effective Date: 07/09/2020

Attachment 2: MSGP Routine Facility Inspection Hard Copy Example, EPC-CP-QP-2108 R0 Form 1 (cont.)

(Page 2 of 3)

240	Product/chemical storage areas (raw material): controls adequate (appropriate, effective, and operating)? If "No" describe.		п	
250	Liquid tank storage/secondary containment: controls adequate (appropriate, effective, and operating)? If "No" describe.	E.	E.	E
260	Industrial processing and finished product storage areas; controls adequate (appropriate, effective, and operating)? If "No" describe.			E
270	Equipment operation and maintenance areas: controls adequate (appropriate, effective, and operating)? If "No" describe.		П	Б
280	Fueling areas: controls adequate (appropriate, effective, and operating)? If "No" describe.	π	Π	Г
290	Outdoor vehicle and equipment washing areas: controls adequate (appropriate, effective, and operating)? If "No" describe	п	E	
300	Machinery: controls adequate (appropriate, effective, and operating)? If "No" describe		- E	101
310	Waste handling and disposal areas: controls adequate (appropriate, effective, and operating)? If "No" describe.			E
320	Erodible areas/construction: controls adequate (appropriate; effective, and operating)? If "No" describe.	. []		
330	Locations and sources of run-on to the site: controls adequate (appropriate, effective, and operating)? If "No" describe.		п	Г
340	Salt storage piles or pile containing salt controls adequate (appropriate, effective, and operating)? If "No" describe.	Ē		Г
350	Dust generation and vehicle tracking: controls adequate (appropriate, effective, and operating)? If "No" describe.	Π		E
360	Housekeeping (Industrial materials/residues/trash in contact with stormwater); controls adequate (appropriate, effective, and operating)? If "No" describe:			
370	Leaks and spills: controls adequate (appropriate, effective, and operating)? If "No" describe	E		n
380	Sector A [03005-] Wood processing, transport or treated wood storage areas: controls adequate (appropriate, effective, and operating)? If "No" describe		П	E
Non-C	ompliance			
400	Free of incidents of observed non-compliance not already identified above? If "No" describe		E	E
Andata	and Capital Measures			
420	Are permit requirements satisfied with existing control measure(s)? If "No" describe additional control measures needed.		п	n
	Report		-	_
Compl	eted: 1/23/2019 10:39:00 AM			
Report	: [Additional notes, observations, or site conditions not documented in Task Line Comments field]			
	Jane Doe			
	(w-LD of 1/23/2019			
l confir	Asignature / Name Date Signature / Name m the information as recorded is true, accurate and complete.	-	Date	
		EPC-CP-	QP-2108	R0 F

MSGP Routine Facility	No: EPC-CP-QP-2108	Page 21 of 21
Inspections	Revision: 0	Effective Date: 07/09/2020

Attachment 2: *MSGP Routine Facility Inspection* Hard Copy Example, EPC-CP-QP-2108 R0 Form 1 (cont.)

(Page 3 of 3)

CERTIFICATION STATEMENT

"I certify under penalty of law that this document and all attachments were prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gathered and evaluated the information submitted. Based on my inquiry of the person or persons who manage the system, or those persons directly responsible for gathering information, the information submitted is, to the best of my knowledge and belief, true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment for knowing violations".

(Signatory must meet definition in Section B.11.A, eg., FOD, Ops Mgr, DESH Group Leader, EPC Group Leader)

Date	
EPC-CP-QP-2108	R0 For
	EPC-CP-QP-2109

ATTACHMENT 17: EPC-CP-QP-022, MSGP CORRECTIVE ACTIONS

Revision: ${f 3}$



Effective Date: 12/20/2018

Environment, Safety, Health, and Quality, Safeguards and Security Directorate

Environmental Protection and Compliance Division – Compliance Programs

Quality Procedure

MSGP Corrective Actions

Document Owner/Subject Matter Expert:

Name:	Organization:	Signature:	Date:
Holly Wheeler	EPC-CP	Signature on File	12-19-18

Derivative Classifier: 🔀 Unclassified			
Name:	Organization:	Signature:	Date:
Jacob Meadows	EPC-CP	Signature on File	12-19-18

Approval Signatures:			
Subject Matter Expert:	Organization:	Signature:	Date:
Holly Wheeler	EPC-CP	Signature on File	12-19-18
Responsible Line Manager:	Organization:	Signature:	Date:
Terrill Lemke	EPC-CP Team Leader	Signature on File	12-20-18
Responsible Line Manager	Organization	Signature:	Date:
Taunia Van Valkenburg	EPC-CP Group Leader	Signature on File	12-20-18

This copy is uncontrolled.

Users are responsible for ensuring they work to the latest approved version. To document a required read, Login to <u>UTrain</u>, and go to the Advanced Search.

MSGP Corrective Actions	EPC-CP-QP-022	Page 2 of 31
WISGP COTTECTIVE ACTIONS	Revision: 3	Effective Date: 12/20/2018

Revision History

Document Number and Revision [Include revision number, beginning with Revision 0]	Effective Date [Document Control Coordinator inserts effective date]	Description of Changes [List specific changes made since the previous revision]
0	08/10	New Document.
1	11/10	Incorporated EPC-CP-QP-062 <i>MSGP Routine Inspections</i> into this document.
2	01/13	Biennial revision, new template implemented.
EPC-CP-QP-022 R3	12/202018	Revision to reflect new 2015 MSGP requirements. New procedure format was used and organizational changes made. This document replaces ENV-RCRA-QP-022, R2, which was split into EPC-CP-QP-023, R0, MSGP Industrial Stormwater Routine Facility Inspections, and EPC-CP-QP- 022, R3, MSGP Corrective Actions.

Table of Contents

Revis	ion Hi	istory	.2
Table	e of Co	ontents	.3
1.0	Intro	duction	.5
	1.1	Purpose	
	1.2	Scope	.5
	1.3	Applicability	.5
2.0	Preca	autions and Limitations	.5
3.0	Prere	equisite Actions	.6
	3.1	Planning and Coordination	.6
	3.2	Tools and Equipment	.6
4.0	Roles	s and Responsibilities	.6
	4.1.	EPC-CP MSGP Stormwater Personnel	.6
	4.2	Deployed Environmental Professionals	.7
	4.3	EPC-CP Storm Water Team Leader	.8
	4.4	EPC-CP Group Leader	.8
	4.5	DESH Manager	.8
	4.6	Facilities Operations Director	.9
5.0	Proce	ess Description	.9
	5.1	Identifying Conditions Requiring Corrective Actions	.9
	5.2	Corrective Action Deadlines and Documentation	10
		5.2.1 Immediate Action	10
		5.2.2 Subsequent Action	11
		5.2.3 Corrective Action Documentation	
	5.3	Effect of Corrective Action	12
	5.4	Substantially Identical Outfalls	13
	5.5	Spills	13
	5.6	Allowable Non-Stormwater Discharges	13
	5.7	Entering a Condition Requiring Corrective Action	
	5.8	Updating Corrective Actions	18
	5.9	Validation of Corrective Actions	18
	5.10	Issues Management	19
	5.11	Notifications for New and Overdue Corrective Actions	19
6.0	Train	ning	20
7.0	Reco	rds	20
8.0	Defir	nitions and Acronyms	21
	8.1	Definitions	21
	8.2	Acronyms	21
9.0	Refe	rences	22
10.0		chments	
		chment 1 – Screenshot Example of CAR Database	
		chment 2 – Lists of Limited Values in the CAR Database	
	Attac	chment 3 – Example New Corrective Action Finding Notification	29

MSGP Corrective Actions	EPC-CP-QP-022	Page 4 of 31
	Revision: 3	Effective Date: 12/20/2018

Attachment 4 – Example Weekly Notification of Outstanding Corrective Action Findings	
Attachment 5 – Example Outstanding Corrective Action Report	

1.0 INTRODUCTION

The National Pollutant Discharge Elimination System (NPDES) Multi-Sector General Permit (MSGP) contains specific environmental requirements for identifying, implementing, documenting and reporting conditions requiring corrective actions. Laboratory personnel (the Deployed Environmental Professionals (DEPs) and Environmental Protection and Compliance Division – Compliance Programs (EPC-CP) Storm Water Team (also referred to as EPC-CP MSGP stormwater personnel) are required to perform routine facility inspections and document all conditions requiring corrective actions found on an inspection form (see EPC-CP-QP-023). Conditions requiring corrective actions can be identified during facility walk-downs, normal daily operations, and/or analytical data evaluations, and can be identified by facility personnel, the DEP or EPC-CP MSGP stormwater personnel.

1.1 Purpose

This procedure governs the activities of Laboratory personnel working at Los Alamos National Laboratory (LANL) involved in identifying, implementing, documenting and entering a condition requiring corrective action, including a permit limit exceedance, into the MSGP Corrective Action Report (CAR) Findings database or CAR database. Part 4.4 of the MSGP contains specific documentation requirements relative to corrective actions. This procedure satisfies these requirements.

1.2 Scope

Requirements set forth in this document apply to personnel responsible for meeting the permit conditions on behalf of LANL industrial sites covered by the MSGP. This permit requires periodic inspection of sites and identification, implementation, documentation, tracking and reporting of conditions requiring corrective actions.

1.3 Applicability

This procedure applies to the EPC-CP MSGP stormwater personnel and DEPs who conduct stormwater inspections and monitoring activities at permitted MSGP sites within LANL.

2.0 PRECAUTIONS AND LIMITATIONS

- 2.1 The hazard level for field activities and office work described in this procedure is a <u>LOW hazard</u> rating and does not require an Integrated Work Document (IWD).
- 2.2 Inspections or walk-downs may be discontinued during periods or conditions that make sites dangerous for worker safety or prevent personnel from safely accessing sites (e.g., weather-related events such as flash floods, flooding, lightning, wildfires, hail, icy roads, deep snow, or LANL operations such as firing shots or open burning).

3.0 PREREQUISITE ACTIONS

3.1 Planning and Coordination

DEPs and EPC-CP MSGP stormwater personnel require a CAR database user account (<u>https://msgp-car.lanl.gov/forms/frmservlet?config=msgp_car</u>). Facility Operations Directors (FODs), Deployed Environment, Safety, and Health (DESH) Managers and Operations (Ops) Managers can request a read-access account by contacting the EPC-CP MSGP data administrator for access.

3.2 Tools and Equipment

Tools and equipment for documenting inspections and updating the CAR database include the following:

- LANS issued tablet or notebook style computer with Safari web browser and Blackberry UEM™app. (see <u>https://int.lanl.gov/policy/documents/P217.pdf</u> for requirements on using portable electronic devices on Laboratory property), and
- Access to the CAR database.

Tools and equipment for field work associated with performing inspections and site walk-downs are listed below.

- Sturdy hiking boots or steel or composite toed shoes with soles that grip (some sites require steel or composite toed shoes).
- Safety glasses if required by site.
- Cell phone (only government cell phones with batteries removed are allowed in secure areas.) See https://int.lanl.gov/policy/documents/P217.pdf for requirements on using portable electronic devices on Laboratory Property.)
- Copy of this procedure.
- Copy of facility specific Stormwater Pollution Prevention Plan (SWPPP) and map(s) (as needed).
- Necessary access.
- Stockpile of temporary stormwater controls (Best Management Practices [BMPs], e.g., inlet protection, absorbent pads for spills, gravel bags, S-Fence, wattles, etc.)

4.0 ROLES AND RESPONSIBILITIES

Specific roles and responsibilities for implementation of requirements contained in the MSGP are provided below.

4.1 EPC-CP MSGP Stormwater Personnel

EPC-CP MSGP stormwater personnel will be fully knowledgeable of the specific regulatory requirements identified in the MSGP. Additional responsibilities are listed below.

- Implement this procedure;
- Oversee the corrective action process;
- Identify conditions requiring corrective action during internal routine facility inspections, "no exposure" assessments, and/or facility walk-downs performed by them, or during evaluation of monitoring data when permit limits are exceeded;
- Perform a quality review of conditions requiring corrective action submitted in the CAR database;
- Notify managers and/or legal counsel of non-compliances;
- Assist DEPs and other customers with issues associated with the CAR database;
- Prepare and submit 45-day exceedance notification to Region 6, Environmental Protection Agency (EPA) containing information provided by the DEP;
- Prepare and submit the Annual Report summarizing all conditions requiring corrective action for the year in EPA's electronic NPDES eReporting tool (NeT);
- Prepare management requested metrics relative to conditions requiring corrective action;
- Provide information to the Issues Management Coordinator (IMC) for entering water quality exceedances and other permit violations into the Issues Management (IM) tool; and
- Train personnel to use the CAR database.

4.2 Deployed Environmental Professionals

DEPs will be fully knowledgeable of the site-specific SWPPP for their assigned sites and corrective action requirements identified in the MSGP. In addition, they shall be appropriately trained to meet the job qualifications identified in the *Quality Assurance for Stormwater Multi-Sector General Permit for Industrial Activities Program* (ENV-CP-QAPP-MSGP) and shall be familiar with the regulatory requirements identified in the MSGP, demonstrated by achieving a satisfactory score on the *MSGP Routine Facility Inspections* on-the-job training course #53040. Further, they shall be familiar with facility operations and controls to minimize potential pollutant sources and proactively maintain controls in an attempt to prevent conditions that require corrective action.

The DEPs are responsible for implementing this procedure. They will identify conditions requiring corrective actions observed at their industrial sites and enter them into the CAR database. DEPs act as liaison between the FOD, DESH Manager and facility/operations personnel to ensure all corrective actions are addressed appropriately by overseeing maintenance and/or installation of additional controls, as needed. DEPs are responsible for ensuring corrective action(s) is completed per MSGP requirements and the corrective action timeline (see Sections 5.2.1 and 5.2.2 of this procedure). They will also provide timely updates to the CAR database for closure or update of corrective actions as they are implemented.

When permit limits are exceeded, DEPs are responsible for identifying the source and maintaining existing controls or implementing additional controls, as necessary, to prevent further exceedances.

MSGP Corrective Actions	EPC-CP-QP-022	Page 8 of 31	
WISGP COTrective Actions	Revision: 3	Effective Date: 12/20/2018	

If the DEP or EPC-CP MSGP stormwater personnel determine that additional controls are necessary, or that existing controls are insufficient and require replacement with a different type of control, the DEPs are responsible for the selection and oversight of proper installation of appropriate control measures per guidance provided in the LANL Stormwater BMP Manual.

DEPs will notify the EPC-CP MSGP data administrator or MSGP Program Lead of key personnel changes (FOD, DESH Manager, Ops Manager, DEP) to ensure automated CAR status notifications are distributed to the appropriate personnel.

CAUTION

Failure to appropriately control pollutant discharges can result in fines and penalties.

Implementing the same control measure numerous times without an improvement in minimization of off-site pollutants is an indication that the control measure is not stringent enough to meet Technology-Based or Water Quality-Based effluent limits identified in the MSGP. Per the MSGP, documentation is required in the SWPPP that justified the selection, design, installation and implementation of a control measure to ensure effluent limits are met.

4.3 EPC-CP Storm Water Team Leader

The EPC-CP Storm Water Team Leader (or team leader) is responsible for compliance oversight relative to the MSGP. The team leader will ensure resources needed to implement the regulatory requirements identified in the MSGP are identified and environmental risks are assessed. Upper management will be notified of these resources or environmental risks, as deemed necessary. In the event there is a dispute regarding the regulatory requirements contained in the MSGP, the Team Leader will make the final determination of the required action. The Team Leader will notify upper management of instances of non-compliance with the permit.

4.4 EPC-CP Group Leader

The EPC-CP Group Leader or designee is responsible for ensuring there are adequate resources to implement the regulatory requirements identified in the MSGP. The group leader also acts as the duly authorized signatory that certifies the Annual Report or Routine Facility Inspections conducted by EPC-CP personnel. The group leader will notify upper management of instances of non-compliance with the permit or other identified environmental risk.

4.5 DESH Manager

The DESH Manager shall work with programmatic entities and the FOD to identify resources for their industrial sites to ensure permit requirements can be implemented. The DESH Manager is responsible for the performance of DEPs under their management. They also provide oversight for ensuring that industrial sites are complying with the MSGP and are responsible for notifying upper management of instances of non-compliance with the permit or other identified environmental risk they become aware of.

MSGP Corrective Actions	EPC-CP-QP-022	Page 9 of 31
NISGP COTTECTIVE ACTIONS	Revision: 3	Effective Date: 12/20/2018

4.6 Facilities Operations Director

The FOD provides organizational leadership to ensure that all facility and programmatic activities under their authority are performed in compliance with the MSGP. The FOD is also responsible for establishing an environmental compliance envelope. It is the FOD's responsibility to maintain trained and qualified DEPs and Waste Management Coordinators (WMCs) on staff.

5.0 PROCESS DESCRIPTION

Requirements regarding corrective actions are described in Part 4 of the MSGP. These requirements and conditions are summarized in this section and directly correspond to data fields and lists of values available in the CAR database.

5.1 Identifying Conditions Requiring Corrective Actions

Deployed Environmental Professional (DEP)

- [1] <u>IF</u> any of the following conditions are identified, <u>THEN</u> review and revise, as appropriate, the selection, design, installation, and implementation of control measures in the SWPPP to eliminate the condition and prevent recurrence in the future:
 - An unauthorized release or discharge (e.g., spill, leak, or discharge of nonstormwater not authorized by the MSGP [see Section 5.6 of this procedure for a description of allowable discharges]);
 - An inspection or evaluation of the facility by an EPA official and/or local or State entity, determines that modification to the control measures are necessary to meet the non-numeric effluent limits in the MSGP;
 - It is observed during the routine facility inspection, facility walk-down, and/or the quarterly visual assessment that the control measures are not being properly operated and maintained;
 - Construction or a change in design, operation, or maintenance at the facility significantly changes the nature of pollutants discharged in stormwater from the facility, or significantly increases the quantity of pollutants discharged;
 - The average of four quarterly sampling results exceeds an applicable benchmark. If less than four benchmark samples have been taken, but the results are such that an exceedance of the four quarter average is mathematically certain, (i.e., if the sum of quarterly sample results to date is more than four times the benchmark level) this is considered a benchmark exceedance;
 - If effluent limitation guidelines are exceeded at the Asphalt Batch Plant (Sector D); or
 - If impaired water quality standards are exceeded.

MSGP Corrective Actions	EPC-CP-QP-022	Page 10 of 31
	Revision: 3	Effective Date: 12/20/2018

DEP and/or EPC-CP MSGP stormwater personnel

[2] Enter all conditions requiring a corrective action into the EPC-CP MSGP CAR database.

DEP and/or Facility Personnel

- [3] Take immediate action to mitigate the condition requiring a corrective action.
- [4] If needed, follow the permit timeline and process for individual corrective actions that require extensive maintenance.
- [5] Any person authorized to conduct work at LANL can identify a potential stormwater issue. If this occurs, they will:
 - [a] Contact the DEP or EPC-CP MSGP stormwater personnel.
 - [b] The DEP or EPC-CP MSGP stormwater personnel will determine if a condition exists that requires a corrective action.

5.2 Corrective Action Deadlines and Documentation

Specific deadlines for taking corrective action and required documentation are provided in the subsections below.

5.2.1 Immediate Action

DEP and/or Facility Personnel

- [1] **IF** a condition exists that requires corrective action, as described in Section 5.1 [1], **THEN** take the following action immediately (on the same day the condition is found):
 - [a] All reasonable steps necessary to minimize or prevent the discharge of pollutants until a permanent solution is installed and made operational.
 - [b] Clean up any contaminated surfaces so that material will not discharge during subsequent storm events.
 - [c] Minimize or prevent the discharge of pollutants until a permanent solution (if necessary) is installed and made operational.
 - [d] Any corrective action resulting in a change to a stormwater control or procedure (documented in the SWPPP) requires modification of the SWPPP within 14 calendar days of completing corrective action work.

NOTE

For minor conditions, immediate action is often sufficient and no additional action is necessary.

[2] <u>IF</u> a condition is identified at a time in the work day when it is too late to initiate corrective action (i.e., 3:00 pm or later), <u>THEN</u>:

MSGP Corrective Actions	EPC-CP-QP-022	Page 11 of 31
	Revision: 3	Effective Date: 12/20/2018

- [a] Corrective action must begin no later than the following work day.
- [b] Implement the requirements identified in Section 5.2.1 [1] above.

CAUTION

Solely calling or e-mailing personnel requesting action to be taken is not considered taking immediate action. Entering a Facility Service Request (FSR) is appropriate if it formally starts the work process to address the condition. Temporary BMPs still need to be put in place to minimize or prevent off-site migration of pollutants, especially if a storm event is likely.

5.2.2 Subsequent Action

DEP and/or Facility Personnel

- [1] <u>IF</u> additional action is required, <u>THEN</u>:
 - [a] Complete the corrective action (e.g., install a new or modified control and make it operational or complete the repair) <u>before the next storm event or within 14</u> <u>calendar days</u> from the time of discovery.
 - [b] Any corrective action resulting in a change to a stormwater control or procedure documented in the SWPPP requires modification of the SWPPP within 14 calendar days of completing corrective action work.
- [2] **IF** completion of the corrective action is <u>infeasible</u> within the 14-day timeframe, **THEN**:
 - [a] Document the reasoning in the database.
 - [b] Provide a schedule for completion of the corrective action in the database.

NOTE

Completion of the corrective action cannot exceed 45 days from the time of discovery without having to notify EPA. These time intervals are not grace periods, but are schedules considered reasonable for documenting finding(s) and for making repairs and improvements. They are included in the MSGP to ensure that the conditions prompting the need for these repairs and improvements are not allowed to persist indefinitely. In no instance will the corrective action remain open indefinitely (Part 4.3.2 of the MSGP).

5.2.3 Corrective Action Documentation

DEP and/or EPC-CP

[1] Document existence of any of the conditions listed in Section 5.1 [1] of this procedure in the CAR database within 24 hours of becoming aware of such condition (or if identified late in the work day, by the following work day).

- [2] Include the following information in the documentation:
 - Description of the condition triggering the need for corrective action review. For any spills or leaks, include the following information:
 - a description of the incident including material, date/time, amount, location, and reason for spill;
 - any leaks, spills or other releases that resulted in discharges of pollutants to waters of U.S., through stormwater or otherwise;
 - Date the condition was identified; and
 - Description of immediate actions taken (Part 4.3.1 of the MSGP) to minimize or prevent the discharge of pollutants. For any spills or leaks, include response actions, the date/time clean-up was completed, notifications made (if any), and staff involved. Also include any measures taken to prevent the reoccurrence of such releases (Part 2.1.2.4 of the MSGP).
- [3] Provide the dates when each corrective action was initiated and completed (or is expected to be completed).
 - [a] If applicable, document why it is infeasible to complete the necessary installations or repairs within the 14-day timeframe, and
 - [b] Document your schedule for installing the controls and making them operational as soon as practicable after the 14-day timeframe.
 - [c] **IF** EPA must be notified regarding an extension of the 45-day timeframe, **THEN** the DEP must document the rationale for an extension.

EPC-CP MSGP stormwater personnel

[4] Prepare and submit 45-day exceedance notifications based on information entered into the CAR database by the DEPs.

DEP

- [5] Ensure that the information in the CAR database is kept up-to-date, to include the following:
 - [a] a thorough description of the nature of the condition requiring corrective action,
 - [b] corrective action(s) taken and/or outstanding,
 - [c] the steps and schedule for completing a corrective action (if not completed within 14 days), and
 - [d] rationale for why the corrective action cannot be completed within 45-days.

5.3 Effect of Corrective Action

When the condition requiring corrective action is a permit violation (e.g., non-compliance with an effluent limit or exceedance of a water quality standard), correcting it does not remove the original

MSGP Corrective Actions	EPC-CP-QP-022	Page 13 of 31
	Revision: 3	Effective Date: 12/20/2018

violation. Additionally, failing to take corrective action in accordance with Part 4 of the MSGP is an additional permit violation.

NOTE The EPA will consider the appropriateness and promptness of corrective action in determining enforcement responses to permit violations (Part 4.5 of the MSGP).

5.4 Substantially Identical Outfalls

When the condition requiring corrective action is associated with an outfall that has been identified as a "substantially identical outfall" (see Parts 3.2.3 and 6.1.1 or the MSGP), a review will assess the need for corrective action for all related substantially identical outfalls. Any necessary changes to control measures that affect these other outfalls will be made before the next storm event if possible, or as soon as practicable following that storm event. Any condition requiring corrective action(s) will be addressed within the timeframes set forth in Part 4.3 of the MSGP (also see Section 5.2 of this procedure).

5.5 Spills

DEP and/or Facility Personnel

- [1] Clean up all leaks or spills immediately and enter into the CAR database.
 - [a] If the spill is immediately cleaned up, and controls are implemented to prevent further leakage, the condition requiring corrective action can be closed.

5.6 Allowable Non-Stormwater Discharges

The following are allowable non-stormwater discharges authorized by the MSGP:

- Discharges from emergency/unplanned fire-fighting activities;
- Fire hydrant flushing;
- Potable water, including water line flushing;
- Uncontaminated condensate from air conditioners, coolers/chillers, and other compressors and from the outside storage of refrigerated gases or liquids;
- Irrigation drainage;
- Landscape watering provided all pesticides, herbicides, and fertilizer have been applied in accordance with the approved labeling;
- Pavement wash waters where no detergents or hazardous cleaning products are used (e.g., bleach, hydrofluoric acid, muriatic acid, sodium hydroxide, nonylphenols), and wash waters do not come into contact with oil and grease deposits, sources of pollutants associated with industrial activities (see Part 5.2.3 of the MSGP), or any other toxic or hazardous materials, unless residues are first cleaned up using dry clean-up methods (e.g., applying absorbent

MSGP Corrective Actions	EPC-CP-QP-022	Page 14 of 31
	Revision: 3	Effective Date: 12/20/2018

material and sweeping, using hydrophobic mops/rags) and you have implemented appropriate control measures to minimize discharges of mobilized solids and other pollutants (e.g., filtration, detention, settlement);

- Routine external building washdown/power wash water that does not use detergents or hazardous cleaning products (e.g., those containing bleach, hydrofluoric acid, muriatic acid, sodium hydroxide, nonylphenols);
- Uncontaminated ground water or spring water;
- Foundation of footing drains where flows are not contaminated with process materials; and
- Incidental windblown mist from cooling towers that collects on rooftops or adjacent portions of your facility, but not intentional discharges from the cooling tower (e.g., "piped" cooling tower blowdown or drains).

5.7 Entering a Condition Requiring Corrective Action

To enter a condition requiring corrective action into the CAR database, perform the steps in this section.

Enter clear, complete, and concise language. Correct grammar, punctuation, and spelling errors.

Select the appropriate value from each pull-down menu that applies to the condition requiring corrective action. This information will be used to populate a report that will be submitted to the EPA and is extracted from the database to populate automatic e-mail notifications to managers. Therefore, it is critical that all information entered into the CAR database is correct.

DEP or EPC-CP MSGP stormwater personnel

- [1] Using internet explorer, access the CAR database at <u>https://msgp-car.lanl.gov/forms/frmservlet?config=msgp_car</u>.
- [2] From the main screen, click on "Enter New Corrective Action."
 - [a] Select the "Corrective Action Header" tab.
 - [b] Enter the following (refer to Attachment 1 for data entry screenshot cross reference to Item numbers in red listed below):
 - Item 1: Name of facility by clicking on the "List" tab and selecting a facility (refer to Attachment 2 for a list of available facilities).
 - Item 2: Date/Time problem was identified (mm/dd/yyyy hh:mm) (*the inspection date or the date you first become aware of the issue*).

There must be a space between the date (mm/dd/yyyy) and the time (hh:mm).

All dates and times will be entered as mm/dd/yyyy hh:mm in 24-hr (military time) format. Time is tracked to document whether immediate action was taken, whether the issue was documented within 24 hours, and the specific time interval before a corrective action is completed and closed (see Section 5.2 of

MSGP Corrective Actions	EPC-CP-QP-022	Page 15 of 31	
	Revision: 3	Effective Date: 12/20/2018	

this procedure for corrective action deadlines). Do not leave time as 00:00 (the system default) unless the action occurred at midnight.

Item 3: Date/Time of Notification to EPC-CP (mm/dd/yyyy hh:mm) (the date the condition is entered into the CAR database or verbal or written notification is provided to the EPC-CP MSGP Program Lead. Conditions reported by verbal or written notification must still be entered into the CAR database.)

The existence of any of the conditions listed in Section 5.1 of this procedure must be documented in the CAR database within 24 hours of becoming aware of such condition (or if identified late in the work day, by the following work day).

• Item 4: FOD Responsible for CA (Name & Org) by clicking in the box. FOD designations (for example "STO") and the associated name list will pop up. Select the appropriate FOD.

Contact the EPC-CP MSGP Program Lead at 667-1312 or <u>hbenson@lanl.gov</u> if the FOD name or organization is incorrect, so this can be corrected.

- Item 5: Describe Specific Evaluation Location (for example, "Northeast corner of Building TA-3-66.")
- Item 6: Inspector Z-Number by clicking in the box, which will populate with the Z number of the person who is logged into the database and performing entry. In most instances, the DEP will be identified as the inspector.
- Item 7: Person Identifying Condition Z-Number by clicking in the box, which will populate with the Z number of the person who is logged into the database and peforming entry. If the person identifying the condition is someone other than the inspector, enter that person's Z-number.

Any person authorized to conduct work at LANL can identify a potential stormwater issue. If this occurs, they will contact the DEP or EPC-CP MSGP stormwater personnel who will determine if a condition exists that requires corrective action.

- Item 8: Status defaults to "A new corrective action" without making a selection. In the event a condition is entered that is determined to not require corrective action, this status can be changed to "Void" by clicking in the box and selecting from the Status list. The decision to assign a status of "Void" is at the discretion of EPC-CP MSGP stormwater personnel and reserved for EPC-CP use.
- Item 9: If the Status is changed to "Void," enter a clear rationale for voiding the record.
- Item 10: Once all of the above information is entered correctly, click "Save" and go to Step 3.

All boxes identified with a red asterisk are "required fields" meaning the form cannot be saved unless these fields are completed. For the purpose of fulfilling

MSGP Corrective Actions	EPC-CP-QP-022	Page 16 of 31
	Revision: 3	Effective Date: 12/20/2018

corrective action documentation requirements (see Section 5.2.3 of this procedure), all applicable fields are required fields.

The system will automatically assign a Corrective Action Report identification (ID) number and move to the "Corrective Action Details" tab.

- [c] Select the "Corrective Action Details" tab.
- [d] Enter the following:
 - Item 11: Identify the condition triggering the need for this review by clicking on the "List" button and selecting the appropriate condition or, if none of the available conditions fit the issue, selecting "Other" and entering a description of the condition (refer to Attachment 2 for a list of available conditions/finding descriptions).

These conditions are described in Section 5.1 of this procedure. Qualified personnel (EPC-CP MSGP stormwater personnel and DEPs) must be knowledgeable of these conditions and select the correct one when entering an issue. If there is uncertainty about which condition applies, refer to the definitions in Section 8.1 of this procedure or contact the MSGP Program Lead at 667-1312 or hbenson@lanl.gov for clarification prior to selecting "Other."

- Item 12: If the condition in Item 11 is set to "Other," enter a description of the condition in this field.
- Item 13: Briefly describe the nature of the problem identified during the inspection (e.g., erosion, damage to a BMP, trash, spill, etc.,) and the specific evaluation location (e.g., at TA-60 Roads and Grounds).

Spills or other emergency conditions meeting the criteria for corrective action (identified in Parts 4.1 and 4.2 of the MSGP) will require documentation in the CAR database even though the condition was not identified during an inspection.

- Item 14: Enter how the problem was identified by clicking on the "List" button and selecting the appropriate option, or if none of the available options fit, selecting "Other."
- Item 15: If "Other" is selected for Item 14, enter a description of how the problem was identified in this field.
- Item 16: Enter a description of the condition requiring corrective action, or identify action to be taken to eliminate or further investigate the problem (e.g., describe modifications or repairs to control measures, work conducted to address the condition or to be scheduled in the future, etc.,) or if no modifications are needed, the basis for that determination. Include relevant dates and facts when updating this field as the corrective action progresses.
- Item 17: Indicate whether the problem was identified at a Substantially Identical Outfall (see Section 5.4 of this procedure) by typing "Y" for yes and "N" for no.

MSGP Corrective Actions	EPC-CP-QP-022	Page 17 of 31
	Revision: 3	Effective Date: 12/20/2018

- Item 18: If the answer to Item 17 is "Y," enter the associated SIO(s) in this field. If the answer to Item 17 is "N," leave this field blank. SIOs are identified in the site-specific SWPPPs. For assistance with identifying SIOs contact the MSGP Program Lead.
- Item 19: If the answer to Item 17 is "Y," describe how the corrective action taken is appropriate for all SIOs (see Section 5.4 of this procedure), document any additional corrective action(s) needed for any of the SIOs, or document why no additional action is needed for the SIOs. If the answer to Item 17 is "N," leave this field blank.
- Item 20: Did/will the corrective action require modification to the SWPPP? Type in "Y" for yes and "N" for no (see Section 5.1 of this procedure for conditions that require SWPPP review and revision).
- Item 21: Date/Time Corrective Action was initiated (mm/dd/yyyy hh:mm).

The duration between the Date/Time problem was identified and Date/Time corrective action was initiated is used to determine whether "immediate action" was taken (see Section 5.2.1 of this procedure). Immediate action is a requirement of the MSGP and therefore, will be documented in accordance with permit requirements.

 Item 22: Date/Time corrective action was completed OR expected completion Date/Time (mm/dd/yyyy hh:mm).

If the corrective action has not been completed, enter an expected completion date and time. The system will not allow entry of a date in both locations.

The duration between the Date/Time Problem was Identified and Date/Time corrective action was completed <u>or</u> the Date/Time Problem was identified and expected completion Date/Time is used to determine whether "subsequent action" timeframes and documentation requirements were/are being met, and to forecast where a 45-day exceedance notification to EPA is required (see Section 5.2.3 of this procedure). When information is incorrect or not entered, the MSGP data administrator or Program Lead will contact the originator and request correction(s).

- Item 23: If the corrective action is not or will not be completed within 14 days, provide the status of the corrective action at the end of the 14 day timeframe, the rationale for why it is infeasible to complete the corrective action within 14 days, and describe any remaining steps (including timeframe/schedule associated with each step) necessary to complete the corrective action.
- Item 24: Date EPA notified of intent to exceed 45 Days (mm/dd/yyyy hh:mm) is to be completed by EPC-CP MSGP stormwater personnel to document submittal of notification letter.
- Item 25: Once all of the above information is entered correctly, click "Save" so the corrective action information is retained.

MSGP Corrective Actions	EPC-CP-QP-022	Page 18 of 31
	Revision: 3	Effective Date: 12/20/2018

[3] **<u>IF</u>** there are additional conditions to enter requiring corrective action, as described in Section 5.1 [1],

THEN perform these steps:

- [a] Return to the "Corrective Action Header" tab.
- [b] Click the "Enter New Corrective Action" button in the lower left hand corner of the screen.
- [c] Click "Back to Record Selection" to return to the list of saved conditions requiring corrective action on the initial screen (if desired).

5.8 Updating Corrective Actions

DEP or EPC-CP MSGP stormwater personnel

- [1] Access the CAR database at <u>https://msgp-</u> car.lanl.gov/forms/frmservlet?config=msgp_car.
 - [a] On the main screen, scroll down to the corrective action number to be edited.
 - [b] Click "Edit."
- [2] Navigate to the desired field, and input the updated information. Most changes will occur relative to updating the status, schedule, and dates of corrective actions.
- [3] Click "Save" to save all changes to the information.

5.9 Validation of Corrective Actions

EPC-CP MSGP stormwater personnel

- [1] Access the CAR database at <u>https://msgp-</u> <u>car.lanl.gov/forms/frmservlet?config=msgp_car</u>.
- [2] Ensure information entered into the CAR database is correct.
 - [a] Check all entered fields for a condition requiring corrective action to ensure that information is clear, correct, and concise.
 - [b] <u>IF</u> not, <u>THEN</u> notify the DEP of the information that needs to be changed.
 - [c] The DEP is responsible for ensuring all information is validated before generating the annual report.
- [3] <u>IF</u> the identified condition requiring corrective action is a repeat of a previous condition or if it is determined not to be a condition requiring corrective action, <u>THEN</u>
 - [a] Under "Status," select "Void."
 - [b] The "Void" designation allows MSGP stormwater personnel to manually exclude this information in the annual report.

MSGP Corrective Actions	EPC-CP-QP-022	Page 19 of 31	
WISGP COTTECTIVE ACTIONS	Revision: 3	Effective Date: 12/20/2018	

5.10 Issues Management

EPC-CP MSGP stormwater personnel or DEPs use the IM tool as the institutional performance issues and tracking system for identified quality assurance (QA) affecting issues. A QA affecting issue includes, but is not limited to, the following conditions.

- Exceedance of a water quality standard.
- Exceedance of an effluent limitation (i.e., at the Asphalt Batch Plant).
- Repeat conditions requiring corrective actions or trends identified by EPC-CP MSGP stormwater personnel.
- Conditions requiring immediate action, where failure to take action would result in pollutants being released to waters of the state.
- Immediate non-compliance with the MSGP.
- Violations identified by the regulatory authority.

The MSGP Program Lead periodically evaluates a summary of open conditions requiring corrective actions in the CAR database. Using the above conditions, the MSGP Program Lead or DEP determines which corrective actions, if any, will be transferred into the IM tool.

DEP or EPC-CP MSGP stormwater personnel

- [1] <u>IF</u> an issue needs to be entered into the IM tool, <u>THEN</u> send the following information to the EPC Division IMC for entry into the IM tool:
 - Organization responsible for the issue/problem;
 - A description of the nature of the condition identified and what needs to be done to address it;
 - Regulatory citation for the non-compliance;
 - Issues Responsible Manager (IRM);
 - Action, actionee, and due date for each issue; and
 - Whether the issue was identified internal or external to LANL.

5.11 Notifications for New and Overdue Corrective Actions

- [1] When a new condition requiring corrective action is entered into the CAR database, the FOD, Ops Manager, DESH Manager, inspector (usually the DEP) and EPC-CP MSGP stormwater personnel and managers are notified automatically by e-mail on the evening of the day the corrective action was entered.
- [2] Automated e-mail notifications will be sent during the corrective action process depending on the length of time it will take to close.
- [3] A notification will be sent out:

MSGP Corrective Actions	EPC-CP-QP-022	Page 20 of 31	
WISGP COTTECTIVE ACTIONS	Revision: 3	Effective Date: 12/20/2018	

- When a new corrective action is entered into the database (see Attachment 3); and
- Weekly notifications of outstanding (open) corrective actions (see Attachment 4).

Each notification contains a hyperlink to a web-based report containing a list of all open issues and timeline status where final corrective actions have not been completed (see Attachment 5) by the FOD. The report contains the FOD, Facility, unique Corrective Action identification number assigned by the CAR database, the person identifying the condition, the date the issue was identified, the date corrective action was initiated, the projected completion date, and a color-coded count (corresponding to the Corrective Action deadlines in Section 5.2 of this procedure) of the number of days to take action and the number of days the issue has been open, and the issue/problem description.

These notifications serve to apprise recipients of the status of open conditions requiring corrective actions and to provide sufficient time for MSGP stormwater personnel to provide documentation to EPA at the 45-day deadline. This will assist the FOD, DESH Managers, Ops Managers, and the DEPs with keeping track of conditions requiring corrective actions.

6.0 TRAINING

The following personnel require training before implementing this procedure:

- EPC-CP Group Leader and Team Leader;
- EPC-CP MSGP stormwater personnel;
- DEPs; and
- Other LANL or subcontract personnel identified as being required to conduct stormwater inspections, or other assessments and enter conditions requiring corrective actions into the CAR database as part of their job duties.

For EPC-CP MSGP stormwater personnel, the training method for this procedure is "self-study" (reading). DEPs shall achieve a satisfactory score on Training Course 53040, *MSGP Routine Facility Inspections OJT*. Other participating groups may require training documentation pursuant to local procedures.

Personnel performing this procedure will be familiar with the most current version of the following procedure:

• ENV-CP-QAPP-MSGP, Multi-Sector General Permit for Industrial Activities Program

7.0 RECORDS

Conditions requiring corrective actions are contained within the CAR database. DEPs will retain documentation substantiating these conditions, corrective actions, and timelines reported in the CAR database (e.g., e-mails, FSRs, Work Orders, etc., as appropriate). These documents shall be made available to EPC-CP upon request.

8.0 DEFINITIONS AND ACRONYMS

See LANL Definition of Terms.

8.1 Definitions

Best Management Practice (BMP)—Schedules of activities, prohibitions of practices, maintenance procedures, and other management practices to prevent or reduce the pollution of "waters of the United States." BMPs also include treatment requirements, operating procedures, and practices to control plant site runoff, spillage or leaks, sludge or waste disposal, or drainage from raw material storage. (40 CFR Part 122.2)

Control Measure—Any BMP or other method (including effluent limitations) used to prevent or reduce the discharge of pollutants to waters of the United States.

Numeric effluent limitation—The degree of effluent reduction attainable by the application of the best practicable control technology currently available (see 40 CFR Part 443.12). For LANL, numeric effluent limitations apply only to the Asphalt Batch Plant (Sector D) (see Table 1-1 of the MSGP). Constituents with limitations for Sector D include Total Suspended Solids, pH, and oil and grease (see Table 8.D-2 of the MSGP).

Note: Exceedance of a numeric effluent limitation is a violation of the MSGP (see Part 4.1 of the MSGP).

Non-numeric effluent limitations—Per Part 2.1.2 of the MSGP, these include minimizing exposure, good housekeeping, maintenance, spill prevention and response, erosion and sediment controls, management of runoff, salt storage controls, employee training, elimination of non-stormwater discharges, and minimizing dust generation and vehicle tracking of industrial materials.

Unauthorized release or discharge—The release of any liquid or solid substance (within the boundary of an MSGP site) that is not an allowable non-stormwater discharge (see Section 5.6). Examples are hydraulic oil, gasoline, diesel, powdered concrete, concrete washout, steam condensate line leaks, etc.

Impaired water quality exceedance—Exceedance of a New Mexico water quality standard. These standards are specified in the New Mexico Administrative Code, Title 20, Chapter 6, Part 4, *Standards for Interstate and Intrastate Surface Waters*.

Note: Industrial stormwater discharges must be controlled as necessary to meet applicable water quality standards within the State of New Mexico (see Part 2.2.1 of the MSGP).

8.2 Acronyms

BMP	Best Management Practice
CA	Corrective Action
CAR	Corrective Action Report
EPA	Environmental Protection Agency

See LANL Acronym Master List.

MSGP Corrective Actions	EPC-CP-QP-022	Page 22 of 31
WISGP COTTECTIVE ACTIONS	Revision: 3	Effective Date: 12/20/2018

EPC-CP	Environmental Protection and Compliance-Compliance Programs	
DEP	Deployed Environmental Professional	
DESH	Deployed Environmental, Safety and Health	
ID	Identification	
IM	Issues Management	
IMC	Issues Management Coordinator	
IRM	Issues Responsible Manager	
IWD	Integrated Work Document	
FOD	Facility Operations Director	
FSR	Facility Service Request	
HEY	Heavy Equipment Yard	
LANL	Los Alamos National Laboratory	
MSGP	Multi-Sector General Permit	
Ν	No	
NPDES	National Pollutant Discharge Elimination System	
Ops	Operations	
Р	Procedure	
PD	Program Description	
QA	Quality Assurance	
QP	Quality Procedure	
SD	System Description	
STO	Science and Technology Operations	
SWPPP	Stormwater Pollution Prevention Plan	
40 CFR	Title 40 of the Code of Federal Regulations	
WMC	Waste Management Coordinator	
Y	Yes	

9.0 REFERENCES

- Final National Pollutant Discharge Elimination System (NPDES) General Permit for Stormwater Discharges from Industrial Activities. Federal Register: June 16, 2015, Volume 80, Number 115.
- <u>Unites States Environmental Protection Agency (EPA) National Pollutant Discharge</u> <u>Elimination System (NPDES) Multi-Sector General Permit For Stormwater Discharges</u> <u>Associated With Industrial Activity (MSGP)</u>
- Los Alamos National Laboratory Storm Water BMP Manual

- PD100, DOE/NNSA Approved Los Alamos National Laboratory 10 CFR 857 Worker Safety and Health program Description
- <u>SD100, Integrated Safety Management System</u>
- <u>P101-18, Procedure for Pause/Stop Work</u>
- EPC-CP-QP-023, MSGP Routine Facility Inspections

10.0 ATTACHMENTS

Attachment 1: Screenshot Example of CAR Database

- Attachment 2: Lists of Limited Values in the CAR Database
- Attachment 3: Example New Corrective Action Finding Notification
- Attachment 4: Example Weekly Notification of Outstanding Corrective Action Findings

Attachment 5: Example Outstanding Corrective Action Report

MSGP Corrective Actions	EPC-CP-QP-022	Page 24 of 31
WISGF COTTECTIVE ACTIONS	Revision: 3	Effective Date: 12/20/2018

Attachment 1 – Screenshot Example of CAR Database

Page 1 of 3

Corrective Action Header tab

DES MSGP CORREC	TIVE ACTION	NREPORT		ld. Number	: 1150	(Assigned by	(computer)
Name of Facility : TA-	-60-1 Heavy	Equipment Yar	d	List			
Date problem was ider	ntified : 05/	19/2017 09:00	Date o	f Notification	to EPC-CP :	05/19/2017	12:00
FOD Responsible for C	A (Name & (Org): UI		Erickson An	drew W		
Describe Specific Eval	luation Loca	tion : Trench	n drain east o	of the high ba	ay that drains	to the oil w	ater separ
Inspector Z-Number :	123456	Doe, Jane			EPC-CP		
Person Identifying Condition Z-Number :	123456	Doe, Jane			EPC-CP		
I	Date Forma	at Must be ent	ered as MN		HH24:MI		
	Date Forma	at Must be ent	ered as MM	1/DD/YYYY	HH24:MI	Annual Re	port ID (s):
		at Must be ent	ered as MM	1/DD/YYYY	HH24:MI	Annual Rej	port ID (s):
Status: 1			tered as MM	1/DD/YYYY	HH24:MI	Annual Rej	port ID (s):
Status: 1	new correc		ered as MN	1/DD/YYYY	HH24:MI	Annual Rep	port ID (s):
Status: 1	new correc		tered as MN	I/DD/YYYY	HH24:MI	Annual Rep	port ID (s):
Status: 1	new correc	tive action ?		I/DD/YYYY rd Selection		10	port ID (s):

MSGP Corrective Actions	EPC-CP-QP-022
WISGP COTTECTIVE ACTIONS	Revision: 3

Attachment 1 – Screenshot Example of CAR Database (cont.)

Page 2 of 3

Corrective Action Details tab

	for this review: If other, (describe here):
ontrol measures not properly operated or	
Briefly describe the nature of problem ide	entified: (e.g., Erosion problem identified during inspection).
	-60 HEY that drains to an oil/water separator was not draining during that was previously identified on 3/22/2017 (see CAR #1067), when 025.
How problem was identified:	If other, (describe here):
Other (describe) :	List During monitoring after a storm event
	to be taken to eliminate or further investigate the problem (e.g., neasures, analyses to be conducted, etc.) or if no modifications
l/water constant is required to close this	umentation of actual maintenance done on the trench drain and corrective action. Additional controls may need to be implemented all that is Substantially Identical? Yes/No : Y nd 025
	prrective action taken is appropriate for all related SIOs:
19/2017: Temporarily pumping water will	prrective action taken is appropriate for all related SIOs: prevent discharge from reaching the SIOs. 6/5/2017: Unclogging the ater separator will prevent unauthorized discharges such as oil.
19/2017: Temporarily pumping water will ench drain and maintenance on the oil/wa	prevent discharge from reaching the SIOs. 6/5/2017: Unclogging the ter separator will prevent unauthorized discharges such as oil.
19/2017: Temporarily pumping water will pench drain and maintenance on the oil/wa 11. Did/will this corrective action require	prevent discharge from reaching the SIOs. 6/5/2017: Unclogging the ater separator will prevent unauthorized discharges such as oil. modification of your SWPPP ? Yes/No :
19/2017: Temporarily pumping water will p ench drain and maintenance on the oil/wa 11. Did/will this corrective action require 12. Date corrective action initiated (MM/	prevent discharge from reaching the SIOs. 6/5/2017: Unclogging the ater separator will prevent unauthorized discharges such as oil. modification of your SWPPP ? Yes/No : Y DD/YYYY HH24:MI): 05/19/2017 14:00 OR expected completion :
19/2017: Temporarily pumping water will p ench drain and maintenance on the oil/wa 11. Did/will this corrective action require 12. Date corrective action initiated (MM/ 13. Date corrective action completed (M	prevent discharge from reaching the SIOs. 6/5/2017: Unclogging the ater separator will prevent unauthorized discharges such as oil. modification of your SWPPP ? Yes/No : Y DD/YYYY HH24:MI): 05/19/2017 14:00 OR expected completion : M/DD/YYYY HH24:MI): 06/05/2017 16:00 completed within 14 days of discovery, describe any remaining

MSGP Corrective Actions	EPC-CP-QP-022	Page 26 of 31
WISGP COTTECTIVE ACTIONS	Revision: 3	Effective Date: 12/20/2018

Attachment 1 – Screenshot Example of CAR Database (cont.)

Page 3 of 3

Full Text for Item 16: Description of Corrective Action Taken or to be Taken

On 05/19/2017, HEY personnel pumped water from the trench drain into storage tanks to prevent overflow and release. Sediment was also removed from the trench drain and placed into drums. An on-site supervisor submitted an FSR to unclog the line. Documentation of actual maintenance done on the trench drain and oil/water separator is required to close this corrective action. Additional controls may need to be implemented until maintenance is complete to ensure that oil is not discharged into the drainage channel north of the site. In addition, the SWPPP must be modified to identify the preventative maintenance schedule and include the procedure for conducting it. On 05/30/2017, the SWPPP was modified to include a quarterly maintenance schedule and a procedure for routine maintenance on the oil/water separator. On 06/05/2017, MSS jet-routed the drain to remove the clog and a subcontractor performed maintenance on the oil/water separator.

MSGP Corrective Actions	EPC-CP-QP-022	Page 27 of 31
WISGP COTTECTIVE ACTIONS	Revision: 3	Effective Date: 12/20/2018

Attachment 2 – Lists of Limited Values in the CAR Database

Page 1 of 2

Name of Facility (Item 1 on Attachment 1 Screenshot)

Find TA-%
Msgp_Facility_Desc
TA-14-23 OBOD
TA-15-185 PHERMEX
TA-15-313 Machine Shop
TA-16-0388 Burning Ground
TA-16-0399 Burning Ground
TA-22-52 Machine Shop
TA-3-22 Power & Steam Plant
TA-3-30 Warehouse
TA-3-32 Metal Shop
TA-3-34 Metal Shop
TA-3-38 Carpenter Shop
TA-3-38 Metals Fab. Shop
TA-3-39 & 102 Metal Shop
TA-3-66 Sigma Facility
TA-33-113 Machine Shop
TA-33-39 Machine Shop
TA-35-125 Machine Shop
TA-35-2 Machine Shop
TA-36-8 Minie
TA-39-57 OBOD
TA-39-6 OBOD
TA-46-31 Machine Shop
TA-46-77 Machine Shop
TA-48-8 Machine Shop
TA-50-37 WCRRF
TA-50-54 Metal Shop
TA-50-69 WCRRF
TA-53-16 Machine Shop
TA-53-18 Machine Shop
TA-53-2 Machine Shop
TA-53-22 Machine Shop
TA-53-26 Machine Shop
TA-53-39 Shop and Storage Building
TA-54 Area G
TA-54 Area L
TA-54 Maintenance Facility W
TA-54 RANT
TA-55 Plutonium Facility
TA-55-314 Warehouse
TA-60 Asphalt Batch Plant
TA-60 MRF
TA-60 Roads and Grounds
TA-60-1 Heavy Equipment Yard
TA-60-2 Warehouse
TA-63 Transuranic Waste Facility
TA-9-28 Heavy Equipment Maintenance Operations Facility
Eind QK Cancel

MSGP Corrective Actions	EPC-CP-QP-022	Page 28 of 31
MSGP Corrective Actions	Revision: 3	Effective Date: 12/20/2018

Attachment 2 – Lists of Limited Values in the CAR Database (cont.)

Page 2 of 2

Finding Description/Condition Triggering Need for Review (Item 11 on Attachment 1 Screenshot)

Findings been been been been been been been bee	×		
Find <mark>%</mark>			
Finding_Desc			
Unauthorized release or discharge			
Numeric effluent limitation exceedance			
Control measures inadequate to meet non-numeric effluent limitations	2		
Control measures not properly operated or maintained			
Change in facility operations necessitated change in control measures			
Average benchmark value exceedance			
Other (describe) :			
Impaired water quality exceedance			
	-		
Eind <u>OK</u> Cancel			

Inspection Type/How Problem was Identified (Item 14 on Attachment 1 Screenshot)

How was problem identified : December 2000000000000000000000000000000000000
Find %
Inspection_Type_Desc
Quarterly visual assessment
Routine facility inspection
Benchmark monitoring
Impaired waters monitoring
Effluent limitation guidelines monitoring
Other (describe) :
<u>Find</u> <u>QK</u> <u>Cancel</u>

Attachment 3 – Example New Corrective Action Finding Notification

Page 1 of 1

From: MSGPCorrectiveActionDB@esp-esh-as01.lanl.gov [mailto:MSGPCorrectiveActionDB@esp-esh-as01.lanl.gov] Sent: Friday, January 19, 2018 10:00 PM

To: Cc:

Subject: New Corrective Action finding relative to the NPDES MSGP Program

This email is generated automatically by the National Pollutant Discharge Elimination System (NPDES) Multi-Sector General Permit (MSGP) Corrective Action Report (CAR) database to provide notification of discovery of a new condition requiring corrective action. As the recipient of this notification, you are responsible for immediately taking all reasonable steps necessary to minimize or prevent the discharge of pollutants until a permanent solution is installed and made operational.

"Immediately" requires initial action on the same day a condition is found. However, if a problem is identified at a time in the work day when it is too late to initiate corrective action (after 2 P.M.), the initiation must begin no later than the following work day.

Documentation of newly identified conditions requiring corrective action must occur within 24 hours of discovery, evidenced by entry into the CAR database.

At TA-50-37 WCRRF on 01/17/18, a condition requiring a corrective action was observed and a corrective action report was generated per the 2015 Multi-Sector General Permit requirements for stormwater controls at industrial sites. The condition(s) requiring a corrective action(s) is/are listed below.

CA#: 1296 located at TA-50-37 WCRRF.

Person Identifying Condition: DOE JANE

Description of finding: Unauthorized release or discharge

Condition requiring corrective action: Forklift was leaking hydraulic fluid

Description of the corrective action taken or to be taken to eliminate the condition or further investigation: On 1/17/2018 prior to the start of work the operator noticed the forklift was leading hydraulic fluid from the line to the mast. Approximately 4 to 6 oz leaked onto the asphalt. The Operation Center was notified and the WMC and ENV. The Nuc Operators placed spill pads under the leak. FSR#182723 was entered to repair forklift and apply microblaze. At 1702 MSS personnel applied micro blaze to the spill. On 1/18/2018 the WMC collected all spill pads and managed them accordingly.

Status: The corrective action was initiated on 01/17/2018 and was completed on 01/17/2018.

Click HERE to access the list of MSGP corrective action(s) not yet completed for EWMO.

Click HERE to access the list of all MSGP corrective action(s) not yet completed.

The ESH Deployed Environmental Professional (DEP) assigned to your organization/area is (are) Jane Doe.

The color legend on the linked reports corresponds to the following schedule for corrective action completion as required by the 2015 MSGP:

You must complete the corrective action within 14 calendar days of discovery.

If completion of final corrective actions within 14 days is not feasible, the reason(s) must be documented and a description of steps required and formal schedule for completion, which must be done as soon as practicable after the 14-day timeframe, but not longer than 45 days after discovery. The reasons, steps and schedule for completion must be entered into the CAR database.

If the completion of corrective action will exceed the 45-day timeframe, you make take the <u>minimum</u> additional time necessary, provided that you notify Region 6 of the Environmental Protection Agency:

- of your intent to exceed 45 days,
- your rationale for an extension, and
- a completion date.

To assist the preparation of this notification, as a responsible individual, you must contact the EPC-CP Project Lead at 667-1312 for any corrective action that remains open 35 days or more, and provide a formal status of the progress for each corrective action. By day 40, the DEP nust provide the EPC-CP Project Lead the rationale for potentially exceeding the required 45-day timeframe and a proposed completion date for each associated corrective action. The DEP must also amend the rationale and completion date in the CAR database.

An extension request must be submitted to Region 6 of the U.S. Environmental Protection Agency by EPC-CP personnel prior to day 45 for final corrective actions not completed or estimated to be completed within 45 days of discovery.

The responsible individual must ensure compliance with the proposed completion schedule.

These intervals are not considered grace periods, but are defined schedules to ensure the conditions requiring corrective action do not persist indefinitely.

Where corrective actions result in changes to controls or any procedures documented in the facility's Storm Water Pollution Prevention Plan (SWPPP), the DEP must modify the SWPPP accordingly within 14 calendar days of completing corrective action work.

Attachment 4 – Example Weekly Notification of Outstanding Corrective Action Findings

Page 1 of 1

From: MSGPCorrectiveActionDB@esp-esh-as01.lanl.gov [mailto:MSGPCorrectiveActionDB@esp-esh-as01.lanl.gov] Sent: Monday, January 01, 2018 10:00 PM

To: Cc:

Subject: Weekly Notification of Outstanding NPDES MSGP Corrective Action finding(s)

This email is generated automatically by the National Pollutant Discharge Elimination System (NPDES) Multi-Sector General Permit (MSGP) Corrective Action Report (CAR) database to provide notification of discovery of a new condition requiring corrective action. As the recipient of this notification, you are responsible for immediately taking all reasonable steps necessary to minimize or prevent the discharge of pollutants until a permanent solution is installed and made operational.

"Immediately" requires initial action on the same day a condition is found. However, if a problem is identified at a time in the work day when it is too late to initiate corrective action (after 2 P.M.), the initiation must begin no later than the following work day.

Documentation of newly identified conditions requiring corrective action must occur within 24 hours of discovery, evidenced by entry into the CAR database.

At TA-3-38 Carpenter Shop , 1 total MSGP stormwater corrective action(s) has (have) not been completed.

At TA-3-38 Metals Fab. Shop, 1 total MSGP stormwater corrective action(s) has (have) not been completed.

At TA-60-1 Heavy Equipment Yard, 7 total MSGP stormwater corrective action(s) has (have) not been completed.

At TA-60-2 Warehouse , 4 total MSGP stormwater corrective action(s) has (have) not been completed.

Click HERE to access the list of MSGP corrective action(s) not yet completed for UI.

Click HERE to access the list of all MSGP corrective action(s) not yet completed.

The ESH Deployed Environmental Professional (DEP) assigned to your organization/area is (are) Jane Doe : John Doe.

The color legend on the linked reports corresponds to the following schedule for corrective action completion as required by the 2015 MSGP:

You must complete the corrective action within 14 calendar days of discovery.

If completion of final corrective actions within 14 days is not feasible, the reason(s) must be documented and a description of steps required and formal schedule for completion, which must be done as soon as practicable after the 14-day timeframe, but not longer than 45 days after discovery. The reasons, steps and schedule for completion must be entered into the CAR database.

If the completion of corrective action will exceed the 45-day timeframe, you make take the <u>minimum</u> additional time necessary, provided that you notify Region 6 of the Environmental Protection Agency:

- of your intent to exceed 45 days,
- your rationale for an extension, and
- a completion date.

To assist the preparation of this notification, as a responsible individual, you must contact the EPC-CP Project Lead at 667-1312 for any corrective action that remains open 35 days or more, and provide a formal status of the progress for each corrective action. By day 40, the DEP must provide the EPC-CP Project Lead the rationale for potentially exceeding the required 45-day timeframe and a proposed completion date for each associated corrective action. The DEP must also amend the rationale and completion date in the CAR database.

An extension request must be submitted to Region 6 of the U.S. Environmental Protection Agency by EPC-CP personnel prior to day 45 for final corrective actions not completed or estimated to be completed within 45 days of discovery.

The responsible individual must ensure compliance with the proposed completion schedule.

These intervals are not considered grace periods, but are defined schedules to ensure the conditions requiring corrective action do not persist indefinitely.

Where corrective actions result in changes to controls or any procedures documented in the facility's Storm Water Pollution Prevention Plan (SWPPP), the DEP must modify the SWPPP accordingly within 14 calendar days of completing corrective action work.

MSGP Corrective Actions	EPC-CP-QP-022	Page 31 of 31
WISGP COTTECTIVE ACTIONS	Revision: 3	Effective Date: 12/20/2018

Attachment 5 – Example Outstanding Corrective Action Report

Page 1 of 1

	Einside											
	EPC-CP MultiSector General Permit (MSGP) Corrective Action Report Findings											
				Final					of 02/01/2	2018)		
FOD	RAD	MSGP Facility	CA#	Person Identifying Condition	Date Problem Identified	Corrective Action Initiated Date	Days to Take Action	Projected Completion Date	Projected Days until Completion	(since	EPA Notified of Intent to Exceed 45 Days	Problem Description
UI	DOE JOHN	TA-3-38 Carpenter Shop	1298	DOE JANE	01/31/18		!	02/02/18	1	1		Tarp was totally torn off of the stack of metal posts at the southwest corner of the storage yard.
	DOE JOHN	TA-3-38 Metals Fab. Shop	1299	DOE JANE	01/31/18		!	02/02/18	1	1		A pile of gravel (from a torn gravel bag) is directly east of the trench drain.
Total	Findings:											2
	Legend Indicates immediate action was not taken (i.e., <=2 days of discovery)											
	Between 15 and 34 days of discovery 45 days of discovery or greater											
	Operated by Los Alamos National Security, LLC for the U.S. Department of Energy's NNSA © Copyright LANS, LLC All rights reserved											

ATTACHMENT 18: EPC-CP-QP-2105, MSGP STORMWATER VISUAL ASSESSMENTS

EPC-CP-QP-2105		Revision: 1		Los Alamos			
Effective Date: 09/08/2021		Next Review Da	ite: 09/08/2024	NATIONAL LABORATORY			
Environment, Safety, Health, Quality, Safeguards, and Security Directorate Environmental Protection and Compliance – Compliance Programs Group Quality Procedure							
	MSGP St	ormwate	er Visual Asses	ssments			
Hazard Grading: Image Low Image Moderate Image High/Complex Usage Level: Image Reference Image UET Image Mixed: UET Sections:							
Status:		Major Revisio					
	Review w/No	Changes	Other:				
Safety Basis:	🖾 N/A 🛛	Jusq	USI Number:				
	Do	cument Autho	r/Subject Matter Exper	t:			
Name:		Organization:	Signature:	Date:			
Holly L. Wheeler		EPC-CP	Signature on File	08-30-21			
	Derivative (Classifier: 🔀	Unclassified or 🗌				
Name:		Organization:	Signature:	Date:			
Steven E. Wolfel		EPC-CP	Signature on File	08-31-21			
Approval Signatures:							
EPC-CP Reviewer:		Organization:	Signature:	Date:			
Alethea Banar		EPC-CP	Signature on File	08-31-21			
EPC-CP RLM:		Organization:	Signature:	Date:			
Terrill W. Lemke, Te	eam Leader	EPC-CP	Signature on File	09-07-21			
EPC-CP RLM:		Organization:	Signature:	Date:			
Taunia J. Sandquist	, Group Leader	EPC-CP	Signature on File	09-08-21			
This copy is uncontrolled. Users are responsible for ensuring they work to the latest approved version. To document a required read, Login to <u>UTrain</u> , and go to the Advanced Search.							

MSGP Stormwater Visual	No: EPC-CP-QP-2105	Page 2 of 19
Assessments	Revision: 1	Effective Date: 09/08/2021

REVISION HISTORY

Document Number and Revision	Effective Date	Effective Date
ENV-RCRA-QP-064, R0	7/09	New document MSGP Storm Water Visual Inspections.
ENV-RCRA -QP-064, R1	3/10	Clarifications and added attachments.
ENV-RCRA -QP-064, R2	2/12	Biennial review/revision
EPC-CP-QP-064, R0	10/04/2017	This document replaces ENV-RCRA-QP-064 R2. Converted into new format, and new organization name, clarified steps, updated attachments.
EPC-CP-QP-064, R1	10/09/2018	Removed requirement to conduct visual assessment on filtered samples. Updated form to match text.
EPC-CP-QP-2105, R0	05/12/20	Supersedes EPC-CP-QP-064, R1. Reformat to new EPC-CP template. Re-number procedure and forms to new EPC-CP procedure numbering system.
EPC-CP-QP-2105, R1	09/08/2021	This document supersedes EPC-CP-QP-2105, R0. Updated LANL logo, changed "memorandum" to "cover sheet," changed "modified sampling quarters" to "MSGP monitoring quarters," "best management practice" to "stormwater control measure," and updated facility types and permit section reference to match new permit.

MSGP Stormwater Visual	No: EPC-CP-QP-2105	Page 3 of 19
Assessments	Revision: 1	Effective Date: 09/08/2021

Table of Contents

Revis	sion H	istory	2
1.0	Intro	duction	4
	1.1	Purpose	4
	1.2	Scope	4
	1.3	Applicability	4
2.0	Prec	autions and Limitations	5
	2.1	Precautions	5
	2.2	Limitations	5
3.0	Prer	equisite Actions	5
	3.1	Planning and Coordination	5
	3.2	Special Tools, Equipment, Parts, and Supplies	6
4.0	Visu	ally Assessing Stormwater	7
	4.1	Documenting Sample Information	7
	4.2	Assessing Parameters	
	4.3	Completing the Visual Assessment Form	10
	4.4	Completing the Certification Statement	11
5.0	Trair	ning	11
6.0	Reco	rds	12
7.0	Defi	nitions and Acronyms	12
	7.1	Definitions	12
	7.2	Acronyms	13
8.0	Refe	rences	13
9.0	Atta	chments	13
	Atta	chment 1: Screenshot Examples of EPC-CP-QP-2105 R1 Form 1	14
	Atta	chment 2: EPC-CP-QP-2105 R1 Form 1, MSGP Visual Assessment Hard Copy Example	18

MSGP Stormwater Visual	No: EPC-CP-QP-2105	Page 4 of 19
Assessments	Revision: 1	Effective Date: 09/08/2021

1.0 INTRODUCTION

Los Alamos National Laboratory (LANL) through Environmental Protection and Compliance – Compliance Programs (EPC-CP) conducts stormwater monitoring activities required pursuant to the National Pollutant Discharge Elimination System (NPDES), Multi-Sector General Permit (MSGP). The MSGP requires LANL to monitor stormwater runoff from industrial sites relative to potential pollutants.

1.1 Purpose

This procedure describes the process for conducting visual assessments of stormwater from permitted outfall locations where LANL conducts stormwater monitoring activities for compliance under the MSGP.

1.2 Scope

Requirements set forth in this document apply to active LANL industrial facilities covered by the MSGP. These facilities include, a warehouse, several metal fabrication areas/shops, a heavy equipment yard, an asphalt batch plant, roads and grounds, and a material recycling facility. Inspection waivers may be granted by EPC-CP for adverse weather conditions and unstaffed or inactive sites.

At least once each MSGP monitoring quarter, an unfiltered stormwater sample is collected from each discharge point covered by the MSGP and identified in the site-specific Stormwater Pollution Prevention Plan (SWPPP). The sample must be visually inspected for water quality characteristics. Stormwater samples are collected with an automated sampler, single-stage sampler, or by taking a grab sample. Visual assessments are **not** performed on filtered stormwater.

Visual assessments conducted under this procedure are documented using the Maintenance Connection Express[™] (MC Express) web application on a tablet or notebook style computer. In the event of electronic hardware or web application failure, personnel may use a printed hard copy to document the work.

1.3 Applicability

This procedure applies to the EPC-CP technical staff and subcontractor personnel (as applicable) who conduct stormwater visual assessments during or after measurable storm events at MSGP outfalls.

A measurable storm event is identified in Part 4.1.3 of the MSGP as one that results in an actual discharge from the site that follows the preceding measurable storm event by at least 72 hours (three days).

Page 5 of 19

2.0 PRECAUTIONS AND LIMITATIONS

2.1 Precautions

The hazard level for the activities described in this procedure is <u>LOW</u>, therefore an Integrated Work Document (IWD) Part I is not required. If required by a Facility Operations Division (FOD), an IWD Part II (2101 Form) will address any site-specific requirements and training for the FOD.

Personnel will wear appropriate clothing (e.g., boots, long pants, etc.,) to perform work in the field.

Work may be discontinued during periods or conditions that make sites dangerous for worker safety or prevent personnel from safely accessing sites (e.g., weather-related events such as flash floods, flooding, lightning, wildfires, hail, icy roads, deep snow, or LANL operations such as firing shots or open burns).

If conditions prevent fieldwork, document these conditions on the work order. Multiple attempts can be documented on the original form. If the target date cannot be met, field personnel will contact the Program Lead no less than 24 hours before the target date for guidance.

2.2 Limitations

In MC Express, document responses to each question on a work order by clicking the expand arrow located on the right side of the task line and changing the "Complete" or "Failed" line to "Yes." When using a hard copy form, mark the appropriate check box.

Throughout this process, field personnel will document comments and notations in the "Reading" field of the associated task line. Additional comments not documented in a "Reading" field can be entered in the "Comments" field of the same task line. If field personnel need more space, additional comments can be entered in the "Labor Report Update" field (see Section 4.3) when the work order is updated to "Complete" status. When using a hard copy form, document comments on the corresponding task line. If additional space is needed, comments can be entered in the "Labor Report" section at the bottom of the form.

Some terminology varies between the MC Express software and the Maintenance Connection (MC) desktop software.

- The "Reading" field in MC Express is the same field as "Reading Final" in MC desktop and "Meas." on a hard copy (printed) work order.
- The "Complete" option in MC Express is the same as a "Yes" answer. The "Failed" option in MC Express is the same as a "No" answer. MC desktop and hard copy (printed) work orders use "Yes" and "No" terminology.

3.0 PREREQUISITE ACTIONS

3.1 Planning and Coordination

1. Schedule work to be completed by the target date appearing on the work order(s) or as requested by the MSGP Program Lead if a work order is not issued.

MSGP Stormwater Visual	No: EPC-CP-QP-2105	Page 6 of 19
Assessments	Revision: 1	Effective Date: 09/08/2021

- 2. As specified in the IWD Part II (if applicable), inform (e.g., by e-mail) facility contacts and/or the Deployed Environmental Professional (DEP) of the schedule for work and locations up to a week (preferred) before but no later than the day before (for minor changes) so work is added to the appropriate plan of the day.
- 3. Gather the required equipment (see Section 3.2) for the work to be done.
- 4. Using the Safari or Chrome web browser on a tablet or notebook style computer, log into the MC Express application (http://express.maintenanceconnection.com) and confirm that the work order list displayed matches your sites. If the work order lists do not match, contact EPC-CP Data Management personnel for clarification.
- 5. In MC Express, click on the appropriate work order number to open the work order. The work order will open in the display to the Work Order Summary page.
- 6. Click on the "Tasks" bar to navigate to the work order Tasks page. See MC Express screen shot examples in Attachment 1.
- 7. Always log out of MC Express when you have finished work OR work is interrupted.

3.2 Special Tools, Equipment, Parts, and Supplies

Ensure the following equipment is available in the field vehicle:

- Safety glasses
- Nitrile gloves
- Sturdy hiking boots or steel toed shoes with soles that grip
- Other facility specific personal protective equipment as required by the FOD
- Cell phone (only government cell phones are allowed in secure areas) (See https://int.lanl.gov/policy/documents/P217.pdf for requirements for using portable electronic devices on Laboratory property.)
- Current copy of this procedure
- Current copy of the IWD(s) Part II (as needed)
- Site map(s) (as needed)
- Current electronic work order or paper inspection form
- EPC-CP MSGP Sampling and Analysis Plan (SAP) most recent revision for the current monitoring year OR program specific monitoring plan
- Government issued electronic tablet with Safari web browser and Blackberry UEM[™] app. (See <u>https://int.lanl.gov/policy/documents/P217.pdf</u> for requirements for using portable electronic devices on Laboratory property.)
- Necessary access and station keys

- Access to accurate time measurement
- Clean replacement sample bottles (clear glass or clear poly)
- Paper towels

4.0 VISUALLY ASSESSING STORMWATER

Stormwater visual assessments are determined at a sampling station based on the current year SAP. See Attachment 1 for screen shot examples of EPC-CP-QP-2105 R1 Form 1, *MSGP Visual Assessment*, in MC Express. See Attachment 2 for an example of the form in hard copy format.

NOTE: Each item number listed in red below corresponds to a red numbered box on both screenshots and hard copy format.

4.1 Documenting Sample Information

- [1] Take the sample bottle with water out of the automated sampler or single stage jar off the ground or fill a clear sample bottle with a grab sample and wipe off exterior.
 - [a] Grab samples are collected during daylight hours in a wide-mouth clear glass or plastic container within 30 minutes of discharge from a storm event.
- [2] **ITEM 1**: Document the monitoring period by entering Jan-Mar, Apr-Jun, Jul-Sep, or Oct-Dec.
 - [a] <u>IF</u> the stormwater discharge collected is from a rain event from the previous monitoring period and the visual assessment is made in the following monitoring period,

<u>THEN</u> document monitoring period on the inspection to correspond to the period in which the rain event took place.

- [3] **ITEM 2**: Check the date and time stormwater discharge began and document by entering the date in the following formats: MM/DD/YY or MM-DD-YY. Time must be entered in 24-hour format.
 - [a] <u>IF</u> the discharge date/time is not available (e.g., precipitation report) when the visual is performed in the field,

<u>THEN</u> leave this Task Line incomplete and complete when the information is available.

- [4] **ITEM 3**: Check the date and time the sample was collected and document by entering the date in the following formats: MM/DD/YY or MM-DD-YY. Time must be entered in 24-hour format.
 - [a] <u>IF</u> the collection date/time is not available (e.g., precipitation report) when the visual is performed in the field,

<u>THEN</u> leave this Task Line incomplete and complete when the information is available.

- [5] **ITEM 4**: Check the date and time stormwater was visually assessed and document by entering the date in the following formats: MM/DD/YY or MM-DD-YY. Time must be entered in 24-hour format.
- [6] **ITEM 5**: Describe the nature of the discharge (e.g., rain, snowmelt, hail) and the TOTAL amount of precipitation in inches from the event.
 - [a] <u>IF</u> the total amount of precipitation is not available (e.g., precipitation report) when the visual is performed in the field,

<u>THEN</u> leave this Task Line incomplete and complete when the information is available.

- [7] **ITEM 6**: Check that the sample was collected in the first 30 minutes of discharge and document.
 - [a] <u>IF</u> it is not possible to collect the sample within the first 30 minutes of discharge,
 <u>THEN</u> the sample must be collected as soon as practicable after the first 30 minutes.
 - [b] The field inspector will document the reason a sample could not be collected within the first 30 minutes (e.g., lightning hazard, flooding).

4.2 Assessing Parameters

While conducting the visual assessment, personnel will attempt to relate any evidence of stormwater pollution that is observed in the sample to a pollutant source on the site. A cleanup of the site can be conducted if the pollutant source is known and well defined. Refer to EPC-CP-QP-2109, *MSGP Corrective Actions,* for specific steps to document, track, and report conditions of potential stormwater pollution.

- [1] **ITEM 7**: Observe the color of the discharge in the sample container. Document by describing the color.
- [2] **ITEM 8**: Observe any odors detected from the sample. Document by describing the odor (e.g., musty, sewage, sulfur, sour, solvents, petroleum/gas).
- [3] **ITEM 9**: Observe the clarity of the discharge. Document by describing the clarity (e.g., slightly cloudy, cloudy, opaque).
 - **NOTE 1:** Clarity is described as the depth in which you can look into or through water. For example, an individual can see through a clear glass of clean water in daylight. Generally, the clarity of the water is a good visual indicator of the purity of water. If the water is poor in clarity there is most likely suspended solids throughout the water.
- [4] **ITEM 10**: Observe any floating solids in the discharge. Document by describing the floating solids.

MSGP Stormwater Visual	No: EPC-CP-QP-2105	Page 9 of 19
Assessments	Revision: 1	Effective Date: 09/08/2021

- **NOTE 2**: Careful examination will determine whether the solids are raw materials (e.g., product used to fabricate something, or ingredients used in a formulation) or waste materials (e.g., shavings, woodchips and sawdust, trash).
- [5] **ITEM 11**: Observe any settled solids in the sample. Document by describing the settled solids (e.g., sediment, vegetation, fine, course).
 - **NOTE 3:** Settled solids may be an indicator of unstable ground cover combined with a high-intensity stormwater runoff event.
- [6] **ITEM 12**: Observe any suspended solids in the sample. Document by describing the suspended solids (e.g., vegetation, ash, sediment, fine, course).
 - **NOTE 4:** Most often suspended solids include fine sediment. This may be an indication of an unstable channel with eroding banks. Some water may appear to be colored because of relatively fine particulate material in suspension such as sediment.
- [7] **ITEM 13**: Check to see whether the sample is free of foam. Gently shake the sample container. Document by describing any bubbles in or on the surface of the water and the color of the foam.
 - [a] <u>IF</u> it is determined that foam is caused by a pollutant, <u>THEN</u> complete the visual assessment and contact the EPC-CP MSGP Program Lead <u>immediately</u> following completion of the visual assessment.
 - [b] Follow-up action is required within 24 hours (see EPC-CP-QP-2109).
- [8] **ITEM 14**: Check to see whether the sample is devoid of any oil sheen. Document by describing the thickness and consistency (e.g., flecks, globs).
 - [a] <u>IF</u> an oil sheen is present, <u>THEN</u> contact the EPC-CP MSGP Program Lead <u>immediately</u> following completion of the visual assessment.
 - [b] Document in the Labor Report (ITEM 17) the source of the oil sheen, if existing stormwater control measures (SCMs) are effective in mitigation of potential pollutants, and if a new SCM needs to be installed.
 - [c] Follow-up action is required within 24 hours (see EPC-CP-QP-2109).
- [9] **ITEM 15**: Check to see whether the discharge is free of any other indicators of stormwater pollution not described in any other task line above.
- [10] <u>IF</u> there are any potential sources of pollutants observed on site, <u>THEN</u> document the following and contact the EPC-CP MSGP Program Lead within 24 hours of identification:
 - Potential sources;

- Indicate if there are SCMs on site;
- Evaluate whether the SCMs are working correctly or need maintenance;
- Evaluate whether implementation of additional SCMs are needed to address the observed contaminant.
- [11] Contact the FOD, DEP, and EPC-CP MSGP representative to inform them of the situation.

NOTE 5: Refer to EPC-CP-QP-2109, *MSGP Corrective Actions,* for specific steps to document, track, and report conditions of potential stormwater pollution.

[12] After all task lines have been completed, make sure you have clicked the "Save" bar at the bottom of the page.

4.3 Completing the Visual Assessment Form

- [1] Ensure the inspection form has been filled out completely including information not available during the field inspection (e.g., date/time of discharge, date/time of sample collection, total precipitation amount).
- [2] Click the "Back" arrow button in the upper left-hand corner to exit the work order Tasks page and return to the Work Order Summary page.
- [3] Click the checkered flag A in the upper right corner of the Work Order Summary page to open the Work Order Status Update page. MC Express auto-populates the date and time fields.

CAUTION

MC Express automatically changes the work order status to "Closed."

- [4] **ITEM 16**: Click on the expand arrow located on the right side of the "New Status" field and select "Completed" from the available dropdown menu.
 - [a] Ensure the auto-populated date and time is the date and time that the **work** was completed and *not* the date/time the form was filled out.
 - [b] <u>IF</u> work is performed over multiple days, <u>THEN</u> note the date and time the work began in the Labor Report field.
 - [c] To update the date or time, click the "Date" field and make necessary adjustments using the available timestamp application. Click "Set" to apply changes.
 - [d] IF using a hard copy form,

<u>THEN</u> write the date and time the work was completed.

MSGP Stormwater Visual	No: EPC-CP-QP-2105	Page 11 of 19
Assessments	Revision: 1	Effective Date: 09/08/2021

- [5] **ITEM 17**: The field personnel must type or write his/her name in the "Labor Report Update" field.
- [6] Any additional notes, observations, or site conditions not documented in a task line "Reading" or "Comments" field can be documented in the "Labor Report Update" field.
- [7] Scroll down the page to the "Signature" bar and click the expand arrow on the left side of the bar to open the "Signature" field.
 - [a] **ITEM 18**: Capture an electronic signature by drawing with a finger on the tablet screen. The Lead Inspector is certifying that the information submitted is "true, accurate, and complete" by electronically signing the work order.
 - **NOTE:** The mouse must be used to sign electronically when using MC Express on a desktop screen (not a tablet).
 - [b] If using a hard copy form, the field personnel will sign his/her name and the date of when the form was signed.
 - [c] By signing either electronically or on hard copy, the field personnel is certifying that the information submitted is "true, accurate, and complete."
- [8] Click on the "Save" bar at the bottom of the page to close the "Signature" field.

4.4 Completing the Certification Statement

The EPC-CP MSGP Program Lead or designee will send completed visual assessment forms to the DEPs at the end of each quarter that will contain a certification statement in the cover sheet. The duly authorized signatory may sign and date this certification statement rather than the certification line associated with each attached form. However, the cover sheet and associated completed forms must remain together.

5.0 TRAINING

All EPC-CP personnel that execute the activities specified in this procedure must meet the minimum qualification and training requirements for their position as identified EPC-CP-PIP-2101, *NPDES Multi-Sector General Permit Program Implementation Plan*. This will include "self-study" (required reading), recurring annually, for this procedure as assigned and documented in the LANL UTrain system. Other participating LANL groups may require training to local procedures and document completion of training.

Contract personnel that execute the activities specified in this procedure will be qualified and trained as required by the Exhibit D and Exhibit F. In addition, contract personnel are required to complete "self-study" (required reading) of this procedure.

MSGP Stormwater Visual	No: EPC-CP-QP-2105	Page 12 of 19
Assessments	Revision: 1	Effective Date: 09/08/2021

6.0 RECORDS

MSGP Visual Assessment forms are signed and certified by individual LANL facilities. These completed forms are maintained in the facility's SWPPP and managed by the facility's document management system. The MSGP team may retain a copy for reference purposes.

Below are records generated as a result of implementing this procedure that are identified by title and type.

Record Title	QA Record	Non-QA Record
EPC-CP-QP-2105 R1 Form-1, MSGP Visual Assessment	\square	

7.0 DEFINITIONS AND ACRONYMS

7.1 Definitions

See LANL *Definition of Terms*.

Adverse weather conditions – Weather that prohibits collection of samples such as local flooding, high winds, hurricanes, tornadoes, electrical storms, etc. Could also include drought, extended frozen conditions, etc.

Clarity – Clearness or cleanness of appearance. This includes the visual observation of suspended sediment.

Color – Unpolluted water will be clear and colorless. Color must not be confused with clarity.

Control Measure – Refers to any stormwater control or other method (including narrative effluent limitations) used to prevent or reduce the discharge of pollutants to waters of the United States.

Floating solids – Particulate material floating on the surface of the water. Examples include raw or waste materials and common trash.

Foam – An accumulation of fine frothy bubbles formed in or on the surface of water. A mass of bubbles of air in a matrix of liquid film.

Measurable storm event – Precipitation that results in an actual discharge from ther site that follows the preceding measurable storm event by at least 72 hours (3 days).

Odor – The property or quality of waters that affects or stimulates the sense of smell. Examples of odors that may be present are burnt oil, petroleum hydrocarbon, sewage, diesel, sulfuric, or detergent odors.

Oil sheen – The presence of rainbow-like colors glistening on the surface of a liquid. The color of oil sheen will vary dependent on thickness and consistency.

Settled solids – Settled particulate material i.e., heavier than water. Examples include sand, gravel, metal turnings, and glass.

MSGP Stormwater Visual	No: EPC-CP-QP-2105	Page 13 of 19
Assessments	Revision: 1	Effective Date: 09/08/2021

Suspended solids – Particulate materials that are floating between the bottom of the sample and the surface of the water.

Unstaffed and Inactive Sites – A facility maintaining certification within the SWPPP that it is inactive and unstaffed and visual examinations are not required.

7.2 Acronyms

See LANL Acronym Master List.

DEP	Deployed Environmental Professional
EPC-CP	Environmental Protection and Compliance – Compliance Programs
FOD	Facility Operations Division
IWD	Integrated Work Document
LANL	Los Alamos National Laboratory
MC	Maintenance Connection
MC Express	Maintenance Connection MC Express web application
MSGP	Multi-Sector General Permit
NPDES	National Pollutant Discharge Elimination System
SAP	Sampling and Analysis Plan
SCM	Stormwater Control Measure
SWPPP	Stormwater Pollution Prevention Plan

8.0 **REFERENCES**

EPC-CP-QP-2109, MSGP Corrective Actions

EPC-CP-PIP-2101, NPDES Multi-Sector General Permit Program Implementation Plan

9.0 ATTACHMENTS

Attachment 1: Screenshot Examples of EPC-CP-QP-2105 R1 Form 1, MSGP Visual Assessment in MC Express

Attachment 2: EPC-CP-QP-2105 R1 Form 1, MSGP Visual Assessment Hard Copy Example

MSGP Stormwater Visual	No: EPC-CP-QP-2105	Page 14 of 19
Assessments	Revision: 1	Effective Date: 09/08/2021

Attachment 1: Screenshot Examples of EPC-CP-QP-2105 R1 Form 1 MSGP Visual Assessment in MC Express

(Page 1 of 4)

Work Order Summary Page (Section 3.1, Steps 5 and 6)

(-	MC Expres	s 🔳
WORK ORDER	R: MSGP-4344	^ ⊙
	ASGP00901] MSGP00901 A-3-22 Power & Steam Plant equested	
EXAMPLE	MSGP Visual Assessment	
Task	s	15
Assig	gnments	0
Labo	or	0
Parts	5	0
Othe	er Costs	0
0 Atta	chments	0
Asse	t History	121
More Wo	rk Order Detail	•
0	Refresh 🗰	List

MSGP Stormwater Visual	No: EPC-CP-QP-2105	Page 15 of 19
Assessments	Revision: 1	Effective Date: 09/08/2021

Attachment 1: Screenshot Examples of EPC-CP-QP-2105 R1 Form 1 MSGP Visual Assessment in MC Express (cont.)

(Page 2 of 4)

Work Order Tasks Page – Documenting Sample Information (Section 4.1, Steps 2-7)

(MC Express	
WORK ORDER: MSGP-4344 Tasks		
Tasks 🕥		a
	es to associated SIOs as defined in the SWPPP, where applicable.	
Sample information		
30 1 Document the monitoring	períod.	+
40 2 Document the Date/Time	Discharge began in the "Reading" field of this line (using mm/dd/yy hh:mm form	nat). 🛨
50 3 Document the Date/time	sample collected in the "Reading" field of this line (using mm/dd/yy hh:mm for	mat).
60 4 Document the Date/time	sample visually assessed in the "Reading" field of this line (using mm/dd/yy hh:	mm format).
70 5 Document the nature of c	discharge (e.g., rain, snowmelt). Document the TOTAL amount (in) in the "Readir	ng° field of this line.
80 6 Sample collected in first	30 minutes of discharge? If "Failed" or unknown, provide a reason.	*
C) Re	efresh 🛄 List	
	MC Express	©
	Edit Took 30 Document the monitoring period. Reading	9
	July-Sept	(

+	MC Express	
WORK ORDE	R: MSGP-4344	•
	30 Document the monitoring period.	
Reading		
July-Sept		
Initials		
\sim		
Failed?	-	
No		0
Not Appl	icable?	
No		0
Complete	•7	
Yes		0
Commen	ts	
Commen	ts	
5 Ca	ncel 🖌 Save 🔿	Save/Next

MSGP Stormwater Visual	No: EPC-CP-QP-2105	Page 16 of 19
Assessments	Revision: 1	Effective Date: 09/08/2021

Attachment 1: Screenshot Examples of EPC-CP-QP-2105 R1 Form 1 MSGP Visual Assessment in MC Express (cont.)

(Page 3 of 4)

Work Order Tasks Page – Assessing Parameters (Section 4.2, Steps 1-9)

E	MC Express		
WORK ORDER: MSGP-4344 Tasks		P	\odot
Parameters			
110 Is sample colorless? If "Failed", describe.			*
120 Is sample oderless? If "Failed", provide des	scription (e.g. musty, sewage, sulfur, sour, solvent, petro	oleum/gas)	+
130 Is sample clear? If "Failed", provide descri	ption (e.g., slightly cloudy, cloudy, opaque).		+
140 10 Is sample free of floating solids? If "Failed	", describe if raw or waste material(s) in the comments o	of this line.	+
150 15 sample free of settled solids? If "Failed"	', provide description (e.g., fine, course).		+
160 12 Is sample free of suspended solids? If "Fail	led", provide description (e.g., fine, course).		+
170 13 Is sample foamless after gently shaking? If	f "Failed" describe foam color and location (e.g.,'on the s	urface' or 'in the sample').	+
180 Is sample devoid of an oil sheen? If "Failed	d", describe color and thickness (e.g. flecks, globs).		+
190 15 Is sample free of other obvious indicators	of pollution? If "Failed", describe.		+
1 Refresh		List	

MSGP Stormwater Visual	No: EPC-CP-QP-2105	Page 17 of 19
Assessments	Revision: 1	Effective Date: 09/08/2021

Attachment 1: Screenshot Examples of EPC-CP-QP-2105 R1 Form 1 MSGP Visual Assessment in MC Express (cont.)

(Page 4 of 4)

Work Order Status Update Page – Completing the Form (Section 4.3, Steps 4-6)

4	MC Express	
WORK ORDER: M	SGP-4344	
Issued	/ Completed	
New Status	16	
Completed		0
Date		
6/19/2018 10:	48 AM	
Percent Com	plete 100%	
6		0
Labor Report	Update 17	
Select Comme	nts to Add	0
Jane Admin		-
5 0	ancel	Save

Work Order Status Update Page (Section 4.3, Step 7)

4	-	MC Express	
WORK OR Status Upda	DER: MSGP-434	14	
O Sign	nature 18	3	
(Remov	ve)	2	
N	rome Ad	lmin-	
18	runne fac	v	
5	Cancel		Save

MSGP Stormwater Visual	No: EPC-CP-QP-2105	Page 18 of 19	
Assessments	Revision: 1	Effective Date: 09/08/2021	

Attachment 2: EPC-CP-QP-2105 R1 Form 1, MSGP Visual Assessment Hard Copy Example

(Page 1 of 2)

	os Ala	mos National Laboratory	Work Order MSGP-4: MSGP Monitoring Ste Printed 6/19/2018 - 10:55 AM (Duplicate C		
٨	lainten	ance Details			
1	Request Procedu Last PM	Assessment (EPC-CP- QP-2105 R1 Form 1	MSGP Program Ta RG121.9 TA-60-2 Warehoue Monitored Outfall (026)		
ľ	LUGUTIM		Contrast Adams Inc.		
1	Reason:	EXAMPLE MSGP Visual Assessment	Contact: Admin, Jane Phone: 123-4567		
94	Special	Instructions:			
T	asks				
	# The res	Description ult of this VA applies to associated SIOs as defined in the SWPPP, wh	Meas. No N/A Yes		
1		Information Document the monitoring Period			
	40	Document the Date/Time Discharge began in the "Reading" field of this in mm/dd/yy hh:mm format).			
]	50	Document the Date/time sample collected in the "Reading" field of this lin mm/dd/yy hh:mm format).	e (using		
]	60	Document the Date/time sample visually assessed in the "Reading" field of this line (using mm/dd/yy hh:mm format).			
]	70	Document the nature of discharge (e.g., rain, snowmelt). Document the TOTAL amount (in) in the "Reading" field of this line.			
	80	Sample collected in first 30 minutes of discharge? If "Failed" or unknown, reason.	provide a		
	Parame	iters			
1	110	Is sample colorless? If "Failed", describe. Is sample oderless? If "Failed", provide description (e.g. musty, sewage, s			
]	120	solvent, petroleum/gas)			
	130	Is sample clear? If "Failed", provide description (e.g., slightly cloudy, cloud	dy, opaque). 🔽 🗖 🔽		
,	140	Is sample free of floating solids? If "Failed", describe if raw or waste mate comments of this line.	rial(s) in the		
	150	Is sample free of settled solids? If "Failed", provide description (e.g., fine,			
2	160	Is sample free of suspended solids? If "Falled", provide description (e.g., inc.			
	100	Is sample foamless after gently shaking? If "Failed" describe foam color a			
5	170	(e.g., 'on the surface' or 'in the sample').			
1	1.00	Is sample devoid of an oil sheen? If "Failed", describe color and thickness			
	180	globs).			
5	190	Is sample free of other obvious indicators of pollution? If "Failed", describe			
L	abor R				
-1		ted: 6/19/2018 10:48:00 AM			
	Report:	Jane Admin			
	N				
3		VIML 600000- 6/19/2018 Stonature / Name Date St	Signature / Name Date		

MSGP Stormwater Visual	No: EPC-CP-QP-2105	Page 19 of 19
Assessments	Revision: 1	Effective Date: 09/08/2021

Attachment 2: EPC-CP-QP-2105 R1 Form 1, MSGP Visual Assessment Hard Copy Example (cont.) (Page 2 of 2)

	CERTIFICATION STATEMENT	
a system designed to assure that qualified p the person or persons who manage the syst is, to the best of my knowledge and belief.	sument and all attachments were prepared under personnel properly gathered and evaluated the in em, or those persons directly responsible for gat true, accurate, and complete. I am aware that the he and imprisonment for knowing violations".	formation submitted. Based on my inquiry of hering information, the information submitted
(Signatory must meet definition in Section	on B.11.A, eg. FOD, Ops Mgr, EPC Group or	Team Leader)
Print name and title:	- Chi	
Signature:	Date:	
	4	EPC-CP-QP-2105 R1 Form 1
0	810 - C	
	/	

ATTACHMENT 19: EPC-CP-QP-2103, INSPECTING ISCO STORMWATER RUNOFF SAMPLERS AND RETRIEVING SAMPLES

EPC-CP-TP-2103		Revision: 0		Los Alamos	
Effective Date: 02/24/2020		Next Review I	Date: 02/24/2023	NATIONAL LABORATORY EST. 1943	
Environmen	Environment, Safety, Health, Quality, Safeguards, and Security Directorate				
Environmen	t Protection	and Complia	nce – Compliance F	Programs Group	
Technical Pro	ocedure				
Ins	pecting IS		water Runoff Sa ing Samples	amplers and	
Hazard Grading:	Low	🔀 Moderate	High/Complex		
Usage Level:	🔀 Reference	UET	Mixed: UET Sections:		
Status:	New	Major Revision	Minor Revision		
Review w/No Chang		Changes	Other: <u>New EPC-CP form</u>	nat and numbering system	
			USI Number:		
-					
			r/Subject Matter Expert:		
Name:		Organization:	Signature:	Date:	
Holly L. Wheeler		EPC-CP	Signature on File	02-20-2020	
	Derivativ	ve Classifier: 🔀	Unclassified or 🗌		
Name:		Organization:	Signature:	Date:	
Steven E. Wolfel		EPC-CP	Signature on File	02-19-2020	
		Approv	al Signatures:		
EPC-CP Reviewer:		Organization:	Signature:	Date:	
Terrill W. Lemke		EPC-CP	Signature on File	02-19-2020	
EPC-CP RLM:		Organization:	Signature:	Date:	
Taunia Van Valkent	ourg	EPC-CP	Signature on File	02-24-2020	
	This copy is uncontrolled. Users are responsible for ensuring they work to the latest approved version. To document a required read, Login to <u>UTrain</u> , and go to the Advanced Search.				

Inspecting ISCO Stormwater Runoff	No: EPC-CP-TP-2103	Page 2 of 27
Samplers & Retrieving Samples	Revision: 0	Effective Date: 02/24/2020

REVISION HISTORY

Document Number and Revision [Include revision number, beginning with Revision 0]	Effective Date [Document Control Coordinator inserts effective date]	Description of Changes [List specific changes made since the previous revision]
ENV-RCRA-QP-047, Rev. 0	03/11	New Document.
ENV-RCRA-QP-047, Rev. 1	02/13	Annual Review and Revision
EPC-CP-QP-047, Rev. 2	09/06/2017	Review and revision. Updated document to new template and new group name. Clarified steps. Modified inspection form EPC-CP-Form-1010. Added crosswalk to electronic form in MC Express.
EPC-CP-TP-2103 R0	02/24/2020	Supersedes EPC-CP-QP-047 R2. Reformat to new EPC-CP template. Re-number procedure and forms to new EPC-CP procedure numbering system. Minor edits.

Inspecting ISCO Stormwater Runoff	No: EPC-CP-TP-2103	Page 3 of 27
Samplers & Retrieving Samples	Revision: 0	Effective Date: 02/24/2020

Table of Contents

Revis	ion Hi	story		.2
1.0	Intro	duction		.4
	1.1	Purpose		.4
	1.2	Scope		.4
	1.3	Applicability.		.4
2.0	Preca	utions and Lir	nitations	.5
	2.1	Precautions		.5
	2.2	Limitations		.5
3.0	Prere	quisite Action	S	.6
	3.1	Planning and	Coordination	.6
	3.2		Documents	
	3.3	Special Tools,	, Equipment, Parts, and Supplies	.7
4.0	Inspe	cting the Sam	pler and Sample Retrieval	.8
	4.1	Inspecting the	e Sampler	.8
			rrival	
			er Collection Information	
		4.1.3 Wate	er Retrieval Information	10
		4.1.4 On D	eparture1	10
			oment Specific Tasks	
			tenance Information1	
			e Information1	
	4.2	•	mples1	
	4.3	-	prmwater Samples from the field	
	4.4		he Inspection Form1	
5.0		0	1	
6.0			1	
7.0	Defir		onyms1	
	7.1		1	
	7.2	•	1	
8.0	Refe	ences	1	17
9.0			1	18
	Atta		eenshot Examples of EPC-CP-TP-2103 R0 Form 1, ISCO Sampler Inspection and	
		•	eval in MC Express1	
	Atta		C-CP-TP-2103 R0 Form 1, ISCO Sampler Inspection and Sample Retrieval Hard Copy	
		•		
	Atta	hment 3: Sam	nple Retrieval Flow Diagram2	27

Inspecting ISCO Stormwater Runoff	No: EPC-CP-TP-2103	Page 4 of 27
Samplers & Retrieving Samples	Revision: 0	Effective Date: 02/24/2020

1.0 INTRODUCTION

Los Alamos National Laboratory (LANL) through Environmental Protection and Compliance-Compliance Programs (EPC-CP) conducts stormwater monitoring activities required pursuant to the National Pollutant Discharge Elimination System (NPDES), Multi-Sector General Permit (MSGP) at LANL. The MSGP requires LANL to monitor stormwater runoff from industrial sites relative to potential pollutants.

1.1 Purpose

This procedure describes the process for inspecting ISCO automated samplers and retrieving stormwater runoff samples from outfall locations where LANL conducts stormwater monitoring pursuant to NPDES MSGP requirements. This procedure may also be used for other Associate Laboratory Directorate of Environment, Safety, Health, Quality, Safeguards, and Security (ESHQSS) stormwater monitoring activities as needed.

1.2 Scope

The discharge of stormwater from specified industrial sites at LANL is regulated under the NPDES MSGP. The Laboratory's MSGP requires qualitative and quantitative stormwater monitoring (e.g., sample collection) to evaluate the effectiveness of control measures. Automated ISCO samplers coupled with liquid level actuators are used at MSGP monitoring stations and in support of other stormwater monitoring programs. Refrigerated (Avalanche[®]) and/or non-refrigerated (Model 3700) samplers are deployed and configured with multi-battery arrays, solar panels, and surge protectors.

Field personnel are required to inspect the sampling station while retrieving water samples during MSGP stormwater monitoring periods and at other intervals determined by the program or as directed by the MSGP Program Lead.

Inspections and sample retrieval conducted under this procedure should be documented using the Maintenance Connection Express[™] (MC Express) web application on a tablet or notebook style computer. (In the event of electronic hardware or web application failure, personnel may use a printed hard copy to conduct inspection and sample retrieval.)

1.3 Applicability

This procedure applies to the EPC-CP technical staff and subcontractor personnel (as applicable) conducting activities at automated stormwater sampling stations used for monitoring industrial stormwater discharge under the MSGP or other stormwater monitoring programs.

The MSGP Program Lead is primarily responsible for this procedure. EPC-CP personnel are appointed responsibility for a subset of sampling stations. Other stormwater monitoring programs or projects utilizing this procedure will refer to program or project specific roles and responsibilities.

2.0 PRECAUTIONS AND LIMITATIONS

2.1 Precautions

The hazard level of the activities in this procedure is <u>MODERATE</u>. Hazards in the work described in this procedure are controlled thorough a site specific Integrated Work Document (IWD) Part I. The IWD Part II (Form 2101) addresses site specific requirements and training by the Facility Operations Division (FOD).

Personnel performing steps in this procedure that involve electrical equipment **MUST** be trained to LANL electrical safety standards as prescribed in the IWD before performing those steps.

Personnel must wear appropriate clothing (e.g., boots, long pants, etc.) to perform work in the field.

Work may be discontinued during periods or conditions that make sites dangerous for worker safety or prevent personnel from safely accessing sites (e.g., weather-related events such as flash floods, flooding, lightning, wildfires, hail, icy roads, deep snow, or LANL operations such as firing shots or burns).

In the event of pest infestation (e.g., wasp or rat nests), do not attempt to remove the pest yourself. Call LANL Pest Control to coordinate the removal of the pest(s).

If conditions prevent field work, document the conditions in the Labor Report Update field on the form and notify the Program Lead or designee within 24 hours. Multiple attempts can be documented on the original form. If the target date cannot be met, the field personnel must contact the Program Lead no less than 24 hours before the target date for guidance.

2.2 Limitations

In MC Express, document responses to each question on a work order by clicking the expand arrow located on the right side of the task line and changing the "Complete" or "Failed" or "N/A" line to "Yes". When using a hard copy form, mark the appropriate check box.

Throughout this process, the field personnel will document comments and notations in the "Reading" field of the associated task line. Additional comments not documented in a "Reading" field can be entered in the "Comments" field of the same task line. If field personnel need more space, additional comments can be entered in the "Labor Report Update" field (see Section 4.10) when the work order is updated to "Complete" status. When using a hard copy form, document comments on the corresponding task line. If additional space is needed, comments can be entered in the "Labor Report" section at the bottom of the form.

Some terminology varies between the MC Express software and the Maintenance Connection desktop software.

• The "Reading" field in MC Express is the same field as "Reading Final" in Maintenance Connection desktop and "Meas." on a hard copy (printed) work order.

• The "Complete" option in MC Express is the same as a "Yes" answer; the "Failed" option in MC Express is the same as a "No" answer. Maintenance Connection desktop and hard copy (printed) work orders use "Yes" and "No" terminology.

3.0 PREREQUISITE ACTIONS

3.1 Planning and Coordination

- 1. Ensure that field personnel have access to accurate time measurement at the Site. When at the site, the clock time on the ISCO sampler must be set to Mountain Standard Time (MST) at all times, with no daylight saving time adjustment.
- 2. Schedule work to be completed by the target date appearing on the work order(s) or as requested by the MSGP Program Lead if a form is not issued.
- 3. Obtain any necessary additional paperwork before conducting this work, including IWD's, and excavation permits (as necessary).
- 4. As specified in the IWD, inform (e.g., by e-mail) facility contacts and/or Deployed Environmental Professional of the schedule for sampler work and locations up to a week before (preferred), but no later than the day before (for minor changes) so work may be added to the appropriate plan of the day.
 - **NOTE:** For some FODs like the Utilities and Institutional Facilities FOD, MSGP stormwater monitoring activities are on a standing plan of the day. However, this must be requested each year at the beginning of the monitoring season.
- 5. Gather the required equipment (see Section 3.3) for the work to be done.
- 6. Using the Safari or Chrome web browser on a tablet or notebook style computer, navigate to http://express.maintenanceconnection.com and select English from the available dropdown menu.
- 7. Log into the MC Express application (http://express.maintenanceconnection.com) and confirm that the work order list displayed matches your sites. If the work order lists do not match, contact EPC-CP Data Management personnel for clarification.
- 8. In MC Express, click on the appropriate work order number to open the work order. The work order will open in the display to the Work Order Summary page.
- 9. Click on the "Tasks" bar to navigate to the work order Tasks page. See MC Express screen shot examples in Attachment 1.
- 10. Always log out of MC Express when you have finished work OR if work is interupted.

3.2 Performance Documents

Personnel performing this procedure will be familiar with the most current versions of the following plans and operation manuals if this equipment is utilized. Copies of the following are not required to be on the job site.

- EPC-CP MSGP Sampling and Analysis Plan (SAP) most recent revision for the current monitoring year OR project specific monitoring plan;
- ISCO 3700 Portable Samplers Installation and Operation Guide;
- ISCO Avalanche[®] Installation and Operation Guide; or
- ISCO 701 pH/Temperature Module Installation and Operation Guide (if equipped at a station).

3.3 Special Tools, Equipment, Parts, and Supplies

Ensure the following equipment is available.

- Safety glasses;
- Sturdy hiking boots or steel toed shoes (as needed) with soles that grip and other required facility specific Personal Protective Equipment;
- Nitrile gloves;
- Leather gloves;
- Cell phone (only government cell phones are allowed in secure areas). (See https://int.lanl.gov/policy/documents/P217.pdf for requirements for using portable electronic devices on Laboratory property);
- Copy of this procedure;
- Copy of the IWD;
- EPC-CP MSGP SAP most recent revision for the current monitoring year OR project specific monitoring plan;
- Site Map(s) (as needed);
- Current electronic or paper inspection form EPC-CP-TP-2103 Form 1, *MSGP ISCO Sampler Inspection and Sample Retrieval;*
- Government issued electronic tablet with Safari or Chrome web browser and Blackberry UEM[™] app. (See <u>https://int.lanl.gov/policy/documents/P217.pdf</u> for requirements for using portable electronic devices on Laboratory property);
- Water Sample Collection and Processing Log/Field Chain of Custody (SCPL) (see EPC-CP-QP-2106);
- Access to accurate time measurement;
- Necessary access and station keys;
- Insulated hand tools;
- Charged spare battery(s);

Page 8 of 27

- Battery voltage tester;
- Clean spare tubing (pump, suction, discharge types, sampler specific);
- Certified clean replacement sample bottles (glass and poly);
- Spare/replacement sampler parts (liquid level actuator, distributor arm);
- Shovel;
- Wooden stakes;
- Plastic wire "zip" ties;
- Coolers with ice or Blue Ice[®];
- Paper Towels;
- Marker pen (permanent, waterproof);
- Ball point pen;
- Re-sealable zipper storage bags (e.g., Ziploc[®]);
- Custody seals; and
- 0.45 micron filter (where applicable).

4.0 INSPECTING THE SAMPLER AND SAMPLE RETRIEVAL

Inspection of ISCO samplers is performed weekly during the sampling season. Samples retrieved are determined at a sampling station based on the current year SAP. See Attachment 1 for screen shot examples of EPC-CP-TP-2103 R0 Form 1, *ISCO Sampler Inspection and Sample Retrieval* in MC Express. See Attachment 2 for an example of the form in hard copy format.

NOTE: Each ITEM number listed in red font below corresponds to a red numbered box on both screenshots (Attachment 1) and hard copy format (Attachment 2).

4.1 Inspecting the Sampler

4.1.1 On Arrival

- [1] Remove the top cover from the sampler.
- [2] **ITEM 1**: Check and document the sampler is ON and its condition upon arrival. Explain any non-functional status.
 - [a] <u>IF</u> a sampler has been inactivated (e.g., sample collection completed) prior to this inspection but continues to appear on the inspection form, <u>THEN</u> answer this task line question "N/A."
 - [b] Subsequent questions regarding the inactive sampler may be left unanswered in this section.

- [3] **ITEM 2**: Check and document the ISCO programming displays the following.
 - [a] ISCO 3700 sampler display should indicate "Sampler Inhibited"
 - [b] Avalanche sampler display should indicate "Program Disabled"
 - [c] Document messages other than those in [a] and [b] (e.g., "Done X samples," "sampler off," etc.,).
- [4] <u>IF</u> there is no indication of flow and the sampler triggered due to a non-flow event, <u>THEN</u> describe why the sampler triggered (e.g., animal, tumbleweed, etc.,).
- [5] **ITEM 3**: Check and document the sampler is set to the correct MST +/- no more than 1 minute. Do **NOT** use Daylight Savings Time.
 - [a] <u>IF</u> the sampler is set incorrectly, <u>THEN</u> reprogram for the correct MST.
 - [b] Describe the work performed and correction applied (e.g., "ISCO clock was X minutes slow").
- [6] If the location has more than one sampler, complete Steps 1 through 5 for each sampler.

4.1.2 Water Collection Information

- [1] Don nitrile gloves and safety glasses.
- [2] Remove the center section from the sampler.
- [3] **ITEM 4**: Document evidence of storm water flow at the sampling location by describing the evidence of flow (e.g., sediment or vegetation movement, erosion, standing water).
 - [a] <u>IF</u> the sampler did not trip but there is evidence of flow, <u>THEN</u> document the date and time storm water discharge began from the precipitation report.
 - [b] <u>IF</u> the sampler tripped or collected storm water, <u>THEN</u> document the date/time stamp from the sampler (or from the precipitation report if the sampler did not record a date/time stamp).
- [4] **ITEM 5**: Document that storm water is collected.
 - [a] Document if the water is taken by grab sample.
 - [b] Complete the Bottle Information (ITEM 20) in Section 4.1.7.
 - [c] Follow the steps in thru Section 4.2 Step 16 to retrieve samples.
- [5] **ITEM 6**: For Avalanche samplers only, record the current refrigerator temperature in degrees Celsius (°C) when water is collected.

- [a] <u>IF</u> unable to review the temperature, <u>THEN</u> check "No" and describe the condition (e.g., dead battery, electrical short).
- [6] **ITEM 7**: For Avalanche samplers equipped with an ISCO pH and Temp Module, check and document a pH measurement was taken on the collected water.
 - [a] Record the pH measurement taken at the time Bottle 1 was filled as "Average:Minimum:Maximum."
 - [b] <u>IF</u> unable to review the pH, <u>THEN</u> check "No" and describe the condition (e.g., damaged meter).

4.1.3 Water Retrieval Information

- [1] **ITEM 8**: Check and document whether a sample volume was retrieved from the sampler and taken off site.
 - [a] Record the estimated total volume in liters (L) or milliliters (ml) taken off site.
- [2] **ITEM 9**: Check and document whether a visual assessment of the water was performed (refer to EPC-CP-QP-2105).
 - [a] Do **NOT** conduct a visual assessment on a filtered sample. Record "Filtered sample."

4.1.4 On Departure

WARNING

You MUST be trained to LANL electrical safety standards as prescribed in the IWD before performing Steps 2 and 3.

- [1] Prepare yourself in accordance with the IWD for electrical work (e.g. wear safety glasses and leather gloves, use insulated tools, no jewelry or anything metal hanging from body, etc.,).
- [2] **ITEM 10**: Check that all cable and electrical connections are attached and firmly tightened (not loose) upon departure.
 - **NOTE:** Connections may work loose over time due to temperature changes and if there are dis-similar metals at the connection points. The loose connections can introduce voltage spikes, which inherently cause current spikes that may result in blown fuses.
 - [a] <u>IF</u> the cables require replacement, connections require tightening, or other maintenance performed, <u>THEN</u> describe the work performed (e.g., "tightened connectors on battery).
 - [b] IF maintenance cannot be completed at the time of inspection,

<u>THEN</u> describe the condition (e.g. cables chewed through by animal) and follow-up work needed (e.g., replace cables).

- [3] **ITEM 11**: Use a voltage meter to check the power supply.
 - [a] Record the voltage of the battery(ies) in volts (V).
 - [b] Document if battery voltage is acceptable upon departure from the site (≥11.7 for non-floating charged batteries at ISCO 3700 samplers and ≥11.0 for floating-charged batteries at Avalanche samplers).
 - [c] Replace a battery with a charged battery when the voltage is not acceptable.
 - [d] Check the voltage of the solar panel if access can be gained to the weather protected terminal covers on the back of the panel.
 - [4] Contact the program Electrical Safety Officer if any issues with wiring or batteries cannot be resolved on site.

4.1.5 Equipment Specific Tasks

- [1] **ITEM 12**: Check and document the sampler passes the diagnostic test. (Refer to EPC-CP-TP-2102 or sampler Operator's Guide for instructions on running a diagnostics test.)
 - [a] <u>IF</u> a sampler has been inactivated (e.g., sample collection completed) prior to this inspection but continues to appear on the inspection form,
 <u>THEN</u> answer this task line question as "N/A." Subsequent questions regarding this sampler may be left unanswered in this section.

CAUTION

Only reset the pump counts after replacing the internal pump tubing.

- [2] <u>IF</u> the internal pump tubing has reached or exceeded the preset pump counts (500,000 for ISCO 3700s, 1,000,000 for Avalanches),
 THEN replace the pump tubing and reset the pump counts.
- [3] **ITEM 13**: Check and document the sample tubing is free or clear of debris.
 - [a] Clear obstructions as needed and document maintenance performed.
- [4] Check the physical condition of sample tubing and vent tubing.
 - [a] Replace tubing as needed and document maintenance performed.
- [5] **ITEM 14**: Check and document the sample tubing has passed a suction test.
- [6] **ITEM 15**: Check and document the sampler is ON prior to departing the site.
- [7] **ITEM 16**: Check and document the liquid level actuator has been set to "Latch" prior to departing the site.

- [a] IF the sampler tripped and requires reset of the sampling program, THEN reset the actuator by toggling the switch to "Reset" and back to "Latch."
- [8] **ITEM 17**: Check and document the ISCO programming displays the following.
 - [a] ISCO 3700 sampler display should indicate "Sampler Inhibited."
 - [b] Avalanche sampler display should indicate "Program Disabled."
 - [c] Reprogram the sampler as needed and document maintenance performed.
- [9] Replace and secure the sampler top cover and secure the sampler shelter (if sampler is in a shelter).
- [10] If the location has more than one sampler, complete Steps 1 through 11 for each sampler.

4.1.6 Maintenance Information

- [1] **ITEM 18**: Document maintenance completed while on site that is not documented elsewhere on the work order by describing the work performed.
 - **NOTE**: Maintenance items may include (but are not limited to) site clearing, installing new or additional equipment, removing equipment, animal/pest mitigation, problems with equipment location, etc.
- [2] IF a battery was replaced,

THEN record the voltage of the new battery and the battery identification number.

- [a] <u>IF</u> the battery does not have an identification number, <u>THEN:</u>
 - Contact the MSGP Program Lead to have one assigned.
 - Paint or write the number in a permanent manner on the battery.
- [3] **ITEM 19**: Document if maintenance is needed that was not completed while on site and that is not documented elsewhere on the work order.
 - [a] Describe on the work order the follow-up maintenance needed.
 - [b] When the maintenance has been complete, describe the actions taken to complete the work on the original work order.
 - [c] Record the maintenance completion date and time on the original work order.

4.1.7 Bottle Information

[1] **ITEM 20**: Document water collected by recording the following information for each bottle by position number in the carousel.

Page 13 of 27

- Date (MM/DD/YY or MM-DD-YY) and time the ISCO collected water,
- Volume (L or ml) of water in the bottle,
- Type of bottle (e.g. G for glass, P for poly),
- Specific ISCO displayed message, if present.
- [2] IF the sampler(s) did not trigger,

<u>THEN</u> answer the task line question as "N/A" for Bottle #1 of each sampler and leave the other Bottle task lines unanswered.

- [3] <u>IF</u> a sampler has been inactivated (e.g., sample collection completed) prior to this inspection but continues to appear on the inspection form,
 <u>THEN</u> answer the task line question as "N/A". Subsequent questions regarding this sampler may be left unanswered in this section.
- [4] Proceed to Section 4.4 if no water was collected.

4.2 Retrieving Samples

Refer to the flow diagram in Attachment 3 as an aid in determining sample retrieval.

- [1] Don nitrile gloves and safety glasses.
- [2] Add up the estimated volume of water collected in the sampler.
- [3] Check that the estimated total volume of water in glass and poly matches the required volume for the specific location identified in the MSGP SAP.
 - **NOTE 1:** The volume of water required to complete analytical may vary by monitored location.
 - [a] <u>IF</u> the sample volume is sufficient to fulfill all analytical requirements, <u>THEN</u> continue to Step 4.
 - [b] <u>IF</u> the sample volume is sufficient to fulfill part of the analytical requirements, <u>THEN</u> consult the prioritization order on the MSGP SAP to determine which analytical to fulfill, <u>OR</u> contact the MSGP Data Manager. Continue to Step 4 but retrieve only the volume needed.
 - [c] <u>IF</u> the collected sample will NOT fulfill the minimum required volume for any analytical, THEN:
 - Complete a Visual Assessment if the sample is not filtered (refer to EPC-CP-QP-2105),
 - Record estimated total volume (L or ml) retrieved as "0" in ITEM 8,

- Return all water to the ground at the sampling location,
- Skip to Step 11.

CAUTION

ISCO Avalanche samplers are programmed to cool samples to 4°C. If water is collected and the refrigerator temperature reads higher than 6°C, **do not** retrieve samples that require ICE preservation. Samples do not meet preservation requirements.

- [4] Remove filled and partially filled bottles from the carousel one at a time.
- [5] For samples to be retrieved,
 - [a] Immediately place lids onto the sample bottles.
 - [b] Securely seal the lids.
 - [c] Place a custody seal on each bottle.
- [6] Write the following on each retrieved sample bottle.
 - Date and time collected (e.g., recorded by the ISCO sampler)
 - Sampler Location number
- [7] Conduct a Visual Assessment on a non-filtered sample (refer to EPC-CP-QP-2105).
- [8] Record estimated total volume (L or ml) retrieved in ITEM 8.
- [9] Place retrieved sample bottles in a cooler with blue ice (or equivalent).
- [10] Return any excess stormwater collected that exceeded the amount required to the ground at the location collected.
- [11] Install new certified clean sample bottles in the carousel to replace retrieved bottles.
 - [a] The number and type of bottles may vary. Ensure bottles match the configuration specified in the MSGP SAP.
- [12] Replace the 0.45-micron filter as needed.

NOTE 2: Consult the most current revision of the MSGP SAP for specifics.

- [13] <u>IF</u> the sampler is turned OFF for the quarter but new certified clean sample bottles and/or the filter have not been replaced,
 THEN note this as follow-up maintenance required in ITEM 19.
- [14] Replace and secure the center section of the sampler.
- [15] If the location has more than one sampler, complete Section 4.1.7 thru Section 4.2 for each sampler.
- [16] Return to Section 4.1.2, Step 5.

4.3 Removing Stormwater Samples from the field

- [1] Transport retrieved samples and corresponding SCPL (see EPC-CP-QP-2106) to the EPC-CP Stormwater Program Laboratory at TA-59-1.
- [2] Sign and date/time the SCPL and place it with the samples in the refrigerator.
- [3] Ensure custody seal is intact on each sample bottle.
- [4] Refer to EPC-CP-QP-2106, *Processing MSGP Stormwater Samples* for processing and submitting samples for shipping to the SMO.
- [5] Ensure the EPC-CP Stormwater Program Laboratory door is locked upon exit.

4.4 Completing the Inspection Form

See Attachment 1 for completing the form in MC Express and Attachment 2 for a hard copy example.

- [1] After all task lines have been completed, make sure you have clicked the "Save" bar at the bottom of the page.
- [2] Click the "Back" arrow button in the upper left hand corner to exit the work order Tasks page and return to the Work Order Summary page.
- [3] Click the checkered flag in the upper right corner of the Work Order Summary page to open the Work Order Status Update page. MC Express auto-populates the date and time fields.

CAUTION

MC Express automatically changes the work order status to "Closed."

- [4] **ITEM 21:** Click on the expand arrow located on the right side of the "New Status" field and select "Completed" from the available dropdown menu.
 - [a] Ensure the date and time auto-populated are the date and time the **work was** completed and *not* the date/time the form was filled out.
 - [b] <u>IF</u> work is performed over multiple days, <u>THEN</u> note the date and time the work began in the Labor Report field.
 - [c] To update the date or time, click the "Date" field and make necessary adjustments using the available timestamp application. Click "Set" to apply changes.
 - [d] <u>IF</u> using a hard copy form, <u>THEN</u> write the date and time the work was completed.
- [5] **ITEM 22:** The field personnel must type or write his/her name in the "Labor Report Update" field.

- [6] Additional notes, observations, or site conditions not documented in a task line "Reading" or "Comments" field can be documented in the "Labor Report Update" field.
- [7] Scroll down the page to the "Signature" bar and click the expand arrow on the left side of the bar to open the "Signature" field.
 - [a] **ITEM 23**: Capture an electronic signature by drawing with a finger on the tablet screen.

NOTE: The mouse must be used to sign electronically when using MC Express on a desktop screen (not a tablet).

- [b] If using a hard copy form, the field personnel will sign his/her name and date when the form is signed.
- [c] The field personnel is certifying that the information submitted is "true, accurate, and complete" by electronically signing work order.
- [8] Click on the "Save" bar at the bottom of the page to close the "Signature" field.
- [9] <u>IF</u> completing a hard copy, <u>THEN</u> return the form to the MSGP Program Lead.

5.0 TRAINING

Personnel performing steps in this procedure that involve electrical equipment **MUST** be trained to LANL electrical safety standards as prescribed in the IWD before performing those steps.

All EPC-CP personnel that execute the activities specified in this procedure must meet the minimum qualification and training requirements for their position as identified EPC-CP-PIP-2101, NPDES Multi-Sector General Permit Program. This will include "self-study" (required reading) for this procedure as assigned and documented in accordance with ADESH-TPP-301, *ADESH Training Program Plan*. Other participating LANL groups may require training documentation pursuant to local procedures.

Contract personnel that execute the activities specified in this procedure will be qualified and trained as required by the Exhibit D and Exhibit F. In addition, contract personnel will be required to complete "self-study" (required reading) of this procedure.

6.0 RECORDS

EPC-CP is the Office of Record for this document and must be maintained in accordance with PD1020, Document Control and Records Management and ADESH-AP-006, Records Management Plan. Records generated by this document will be submitted to the Records Management designated point of contact or document manager for document management.

Below are records generated as a result of implementing this procedure. Records generated are identified by title and type.

Record Title	QA Record	Non-QA Record
EPC-CP-TP-2103 R0 Form 1, ISCO Sampler Inspection and Sample Retrieval	\boxtimes	

7.0 DEFINITIONS AND ACRONYMS

7.1 Definitions

See LANL *Definition of Terms*.

7.2 Acronyms

See LANL Acronym Master List.

°C	Degrees in Celsius
EPC-CP	Environmental Protection and Compliance-Compliance Programs
FOD	Facility Operations Division
IWD	Integrated Work Document
L	Liter
LANL	Los Alamos National Laboratory
MC Express	Maintenance Connection MC Express web application
ml	Milliliter
MSGP	Multi-Sector General Permit
MST	Mountain Standard Time
NPDES	National Pollutant Discharge Elimination System
SAP	Sampling and Analysis Plan
SCPL	Sample Collection and Processing Log/Field Chain of Custody
V	Volts

8.0 **REFERENCES**

EPC-CP-QP-2105, MSGP Stormwater Visual Assessments

EPC-CP-QP-2106, Processing MSGP Stormwater Samples

EPC-CP-TP-2102, Installing, Setting Up, and Operating ISCO Samplers

EPC-CP-PIP-2101, NPDES Multi-Sector General Permit Program Implementation Plan

ADESH-TPP-301, ADESH Training Program Plan

ADESH-AP-006, Records Management Plan

PD1020, Document Control and Records Management

Inspecting ISCO Stormwater Runoff	No: EPC-CP-TP-2103	Page 18 of 27	
Samplers & Retrieving Samples	Revision: 0	Effective Date: 02/24/2020	

9.0 ATTACHMENTS


- Attachment 1: Screenshot Examples of EPC-CP-TP-2103 R0 Form 1, *ISCO Sampler Inspection and* Sample Retrieval in MC Express
- Attachment 2: EPC-CP-TP-2103 R0 Form 1, *ISCO Sampler Inspection and Sample Retrieval* Hard Copy Example
- Attachment 3: Sample Retrieval Flow Diagram

Inspecting ISCO Stormwater Runoff	No: EPC-CP-TP-2103	Page 19 of 27
Samplers & Retrieving Samples	Revision: 0	Effective Date: 02/24/2020

Attachment 1: Screenshot Examples of EPC-CP-TP-2103 R0 Form 1, ISCO Sampler Inspection and Sample Retrieval in MC Express

(Page 1 of 6)

Work Order Summary Page (Section 3.1, Steps 8 and 9)



Inspecting ISCO Stormwater Runoff	No: EPC-CP-TP-2103	Page 20 of 27
Samplers & Retrieving Samples	Revision: 0	Effective Date: 02/24/2020

Attachment 1: Screenshot Examples of EPC-CP-TP-2103 R0 Form 1, *ISCO Sampler Inspection and Sample Retrieval* in MC Express (cont.)

(Page 2 of 6)

Work Order Tasks page - On Arrival (Section 4.1.1, Steps 2-5)

	MC Express	
RDER: MS	GP-59941	Po @
RIVAL		
	r ON and functioning properly upon arrival? 10C01437] ISCO 3700 Sampler	0
	sampler display "Sampler Inhibited"? If No, record specific message(s). 10C01437] ISCO 3700 Sampler	0
	r time delta < 1 min (MST)? If No, record adjustment IOC01437] ISCO 3700 Sampler	0
	r ON and functioning properly upon arrival? 10J01522] ISCO Avalanche Sampler	0
	Avalanche display "Program Disabled"? If No, record specific message(s). 10J01522] ISCO Avalanche Sampler	0
	r time delta < 1 min (MST)? If No, record adjustment	0
Asset: [2'	10J01522] ISCO Avalanche Sampler Refresh III List	
Asset: [2	10J01522] ISCO Avalanche Sampler	
Asset: [2	Refresh III List	
Asset: [2	I0J01522] ISCO Avalanche Sampler Refresh MC Express WORK ORDER: MSGP-59941	
Asset: [2	MC Express WORK ORDER: MSGP-59941 Edit Task 20 Is sampler ON and functioning properly upon arrival? [210C01437] ISCO 3700 Sampler Reading Sampler knocked over by bear, power disconnected	
Asset: [2	MC Express WORK ORDER: MC Express WORK ORDER: MSGP-59941 Edit Task 20 Is sampler ON and functioning properly upon arrival? [210c01437] ISCO 3700 Sampler Reading	
Asset: [2	MC Express WORK ORDER: MSGP-59941 Edit Task 20 Is sampler ON and functioning properly upon arrival? [210C01437] ISCO 3700 Sampler Reading Sampler knocked over by bear, power disconnected	
Asset: [2	Refresh List MC Express Edit WORK ORDER: MSGP-59941 Edit Task 20 Is sampler ON and functioning properly upon arrival? [210c01437] ISCO 3700 Sampler Reading Sampler knocked over by bear, power disconnected Initials	
Asset: [2	Refresh List MC Express Edit WORK ORDER: MSGP-59941 Edit Z0 Is sampler ON and functioning properly upon arrival? Z10 Sampler ON and functioning properly upon arrival? Reading Sampler knocked over by bear, power disconnected Initials Edit	
Asset: [2	Refresh List Refresh MC Express WORK ORDER: MSGP-59941 Edit Task 20 Is sampler ON and functioning properly upon arrival? [210C01437] ISCO 3700 Sampler Reading Sampler knocked over by bear, power disconnected Initials Failed?	
Asset: [2	Refresh List MC Express WORK ORDER: MSGP-59941 Edit Task 20 Is sampler ON and functioning properly upon arrival? 210201437] ISCO 3700 Sampler Reading Sampler knocked over by bear, power disconnected Initials Failed? Yes No No	
Asset: [2	Refresh List MC Express WORK ORDER: MSGP-59941 Edit Task 20 Is sampler ON and functioning properly upon arrival? [210c01437] ISCO 3700 Sampler Reading Sampler knocked over by bear, power disconnected Initials Failed? Yes No Complete? No	
Asset: [2	Refresh List MC Express WORK ORDER: MSGP-59941 Edit Task 20 Is sampler ON and functioning properly upon arrival? 210201437] ISCO 3700 Sampler Reading Sampler knocked over by bear, power disconnected Initials Failed? Yes No No	

Inspecting ISCO Stormwater Runoff	No: EPC-CP-TP-2103	Page 21 of 27
Samplers & Retrieving Samples	Revision: 0	Effective Date: 02/24/2020


Attachment 1: Screenshot Examples of EPC-CP-TP-2103 R0 Form 1, *ISCO Sampler Inspection and Sample Retrieval* in MC Express (cont.)

(Page 3 of 6)

Work Order Task Page – Water Collection Information and Water Retrieval Information (Sections 4.1.2, Steps 3-6 and 4.1.3, Steps 1 and 2)



Work Order Task Page - On Departure (Sections 4.1.4, Steps 2 and 3)




Inspecting ISCO Stormwater Runoff	No: EPC-CP-TP-2103	Page 22 of 27
Samplers & Retrieving Samples	Revision: 0	Effective Date: 02/24/2020


Attachment 1: Screenshot Examples of EPC-CP-TP-2103 R0 Form 1, *ISCO Sampler Inspection and Sample Retrieval* in MC Express (cont.)

(Page 4 of 6)

Work Order Task Page – Equipment Specific Tasks (Sections 4.1.5, Steps 1-8)



Work Order Task Page – Maintenance Information (Sections 4.1.6, Steps 1-3)




Inspecting ISCO Stormwater Runoff	No: EPC-CP-TP-2103	Page 23 of 27
Samplers & Retrieving Samples	Revision: 0	Effective Date: 02/24/2020

Attachment 1: Screenshot Examples of EPC-CP-TP-2103 R0 Form 1, ISCO Sampler Inspection and Sample Retrieval in MC Express (cont.)

(Page 5 of 6)

Work Order Task Page – Bottle Information (Sections 4.1.7, Step 1)




Inspecting ISCO Stormwater Runoff	No: EPC-CP-TP-2103	Page 24 of 27
Samplers & Retrieving Samples	Revision: 0	Effective Date: 02/24/2020

Attachment 1: Screenshot Examples of EPC-CP-TP-2103 R0 Form 1, *ISCO Sampler Inspection and Sample Retrieval* in MC Express (cont.)

(Page 6 of 6)

Work Order Status Update Page (Section 4.4, Steps 4 and 5)



Work Order Status Update Page (Section 4.4, Step 7)

Æ		MC Express	
WORK OR Status Upda	DER: MSGP-5994		
	nature 23		
(Remov		1 .	
6	Ime A	Amin	
5	Cancel		Save

Inspecting ISCO Stormwater Runoff	No: EPC-CP-TP-2103	Page 25 of 27	
Samplers & Retrieving Samples	Revision: 0	Effective Date: 02/24/2020	

Attachment 2: EPC-CP-TP-2103 R0 Form 1, *ISCO Sampler Inspection and Sample Retrieval* Hard Copy Example

(Page 1 of 2)

os Alamos National Lab - ADESH		Work Order MSGP-59941 MSGP Monitoring Stations					
Mainton	nance Details		Printed	8/10/2017	- 11:25 /	AM (Dup	licate Co
Request Procedu	ted By: Admin, Jane on 8/10/2019 11:23:00 AM	Target:12/31/2019 Priority/Type: / Inspection Department: Utilities and Infrastructure	▲ RG12	38 Carpen ored Outfa	iter Sho		
Last PM Project				Admin, Ja 123-4567			
Reason	Example ISCO Sampler Inspec	tion and Sample Retrieval					
Tasks -							
#	Description			Meas	No	N/A	Yes
ON AR	ISCO 3700 Sampler [210C0143]	7] Is sampler ON and functioning properly upo					П
30	record specific message(s).	7] Does the sampler display "Sampler Inhibite		_		п	<u> </u>
40	adjustment	7] Is sampler time delta < 1 min (MST)? If No, 01522] Is sampler ON and functioning proper			п	п	п
50	arrival?	01522] Does the Avalanche display "Program	1.5		E	п.	п.
60	Disabled"? If No, record specific			-			<u> </u>
70 Water (record adjustment				F	F	_ <u> </u>
90		6 (but no water collected), describe and record	date/time		Ē.		
100	Is any water collected? If YES, c	omplete Bottle Information section.			—		П
110	ISCO Avalariche Sampler [210J0 refrigerator temperature (C)	01522] If water was collected, record current		_	E	Π	E
120		1C01137] If water was collected, record the p the sample date/time: AVERAGE_MINIMUM:	н				
1	Retrieval information					1	
140		D? If Yes, record total volume retrieved. rmed? If Yes, complete the MSGP Visual Asse	essment		-	-	-
	PARTURE			-			- 1.2
170	Are electrical connections securi			-		. []	
180		owering sampler, Voltage(s) >/=11,7V?	-	-	П		_
Equipm 200	nent specific tasks	7] Does the sampler pass the ISCO diagnosti	or tact?		-	÷.	
210		 Joes the sampler pass the ISCO diagnostic Is intake tubing free/clear of debris? 	ora reary	-	-	-	E
220		Is intake tubing free/clear of debris / Does sample tubing pass suction test?		-		-	-
220		 Joes sample tubing pass suction test? Is sampler on upon departure? 		-		1	-
720		 7] Is sampler on upon departure? 7] Has the actuator switch been reset to "Lato" 	610	-		1	-
230			41 7		L-1-	1.1	1.1.1
230 240 250		7] Does ISCO display "Sampler Inhibited" on			E		E

Inspecting ISCO Stormwater Runoff	No: EPC-CP-TP-2103	Page 26 of 27	
Samplers & Retrieving Samples	Revision: 0	Effective Date: 02/24/2020	

Attachment 2: EPC-CP-TP-2103 R0 Form 1, *ISCO Sampler Inspection and Sample Retrieval* Hard Copy Example (cont.)


(Page 2 of 2)

260	ISCO Avalanche Sampler [210J01522] Does the sampler pass the ISCO diagnostics test?	10	1.4	1
270	ISCO Avalanche Sampler [210J01522] Is intake tubing free/clear of debris?	E		E
280	ISCO Avalanche Sampler [210J01522] Does sample tubing pass suction test?		17	_
290	ISCO Avalanche Sampler [210J01522] Is sampler on upon departure?	- E		
300	ISCO Avalanche Sampler [210J01522] Has the actuator switch been reset to "Latch"?			
310	ISCO Avalanche Sampler [210J01522] Does Avalanche display "Program Disabled" on departure?		n.	
Mainte	nance information			
330	Is any maintenance not described above completed during inspection? If Yes, describe.		10	г
340	Is any follow-on maintenance not described above required? If Yes, describe.		E	Ē
Bottle messa 360	Information: IF bottle collected record bottle type (P or G), collection date & time, volume, a ges ISCO 3700 Sampler [210C01437] Bottle #1?	and/or any I	sco	
370	ISCO 3700 Sampler [210C01437] Bottle #2?	-	-	1
380	ISCO 3700 Sampler [210001437] Bottle #3?		E	
390	ISCO 3700 Sampler [210C01437] Bottle #4?		10	- F
400	ISCO 3700 Sampler [210C01437] Bottle #5?	- E	E	Ē
410	ISCO 3700 Sampler [210C01437] Bottle #6?		1	E
420	ISCO 3700 Sampler [210C01437] Bottle #7?		-	
430	ISCO 3700 Sampler [210C01437] Bottle #8?		T	Ē
440	ISCO 3700 Sampler [210C01437] Bottle #9?	5	0	Ē
450	ISCO 3700 Sampler [210C01437] Bottle #10?		E	- F
460	ISCO 3700 Sampler [210C01437] Bottle #11?			Ē
470	ISCO 3700 Sampler [210C01437] Bottle #12?	- E	1	Ē
480	ISCO Avalanche Sampler [210J01522] Bottle #1?			Ē
490	ISCO Avalanche Sampler [210J01522] Bottle #22	17		Г
500	ISCO Avalanche Sampler [210J01522] Bottle #31			Ē
510	ISCO Avalanche Sampler [210J01522] Bottle #4?			Г
Compl	Report leted: 5/30/2019 4:44:00 PM t: Jane Admin			
	June Adam, a 5/30/2019 Signature / Name Signature / Name Signature / Name		Date	-
contit	in the information as recorded is true, accurate and complete.			

Inspecting ISCO Stormwater Runoff	No: EPC-CP-TP-2103	Page 27 of 27
Samplers & Retrieving Samples	Revision: 0	Effective Date: 02/24/2020

Attachment 3: Sample Retrieval Flow Diagram

(Page 1 of 1)



ATTACHMENT 20: EPC-CP-QP-2106, PROCESSING MSGP STORMWATER SAMPLES

EPC-CP-QP-2106		Revision: 0	Revision: 0				
Effective Date: 10/18/2019		Next Review Dat	e: 10/18/2022	NATIONAL LABORATORY EST. 1943			
Environment, Safety, Health, Quality, Safeguards, and Security Directorate							
Environment	Environment Protection and Compliance – Compliance Programs Group						
Quality Proc	edure						
	Process	ing MSGP S	tormwater Sa	mples			
Hazard Grading:	🛛 Low [Moderate	High/Complex				
Usage Level:	Reference	UET					
Status:	 New	Major Revision	 Minor Revision				
				mat and numbering system			
Safety Basis:	⊠ N/A [
Survey Busisi			ubject Matter Expert:				
Name:		lization:	Signature:	Date:			
Holly L. Wheeler	EPC-0		Signature on File	10-17-19			
Name:		e Classifier: 🔀 Ur	classified or	Date:			
Steven E. Wolfel	EPC-0	CP	Signature on File	10-17-19			
		Approval	Signatures:				
EPC-CP Reviewer:	_	ization:	Signature:	Date:			
Terrill W. Lemke		CP Team Leader	Signature on File	10-17-19			
EPC-CP RLM:	_	ization:	Signature:	Date:			
Taunia Van Valkenburg EPC-CP Group Leader Signature on File 10-18-19 This copy is uncontrolled. Users are responsible for ensuring they work to the latest approved version. To document a required read, Login to UTrain, and go to the Advanced Search.							

Processing MSGP Stormwater	No: EPC-CP-QP-2106	Page 2 of 19
Samples	Revision: 0	Effective Date: 10/18/2019

REVISION HISTORY

Document Number and Revision [Include revision number, beginning with Revision 0]	Effective Date [Document Control Coordinator inserts effective date]	Description of Changes [List specific changes made since the previous revision]
ENV-RCRA-QP-048, Rev. 0	07/2011	New document
ENV-CP-QP-048, Rev. 1	09/2013	Annual Review and Revision, new format, process change, and new organization name.
EPC-CP-QP-048, Rev. 2	06/05/2017	Review and Revision, new format, and new organization name, clarified steps, updated attachments.
EPC-CP-QP-048 R3	10/05/2017	Updated Sample Collection Log instructions, added a step describing evidence of flow, and added section for addressing excess stormwater material.
EPC-CP-QP-048 R4	01/31/2019	Sample Collection Log form and associated text updated. Added text for collecting quality control samples.
EPC-CP-QP-2106 R0	10/18/2019	Supersedes EPC-CP-QP-048 R4. New EPC-CP procedure format and numbering system. Minor editorial updates.

Table of Contents

Revis	ion Hi	story	2
1.0	Intro	duction	4
	1.1	Purpose	4
	1.2	Scope	4
	1.3	Applicability	4
2.0	Preca	autions and Limitations	4
3.0	Prere	equisite Actions	
	3.1	Planning and Coordination	
	3.2	Performance Documents	-
	3.3	Special Tools, Equipment, Parts and Supplies	5
4.0	Proc	essing Samples	6
	4.1	Preparation for Processing Samples	6
	4.2	Filtering Samples	
	4.3	Preserving Unfiltered and Filtered Samples	
	4.4	Quality Control Samples	
		4.4.1 Field Blank Samples	
		4.4.2 Field Duplicate Samples	
	4.5	Handling Excess Stormwater	
	4.6	Submit Samples for Shipping to Offsite Analytical Laboratory	
5.0		ing	
6.0		rds	
7.0		nitions and Acronyms	
	7.1	Definitions	
	7.2	Acronyms	
8.0		rences	
9.0		chments	
		chment 1: Water Sample Collection and Processing Log/Field Chain of Custody Example	
		chment 2: Sample Container Labels Example	
	Atta	chment 3: Chain of Custody/Analysis Request Example	.19

Processing MSGP Stormwater	No: EPC-CP-QP-2106	Page 4 of 19
Samples	Revision: 0	Effective Date: 10/18/2019

1.0 INTRODUCTION

Triad LLC, the operator for Los Alamos National Laboratory (LANL or the Laboratory), conducts stormwater monitoring activities pursuant to the National Pollutant Discharge Elimination System (NPDES), Multi-Sector General Permit (MSGP). As part of this monitoring, Environmental Protection and Compliance, Compliance Programs (EPC-CP) personnel collect stormwater discharge samples from outfalls at industrial sites and prepare them for analysis.

1.1 Purpose

This procedure describes the process for filtering, preserving and preparing stormwater samples for shipment to an analytical laboratory from locations where EPC-CP conducts stormwater monitoring activities required pursuant to the NPDES MSGP. This procedure may also be used for other Associate Laboratory Directorate for Environment, Safety, Health, Quality, Safeguards, and Security (ALDESHQSS) stormwater monitoring activities as needed.

1.2 Scope

Stormwater samples are collected in the field with either a refrigerated Avalanche[®] or ISCO 3700 automated sampler, single stage sampler, or by hand. When in-line filtration is not possible, sample filtration, along with chemical preservation (as required) is conducted immediately following sample retrieval in the field or in the EPC-CP Stormwater Laboratory (TA-59-01).

Sample collection, submission, and analysis is conducted using Environmental Protection Agency (EPA) and New Mexico Water Quality Control Commission guidelines. MSGP monitoring samples are collected and analyzed according to test procedures approved under Title 40 of the Code of Federal Regulations Part 136 unless other test procedures have been specified in the MSGP. Quantitation limits associated with these test procedures are sufficiently sensitive to meet MSGP limits.

1.3 Applicability

This procedure applies to EPC-CP technical staff and subcontractor personnel (as applicable) who conduct processing and chemical preservation of stormwater samples either in the EPC-CP Stormwater Laboratory or in the field.

The MSGP Program Lead is the primary person responsible for this procedure. EPC-CP personnel are appointed responsibility for a subset of sampling stations. Other stormwater monitoring programs or projects utilizing this procedure will refer to program or project specific roles and responsibilities.

2.0 PRECAUTIONS AND LIMITATIONS

The hazard level for the activities in this procedure is <u>LOW</u>. An Integrated Work Document Part II (2101 Form) will address any site-specific requirements and training for Facility Operations Divisions (FOD) if required by the FOD.

Processing MSGP Stormwater	No: EPC-CP-QP-2106	Page 5 of 19
Samples	Revision: 0	Effective Date: 10/18/2019

Use only sample containers that are documented to meet or exceed "US EPA Specification and Guidance for Contaminant-Free Sample Container" (Publication 9240.05A, EPA/540/R-93/051, December 1992). Never clean or re-use sample containers. Keep containers in a clean, dry place until a sample is ready for processing and transfer to the appropriate container(s).

3.0 PREREQUISITE ACTIONS

3.1 Planning and Coordination

Refer to the most current revision of the MSGP or program/project specific Sampling and Analysis Plan (SAP) to determine the need for collecting quality control samples. Collect the types and quantities of quality control samples at the locations specified.

Schedule and complete stormwater processing to meet the analytical holding time requirements identified in the MSGP SAP or as requested by the MSGP Program Lead. Other stormwater monitoring programs or projects utilizing this procedure will refer to their program or project specific SAP.

The MSGP Data Manager will generate Water Sample Collection and Processing Log/Field Chain of Custody (SCPL) form(s) at the beginning of the MSGP monitoring season and/or the beginning of each MSGP monitoring quarter. The MSGP Data Manager will generate Chain of Custody/Analysis Request(s) from the Environmental Information Management (EIM) database as stormwater is collected. If the MSGP Data Manager is not available, forms will be obtained from the EPC-CP Sample Management Office (SMO).

3.2 Performance Documents

Personnel performing this procedure will be familiar with the most current versions of the following documents if the equipment or chemicals are utilized.

- Peristaltic Pump User Manual (e.g., GeoTech)
- Material Safety Data Sheet or Safety Data Sheet for preservation chemicals

3.3 Special Tools, Equipment, Parts and Supplies

Ensure the following equipment is available:

- Safety glasses with side shields
- Nitrile gloves
- Lab coat
- Eyewash in Stormwater Lab (or portable eyewash in the field)
- Water SCPL form
- Chain of Custody/Analysis Request
- EPC-CP MSGP SAP most recent revision for the current monitoring year OR project specific monitoring plan

- Sample containers (glass and poly bottles)
- Sample container lids
- Acid and base preservatives
- Clean silicon (e.g., Tygon) tubing
- Portable peristaltic pump (e.g., Geopump or equivalent)
- 0.45 micron (μm) and/or 0.10 μm cartridge filters (where applicable)
- Deionized water (where applicable)
- Paper towels
- Coolers with ice, Blue Ice®, or equivalent
- Ball point pen
- Permanent marker
- Chain-of-custody seals/tape
- Copy of this procedure
- Cell phone (only government cell phones are allowed in secure areas) (See https://int.lanl.gov/policy/documents/P217.pdf for requirements for using portable electronic devices on Laboratory property.

4.0 PROCESSING SAMPLES

In this procedure, sample collection bottles are the bottles in which the sample was collected in the field. Sample containers are containers into which the original sample is transferred (as necessary) during processing and shipped to the analytical laboratory.

NOTE: Prior to performing any of the steps in the following sub-sections, ensure that you are wearing the proper clothing. Don nitrile gloves, safety glasses with side shields, and a lab coat. Confirm that the eyewash station is operational prior to processing samples.

4.1 Preparation for Processing Samples

Sample Retriever

[1] Arrange sample collection bottles on the workbench in order by MSGP sampling location, ensuring to distinguish bottles collected via in-line filtration from non-filtered bottles, where applicable.

CAUTION

Process only one sample set (i.e., samples listed on one SCPL form or samples from one location) at a time to ensure stormwater from different locations is not co-mingled.

Processing MSGP Stormwater	No: EPC-CP-QP-2106	Page 7 of 19
Samples	Revision: 0	Effective Date: 10/18/2019

- [2] Cross-check the Location ID (e.g., MSGP00201) on the sample bottles with the LOCATION ID on the SCPL form (see example in Attachment 1).
- [3] Ensure the pre-populated information on the SCPL form is correct. Document any changes [e.g., change FIELD MATRIX code from rain (WT) to snowmelt (WM)].
- [4] Write the following information on the SCPL.
 - [a] Sampler Inspection and Sample Retrieval form (refer to EPC-CP-QP-2103) identification number (e.g., Work Order: MSGP-xxxx);
 - [b] Date/time the sample was collected in the field (e.g., date/time automated sampler filled sample bottles or a grab sample was taken);
 - [c] Date/time the sample was retrieved from the field;
 - [d] "Not Applicable" (N/A) in the LOCATION SYNONYM(S) field unless the information is required by the SAP;
 - [e] N/A in the PRIORITY box if box is not pre-populated;
 - [f] Any pertinent information regarding sample collection and/or retrieval in the SAMPLE COMMENTS field (e.g., grab sample collected by hand, recent erosion observed up-gradient of sampler) or N/A;
 - [g] N/A for FIELD PARAMETER Sample Time (this is documented at the top of the form as COLLECTION TIME);
 - [h] pH measurement taken at the time the sample was collected in the field (if applicable) or N/A;
 - [i] Indicate if a visual assessment was performed.
 - IF a visual assessment WAS NOT performed, THEN write N or No in the Visual Inspection space.
 - <u>IF</u> a visual assessment <u>WAS</u> performed, <u>THEN</u> write Y or Yes in the Visual Inspection space and the identification number from the MSGP Visual Assessment form (refer to EPC-CP-QP-2105) (e.g., MSGP-xxxx).
 - [j] The printed name and signature of the person who retrieved the sample in the COLLECTED BY box and date/time the sample was retrieved from field
- [5] <u>IF</u> the person who retrieved the sample is processing, <u>THEN</u> write N/A in the first RELINQUISHED BY and RECEIVED BY boxes.
- [6] <u>IF</u> the person who retrieved the sample is NOT processing, <u>THEN</u>
 - [a] He/she will print and sign his/her name and the date/time samples are relinquished to the processor in the RELINQUISHED BY box.

Processing MSGP Stormwater	No: EPC-CP-QP-2106	Page 8 of 19
Samples	Revision: 0	Effective Date: 10/18/2019

[b] The processor will print and sign his/her name and the date/time samples are received in the first RECEIVED BY box.

Sample Processor

- [7] Ensure the following information is correct for the analysis requested on the SCPL.
 - [a] Sample container volume and type [e.g., 500 milliliter (mL) POLY].
 - [b] Preservation type (e.g., ICE, HNO₃).
 - [c] Note any deviation from the planned sample container volume, type, or preservation on the SCPL.
- [8] Determine which samples require filtration and chemical preservation as requested on the SCPL.
 - [a] Mark each container lid with the 3-digit outfall ID, required analysis, filtration requirement, and preservative requirement.

NOTE 2: Requirements are also identified in the most current SAP revision.

- [9] For split samples, follow these steps:
 - [a] Turn the sample collection bottle upside down multiple times to ensure sediment is loose from the bottom of the bottle.
 - [b] Pour sample into sample containers ensuring the sample remains homogenized throughout the transfer.
- [10] Refer to Section 4.2 Filtering Samples, Section 4.3 Preserving Unfiltered and Filtered Samples, and Section 4.4 Quality Control Samples as needed.
- [11] Indicate if each sample on the SCL was collected by writing Y for Yes or N for No in the COLLECTED Y/N box.
- [12] <u>IF</u> the SPECIAL INSTRUCTIONS box is not pre-populated, <u>THEN</u> write N/A in the box.
- [13] Document any other deviations from the planned sample processing on the SCPL (e.g., turbid sample required extra filtration step, used standard deionized water in lieu of ultrapure water for field blank) under PROCESSING COMMENTS or SAMPLING COMMENTS,

OR write N/A.

- [14] <u>IF</u> no further processing is required (e.g., chemical preservation), <u>THEN</u> apply a chain-of-custody seal/tape around the bottle and lid and sign and date the seal/tape.
- [15] The person processing the sample will print and sign his/her name and indicate the date/time samples were processed in the PROCESSED BY box.
- [16] Proceed to Section 4.5.

Processing MSGP Stormwater	No: EPC-CP-QP-2106	Page 9 of 19
Samples	Revision: 0	Effective Date: 10/18/2019

4.2 Filtering Samples

Filter samples if specified on the SCPL or if an in-line filter was not used during sample collection.

- [1] Select the appropriate sized cartridge filter (e.g., 0.10µm or 0.45µm).
- [2] Set up the filter assembly.
 - [a] Attach an appropriate amount of silicone tubing to both ends of the cartridge filter.
 - [b] Place the filter upstream of the peristaltic pump to prevent overpressurization.
 - [c] <u>IF</u> the sample contains a significant amount of sediment, <u>THEN</u> a pre-filter of the same size or larger micron capacity may be used.
- [3] For split filtered samples, follow these steps:
 - [a] Move the intake tube up and down through the sample during filtration.

NOTE 1: A sample collected solely for filtration can be filtered without being homogenized by gently shaking.

- [4] Replace the filter if any of the following conditions occur:
 - flow diminishes,
 - the pump begins to make a grinding sound, or
 - the tubing is forced off the filter by backpressure.
- [5] Place the lid on the container.
 - [a] Ensure the lid is securely affixed to the container.
 - [b] Add a check mark next to the filtered requirement previously marked on the lid to indicate that filtration has been completed.
 - [c] Clean and dry the exterior of sample container.
 - [d] Check sample container for leakage and breakage.
- [6] Remove and dispose of filter and tubing when filtration of one sample set (location) has been completed.

NOTE 2: A new filter must be used with each new sample set.

[7] Return to Section 4.1, Step 11.

4.3 Preserving Unfiltered and Filtered Samples

Preservation entails the addition of acid or base to a sample. Acids currently used include hydrochloric acid (HCl), nitric acid (HNO₃), and sulfuric acid (H₂SO₄). Bases currently used in preservation include sodium hydroxide (NaOH). Review the appropriate Material Safety Data Sheet or Safety Data Sheet for specific guidelines prior to preserving samples. Specific acids/bases used

Processing MSGP Stormwater	No: EPC-CP-QP-2106	Page 10 of 19
Samples	Revision: 0	Effective Date: 10/18/2019

depend on the required monitored parameters and are subject to change (e.g., biennial Clean Water Act §303(d)/305(b) Integrated Report updates).

WARNING
Preservatives are strong acids and bases that can cause severe burns. Take extreme care when
using these acids and bases.

- [1] Review the analysis requested on the SCPL or SAP.
- [2] Select the pre-measured preservative type and size that matches the sample container size.
 - [a] <u>IF</u> you only have one size pre-measured preservative that does not match the sample container size, <u>THEN</u> you will use more than one. For example, if you have a 1-liter sample container and 500 mL pre-measured preservative vial, you will need to add two preservative vials to the sample container.
 - **NOTE:** Never "split" a larger volume pre-measured vial to preserve a smaller volume container (e.g., do not pipette from a 1-liter, pre-measured preservative vial to preserve a 500 mL sample). Error in measurement precision may lead to a risk of violating Department of Transportation shipping requirements.
- [3] Add the preservative (acid or base) to the sample.
 - [a] Securely affix the lid to the container.
 - [b] Agitate the preserved sample by turning the container upside down two to three times.
- [4] Add a check mark next to the preservation type previously marked on the lid to indicate that preservation has been completed.
 - [a] Clean and dry the exterior of sample container.
 - [b] Check sample container for leakage and breakage.
- [5] Return to Section 4.1, Step 11.

4.4 Quality Control Samples

Refer to the SCPL or the program specific SAP for the types and quantities of quality control samples and the locations where these samples will be collected.

4.4.1 Field Blank Samples

- [1] Review the analysis requested on the SCPL or SAP.
 - [a] Ensure the sample container volume, type, and preservation type is correct for the analysis requested (e.g., 500 mL POLY, HNO₃).

Processing MSGP Stormwater	No: EPC-CP-QP-2106	Page 11 of 19
Samples	Revision: 0	Effective Date: 10/18/2019

[b] Note any deviation from the planned sample container volume or type on the SCPL.

CAUTION

DO NOT use tap, distilled, or drinking water purchased from a local store. These sources may not meet the water quality standards specified in the New Mexico Administrative Code (Title 20, Chapter 6, Part 4).

- [2] Obtain analyte free water (e.g., High Performance Liquid Chromatography grade ultrapure in amber glass) in sealed bottle(s) in sufficient quantity to fulfill the analysis requested.
- [3] Select another empty sample container(s) of the same type and volume for the analysis requested.
- [4] Mark the bottle and container lids with the 3-digit outfall ID and "Field Blank".
- [5] Transport both the field blank bottle(s) and container(s) to the sampling location.
- [6] During retrieval of samples, open the field blank bottle(s) and pour the analyte free water into the field blank sample container(s).
- [7] Securely affix the lid(s) to the container(s).
- [8] Replace the lid on the analyte free water bottle.
 - [a] <u>IF</u> 500 mL or greater remain in the bottle, <u>THEN</u> replace lid and mark the bottle with the date it was opened and "For Decon Use Only".
 - [b] <u>IF</u> less than 500 mL remain in the bottle, <u>THEN</u> dispose of water in the EPC-CP Stormwater Laboratory sink and dispose of the bottle.
- [9] Return the field blank containers with retrieved samples to the EPC-CP Stormwater Laboratory (TA-59-01) for any further required processing.
- [10] Return to Section 4.1, Step 11 to complete sample processing.

4.4.2 Field Duplicate Samples

- [1] Review the analysis requested on the SCPL or SAP.
 - [a] Ensure the sample container volume, type, and preservation type is correct for the analysis requested (e.g., 500 mL POLY, HNO₃).
 - [b] Note any deviation from the planned sample container volume, type, or preservation on the SCPL.
- [2] Field duplicate samples must be samples collected from the same location, at the same time, and in the same manner:

Processing MSGP Stormwater	No: EPC-CP-QP-2106	Page 12 of 19	
Samples	Revision: 0	Effective Date: 10/18/2019	

• Select two sample collection bottles next to each other in the automated sampler carousel.

- Select one sample collection bottle to split into separate sample containers
- [3] For split samples, follow these steps:
 - [a] Turn the sample collection bottle upside down multiple times to ensure sediment is loose from the bottom of the bottle.
 - [b] Pour sample into sample containers ensuring the sample remains homogenized throughout the transfer.
- [4] Return to Section 4.1, Step 11 to complete sample processing.

4.5 Handling Excess Stormwater

Minimize the amount of stormwater sample brought into the EPC-CP Stormwater Laboratory. Field personnel will attempt to retrieve only the volumes needed to fulfill the requested analyses from the current MSGP SAP or program/project specific SAP.

[1] <u>IF</u> any excess stormwater sample exists after processing has been completed, <u>THEN</u> perform the following steps.

Sample Processor

- [a] Ensure the container is labeled with the site of origin, date and time sample was collected, and "Return to Site."
- [b] Place the container in the designated storage location in the EPC-CP Stormwater Laboratory.

EPC-CP technical staff

- [c] Return the sample to the site of origin as soon as possible.
- [d] Discharge at the sampler location.
- [2] <u>IF</u> the excess stormwater has been altered (e.g., tap water or preservative added), <u>THEN</u> contact the TA-59-0001 Waste Management Coordinator for further instruction.

4.6 Submit Samples for Shipping to Offsite Analytical Laboratory

Sample Processor

[1] Deliver completed SCPL(s) to the MSGP Data Manager.

MSGP Data Manager

[2] Process the sample information in the EIM system.

Processing MSGP Stormwater	No: EPC-CP-QP-2106	Page 13 of 19
Samples	Revision: 0	Effective Date: 10/18/2019

- [a] Capture any documented deviations from planned conditions (as noted on the SCPLs).
- [b] Generate Chain of Custody/Analysis Request (COC) form(s) and sample container labels to reflect the processed samples (see examples in Attachments 2 and 3).

Sample Processor

- [3] Ensure the sample containers are securely sealed and wiped dry.
- [4] Cross-check to ensure the Sample ID on the SCPL matches the Field Sample ID on the COC.
- [5] Compare the information from the SCPL and lid of each container and apply the correct labels to the sample containers.
- [6] <u>IF</u> the person who processed the sample is NOT submitting the samples to the SMO, <u>THEN</u>
 - [a] He/she will print and sign his/her name and the date/time samples are relinquished to the submitter in the second RELINQUISHED BY box.
 - [b] The submitter will print and sign his/her name and the date/time samples are received in the second RECEIVED BY box.

EPC-CP technical staff

- [7] Place the sample(s) in a cooler with sufficient Blue Ice[®] (or equivalent) to maintain the required preservation temperature ($\leq 4^{\circ}$ C).
 - **NOTE:** Cushioning material (e.g., bubble wrap) may be used to separate containers to avoid breakage during transport
- [8] Place the SCPL(s) and COC(s) in a zip lock type bag, seal, and place in the cooler with samples.
- [9] Transport samples to the SMO.
 - [a] Deliver samples during SMO business hours by 2pm for same day shipping.
 - [b] Coordinate with the SMO for delivery during other times or for delivery of samples that have limited holding times.
 - [c] If delivery of samples to the SMO will be delayed, place sample containers with SCPL(s) in the EPC-CP Stormwater Laboratory refrigerator and ensure the refrigerator is locked.
- [10] Complete the COC form as follows:
 - [a] On the Relinquished By line, the person submitting the sample(s) will sign and print his/her name and date/time samples are relinquished to the SMO.

- [b] The SMO personnel accepts the sample(s) by signing and printing his/her name and recording the date/time on the Received By line.
- [11] Complete the SCPL form as follows:
 - [a] Ensure all fields are filled out with sample information or N/A. Do not leave blank fields.
 - [b] In the RELINQUISHED BY box, the person submitting the sample(s) will sign and print his/her name. Sign and print your name on the SCPL in the "Relinquished By" box.
 - [c] Record the date/time that matches the data and time RELINQUISHED BY on the COC.
 - [d] Record the COC number (e.g., 2017-xxxx) in the RECEIVED BY box.
- [12] Ensure the following steps are taken:
 - [a] SMO makes a copy of the SCPL(s) to accompany the COC and samples.
 - [b] Keep the original SCPL(s) for the MSGP program.
 - [c] Make a copy of the signed Chain of Custody/Analysis Request.
- [13] Deliver the copy of the signed COC and original SCPL(s) to the MSGP Data Manager for record keeping.

5.0 TRAINING

All EPC-CP personnel that execute the activities specified in this procedure must meet the minimum qualification and training requirements for their position as identified EPC-CP-PIP-2101, NPDES Multi-Sector General Permit Program. This will include "self-study" (required reading) for this procedure as assigned and documented in accordance with ENV-DO-QP-115, *Personnel Training*. Other participating LANL groups may require training documentation pursuant to local procedures.

Contract personnel that execute the activities specified in this procedure will be qualified and trained as required by the Exhibit D and Exhibit F. In addition, contract personnel will be required to complete "self-study" (required reading) of this procedure.

Personnel performing this procedure will be familiar with the most current versions of the following procedures and operation manuals:

- EPC-CP MSGP SAP for the current monitoring year
- EPC-CP-QP-2103 Inspecting Stormwater Runoff Samplers and Retrieving Samples for the MSGP

6.0 RECORDS

EPC-CP is the Office of Record for this document and must be maintained in accordance with PD1020, Document Control and Records Management and ADESH-AP-006, Records Management

Processing MSGP Stormwater	No: EPC-CP-QP-2106	Page 15 of 19
Samples	Revision: 0	Effective Date: 10/18/2019

Plan. Records generated by this document will be submitted to the Records Management designated point of contact or document manager for document management.

Below are records generated as a result of implementing this procedure. Records generated are identified by title and type.

Record Title	QA Record	Non-QA Record
*Water Sample Collection and Processing Log/Field Chain of Custody	\boxtimes	
*Chain of Custody/Analysis Request	\boxtimes	
Copy of log book entry(s) (if a log book is used)	\square	
Other pertinent field or lab notes (if additional notes are required)	\square	

*The original document is part of the data package QA records for the SMO. MSGP retains a copy for tracking purposes only.

7.0 DEFINITIONS AND ACRONYMS

7.1 Definitions

See LANL *Definition of Terms*.

7.2 Acronyms

See LANL Acronym Master List.

СОС	Chain of Custody/Analysis Request
EIM	Environmental Information Management
EPA	Environmental Protection Agency
EPC-CP	Environmental Protection and Compliance – Compliance Programs
LANL	Los Alamos National Laboratory
μm	Micron
mL	Milliliter
MSGP	Multi-Sector General Permit
N/A	Not Applicable
NPDES	National Pollutant Discharge Elimination System
SAP	Sample Analysis Plan
SCPL	Water Sample Collection and Processing Log/Field Chain of Custody
SMO	Sample Management Office

8.0 **REFERENCES**

None.

Processing MSGP Stormwater	No: EPC-CP-QP-2106	Page 16 of 19
Samples	Revision: 0	Effective Date: 10/18/2019

9.0 ATTACHMENTS

Attachment 1:Water Sample Collection and Processing Log/Field Chain of Custody ExampleAttachment 2:Sample Container Labels ExampleAttachment 3:Chain of Custody/Analysis Request Example

Processing MSGP Stormwater	No: EPC-CP-QP-2106	Page 17 of 19
Samples	Revision: 0	Effective Date: 10/18/2019

Attachment 1: Water Sample Collection and Processing Log/Field Chain of Custody Example

(Page 1 of 1) Los Alamos National Laboratory WATER SAMPLE COLLECTION AND PROCESSING LOG/FIELD CHAIN OF CUSTODY EVENT ID: 11743 EVENT NAME: MSGP 2018 SAMPLE ID: MSGP-18-153015 WORK ORDER: MSGP- 12345 COLLECTION RETRIEVAL 09:25 07/01/18 16:03 07/03/18 DATE/TIME: DATE/TIME: LOCATION ID: MSGP04301 SAMPLER TYPE: APS-R LOCATION TYPE: WCS SAMPLE PREP: UF LOCATION SYNONYM(S): NA FIELD QC TYPE: REG FIELD MATRIX: WT SAMPLE USAGE: COMP COLLECTED SPECIAL PROCESSING PRIORITY ORDER CONTAINER PRESERVATIVE # Y/N INSTRUCTIONS COMMENTS 500 ML POLY MSGP-TSS 1 ICE NA NIA NIA γ allele o SAMPLE COMMENTS: NIA FIELD PARAMETERS: Sample Time NA HH:MM PH 6.2 SU Visual Inspection_ SU Visual Inspection WO# MSGP- 67890 COLLECTED BY Jane Doc Date/Time 07/03/18 (Printed Name) (Signature) 09:25 Date/Time Date/Time RELINQUISHED BY RECEIVED BY John Smith Jane Doe 07/03/18 (Printed Name) (Printed Name) 07/03/18 (Signature) (Signature) Smul 10:05 10:05 Date/Time PROCESSED BY John Smith (Printed Name) 07/03/18 (Signature) 13:00 RELINQUISHED BY Date/Time Date/Time RECEIVED BY John Smith See CoC# 07/04/18 (Printed Name) (Printed Name) Bin (Signature) 08:35 (Signature) 2017-1326 Date/Time Date/Time **RELINQUISHED BY** RECEIVED BY (Printed Name) A/V (Printed Name) Alu (Signature) (Signature) Report Date: 08/01/2018

Processing MSGP Stormwater	No: EPC-CP-QP-2106	Page 18 of 19
Samples	Revision: 0	Effective Date: 10/18/2019

Attachment 2: Sample Container Labels Example

(Page 1 of 1)

Sample ID: MSGP-17-13	1786		
Container: 500 ML POL	Y		1 of 1
Preservative: HNO3 ICE	6		
Analysis: NPDES-Al-Tota	al Recoverable		
Data/ 04/01/201	17 Time:	16:03	-

Los Alamos Natio	onal Labora	tory
Sample ID: MSGP-17-131787		
Container: 500 ML POLY		1 0/ 1
Preservative: HNO3 ICE		
Analysis: NPDES-Al-Total Recoverable	,	
Date/ 04/01/2017	Time: 16:03	6

Processing MSGP Stormwater	No: EPC-CP-QP-2106	Page 19 of 19
Samples	Revision: 0	Effective Date: 10/18/2019

Attachment 3: Chain of Custody/Analysis Request Example

(Page 1 of 1)

LANL SMO		9	Chair	10	fC	Cus	sto	dy	/Aı	na	lys	sis	Re	equ	es	t				2	OC/Lab Re 2017-1326 Page 1 of 1	quest	#:
Client Contact:	Lab Agreem	ent#:		Site	Nam	ne:	Lo	os Ala	amos	Nati	onal	Labo	rator	y	10						_		
	Project Num Analysis Turn 24 Hour-	ber:											T							Ra	ad Screenin	ng Info):
F	14 Days - 21 Days -			nZ.o								1	1								b Reportin Method De	-	10.55
Field Sample ID	Sample Date	Sample Time	Sample Matrix	MSGP-Zn									X	1									
MSGP-17-131904	Apr 1 2017	16:03	W	1						-	1		1										
MSGP-17-132187	Apr 1 2017	16:03	W	1					1				1								-		_
	1.1				1.1					Ì											_		_
	1.000	2.6.24						1												-		_	_
	1	10.0	1. 21						13	6												_	_
Sector sector in	1					2	1		1								-			-			_
						2	-	1				-	-				-			-			_
				1		N	1	1				-				-	+			-		_	_
	1					1	1	1	-			-	-			_	-	-		-			_
		-	1				-	-	-	-	-	-	-		_	-	+	-	\square	-		_	
		-	1		8.	-	-	-	-	_	-	-	-	-	_	-	+			+		_	_
			V	1	r.,	-	-	-	-		-	-	-			-	+			-			
					-	_	-	-	-		-	+	+			-	+	-	\vdash	-	_		_
		_	-			-	-	+	-		-	-	-	-		+	+	-	\square	+			
	-					-	-	+	-		-	-	-	-	-		+	-		+		-	
	-		-	-	_	-	-	-	-		-	-	-	-		-	-	-	\vdash	-		_	
			-					1			_					_		1				-	_
Special Instructions:																						4/1=	2/17
Relinquished by forme	Print	Name Jo	ine Doc		Date	n/Time	104/12	171	R	ecelv	ed by:	1	20	2	e	Print N	lame	BO	Fre.	on	Date/Tim	ie: 3	:10
Relinquished by:	Print	Name:				miT\e					ed by					Print Name:			Date/Tim	e:			
Relinquished by:	Print	Name:			Date	miT/e) ;		R	ecelv	ed by:	:				Print N	lame				Date/Tim	0:	

ATTACHMENT 21: EPC-DO-QP-0903, ENVIRONMENTAL REPORTING REQUIREMENTS FOR RELEASES OR EVENTS

EPC-CP-QP-0903		Revision: 0				
Effective Date: 08/10/2021		Next Review Dat	e: 08/10/2024	NATIONAL	LABORATORY	
Environment, Safety, Health, Quality, Safeguards, and Security Directorate						
Environmental Protection and Compliance – Compliance Programs Group						
Quality Procedure						
Environmental Reporting Requirements for Releases or Events						
Hazard Grading:	🖂 Low	Moderate	High/Complex			
Usage Level:	Reference			tions:		
_						
Status:	New	Major Revisi				
	Review w/No Cł					
Safety Basis:	🖂 N/A	USQ	USI Number:			
	D	ocument Autho	r/Subject Matter Exper	t:		
Name:		Organization:	Signature:		Date:	
Steve Pearson		EPC-CP	Signature on File		08-10-21	
[Derivative		Unclassified or 🗌		1	
Name:		Organization:	Signature:		Date:	
Steve Wolfel		EPC-CP	Signature on File		08-10-21	
Approval Signatures:						
EPC-WMP Reviewer:		Organization:	Signature:		Date:	
Patrick Padilla, Tear	n Leader	EPC-WMP	Signature on File		08-10-21	
EPC-CP RLM:		Organization:	Signature:		Date:	
Taunia Jean Sandqu	iist, Group Leader	EPC-CP	Signature on File		08-10-21	
	This copy is uncontrolled. Users are responsible for ensuring they work to the latest approved version. To document a required read, Login to UTrain, and go to the Advanced Search.					

Environmental Reporting	EPC-CP-QP-0903	Page 2 of 27
Requirements for Releases or Events	Revision: 0	Effective Date: 08/10/2021

REVISION HISTORY

Document Number and Revision [Include revision number, beginning with Revision 0]	Effective Date [Document Control Coordinator inserts effective date]	Description of Changes [List specific changes made since the previous revision]
0 02/09		New document
1	4/10	Revision and update
ENV-DO-QP-101 R2	6/12	Biennial Review/Revision, new template implemented.
EPC-DO-QP-101 R3	08/07/17	Revision and update. This document replaces ENV-DO- QP-101 R2. New document number reflects organizational name change.
EPC-CP-QP-0903 R0	08/10/2021	This document replaces EPC-DO-QP-101, R3. This update includes updating appropriate sections to reflect regulations and organizational changes. Implements new EPC-CP template and document number.

Environmental Reporting	EPC-CP-QP-0903	Page 3 of 27
Requirements for Releases or Events	Revision: 0	Effective Date: 08/10/2021

Table of Contents

Revis	ion Hi	istory		2
1.0	Intro	duction		4
	1.1	Purpos	e	4
	1.2	Scope.		4
	1.3	Applica	bility	4
2.0	Preca	autions a	and Limitations	4
3.0	Prere	equisite .	Actions	4
	3.1	Plannir	g and Coordination	4
	3.2	Collabo	ration with other Subject Matter Experts (SMEs)	5
4.0	Proce	ess Desc	ription	5
	4.1	•	ng Releases to Pueblo Environment Departments	
	4.2	Respon	sibility of On-Call Representatives	6
	4.3	Follow-	up Reporting	6
	4.4		ry of Policy Reporting	
	4.5	Using t	his procedure	
		4.5.1	Determining if a Release is Reportable under RCRA	8
		4.5.2	Determining if a Release is Reportable under TSCA	
		4.5.3	Determining if a Release is reportable under the CWA NMWQA, and NMWQCC	9
			4.5.3.1 Reporting Requirements for Petroleum Storage Tanks	
			4.5.3.2 Reporting Requirements under the NPDES Pesticide General Permit	11
		4.5.4	Determining if a Release is Reportable under CERCLA or EPCRA	
			4.5.4.1 Regulatory Classification of the Released Material	
		4.5.5	Determining Release Impacts to Biological or Cultural Resources	
		4.5.6	Reporting a Release or Event	16
		4.5.7	Steps to Notify LANL Management, the Laboratory Tribal Liaison, and Department	
			Energy Los Alamos Field Office (NA-LA)	
5.0	Train	ing		18
6.0	Reco	rds		18
7.0	Defir	nitions a	nd Acronyms	19
	7.1	Definiti	ons	19
	7.2	Acrony	ms	20
8.0	Refe	rences		22
9.0	Appe	endices .		23
10.0	Attac	chments		23
			L: Emergency Notification Requirements for RCRA	
	Attac	chment 2	2: Summary of Emergency Release or Event Reporting Requirements	25

Environmental Reporting	EPC-CP-QP-0903	Page 4 of 27
Requirements for Releases or Events	Revision: 0	Effective Date: 08/10/2021

1.0 INTRODUCTION

This Environmental Protection and Compliance – Compliance Programs (EPC-CP) procedure describes how to determine whether an unplanned release, spill, fire, or other event needs to be reported under environmental regulations and how to fulfill all immediate reporting requirements (within the first 24 hours). Emergency and abnormal event notification requirements for reporting to Laboratory and DOE management are specified in PD1200, *Emergency Management Program*, and P322-3, *Performance Improvement from Abnormal Events*. Environmental reporting requirements regarding releases or other events are included in this procedure.

1.1 Purpose

This procedure describes the actions that must be performed within the first 24-hours of the release. This procedure does **not** cover the response procedures for "continuous releases" under Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) and Emergency Planning and Community Right-to-Know Act (EPCRA) (see definitions) nor the follow-up notifications and reports.

1.2 Scope

This procedure describes the separate environmental pathway processes that determine if a release or event at Los Alamos National Laboratory (LANL or the Laboratory) is reportable.

1.3 Applicability

This procedure applies to EPC-DO on-call representatives and subject matter experts (SMEs) who must respond to any release, spill, or event at the Laboratory that may require immediate notification to local, state or federal regulatory agencies.

2.0 PRECAUTIONS AND LIMITATIONS

The work described in this procedure includes fieldwork that does not require an Integrated Work Document (IWD), has a **LOW hazard** rating and has been analyzed by an SME, the EPC-CP group leader and the responsible line manager (RLM), and is consistent with LANL P300, *Integrated Work Management* (IWM).

Actions specified within this procedure, unless preceded with "should" or "may," are to be considered mandatory (i.e., "shall", "will", "must").

3.0 PREREQUISITE ACTIONS

None.

3.1 Planning and Coordination

Events covered by this procedure include detonation or burns of unstable material, leaking or compromised gas cylinders, puncturing of bulging containers, fires, explosions, chemical or

radiological spills, wastewater spills, potable water discharges, and other unplanned releases at the Laboratory.

On a quarterly basis, EPC-CP will prepare a list of individuals designated as on-call representatives and will designate the week each will be on-call. This list will be distributed to on-call representatives and Laboratory managers including Deputy Directorate for Operations (DDOPS), Associate Directorate for Environment, Safety, and Health, Quality, Safeguards & Security (ESHQSS), Emergency Operations Center (EOC), Environmental Protection and Compliance Division – Compliance Programs Group (EPC-CP), and the Environmental Stewardship Group (EPC-ES).

Note: the on-call list should also be available on the LANL internal website. Environmental Home page, Environmental Contacts – On-Call Schedule. The on-call representative can be reached by pager at 505-664-7722.

3.2 Collaboration with other Subject Matter Experts (SMEs)

If needed, coordinating with other on-call SMEs and the EOC to ensure the required notifications for environmental reporting and abnormal events are being addressed for the Laboratory.

4.0 PROCESS DESCRIPTION

4.1 Reporting Releases to Pueblo Environment Departments

The Memorandum of Agreement between the U.S. Department of Energy through the Los Alamos Field Office of the National Nuclear Security Administration (NNSA), the Office of Environmental Management (EM), and the Pueblo de San Ildefonso strengthens the existing relationship between the parties as evidenced in the Restatement of 2005 Accord (MOA). It provides the foundation and framework for the parties to address and resolve specific issues of mutual concern. This MOA requires both DOE field offices (NNSA and EM) and its contractors to follow the protocols between the parties.

The Cooperative Agreements between the Pueblos of Cochiti, Jemez, and Santa Clara and the Los Alamos National Laboratory establish trust relationships with the Pueblos to resolve issues of mutual concern. To the extent funding is available and as otherwise agreed to in writing by Triad and the Pueblos, Triad will provide in-kind technical assistance to the Pueblos in areas of economic development, education, cultural resources, the environment, and emergency preparedness and response.

In the event of a release that impacts or may potentially impact Pueblo lands, notification to the impacted Pueblo Environment Department will be coordinated through the Laboratory's Tribal Liaison (505-629-2198) who will contact and notify the Department of Energy (DOE) Los Alamos Field Office (NA-LA) Intergovernmental Specialist to notify the Pueblos pursuant to protocols. If the release is identified to be an emergency where activation of the EOC is necessary, the LANL Emergency Response Organization will be responsible for contacting the affected Pueblos in accordance with PD1200, Emergency Management Program.

A list of Pueblo contacts is kept at the Laboratory's Tribal Liaison's office.

Environmental Reporting	EPC-CP-QP-0903	Page 6 of 27
Requirements for Releases or Events	Revision: 0	Effective Date: 08/10/2021

4.2 Responsibility of On-Call Representatives

The EPC on-call representative is the party primarily responsible for:

- 1) Responding to any notifications received on the Spills/Unplanned Release pager.
- 2) Determining if the incident will require immediate notification to external agencies in accordance with LANL, state, and federal regulatory reporting requirements.
- 3) Notifying EPC Division management of immediate reporting requirements.
- 4) In the event that the release is a non-emergency and Pueblo lands are impacted, notification to the impacted Pueblo Environment Department will be coordinated through the Laboratory's Tribal Liaison (505-629-2198) who will contact and notify the Department of Energy (DOE) Los Alamos Field Office (NA-LA) Intergovernmental Specialist to notify the Pueblos and the Office of Environmental Management if necessary.

The EPC on-call representative is not responsible for the following and EOC will make these determinations:

- 1) If the Resource Conservation Recovery Act (RCRA) Contingency Plan must be implemented.
- 2) If a shock-sensitive material, leaking, or compromised gas cylinder constitutes an emergency.
- 3) If the release is associated with an emergency where activation of the EOC is necessary, and if so, contacting the affected Pueblos in accordance with PD1200, *Emergency Management Program*.

However, in order to ensure that the appropriate expertise is available for the affected media, the EPC on-call representative may immediately confer with an SME of the EPC group that has programmatic responsibility. If an SME from the responsible group is able to respond to the event, the <u>remaining steps in this procedure may be passed to that person</u>. See the link for EPC Contacts: <u>Environmental Protection and Waste Management Contacts list</u>.

Note: The Pueblo Environmental Department(s) notification process will be implemented in parallel with regulatory- or permit-driven reporting. In the event of a conflict between the two reporting needs, this process is second priority.

4.3 Follow-up Reporting

This procedure describes the initial external notifications (within the first 24 hours) to regulatory agencies. After completion of the steps in this procedure, the EPC group or team specifically responsible for compliance with the relevant regulations will complete the required notifications and reports, as applicable under the appropriate regulations, according to established procedures.

Environmental Reporting	EPC-CP-QP-0903	Page 7 of 27
Requirements for Releases or Events	Revision: 0	Effective Date: 08/10/2021

4.4 Summary of Policy Reporting

The EPC on-call representative and spill response SMEs have the authority and responsibility for deciding when to report an event and for making notifications to regulatory agencies within the applicable regulatory deadlines.

LANL management and Department of Energy (DOE) Los Alamos Field Office (NA-LA) must be informed as soon as possible that a report was or will be made, but their approval is not required prior to the report being made to the regulatory agency. LANL Facility Operations Director (FOD) management, with input from EPC SMEs, will determine if an Occurrence Reporting Processing System (ORPS) report or other type of Lessons Learned will be necessary.

NOTE: EOC maintains a current list of on-call LANL managers.

4.5 Using this procedure

This procedure has seven separate paths (and corresponding sections) to follow for determining if a release or event is reportable. Follow each of these paths to determine if one or more are applicable:

- [1] Resource Conservation and Recovery Act (RCRA)
- [2] Toxic Substances Control Act (TSCA)
- [3] Clean Water Act (CWA), New Mexico Water Quality Act (NMWQA), and New Mexico Water Quality Control Commission (NMWQCC) Regulations
- [4] Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) and Emergency Planning and Community Right-to-Know Act (EPCRA)
- [5] Clean Air Act (CAA)
- [6] Biological
 - [a] Endangered Species Act
 - [b] Bald and Golden Eagle Protection Act
 - [c] Migratory Bird Treaty Act
 - [d] New Mexico Wildlife Conservation Act
- [7] Cultural
 - [a] National Environmental Policy Act (NEPA)
 - [b] National Historic Preservation Act
 - [c] Native American Graves Protection and Repatriation Act
 - [d] Archaeological Resources Protection Act

Environmental Reporting	EPC-CP-QP-0903	Page 8 of 27
Requirements for Releases or Events	Revision: 0	Effective Date: 08/10/2021

Each release needs to be evaluated for all potential reporting requirements. For example, a Reportable Quantity (RQ), defined under CERCLA or EPCRA may not be met, **but the release may be reportable** under RCRA, New Mexico Water Quality Control Commission (NMWQCC), and/or Clean Water Act (CWA) requirements.

NOTE: The 24-hour deadline (immediate in some cases) applies regardless of whether it occurs during business hours, after business hours or on non-business days.

4.5.1 Determining if a Release is Reportable under RCRA

Follow the flow chart in Attachment 1 to determine if an event is reportable under RCRA regulations.

Under the RCRA permit No. NM0890010515-1 requirements, the EOC manager determines if the "RCRA Contingency Plan" provisions should be implemented. The EPC on-call representative or an EPC Waste Management Programs (EPC-WMP) RCRA SME performs notifications that may be required.

The EOC Manager will normally attempt to contact an EPC-WMP SME for guidance in making this decision. If the EPC-WMP SME is successfully contacted, the remaining steps for determining if a release is reportable under RCRA may be passed on to this individual.

The EPC on-call representative makes the determination that one or more of these conditions occurred through consultation with EPC-WMP and appropriate SMEs. The 24-hour notification can be made by the EPC on-call representative or by an EPC SME.

The EOC manager makes the determination that unstable chemicals, leaking, or compromised gas cylinders represent an emergency situation. The EOC manager works with EPC-WMP to ensure that 24-hour notifications are made by the on-call representative or EPC-WMP SME.

If a release/event is reportable under RCRA rules, determine if the release/event is reportable under other rules and proceed to Section 4.4.5 Reporting a Release or Event.

4.5.2 Determining if a Release is Reportable under TSCA

In practice, only spills of Polychlorinated Biphenyls (PCBs) or PCB-suspect untested mineral oil to the environment (generally outdoors or with the potential to reach the outdoors) are reportable. Spills that are contained indoors are generally not reported.

A discharge of PCBs is reportable to the Environmental Protection Agency (EPA) under TSCA if 1 pound of PCBs by weight is released in accordance with 40 CFR 761.125(a)(1), *Requirements for PCB spill cleanup*. Notify the EPA regional office and proceed with the immediate clean-up requirements noted in 40 CFR 761.125(a)(1) in the shortest possible time after discovery, but in no case later than 24-hours after discovery. Additionally, reporting requirements are triggered if over 270 gallons of untested mineral oil suspected of containing PCBs has been spilled.

Follow the steps in Section 4.5.4, *Determining if a Release is Reportable under CERCLA, EPCRA, or Other Regulations* to determine if the RQ for PCBs has also been exceeded.

Environmental Reporting	EPC-CP-QP-0903	Page 9 of 27
Requirements for Releases or Events	Revision: 0	Effective Date: 08/10/2021

There are six items containing PCBs that are out of service at the Chemistry and Metallurgy Research (CMR) Building. They are scheduled for removal within the next year or so. All other known PCB equipment at the Laboratory have been taken out-of-service and disposed of in accordance with TSCA regulations.

If a release is reportable under TSCA, continue through the next sections to determine if the release/event is reportable under other rules and proceed to *Reporting a Release or Event* and determine if additional reporting is necessary.

If the spill is	Then
equal to or over 1 pound by weight of PCBs (TSCA) or greater than 270 gallons of untested mineral oil suspected of containing PCBs	Report to the National Response Center (1-800-242-8802) immediately (within 15 minutes of discovery). Additionally, contact EPA Region 6 (Office of Prevention, Pesticides and Toxic Substances Branch) through EPA's 24-hour spill response number 866-372-7745 as soon as possible after discovery, but no later than 24-hours after discovery.

4.5.3 Determining if a Release is reportable under the CWA NMWQA, and NMWQCC

20.6.2.1203 New Mexico Administrative Code (NMAC) Reporting

The NM Water Quality Act (NMWQA) does not use Reportable Quantities (as described in the next section). Instead, the NM Water Quality Control Commission (NMWQCC) regulations state, "With respect to any discharge from any facility of oil or other water contaminant, in such quantity as may with reasonable probability injure or be detrimental to human health, animal or plant life, or property, or unreasonably interfere with the public welfare or the use of property, notifications (to the New Mexico Environment Department (NMED)) and corrective actions are required."

The above rule requires the use of professional judgment to determine the magnitude and extent of the release and ultimately if external reporting is required. While no quantifiable metric is available to assist in making this determination, in general if any of the following three conditions are met external reporting will be completed:

- 1) more than 10-gallons of oil or other liquid is released,
- 2) if any volume of oil or other liquid reaches a watercourse, or
- 3) if it adversely impacts a Solid Waste Management Unit (SWMU) or Area of Concern (AOC), for example, requiring excavation or causing erosion.

The EPC on-call representative or SME has the authority and responsibility to make this determination.

Additionally, unplanned releases of potable water or steam condensate require reporting pursuant to 20.6.2.1203 if the release does not reach a watercourse, or if it adversely impacts a SWMU or AOC, as directed in the LANL Liquid Discharge Reporting Guidance (Decision Tree), dated March 10, 2009.

Environmental Reporting	EPC-CP-QP-0903	Page 10 of 27
Requirements for Releases or Events	Revision: 0	Effective Date: 08/10/2021

Consult with the Triad LLC, EPC-WMP Consent Order Site coordinator to confirm the location and to determine if there are potential impacts to SWMUs or AOCs from any releases that may occur.

Groundwater Discharge Permit Reporting

The Laboratory has three current or draft Groundwater Discharge Permits (DPs) that include notification and reporting requirements in the event of an unpermitted discharge. Spills of **any volume** associated with any of the Groundwater DPs require reporting to NMED pursuant to 20.6.2.1203 NMAC.

1) DP-857: Sanitary Waste Water System (SWWS) Plant, Sanitary Effluent Reclamation Facility (SERF), and Sigma Mesa Evaporation Basins. Permit Condition No. 44.

The unauthorized release of untreated and treated sanitary wastewater, reuse wastewater, blended wastewater, and reject wastewater would be subject to reporting under Condition No. 44.

2) DP-1589: Septic Tank/Disposal Systems. Permit Condition No. 23.

The unauthorized release of untreated wastewater, septage, treated wastewater surfacing from failing disposal systems (leach fields), and treated wastewater surfacing from overflowing septic tanks would be subject to reporting under Condition No. 23.

3) DP 1132: Radioactive Liquid Waste Treatment Facility (RLWTF). Permit Condition No. 38.

In the event of a release unauthorized in this Discharge Permit, the Permittees shall take measures to mitigate damage from the unauthorized discharge and initiate the notification and corrective actions required in 20.6.2.1203 NMAC under Condition No. 38.

Clean Water Act Reporting

Oil discharges (film/sheen/discoloration) to water in stream channels must also be reported to the National Response Center (NRC) immediately (within 15 minutes of discovery) pursuant to 40 CFR 110.6, Discharge of Oil.

National Pollutant Discharge Elimination System (NPDES) Outfall Reporting

The EPC-DO on-call SME must provide notification to the NPDES Outfall Permit Program Lead and/or the EPC-CP Water Quality Team Leader in the event of a leak, unplanned release, overflow, or bypass of treatment from an NPDES permitted outfall and/or the sources upon discovery in order to meet applicable reporting requirements (i.e., 24-hr and 5-day written). Outfall sources include, but are not limited to, the following:

- 1) Sanitary Waste Water System (SWWS) equipment, tanks, lift stations, septic tanks, and piping.
- 2) Sanitary Effluent Reclamation Facility (SERF) equipment, tanks, lift stations, and piping.
- 3) Radioactive Liquid Waste Treatment Facility (RLWTF) equipment, tanks, lift stations, and piping.

- 4) High Explosives Waste Treatment Facility (HEWTF) equipment, tanks, and piping.
- 5) Cooling towers.
- 6) Storage tanks (i.e., influent, effluent, reuse tank).
- 7) Other water treatment equipment and piping.

4.5.3.1 Reporting Requirements for Petroleum Storage Tanks

As defined in 20.5.118 NMAC, Environmental Protection, Petroleum Storage Tanks - Reporting Investigations of Suspected and Confirmed Releases, the NMED requires verbal reporting within 24hours of a petroleum product release from regulated tanks to the NMED Petroleum Storage Tank Bureau (PSTB) when there is:

- 1) any suspected or confirmed release of regulated substances
- 2) evidence of release of regulated substances
- 3) unusual operational conditions (that would cause concern about a release)
- 4) monitoring results that show loss from the system

Regulated tanks include those with a capacity between 1,320 gallons and 55,000 gallons. Regulated substances for Aboveground Storage Tanks (AST) includes, but is not limited to, petroleum and petroleum-based substances comprised of a complex blend of hydrocarbons derived from crude oil through processes of separation, conversion, upgrading and finishing, such as motor fuels (including ethanol-based motor fuels), jet fuels, distillate fuel oils, residual fuel oils, lubricants, petroleum solvents, and used oils.

Notice of any suspected or confirmed release from a storage tank system needs to be completed within 24 hours. Contact the EPC-CP AST Program Leader and/or the EPC-CP Water Quality Team Leader prior to completing any external notifications. The PSTB can be reached at 505-476-4397 (Santa Fe PSTB District 2) during business hours and 505-827-9329 (NMED Emergency Spill Hotline) during non-business hours. The NRC must be contacted at (800) 424-8802 immediately if oil or a sheen of oil from a spill or release hits a watercourse. A written report describing the spill, release or suspected release and any investigation or follow-up action needs to be submitted to the PSTB within 7 days of the incident.

If a facility discharges greater than 1,000 gallons of oil in a single discharge or discharges more than 42-gallons of oil in each of two discharges, as described in 40 CFR 112.1(b) and occurring within any twelve month period, the facility shall submit a report to the EPA Regional Administrator within 60 days of the discharge per 40 CFR 112.4.

4.5.3.2 Reporting Requirements under the NPDES Pesticide General Permit

Adverse incidents require reporting to the EPA under the NPDES Pesticide General Permit (PGP). An adverse incident is defined as an unusual or unexpected incident resulting from pesticide

applications that an operator has observed upon inspection or of which the operator otherwise becomes aware, in that:

- 1) There is evidence that a person or non-target organism has likely been exposed to a pesticide residue, and
- 2) The person or non-target organism suffered a toxic or adverse effect.

The phrase <u>toxic or adverse effect</u> includes effects that occur within Waters of the United States on non-target plants, fish, or wildlife that are unusual or unexpected (e.g., effects are to organisms not otherwise described on the pesticide product label or otherwise not expected to be present) as a result of exposure to a pesticide residue, and may include:

- [a] Distressed or dead juvenile and small fishes
- [b] Washed up or floating fish
- [c] Fish swimming abnormally or erratically
- [d] Fish lying lethargically at water surface or in shallow water
- [e] Fish that are listless or nonresponsive to disturbance
- [f] Stunting, wilting, or desiccation of non-target submerged or emergent aquatic plants
- [g] Other dead or visibly distressed non-target aquatic organisms (amphibians, turtles, invertebrates, etc.)

The phrase <u>toxic or adverse effects</u> also includes any adverse effects to humans (e.g., skin rashes) or domesticated animals that occur either from direct contact with or as a secondary effect from a discharge (e.g., sickness from consumption of plants or animals containing pesticides) to Waters of the United States that are temporally and spatially related to exposure to a pesticide residue (e.g., vomiting, lethargy).

If an operator observes or otherwise becomes aware of an adverse incident due to pesticide application, the operator must notify the EPA Incident Reporting contact within 24 hours of the operator becoming aware of the adverse incident. EPA Incident Reporting Contacts are listed at https://www.epa.gov/npdes/pesticide-permitting.

If an operator becomes aware of an adverse incident affecting a federally listed threatened or endangered species or its federally designated critical habitat, that may have resulted from a discharge from the operator's pesticide application, the operator must <u>immediately</u> (within 15 minutes of discovery) notify the U.S. Fish and Wildlife Service. This notification must be made by phone to the contact listed on the EPA's website (<u>https://www.epa.gov/npdes/pesticide-permitting</u>).

Environmental Reporting	EPC-CP-QP-0903	Page 13 of 27
Requirements for Releases or Events	Revision: 0	Effective Date: 08/10/2021

4.5.4 Determining if a Release is Reportable under CERCLA or EPCRA

Under CERCLA or EPCRA, the RQ is the threshold that requires immediate regulatory notification of a release. An RQ is based on the quantity of chemical released within any 24-hour period. Information on the RQ program as implemented by the DOE is on the web at:

https://www.energy.gov/ehss/services/environment/environmental-policy-andassistance/reportable-quantity-calculator

- 1) In the event of a release, determine the quantity released in pounds or kilograms for hazardous substances, or in curies for a release of radioactive material.
- 2) Compare the released value with the RQ threshold.
 - [a] CERCLA RQs of hazardous substances are listed in 40 CFR 302.4, Designation of Hazardous Substances. Hazardous substances and their RQs are listed in Table 302.4, and radionuclides are listed in 40 CFR 302.4, Appendix B. The DOE has also approved use of an on-line "Reportable Quantity Calculator" that can be used to assist in this determination. The RQ calculator is located at: https://rgcalculator.projectenhancement.com/
 - [b] If a hazardous material is not listed in the statute, the RQ has been set by Congress to be 100 pounds. For radionuclides, the RQ is 1 curie for radionuclides not otherwise listed.
 - [c] For mixtures of hazardous materials and/or radionuclides, or when the hazardous material table and radionuclide table are in conflict, the lowest RQ shall apply.
 - [d] If an RQ is met or exceeded, an immediate (within 15 minutes of discovery) notification must be made to the NRC (1-800-424-8802) pursuant to 40 CFR 302.6, *Notification of Requirements*.
 - [e] If a release of an airborne radionuclide exceeds an RQ listed in Appendix B to 40 CFR 302.4, verbally notify the EPA Region 6 Health Physicist after the NRC notifications have been completed. The EPA Region 6 Health Physicist can be reached at:

Office-(214) 665-8541; Mobile-(214) 755-1530; Home-(972) 937-1900.

The team leader for Radioactive Air Emissions Management (RAEM) in EPC-CP can provide assistance with determining RQs and releases for radioactive material releases and with notifying EPA Region 6.

- [f] If an RQ is not exceeded, notify the appropriate media SME so they can perform any required follow-up notification and documentation with the appropriate regulatory agency.
- 3) Additional notifications under EPCRA must be made if a release of a hazardous or extremely hazardous substance listed in 40 CFR 355 Appendices A and B occurs.

- [a] If an extremely hazardous substance is not listed in the statute, the RQ has been set by Congress to be 1 pound.
- [b] If the released quantity meets or exceeds the RQ established under EPCRA, in addition to notifying the NRC above, an immediate (within 15 minutes of discovery) notification must be made to the Local Emergency Planning Committee (LEPC) community emergency coordinator and to the State Emergency Response Commission (SERC) (see Attachment 2 for contact information).

The lists of CERCLA hazardous substances and EPCRA extremely hazardous substances are two separate lists that include a number of common substances. However, not all extremely hazardous substances are listed hazardous substances. In some instances, a release of an extremely hazardous substance may be reportable under EPCRA, but not reportable under CERCLA.

Releases that occur within a closed space with no emissions to the ambient environment are exempt from CERCLA and EPCRA reporting requirements.

NOTE: Response procedures for "Continuous Releases" are not covered in this procedure.

4.5.4.1 Regulatory Classification of the Released Material

The on-call EPC SME will determine the regulatory classification of the substance released with respect to the hazard classifications:

1) Extremely Hazardous Substance (EHS) and/or Hazardous Substance (HS)

Often during the course of an emergency, complete information will not be available regarding type and amount of material released. In this case, best professional judgment must be used to establish the level of confidence associated with the estimates. If the uncertainty is high enough that future estimates may require reporting, it is best to be conservative and report the release following the reporting requirements detailed in Section 4.5.6, *Reporting a Release or Event*.

After determining the RQ of a released material, the EPC on-call representative or SME will perform the following steps to determine if an RQ has been exceeded.

- 1) Obtain an estimate of the quantity and type of material released (e.g., 4 pounds of chlorine gas or 150 curies of tritium).
- 2) Compare this quantity against the RQs provided in 40 CFR Table 302.4 and 40 CFR 355, Appendices A and B.

If this is an airborne release of radioactive materials that meets or exceeds the RQ, immediate (within 15 minutes of discovery) reporting to the NRC and the EPA Region 6, Regional Health Physicist is required. Note that for radioactive materials, the RQ is provided in activity units (curies or becquerels). Also, note that some materials have an RQ value for both chemical exposure (Table 302.4) and for radiological exposure (Appendix B to 302.4). In these cases, the RQ applying to the smallest quantity of material will apply.

For all radioactive material releases, a radiological dose assessment must also be performed within 24-hours of the release. This dose assessment should be made by an environmental health physicist in EPC-CP or EPC-ES. The on-call individual should contact an EPC health physicist for this evaluation.

Immediate evaluation – RQ comparison (of a radioactive material release)

- [a] **If the release...**Is equal to or greater than the RQ then Proceed to Section 4.5.6 Reporting a Release or Event.
- [b] If the release...Is less than the RQ, then No immediate reporting is required. Contact an environmental health physicist in EPC-CP or EPC-ES to complete follow-up dose assessment.
- 4) If this is a release of non-rad material, it is reportable if the RQ is exceeded:
 - [a] **If** the **amount released is...**Equal to or greater than the RQ, then proceed to Section 4.5.6 Reporting a Release or Event.
- 5) Continue to re-evaluate the release as new data becomes available. Perform Steps 1 through 4 as necessary.

4.5.5 Determining Release Impacts to Biological or Cultural Resources

There are laws and regulations related to the protection of biological and cultural resources that are applicable to the Laboratory. These laws and regulations include:

- 1) National Environmental Policy Act (NEPA)
- 2) Endangered Species Act
- 3) Bald and Golden Eagle Protection Act
- 4) Migratory Bird Treaty Act
- 5) New Mexico Wildlife Conservation Act
- 6) National Historic Preservation Act
- 7) Native American Graves Protection and Repatriation Act
- 8) Archaeological Resources Protection Act

The EPC-CP SME is responsible for contacting a biological resources SME and a cultural resources SME within one business day from when a release/event occurs. This allows biological and cultural resources staff to report to their regulators within the required timeframe, identify if additional requirements are necessary for clean-up activities, and complete any other associated compliance regulations. The cultural resources SME will identify if there are impacts from the release/event to archaeological sites or historic buildings/structures.

Environmental Reporting	EPC-CP-QP-0903	Page 16 of 27
Requirements for Releases or Events	Revision: 0	Effective Date: 08/10/2021

Additionally, if there is a release of contaminants to a wetland, or impacts to the beneficial values of a wetland, the EPC on-call representative will coordinate with other EPC SMEs for applicable federal and state notifications and required actions as outlined in Section 4.5.3.

Contact a Biological Resources SME through the EPC-ES group office at 505-665-8855 and <u>epc_biologists@lanl.gov</u> as parallel contact information for Biological Resources.

Contact a Cultural Resources SME through the EPC-ES group office at 505-665-8855 or use cultural@lanl.gov.

4.5.6 Reporting a Release or Event

If a release or event is reportable (as determined by one or more of the previous sections), the Laboratory is required to meet certain reporting requirements. The emergency notification requirements must be followed upon determination that a release or event is reportable.

For informational purposes, a Summary of Emergency Release or Event Reporting Requirements is provided in Attachment 2. This document summarizes the primary statutes and the associated reporting requirements.

Maintain a notebook to record pertinent information about the release and to document the actions taken (see Section 6.0 *Records*).

Any release to the environment that has been determined to be reportable by the EPC on-call representative or SME shall be reported through the LANL management chain in accordance with PD1200, Emergency Management Program, and P322-4, Performance Improvement from Abnormal Events.

Triad management and DOE shall be notified if a release notification to state or federal regulatory agencies is required. Management approval is not required prior to completing environmental notifications to the regulatory agencies in order to assure that the deadline for reporting is not exceeded.

Perform the following steps immediately after establishing that reporting is required:

- 1) Compile release information including:
 - a) The source, cause, type and quantity of the release;
 - b) Time and duration of the release;
 - c) Extent of any protective and corrective actions taken;
 - d) Name, address, and telephone number of the person to contact for further information
 - e) Whether the substance is an HS or EHS
 - f) Associated health risks and medical attention necessary for exposed individuals;
 - g) If available, information concerning the release of any contaminants, hazardous and/or mixed waste that may endanger public or private drinking water supplies;

- h) Assessment health risks and medical attention necessary for exposed individuals;
- i) If available, estimated quantity and disposition of recovered material that resulted from the incident;
- j) Precautions to take due to the release/event, including, in the case of fire, those associated with special hazards due to the release of contaminants, hazardous and/or mixed waste;
- k) Any other information that may help emergency personnel responding to the incident; and
- I) Environmental media impacted from the release,
- 2) Notify LANL management, the Laboratory Tribal Liaison, and the respective FOD.

NOTE: Management approval is not required prior to completing environmental notifications to the regulatory agencies in order to assure that the deadline for reporting is not exceeded.

- Provide notification to the regulatory agency as required by the applicable regulation(s) detailed in Sections 4.5.1 – 4.5.4. Reference Attachment 2 for a summary of the applicable reporting requirements.
- 4) Notify programmatic SMEs that may be impacted or required to complete follow-up reporting.

4.5.7 Steps to Notify LANL Management, the Laboratory Tribal Liaison, and Department of Energy Los Alamos Field Office (NA-LA)

The EPC on-call representative will complete the following steps to provide notification to LANL Management and the Laboratory Tribal Liaison.

1) Determine that a release to the environment is reportable to state or federal entities as required under applicable regulations.

NOTE: Occurrence Reporting and Procession System (ORPS) reporting is a FOD and Responsible Associate Director (RAD) responsibility and commonly they will seek advisement from EPC SMEs.

- 2) Provide notification to the EPC-CP Water Quality Team Leader, the EPC-CP Group Leader, and the EPC-DO Division Leader of the release and the required external notifications.
- 3) Provide notification to the Laboratory Tribal Liaison (if release/event impacts or may potentially impact Pueblo lands) of the release and the required external notifications. Notification to the impacted Pueblo Environment Department will be coordinated through the Laboratory's Tribal Liaison (505-629-2198) who will contact and notify the Department of Energy (DOE) Los Alamos Field Office (NA-LA) Intergovernmental Specialist to notify the Pueblos pursuant to protocols.

- 4) Complete environmental reporting to state and federal agencies in accordance with all applicable regulations.
- 5) Notify the appropriate program SME that may be impacted or be required to complete follow-up release reporting.

After all the above notifications have been made, or when requested, the EPC on-call representative or SME will hand off responsibility for additional actions and follow-up to the affected environmental group. (The group that will be responsible will depend on the type and location of the release and the governing regulations or statutes.)

In order to communicate events at LANL that may impact the public and or the environment, EPC staff may provide a courtesy notification to NMED of events that may not require formal regulatory notification. Examples of such events in the past have been small wildland fires.

5.0 TRAINING

The training method for this procedure will be "self-study" (reading) and is documented in accordance with PD781, *Training Program Management*.

The following personnel require training before implementing this procedure:

• EPC managers, designated on-call representatives, and SMEs who may be asked to fulfill immediate reporting requirements during release-related exercises or during actual releases.

Annual retraining to this procedure is required.

6.0 RECORDS

EPC-CP is the Office of Record for this document and must be maintained in accordance with P1020-1, Laboratory Records Management. Records generated by this document will be submitted to the records management designated point-of-contact or document manager for document management.

- Field documentation of the release, include:
 - Time and date of the release
 - Time, date, and description of notifications
 - Location and source of the release
 - Type of material released
 - Quantity of material released
 - Impacted media
 - Time release was stopped
 - Any immediate mitigation actions taken to contain or control the release

- Documentation of any verbal notifications
- Samples taken
- Copies of any written notifications generated
- Documentation of any analytical results and quality assurance of results
- Contingency and/or emergency plan documentation
- Documentation of any RCRA permit non-compliance that threatens human health and environment
- Documentation of treatment of any RCRA unstable chemicals, leaking, or compromised gas cylinders

As a result of implementing this procedure, below are the records generated that are identified by title and type.

Record Title	QA Record	Non-QA Record
Copies of any written notifications generated	\boxtimes	
Documentation of any analytical results, and quality assurance of results	\square	
Contingency and / or emergency plan documentation	\square	
Documentation of any RCRA permit non-compliance that threatens human health and environment	\square	
Documentation of treatment of any RCRA unstable chemicals, leaking or compromised gas cylinders		

7.0 DEFINITIONS AND ACRONYMS

7.1 Definitions

Continuous Release – A release is continuous if it "occurs without interruption or abatement or if it is routine, anticipated, intermittent, and incidental to normal operations or treatment processes." The release must also be "stable in quantity and rate," which means that it must be predictable and regular in the amount and rate of emission. The response procedures for continuous releases are not covered by this document. See guidance in Reporting Continuous Releases of Hazardous and Extremely Hazardous Substances under CERCLA and EPCRA.

Environment – Includes "water, air, land, and the interrelationship that exists among and between water, air, land, and all living things." (40 CFR 355.20).

Extremely Hazardous Substance (EHS) – EPCRA establishes emergency reporting requirements for extremely hazardous substances in 40 CFR 355, Appendix A. All of these substances are also CWA and CERCLA "hazardous" substances.

Hazardous Substance (HS) – These substances are summarized in 40 CFR Part 302. As used in this context, this refers to:

- 1) any elements, compounds, mixtures, solutions, or substances specially designated by EPA under Section 311 of the Clean Water Act (CWA) (40 CFR 116.4);
- 2) any toxic pollutants listed under Section 307(a) of the CWA;
- 3) any hazardous substances regulated under Section 311 (b)(2)(A) of the CWA;
- 4) any listed or characteristic RCRA hazardous waste (40 CFR 261),
- 5) any hazardous air pollutants listed under Section 112 of the Clean Air Act (CAA); or
- 6) any imminently hazardous chemical substances or mixtures regulated under Section 7 of the Toxic Substances Control Act (TSCA).

Release – Any unpermitted spilling, leaking, pumping, pouring, emitting, emptying, discharging, injecting, escaping, leaching, dumping, or disposing of contaminants into the environment, excluding:

- 1) emissions from the engine exhaust of any vehicle,
- 2) certain releases of source, byproduct, or special nuclear material from a nuclear incident, or
- 3) normal application of fertilizer.

AOC	Area of Concern
AST	Aboveground Storage Tank
САА	Clean Air Act
CERCLA	Comprehensive Environmental Response, Compensation, and Liability Act
CMR	Chemistry and Metallurgy Research
CFR	Code of Federal Regulations
CWA	Clean Water Act
DDOPS	Deputy Directorate for Operations
DOE	Depart of Energy
DOE-LAFO	Department of Energy – Los Alamos Field Office
EHS	Extremely Hazardous Substance
EM	Office of Environmental Management
EOC	Emergency Operations Center
EPA	Environmental Protection Agency
EPC-CP	Environmental Protection and Compliance – Compliance Programs Group
EPC-DO	Environmental Protection and Compliance Division
EPC-ES	Environmental Protection and Compliance – Environmental Stewardship Group

7.2 Acronyms

Environmental Reporting	EPC-CP-QP-0903	Page 21 of 27
Requirements for Releases or Events	Revision: 0	Effective Date: 08/10/2021

EPCRA	Emergency Planning and Community Right-to-Know-Act
EPC-WMP	Environmental Protection and Compliance – Waste Management Programs Group
ESHQSS	Environment, Safety, Health, Quality, Safeguards and Security
FOD	Facility Operations Director
GWDP	Ground Water Discharge Permit
HEWTF	High Explosives Waste Treatment Facility
HS	Hazardous Substance
IWD	Integrated Work Document
IWD	Integrated Work Document
LANS	Los Alamos National Security
LANL or Laboratory	Los Alamos National Laboratory
LEPC	Local Emergency Planning Committee
MOA	Memorandum of Agreement
NA-LA	Los Alamos Field Office
NMAC	New Mexico Administrative Code
NMED	New Mexico Environment Department
NMWQA	New Mexico Water Quality Act
NMWQCC	New Mexico Water Quality Control Commission
NNSA	National Nuclear Security Administration
NPDES	National Pollutant Discharge Elimination System
NRC	National Response Center
ORPS	Occurrence Reporting and Processing System
OSC	On-Scene Commander
PADOPS	Principal Associate Directorate Operations
PCBs	Polychlorinated Biphenyls
PGP	Pesticide General Permit
PST	Petroleum Storage Tank
PSTB	Petroleum Storage Tank Bureau
QP	Quality Procedure
RAD	Responsible Associate Director
RAEM	Radioactive Air Emissions Management team within EPC-CP
RCRA	Resource Conservation and Recovery Act
RLM	Responsible Line Manager
RQ	Reportable Quantity
SARA	Superfund Amendments and Reauthorization Act
SDS	Safety Data Sheet
SERC	State Emergency Response Commission
SERF	Sanitary Effluent Reclamation Facility

Environmental Reporting	EPC-CP-QP-0903	Page 22 of 27
Requirements for Releases or Events	Revision: 0	Effective Date: 08/10/2021

SEO-DO	Security and Emergency Operations Division
SME	Subject Matter Expert
SWMU	Solid Waste Management Unit
SWWS	Sanitary Waste Water System
TSCA	Toxic Substances Control Act
UIC	Underground Injection Control

8.0 REFERENCES

40 CFR 261, Protection of Environmental, Identification and Listing of Hazardous Waste

40 CFR 302, Protection of Environment, EPA, Designation, Reportable Quantities, and Notification

40 CFR 302.4, Designation of Hazardous Substances

40.CFR.302.6, Notification of Requirements

40 CFR 355, Emergency Planning & Notification

40 CFR 761.125(a)(1), Requirements for PCB spill cleanup

40 CFR 110.6, Discharge of Oil

20.5.7 NMAC, Environmental Protection, Petroleum Storage Tanks - Reporting Investigations of Suspected and Confirmed Releases

DOE – Office of Environmental Guidance, CERCLA Information Brief, EH-231-001-0490 (April 1990)

Federal Register, Volume 67, No. 47, Notices FRL-7172-4, Guidance on the CERCLA Section 101(10)H, Federally Permitted Release Definition for Certain Air Emissions

PD1200, Emergency Management Program

P1020-1, Laboratory Records Management

P300, Integrated Work Management

PD781, Training Program Management

P322-3, Performance Improvement from Abnormal Events

LANL RCRA Permit No. NM0890010515-1

LANL NPDES Permit No. NM0028355

National Response Center (NRC) Web Site: http://www.nrc.uscg.mil/

NMWQCC Regulations, 20.6.2 NMAC, dated December 1, 2001

New Mexico Environment Department Groundwater Discharge Permit DP-857

New Mexico Environment Department Groundwater Discharge Permit DP-1132

Environmental Reporting	EPC-CP-QP-0903	Page 23 of 27
Requirements for Releases or Events	Revision: 0	Effective Date: 08/10/2021

New Mexico Environment Department Groundwater Discharge Permit DP-1589


New Mexico Administrative Code (NMAC) 20.5.7

9.0 APPENDICES

10.0 ATTACHMENTS

Attachment 1: *Emergency Notification Requirements for RCRA* **Attachment 2:** *Summary of Emergency Release or Event Reporting Requirements*

Environmental Reporting	EPC-CP-QP-0903	Page 24 of 27
Requirements for Releases or Events	Revision: 0	Effective Date: 08/10/2021



Attachment 1: Emergency Notification Requirements for RCRA

Environmental Reporting	EPC-CP-QP-0903	Page 25 of 27
Requirements for Releases or Events	Revision: 0	Effective Date: 08/10/2021

Attachment 2: Summary of Emergency Release or Event Reporting Requirements

NOTE: This is only a guide and does not cover all federal, state, or permit reporting requirements. Refer to the Code of Federal Regulations and the RCRA Permit for more details regarding these regulations.

STATUTE	REGULATIONS	INCIDENT	Immediate Reporting Requirements	Follow Up Reporting Requirements
Clean Water Act	40 CFR §110.6	Oil discharge (film/sheen/discoloration) to water surface or shoreline, or violation of water quality standards.	Immediately (within 15 minutes of discovery) notify the National Response Center.	Follow-up not required.
Clean Water Act	Part III of NPDES Permit No. NM0028355	Leak or unplanned release from an NPDES permitted outfall.	Notify the NPDES Outfall Permit Program Lead and EPC-CP Water Quality Team Leader upon discovery. The program lead or the EPC-CP Water Quality Team Leader will complete initial reporting requirements as required.	Required follow-up reporting will be completed by the NPDES Outfall Permit Program Lead and EPC-CP Water Quality Team Leader.
Clean Water Act (CWA)-NPDES Pesticide General Permit	40 CFR §122.28	Adverse incident that includes evidence that a person or non-target organism has been exposed to a pesticide residue or the person or non-target organism suffered a toxic or adverse effect.	Notify the EPA Region 6 Pesticide Permitting contact (214) 665-7500 within 24 hours.	Submit a 30 Day Adverse Incident Written Report to the EPA Regional Office.
New Mexico Water Quality Control Commission Regulations (NMWQCC Regulations)	20.6.2.1203 NMAC	Discharge from any facility of oil or other water contaminant, in such quantity as may with reasonable probability injure or be detrimental to human health, animal or plant life, or property, or unreasonably interfere with the public welfare or use of the property.	Notify the New Mexico Environment Department 505-827-9329 within 24 hours.	Submit 7 and 15 Day written follow up Corrective Action Reports (Copy EPA Region 6 on the 7 and 15 Day Reports).
New Mexico Water Quality Control Commission Regulations (NMWQCC Regulations)	20.6.2.3104 NMAC	Unplanned release of any volume from an activity or facility covered under an active Groundwater DP: DP-857: SWWS Plant, SERF, and Sigma Mesa Evaporation Basins DP-1589: Septic Tank/Disposal Systems DP-1132 Radioactive Liquid Waste Treatment Facility	Notify the New Mexico Environment Department 505-827-9329 within 24 hours.	Submit 7 and 15 Day written follow up Corrective Action Reports (Copy EPA Region 6 on the 7 and 15 Day Reports)

Environmental Reporting	EPC-CP-QP-0903	Page 26 of 27	
Requirements for Releases or Events	Revision: 0	Effective Date: 08/10/2021	

STATUTE	REGULATIONS	INCIDENT	Immediate Reporting Requirements	Follow Up Reporting Requirements
New Mexico Petroleum Storage Tank Bureau Regulations	20.5.118 NMAC	A release of a petroleum product from regulated aboveground storage tank that exceeds 25 gallons, that causes a sheen on nearby surface water, or that creates a vapor hazard pursuant to 20.5.119.1902 NMAC	Contact the EPC-CP AST Program Lead and/or the EPC-CP Water Quality Team Leader prior to completing any external notifications. If required, the Petroleum Storage Tank Bureau (476- 4397) or NMED Emergency Spill Hotline (505-827-9329) must be contacted within 24 hours.	A written report describing the spill, release or suspected release and any investigation or follow-up action needs to be submitted to the PSTB within 7 days of the incident.
Federal Spill Prevention, Control and Countermeasure Requirements	40 CFR 112.4	A discharge of more than 1000 gallons of oil or more than 42 gallons of oil in a 12-month period.	Contact the EPC-CP AST Program Lead and/or the EPC-CP Water Quality Team Leader prior to completing any external notifications.	A written report describing the cause of the release / discharge of oil, corrective actions, measure's to prevent recurrence shall be submitted to the EPA Regional Administrator within 60 days.
Comprehensive Environmental, Response, Compensation, and Liability Act (CERCLA)	40 CFR §302.6(a)	Hazardous substance (listed in 40 CFR Table 302.4) release (Equal to or greater than an RQ).	Immediately (within 15 minutes of discovery) notify the National Response Center 1-800-424-8802.	Follow-up not required.
Emergency Planning and Community Right- to-Know Act (EPCRA)	40 CFR§ 355.40	Release of an extremely hazardous substance (listed in 40 CFR Part 355 Appendices A and B) or CERCLA hazardous substance (listed in 40 CFR Table 302.4) equal to or greater than RQ.	Immediately (within 15 minutes of discovery) notify the LEPC (505-662-8283) the SERC (505-476-9635). Immediately notify the 911 operator for a release that occurs during transportation or from storage incident to transportation. Notifying the LEPC/SERC is only required for a release of an Extremely Hazardous Substance.	A written follow-up emergency notice must be submitted to the LEPC and SERC as soon as practicable after the release.

Environmental Reporting	EPC-CP-QP-0903	Page 27 of 27
Requirements for Releases or Events	Revision: 0	Effective Date: 08/10/2021

STATUTE	REGULATIONS	INCIDENT	Immediate Reporting Requirements	Follow Up Reporting Requirements
Resource Conservation and Recovery Act (RCRA)	40 CFR 262.34, 263.30, 264.51, 264.56 & .196, 265.51, .56 & .196, 270.14, & .30, 273.17, .37 & .54, 279.43 & .53, 280.50, .52, .53, .60, &.61	Release of hazardous or mixed waste from a permitted unit, interim status, less than 90 day area or a satellite accumulation area which the RCRA Permit Contingency Plan was triggered.	Notify NMED Hazardous Waste Bureau within 24 hours (24 hour emergency phone number: 827-9329; Non-emergency phone number: 476-6000) See Attachment 1 for additional details.	Submit written report to NMED HWB within 5 days.
Clean Air Act/ Radionuclide NESHAP	40 CFR 61, Subpart H	Airborne release of radioactive material in excess of an RQ.	Notify the EPA Region 6 Health Physicist (Office- (214) 665-8541; Mobile- (214) 755-1530; Home – (972) 937-1900) immediately after providing notification to the NRC.	Follow-up will be coordinated by the EPC-CP RAEM team.
New Mexico Air Quality Regulation	20 NMAC 2.7	Incidents in which excess emissions exceed an air quality regulatory limit or air permit emission limit.	File initial report to NMED AQB no later than the end of the next business day after the exceedance was discovered. (Submitted on- line via NMED AQB Secure Extranet Portal (SEP)).	Submit final written report to NMED AQB within 10 business days.
Toxic Substance Control Act (TSCA)	40 CFR 761.120, 761.125	Over 1 pound by weight of PCBs (TSCA) or greater than 270 gallons of untested mineral oil suspected of containing PCBs.	Contact the National Response Center (1-800- 242-8802) and the EPA Region 6 Office of Prevention, Pesticides, and Toxic Substances Branch (1- 866-372-7745) as soon as	Within 24 hours. Follow-up: as required by agency.

ATTACHMENT 22: EPC-CP-QP-1007, SPILL INVESTIGATIONS

EPC-CP-QP-1007		Revision: 0		
Effective Date: 06/03/2020 Next Review D		Date: 06/03/2023	est. 1943	
Environmen	Environment, Safety, Health, Quality, Safeguards, and Security Directorate			
Environmen	t Protection	and Complia	nce – Compliance Pr	ograms Group
Quality Proc	edure			
		Spill Inv	estigations	
Hazard Grading:	Low	Moderate	High/Complex	
Usage Level:	🔀 Reference	UET	Mixed: UET Sections:	
Status:	New	Major Revision	Minor Revision	
	Review w/N	o Changes	Other:	
Safety Basis:	⊠ N/A		USI Number:	
		Document Author	/Subject Matter Expert:	
Name:		Organization:	Signature:	Date:
Steve Pearson		EPC-CP	Signature on File	05-21-20
	Derivativ	e Classifier: 🔀 (Jnclassified or 🗌	
Name:		Organization:	Signature:	Date:
Steve Wolfel		EPC-CP	Signature on File	05-27-20
		Approv	al Signatures:	
EPC-CP Reviewer:		Organization:	Signature:	Date:
Michael Saladen		EPC-CP	Signature on File	05-27-20
EPC-CP RLM:		Organization:	Signature:	Date:
Taunia Van Valkenb	ourg	EPC-CP	Signature on File	06-03-20
This copy is uncontrolled. Users are responsible for ensuring they work to the latest approved version. To document a required read, Login to <u>UTrain</u> , and go to the Advanced Search.				

Spill Investigations	No: EPC-CP-QP-1007	Page 2 of 20
Spill Investigations	Revision: 0	Effective Date: 06/03/2020

REVISION HISTORY

Document Number and Revision [Include revision number, beginning with Revision 0]	Effective Date [Document Control Coordinator inserts effective date]	Description of Changes [List specific changes made since the previous revision]
0	12/98	New Document.
1	06/00	Annual review, added Cerro Grande fire hazards
2	07/01	Annual review.
3	06/03	Annual review.
4	04/04	Annual review, changes to HCPs.
5	02/07	Annual review, changes to reflect organizational restructure.
6	07/08	Annual review.
7	09/10	Biennial Review and revision.
8	04/11	Removed prerequisites, added note re: on-call spill reporting.
9	07/13	Biennial review and revision, implemented new procedure format.
10	09/30/15	Biennial review and revision, implemented new procedure format. Controlled the updated LANL ENV-CP Unplanned Release Report.
EPC-CP-QP-1007, Rev. 0	06/03/2020	Format document into new template and update content. This document was formerly ENV-CP-QP-007 R10.

Spill Investigations	No: EPC-CP-QP-1007	Page 3 of 20
Spin investigations	Revision: 0	Effective Date: 06/03/2020

Table of Contents

Revis	ion Hi	istory		2
1.0	Intro	duction		4
	1.1	Purpos	e	4
	1.2	Scope.		4
	1.3	Applica	ability	4
	1.4	Author	ity	4
2.0	Preca	autions	and Limitations	4
	2.1	Precau	tions	4
	2.2	Limitat	ions	5
3.0	Prere	equisite	Actions	5
	3.1	Plannir	ng and Coordination	5
	3.2	Perfor	mance Documents	6
	3.3	Special	Tools, Equipment, Parts, and Supplies	6
4.0	Perfo	orming S	pill Investigations	6
	4.1	Notific	ation of a Spill or Unplanned Release	6
	4.2	Emerge	ency Spill/Unplanned Release - Responding with EMD-EO	8
	4.2	Non-Er	nergency Spill or Unplanned Release	9
	4.3	Report	ing Spills and/or Unplanned Releases	.11
		4.3.1	Immediate Notification	.11
		4.3.2	Non-Reportable Spills/Unplanned Releases	.12
		4.3.3	Reportable Spills/Unplanned Releases	.12
5.0	Trair	ning		. 13
6.0	Reco	rds		. 13
7.0	Defir	nitions a	nd Acronyms	. 14
	7.1	Definit	ions	. 14
	7.2	Acrony	′ms	. 14
8.0	Refe	rences		. 15
9.0	Atta	chments		. 15
	Atta	chment	1: Release Notification Phone List	.16
	Atta	chment	2: Unplanned Release Report, EPC-CP-QP-1007-Form 1	.17
	Atta	chment	3: 7/15 Day Release Report, EPC-CP-QP-1007-Form 2	.18

Spill Investigations	No: EPC-CP-QP-1007	Page 4 of 20	
Spill Investigations	Revision: 0	Effective Date: 06/03/2020	

1.0 INTRODUCTION

All spills and unplanned releases that occur at Los Alamos National Laboratory (LANL) must be evaluated, remediated, and documented to ensure corrective actions are completed and reporting requirements are fulfilled. The investigation of spills and coordination of corrective actions are delegated to the Environmental Protection and Compliance Division's Compliance Programs Group (EPC-CP).

1.1 Purpose

This EPC-CP procedure describes the steps for performing spill investigations throughout LANL.

1.2 Scope

The scope of this procedure is limited to the performance of spill and unplanned release response by EPC-CP personnel and/or authorized subcontractors. Activities include frequent and unscheduled site visits to any area of the Laboratory upon discovery of a spill or unplanned release as support staff for the on-scene Incident Response Commander, deployed environmental staff, or Facility Operations Directorate (FOD) designated facility representative. Support activities include evaluation and documentation of the spill/unplanned release; guidance regarding remediation; and reporting to regulatory agencies.

1.3 Applicability

This procedure applies to all EPC-CP personnel and after hours on-call personnel responsible for conducting spill investigations.

1.4 Authority

The EPC-CP Group Leader is the issuing authority for this document.

2.0 PRECAUTIONS AND LIMITATIONS

A Hazard Analysis was performed for the tasks associated with this procedure. The hazard rating for the activities described in this procedure is **LOW** and does not require an Integrated Work Document.

2.1 Precautions

Precautions apply to abnormal conditions or hazards to personnel or equipment that can be encountered while performing this procedure. The following precautions shall be taken when performing work using this quality technical procedure:

• Personnel shall wear appropriate clothing (e.g., boots, long pants, gloves, etc.) to perform spill investigations in the field. This may also include safety glasses, a hardhat, a safety vest, and/or safety shoes/boots as required by the location of the tank, equipment, and area to be inspected.

Spill Investigations	No: EPC-CP-QP-1007	Page 5 of 20
Spin investigations	Revision: 0	Effective Date: 06/03/2020

• Work may be paused or discontinued due to conditions that make a location dangerous for worker safety or prevent personnel from safety accessing a site (i.e., flash floods, lightning, wildfires, hail, icy roads, deep snow, extreme temperatures, or hazardous LANL Operations such as firing shots, burns, or security).

2.2 Limitations

Limitations are defined boundaries (i.e., training, hold points) that are NOT to be exceeded while preforming the activities defined in this procedure. The following limitations are applicable to performing work using this technical procedure:

- Perform field activities in accordance with EPC-DO-QP-100, General Field Safety, and/or be escorted by Emergency Management Division – Emergency Operations Group (EMD-EO) or site personnel at all times.
- Spills or unplanned releases that occur on Department of Energy property due to activities performed by an organization not associated with Triad National Security, LLC (e.g., Los Alamos County, Newport News Nuclear BWXT Los Alamos (N3B), etc.,) are the responsibility of that organization. The respective organization is responsible for site remediation, completion of corrective actions, and fulfillment any external reporting requirements.
- Some spills or unplanned releases have 15-minute and 24-hour notification requirements. Personnel using this procedure must be familiar with the reporting requirements of <u>EPC-CP-QP-0903</u>, <u>Environmental Reporting Requirements for Releases</u>.

3.0 PREREQUISITE ACTIONS

3.1 Planning and Coordination

The response to spills and/or unplanned releases requires frequent and unscheduled site visits to any area of the Laboratory. Certain facilities and Laboratory locations require additional training and have specific access requirements that must be followed. Specific activities may include one or more of the following:

- Site-Specific Training (e.g., burn grounds).
- Coordination with Access Control and/or Security for escort, keys, safety (e.g., explosives areas, burn grounds, between security fences).
- Security Clearance (i.e., TA-3-66, TA-55, TA-16).

Site access for spill/unplanned release response will require that the Spill Investigator maintain multiple site-specific training requirements. It will also require that the Spill Investigator coordinate with the Emergency Operations Center (EOC), designated FOD representative, and/or Deployed Environmental Professional (DEP).

Spill Investigations	No: EPC-CP-QP-1007	Page 6 of 20	
Spin investigations	Revision: 0	Effective Date: 06/03/2020	

3.2 Performance Documents

The following documents are required to perform this procedure:

- EPC-CP-QP-1007 Form 1, Unplanned Release Report.
- EPC-CP-QP-1007 Form 2, 7/15 Day Release Report.
- EPC-CP-QP-0903, Environmental Reporting Requirements for Releases.

3.3 Special Tools, Equipment, Parts, and Supplies

Ensure the following are available for spill investigations and field visits:

- Personal protective equipment (PPE) as required by each specific site location (e.g., hardhat, safety vest, safety glasses, safety shoes, etc.)
- Cell phone (only government cell phones are allowed in secure areas.) See <u>https://int.lanl.gov/policy/documents/P217.pdf</u> for requirements for using portable electronic devices on Laboratory property.
- EPC-CP Spills Pager ***Note:** Spills Pager can be configured to forward notifications to a government cell phone and email address.
- External dosimeter (as required by site or facility).
- Field Logbook (maintained to record pertinent information about the spill, i.e., time and date of release, location and source of release, type of material released, quantity of material released, impacted media, time release was stopped, any immediate mitigation actions taken to contain or control the release, time, date and description of notifications, etc.).
- Physical or electronic maps (e.g., utility line locations, Solid Waste Management Unit (SWMU) / Area of Concern (AOC) boundaries, land ownership boundaries).

4.0 PERFORMING SPILL INVESTIGATIONS

4.1 Notification of a Spill or Unplanned Release

The EPC-CP personnel that conduct spill investigations ensure the immediate mitigation of spills and timely notification to appropriate regulatory organizations in the event of a spill or unplanned discharge that has or may adversely affect the environment. Spills/unplanned releases are typically reported by a designated FOD representative (i.e., operations, maintenance) or DEP. If the spill/unplanned release is an emergency (i.e., unknown chemical, toxic chemical, flammable chemical, large volume), it will be reported to the EOC at 667-2400 and the EOC will contact the spill investigator using the EPC Spill pager. If the spill/unplanned release is not an emergency, (potable water, small volume, non-toxic), it will be reported via the EPC Spill pager (664-7722) or by phone call from the DEP or other designated FOD representative (i.e., operations, maintenance, security, health and safety. The EPC-CP Spill Program maintains an on-call schedule for after-hours support

Spill Invostigations	No: EPC-CP-QP-1007	Page 7 of 20
Spill Investigations	Revision: 0	Effective Date: 06/03/2020

for incidents and unplanned releases. This listing is updated every three months with contact information for trained EPC-CP personnel (see Attachment 1). This schedule is submitted electronically to update the Primary On-Call List available through the Laboratory's EMD-EO Organizations.

Spill Investigator/On Call

- [1] Receive notification of a spill or unplanned release from one of the following:
 - Spill Pager (664-7722) or forwarded cell phone.
 - Emergency Operations Center (667-2400).
 - Phone call from the DEP or other designated FOD representative (i.e., operations, maintenance, security, health and safety).
- [2] Document the following information, at a minimum, in the Spill Logbook:
 - Time, Date, and Location of the spill/unplanned release
 - Owner of Spill and Site Contact
 - Material Spilled
 - Approximate Volume of the Spill/Unplanned Release
 - Source of the Spill
- [3] Request that the EOC identify a safe route to the site/location of the spill or unplanned release.

CAUTION

Spills or unplanned releases that occur on Department of Energy property from an organization not associated with Triad National Security, LLC (e.g., Los Alamos County, N3B etc.) are the responsibility of that organization. The respective organization is responsible for site remediation, corrective actions, and external reporting requirements.

- [4] If the owner of the spill is not associated with Triad National Security, LLC, refer the caller to one of the following, as appropriate:
 - Los Alamos County (LAC) Department of Public Utilities at 662-8333 for releases discovered during normal work hours from LAC owned equipment or infrastructure.
 - After Hours LAC Call Police Dispatch at 662-8222 for releases outside of normal work hours from LAC owned equipment or infrastructure.
 - N3B Operations Center at 551-2954 for releases from N3B owned equipment or infrastructure.
- [5] If the owner of the spill is associated with Triad National Security, LLC, prepare for a site visit as follows:

Spill Investigations	No: EPC-CP-QP-1007	Page 8 of 20
Spill Investigations	Revision: 0	Effective Date: 06/03/2020

- [a] Based upon location of the spill/unplanned release, determine what access requirements are applicable (i.e., Q/L Clearance, Site Specific Training) (see Section 3.1).
- [b] Based upon the location and material spilled, determine the appropriate PPE for the site visit (e.g., boots, safety glasses, long pants/shirt, hardhat, safety vest).
- [6] If the spill is de Minimis (low volume); of a known material (potable water, sanitary waste; and personnel have the appropriate knowledge/training, instruct the following:
 - [a] The delegated FOD representative, DEP and/or Waste Management Coordinator (WMC) may remediate the spill without the Spill Investigator being present.
 - [b] The designated FOD representative, DEP, and/or WMC must complete an Unplanned Release Report (Attachment 2) and submit a copy of the report to the Spill Investigator for recordkeeping.

4.2 Emergency Spill/Unplanned Release - Responding with EMD-EO

The Spill Investigator will respond to emergency spills/unplanned releases when notified. Emergency spills/unplanned releases typically include unknown materials leaking from bins, drums, and containers, hazardous materials (i.e., acid, caustic, fuel), or large volumes of petroleum products (i.e., leaking tanks, tanker truck accidents). Emergency spills/unplanned releases are managed by the EOC. The following provides the steps a Spill Investigator will follow when responding to support the EOC for an emergency spill/unplanned release.

Spill Investigator/On Call Spill Responder

- [1] Travel to the location of the spill or unplanned release.
- [2] Report to designated Incident Response Coordinator and receive site-specific safety and security briefing.
- [3] Assess and evaluate nature and extent of the release.
- [4] Provide support and guidance to EMD-DO, Hazmat, and Facility personnel on release mitigation measures and requirements. Examples of the types of support and guidance are:
 - [a] Provide the final inspection of the site to ensure that corrective actions were adequate and are complete.
 - [b] Recommend corrective actions.
 - [c] Inspect the site to ensure that the extent of the spill/unplanned release is adequately defined.

Spill Investigations	No: EPC-CP-QP-1007	Page 9 of 20
Spill Investigations	Revision: 0	Effective Date: 06/03/2020

- [d] Recommend how to stabilize the site for further remediation (i.e., secure the site from storm water).
- [e] Identify watercourse boundaries near the spill/unplanned release.
- [f] Determine if samples need to be collected.
- [g] Recommend sample types and analysis.
- [h] Recommend sample locations and the number of samples to determine extent of condition.
- [5] If sample collection is required, have the DEP/WMC contact the waste management organization and complete a Request for Analysis (RFA), <u>http://int.lanl.gov/environment/waste/sampling.shtml</u>, to schedule sampling. Specify the analytical suite and turn-around time needed for the sample in the RFA.
- [6] Document the following information regarding the spill or unplanned release in the Logbook:
 - Timeline of spill/unplanned release response as it occurs.
 - Nature and extent of the spill/unplanned release (i.e., inside a building, on asphalt, nearest watercourse/drainage area, proximity to SWMU/AOC and/or outfalls).
 - Steps taken to contain the spill.
 - Samples collected, if any. Include number, type, location, and analysis.
 - Spill and control equipment used to remediate the spill.
 - Corrective actions completed and the amount of waste material.

4.2 Non-Emergency Spill or Unplanned Release

The Spill Investigator will respond to non-emergency spills/unplanned releases when notified. Nonemergency spills/unplanned releases typically include potable water leaks; sanitary wastewater leaks, spills, overflows; and small volumes of known chemicals (e.g., hydraulic fluid leaks, vehicle oil leaks). Non-Emergency Spills/Unplanned Releases are typically handled by a designated FOD representative (i.e., operations, maintenance), DEP, or WMC assigned to the area. The following provides the steps a Spill Investigator will follow when responding a non-emergency spill/unplanned release.

Spill Investigator/On Call

- [1] Coordinate with the FOD designee and/or waste management coordinator to visit the location of the spill/unplanned release.
- [2] Travel to the location of the spill/unplanned release.

CAUTION

The Spill Investigator may respond to the spill or unplanned release and determine whether the containment and remediation is beyond the capability of the designated FOD representative, DEP, and/or WMC to respond. The EOC should be contacted if additional technical expertise or materials are needed to remediate the release.

- [3] Assess and evaluate the nature and extent of the release as follows:
 - [a] If the spill/release is a small volume or known material (e.g., sanitary waste, potable water, small hydraulic leak), proceed to step 4.
 - [b] If the spill/release is an unknown (e.g., leaking fluid from a metal recycling bin, drum, battery, or other container), stop work and notify the EOC at 667-2400.
 - [c] If the spill/release is a hazardous material or large volume of petroleum product (i.e., battery acid, chemical tank, fuel, hydraulic fluid, oil), stop work and notify the EOC at 667-2400.
 - [d] If the spill/release appears to be beyond the capability of the designated FOD representative, DEP, and/or WMC to contain and/or remediate, the Spill Investigator shall stop work and notify the EOC at 667-2400 to obtain the appropriate resources.
- [4] Provide guidance to the FOD designee and/or waste management coordinator regarding the containment and/or cleanup of the release. Examples of the types of guidance provided include the following:
 - [a] Provide the final inspection of the site to ensure that corrective actions were adequate and are complete.
 - [b] Recommend corrective actions.
 - [c] Inspect the site to ensure that the extent of the spill/unplanned release is adequately defined.
 - [d] Recommend how to stabilize the site for further remediation (i.e., secure the site from storm water).
 - [e] Identify watercourse boundaries near the spill/unplanned release.
 - [f] Determine if samples need to be collected.
 - [g] Recommend sample types and analysis.
 - [h] Recommend sample locations and the number of samples to determine extent of condition.
- [5] If sample collection is required, have the DEP/WMC contact WM-SVS and complete a RFA, <u>http://int.lanl.gov/environment/waste/sampling.shtml</u>, to schedule sampling. Specify the analytical suite and turn-around time needed for the sample in the RFA.

Spill Investigations	No: EPC-CP-QP-1007	Page 11 of 20
Spill Investigations	Revision: 0	Effective Date: 06/03/2020

- [6] Document the following information regarding the spill or unplanned release in the Logbook:
 - Timeline of spill/unplanned release response as it occurs.
 - Nature and extent of the spill/unplanned release (i.e., inside a building, on asphalt, nearest watercourse/drainage area, proximity to SWMU/AOC and/or outfalls).
 - Steps taken to contain the spill.
 - Samples collected, if any. Include number, type, location, and analysis.
 - Spill and control equipment used to remediate the spill.
 - Corrective actions completed and the amount of waste material.
- [7] Coordinate and document all required follow up corrective actions with the FOD designees, DEP, and/or WMC.
- [8] Determine the applicable internal and external reporting requirements as outlined in Section 4.3.

4.3 Reporting Spills and/or Unplanned Releases

This section describes how to determine whether an unplanned release, spill, or other event needs to be reported under environmental regulations and how to fulfill all immediate reporting requirements (within the first 24-hours).

4.3.1 Immediate Notification

Spill Investigator/On Call Spill Responder

- [1] Identify which of the following internal stakeholders that should receive a report of the spill/unplanned release:
 - EPC-CP Group and Division Management
 - Compliance Subject Matter Experts (SME). This includes Resource Conservation and Recovery Act, National Pollution Discharge Elimination System, Storm water, Groundwater, and/or Waste Management compliance personnel that potentially have permit specific reporting requirements.
 - FOD where the spill/unplanned release occurred.
 - Designated FOD Representative (i.e., DEP, Operations, and Maintenance).

CAUTION

Spills/unplanned releases may have EXTERNAL reporting requirements that must be completed within 15 minutes or 24-hours of discovery based upon EPC-CP-QP-0903, Environmental Reporting Requirements for Releases.

Spill Investigations	No: EPC-CP-QP-1007	Page 12 of 20
Spill Investigations	Revision: 0	Effective Date: 06/03/2020

[2] Identify the verbal and written EXTERNAL reporting requirements in accordance with EPC-CP-QP-0903, Environmental Reporting Requirements for Releases.

4.3.2 Non-Reportable Spills/Unplanned Releases

Spill Investigator/On Call Spill Responder

- [1] Notify the internal stakeholders (i.e., EPC-CP, SME, FOD, and designated FOD Representative) by phone and/or email (Attachment 1). Include the following pertinent facts as recorded in the logbook:
 - Date, Time, Location of the release.
 - Quantity and type of material.
 - Status of corrective actions.
- [2] Document the spill/unplanned release in the spills database.
- [3] Document spills/unplanned releases that are NOT reportable to an external regulatory agency on EPC-CP-QP-1007-Form 1, Unplanned Release Report (Attachment 2).
 - [a] If the Form 1 is completed by a DEP or other designated FOD representative, request a copy of the signed form.
 - [b] Attach completed EPC-CP-QP-1007-Form 1 to the spill database record.
- [4] Submit copies of the accumulated EPC-CP-QP-1007-Form 1's, (annually), to records in accordance with <u>ADESH-AP-006, Records Management</u>.

4.3.3 Reportable Spills/Unplanned Releases

Spill Investigator/On Call Spill Responder

- [1] Notify the internal stakeholders (i.e., EPC-CP, SME, FOD, and designated FOD Representative) by phone and/or email (Attachment 1). Include the following pertinent facts as recorded in the logbook:
 - [a] Date, Time, Location of the release.
 - [b] Quantity and type of material.
 - [c] Status of corrective actions.
- [2] Notify National Nuclear Safety Administration (NNSA)/Los Alamos Site Office (LASO).
- [3] Perform the required EXTERNAL verbal notifications to the appropriate regulatory agencies (i.e., New Mexico Environment Department [NMED], Environmental Protection Agency [EPA]) in accordance with <u>EPC-CP-QP-0903, Environmental Reporting Requirements for Releases</u>.

Spill Investigations	No: EPC-CP-QP-1007	Page 13 of 20
Spill Investigations	Revision: 0	Effective Date: 06/03/2020

- [4] Document spills/unplanned release on EPC-CP-QP-1007-Form 2, 7/15 Day Release Report (Attachment 3).
 - [a] Ensure that the EPC-CP-QP-1007-Form 2 is reviewed and assigned an LA-UR document release number.
 - [b] Attach the final EPC-CP-QP-1007-Form 2 to the spill database record.
 - [c] Submit the final EPC-CP-QP-1007-Form 2 as an e-mail attachment to the appropriate regulatory agency.
 - [d] Submit a copy of the EPC-CP-QP-1007-Form 2 to the internal stakeholders and NNSA/LASO.
- [5] Document the spill/unplanned release in the spills database.
- [6] Attach completed EPC-CP-QP-1007-Form 2 to the spill data base record.
- [7] Electronically file a copy of the EPC-CP-QP-1007-Form 2 in Spills folder located at ENV(\\dcstorage.lanl.gov):\CP\WQ\WQCC COMP PROG.
- [8] Submit copies of the accumulated EPC-CP-QP-1007-Form 2's, (annually), to records in accordance with <u>ADESH-AP-006, Records Management</u>.

5.0 TRAINING

All EPC-CP personnel that execute the activities specified in this procedure must meet the minimum qualification and training requirements for their position as identified in <u>EPC-CP-PIP-1001, New</u> <u>Mexico Water Quality Control Commission (WQCC) Program Implementation Plan (PIP)</u>. This will include "self-study" (required reading) for this procedure as assigned and documented in accordance with <u>ADESH-TPP-301</u>, <u>ADESH Training Program Plan (TPP)</u>.

6.0 RECORDS

EPC-CP is the Office of Record for this document and must be maintained in accordance with PD1020, Document Control and Records Management and ADESH-AP-006, Records Management Plan. Records generated by this document will be submitted to the Records Management designated point of contact or document manager for document management. The following records are generated by this procedure.

Record Title	QA Record	Non-QA Record
EPC-CP-QP-1007 Form 1, EPC-CP Unplanned Release Report	\boxtimes	
EPC-CP-QP-1007 Form 2, EPC-CP 7/15 Day Release Report	\square	
Correspondence (i.e., E-mail Notifications to LANL Management, DOE, and other EPC-CP permit subject matter experts)		

Spill Investigations	No: EPC-CP-QP-1007	Page 14 of 20	
Spill Investigations	Revision: 0	Effective Date: 06/03/2020	

Correspondence - E-mail Submittals of 7/15 Day Release Reports to NMED	\boxtimes	
Logbook		

7.0 DEFINITIONS AND ACRONYMS

7.1 Definitions

See LANL *Definition of Terms*.

Release – Any unpermitted spilling, leaking, pumping, pouring, emitting, emptying, discharging, injecting, escaping, leaching, dumping, or disposing of contaminants into the environment, excluding: (1) emissions from the engine exhaust of any vehicle, (2) certain releases of source, byproduct, or special nuclear material from a nuclear incident, or (3) normal application of fertilizer.

7.2 Acronyms

See LANL Acronym Master List.

AOC	Area of Concern
DEP	Deployed Environmental Professional
EMD-EO	Emergency Management Division -Emergency Operations Group
EOC	Emergency Operations Center
EPC-CP	Environmental Protection and Compliance Group
FOD	Facility Operations Directorate
LAC	Los Alamos County
LANL or the Laboratory	Los Alamos National Laboratory
LASO	Los Alamos Site Office (LASO).
N3B	Newport News Nuclear BWXT Los Alamos
NMED	New Mexico Environment Department
NNSA	National Nuclear Safety Administration
PIP	Program Implementation Plan
PPE	Personal Protective Equipment
SWMU	Solid Waste Management Unit
ТРР	Training Program Plan
WMC	Waste Management Coordinator
WQCC	Water Quality Control Commission
SME	Subject Matter Expert

Spill Investigations	No: EPC-CP-QP-1007	Page 15 of 20
Spill Investigations	Revision: 0	Effective Date: 06/03/2020

8.0 **REFERENCES**

ADESH-AP-006, Records Management Plan

ADESH-TPP-301, ADESH Training Program Plan (TPP)

EPC-CP-PIP-1001, New Mexico Water Quality Control Commission (WQCC) Program Implementation Plan

EPC-CP-QP-0903, Environmental Reporting Requirements for Releases

EPC-DO-QP-100, General Field Safety

P217, Controlled Portable Electronic Devices

9.0 ATTACHMENTS

Attachment 1: Release Notification Phone List

Attachment 2: EPC-CP-QP-1007-Form 1, Unplanned Release Report

Attachment 3: EPC-CP-QP-1007-Form 2, 7/15 Day Release Report

Spill Investigations	No: EPC-CP-QP-1007	Page 16 of 20
Spin investigations	Revision: 0	Effective Date: 06/03/2020

Attachment 1: Release Notification Phone List

Los Ala	nos National Laboratory			
(1)	Emergency Operations Support Center	(505) 667-2400		
(2)	EPC-ES Group Office	(505) 665-8855		
(3)	EPC-CP Group Office	(505) 667-0666		
(4)	EPC-DO	(505) 667-2211		
(5)	EPC-CP Spills Pager	(505) 664-7722		
<u>New M</u>	exico Environment Department			
(1)	NMED Emergency Hotline (24 hours a day)	(505) 827-9329		
(2)	NMED Non-Emergency Hotline (Voicemail; 24 hours a day)	1 (866) 428-6535		
(3)	NMED Surface Water Quality Bureau	(505) 827-0187		
	Jennifer Foote	(505) 827-0596		
(4)	NMED Ground Water Quality Bureau	(505) 827-2900		
	Gerald (Jake) Knutson	(505) 827-2996		
	Steve Pullen	(505) 827-2962		
(5)	NMED Hazardous Waste Bureau	(505) 476-6000		
	Stephen Connolly	(505) 476-6025		
<u>U.S Env</u>	ironmental Protection Agency			
(1)	US EPA Region 6 Spill Reporting (During business hours)	1 (800) 887-6063		
	Emergencies- Contact the NRC	1 (800) 424-8802		
(2)	Nancy Williams	1 (214) 665-7179		
Los Ala	mos Fire Department	(505) 662-8301		
<u>U.S. De</u>	partment of Energy			
(1)	Karen Armijo	(505) 665-7314		
Newpo	rt News Nuclear BWXT Los Alamos (N3B)			
(1)	N3B Operations Center	(505) 551-2954		
New M	exico State Police			
New	Mexico State Police	(505) 827-9604		
EPC-CP On-Call Environmental Representative for Release Assessment and Notifications to External Agencies				
(1) Terrill Lemke	(505) 665-2397 (Office) (505) 699-0725 (Cell)		
(2	Steve Pearson	(505) 667-3005 (Office) (505) 699-3684 (Cell)		
(3) Mike Saladen	(505) 665-6085 (Office) (505) 699-1284 (Cell)		

(505) 664-0105 (Office) (505) 699-7621 (Cell)

(4) Tim Zimmerly

Spill Investigations	No: EPC-CP-QP-1007	Page 17 of 20
spin investigations	Revision: 0	Effective Date: 06/03/2020

Attachment 2: Unplanned Release Report, EPC-CP-QP-1007-Form 1

		mental C	os National Laborat Compliance Program Ined Release Repor	n (EPC-	CP)		
Form Completed By:	Provide State		Telephone:		Group:	2	
Spill Owner Details (Specify):	TRIAD, LLC		iubcontractor:		D Othe	er:	
Date of Spill/Date Spill Discov	vered:	1.1					
Location:							
Material Spilled:							
Hydraulic Fluid			e/coolant		Refrigerant Oil		
Potable Water		Steam Con Lubricants			and the second second		
Diesel		1			Other;		
Volume Spilled:			lume Generated:				
Source of Spill:		A 10 10 10 10 10	ble Water Line				
Vehicle ID:			uppression System		Condensate Lin	e	
Equipment ID: Describe the spill response in cl		Fuel 1			Other:		
Did the spill enter or impact any	of the following?		personal data and the second		1		
	or the following.		Floor Drain, if so pl	ease indic	ate affected facility	/	
(Check as many as apply)	Disposal Facility		Floor Drain, if so pl Watercourse/drain	_		_	
(Check as many as apply) RCRA Treatment Storage I RCRA Satellite Accumulati	Disposal Facility on Area		Watercourse/drain	age area,	if so please indicat	ė	c Canada
(Check as many as apply)	Disposal Facility on Area		÷	age area,	if so please indicat	ė	se indicate
(Check as many as apply)	Disposal Facility on Area		Watercourse/drain	age area,	if so please indicat	ė	se indicate
(Check as many as apply) RCRA Treatment Storage I RCRA Satellite Accumulati RCRA <90 Day Storage Are NPDES MSGP Facility	Disposal Facility on Area ea	Inside	Watercourse/drain Solid Waste Manag None	age area,	if so please indicat	ė	se indicate
(Check as many as apply) RCRA Treatment Storage I RCRA Satellite Accumulati RCRA <90 Day Storage Are NPDES MSGP Facility Did the spill occur inside or o	Disposal Facility on Area ea	□ Inside	Watercourse/drain Solid Waste Manag None Outside	age area,	if so please indicat	ė	se indicate
(Check as many as apply) RCRA Treatment Storage I RCRA Satellite Accumulati RCRA <90 Day Storage Are NPDES MSGP Facility Did the spill occur inside or o Did the spill occur on:	Disposal Facility on Area ea utside a building?		Watercourse/drain Solid Waste Manag None Outside	age area, gement Ur Asphalt	if so please indicat	ė	se indicate
Check as many as apply)	Disposal Facility on Area ea utside a building?		Watercourse/drain Solid Waste Manag None Outside	age area, gement Ur Asphalt Graveler	if so please indicat hit/Area of Concerr	ė	se indicate
Check as many as apply)	Disposal Facility on Area ea utside a building? Concrete Carpeted F	loor	Watercourse/drain Solid Waste Manag None Outside	age area, gement Ur Asphalt Graveler	if so please indicat hit/Area of Concerr d/Rocky Area	ė	se indicate
(Check as many as apply) RCRA Treatment Storage I RCRA Satellite Accumulati RCRA <90 Day Storage Are NPDES MSGP Facility Did the spill occur inside or o Did the spill occur on: (Check as many as apply)	Disposal Facility on Area ea utside a building? Concrete Carpeted F J Tile	loor	Watercourse/drain Solid Waste Manag None Outside	Asphalt Gravelec Soil/Veg Other:	if so please indicat hit/Area of Concerr d/Rocky Area	e h, if so pleas	
(Check as many as apply) RCRA Treatment Storage I RCRA Satellite Accumulati RCRA <90 Day Storage Are NPDES MSGP Facility Did the spill occur inside or o Did the spill occur on: (Check as many as apply)	Disposal Facility on Area ea utside a building? Concrete Carpeted F Tile Tile Wooden Fl Soil Air	loor	Watercourse/drain Solid Waste Manag None Outside	Asphalt Gravelec Soil/Veg Other:	if so please indicat hit/Area of Concerr d/Rocky Area etated Area	e h, if so pleas	
Check as many as apply) RCRA Treatment Storage I RCRA Satellite Accumulati RCRA <90 Day Storage Are	Disposal Facility on Area ea utside a building? Concrete Carpeted F Tile Tile Wooden Fl Soil	loor	Watercourse/drain Solid Waste Manag None Outside	Asphalt Gravelec Soil/Veg Other:	if so please indicat hit/Area of Concerr d/Rocky Area etated Area	e h, if so pleas	
(Check as many as apply) RCRA Treatment Storage I RCRA Satellite Accumulati RCRA <90 Day Storage Are	Disposal Facility on Area ea utside a building? Concrete Carpeted F Tile Tile Wooden Fl Soil Air	loor	Watercourse/drain Solid Waste Manag None Outside	Asphalt Gravelec Soil/Veg Other:	if so please indicat hit/Area of Concerr d/Rocky Area etated Area	e h, if so pleas	
(Check as many as apply)	Disposal Facility on Area ea utside a building? Concrete Carpeted F Tile U Gooden Fi Soll Air Other:	iloor loor/Deck	Watercourse/drain Solid Waste Manag None Outside	Asphalt Gravelec Soil/Veg Other:	if so please indicat hit/Area of Concerr d/Rocky Area etated Area re collected, indicat	te h, if so pleas	l suite:
(Check as many as apply) RCRA Treatment Storage I RCRA Satellite Accumulati RCRA Satellite Accumulati RCRA <90 Day Storage Are	Disposal Facility on Area ea utside a building? Concrete Carpeted F Tile U Gooden Fi Soll Air Other:	iloor loor/Deck	Watercourse/drain Solid Waste Manag None Outside	Asphalt Gravelec Soil/Veg Other:	if so please indicat hit/Area of Concerr d/Rocky Area etated Area re collected, indicat	te h, if so pleas	I suite: te, and complete
(Check as many as apply) RCRA Treatment Storage I RCRA Satellite Accumulati RCRA <90 Day Storage Are NPDES MSGP Facility Did the spill occur inside or o Did the spill occur on: (Check as many as apply) Samples Collected: None Water Certification certify that I am knowledgeal: Name of Certifying Official: Certification:	Disposal Facility on Area ea Futside a building? Concrete Carpeted F Tile Tile Vooden Fl Soil Air Other: ple about the information	iloor loor/Deck	Watercourse/drain Solid Waste Manag None Outside I I I I I I I I I I I I I I I I I I I	Asphalt Gravelec Soil/Veg Other:	if so please indicat hit/Area of Concerr d/Rocky Area etated Area re collected, indicat	te analytica ue, accurat	I suite: te, and complete
(Check as many as apply) RCRA Treatment Storage I RCRA Satellite Accumulati RCRA Satellite Accumulati RCRA <90 Day Storage Are	Disposal Facility on Area ea Futside a building? Concrete Carpeted F Tile Tile Vooden Fl Soil Air Other: ple about the information	iloor loor/Deck	Watercourse/drain Solid Waste Manag None Outside I I I I I I I I I I I I I I I I I I I	Asphalt Gravelec Soil/Veg Other:	if so please indicat hit/Area of Concerr d/Rocky Area etated Area re collected, indicat	te analytica ue, accurat	I suite: te, and complete

Spill Investigations	No: EPC-CP-QP-1007	Page 18 of 20	
Spill Investigations	Revision: 0	Effective Date: 06/03/2020	

Attachment 3: 7/15 Day Release Report, EPC-CP-QP-1007-Form 2

	A DISCHAR	ATORY LA-UR-		Calendar Year
NPDES or Operational Spill/Rel ER Spill/Rel Other Spill/Rel	lease 🗌 🛛 –Indicate	e with "X" in appropria	te box.	Release ID Number:
Responsible Facility/User Group Contact Person Phone # Release/Discharge Location:	:	C4	Pager #:	
TA: Building: The release/discharge is associated Init (SWMU), indicate the site/unit nur NPDES Outfall: PRS: Indicate with "X" in appropriate box(e Relationship of the Discharge to a SW	mber and its relations SWMU: PRS/ es).			I Waste Management
Discharge Discharge Discharge Cleanup Cleanup Started:	Discharge Discovered:	Date & Time Cleanup Completed:	Discharge Stopped: Date & Time	Date & Time
laterial(s) Released / Discharged:	Date & Time		Date & fime	

Spill Investigations	No: EPC-CP-QP-1007	Page 11 of 20	
spin investigations	Revision: 0	Effective Date: 06/03/2020	

Release/Discharge Mit	igation Method:					
Weather Conditions:						
Duration of Relea Discharge, in HOU		Est. Volume relea	ased,in gallons:	Est. V	olume Recovered in gallon	
Corrective Actions Tak	en (ie, type of BMI	Ps, etc):				
learest Watercourse (the release/discharg		Course describe the	estimated sur	fare area affert	ted presence of	
elease/discharge now						
epth to Groundwater, istance to Nearest Dr	inking Water Well,			Well		
	24-HOUR F Contact Perso	RELEASE / DISC		OTIFICATIO Fax	NS Date & Time (or C	comment)
EPA:						,
NMED/SWQB:						
NMED/GWQB:					I	
NMED/HRMB:						
NMED/DOE-OB:						
EPC-CP:						
DOE:						
OTHER:						
OTHER:						
Comments:			L			
Form Completed By:	Г]				

Spill Investigations	No: EPC-CP-QP-1007	Page 12 of 20	
Spin investigations	Revision: 0	Effective Date: 06/03/2020	

7 DAY RELEASE / DISCHARGE ACTIONS				
7 Day Notice 7 Day Notice Date:	7 Day Notice By:			
Comments:				
15 DAY RELEASE / L	DISCHARGE ACTIONS			
15 day Follow-up Due:	15-day Follow-Up By:			
Comments:				
NMED 30 DAY APPRO	VAL / DISAPPROVAL			
NMED 30 Day Response Date:				
Comments:				
Peter Maggiore, Acting Assistant Manager National Security Missions	Jennifer Payne, EPC Division Director Triad National Security, LLC.			
Los Alamos Field Office	Los Alamos National Laboratory			
3747 West Jemez Road MS-A316	P.O. Box 1663, MS K404			
Los Alamos, New Mexico 87544 (505) 606-0397	Los Alamos, New Mexico 87544 (505) 667-2211			

EPC-CP-QP-1007 Form 2

ATTACHMENT 23: EPC-CP-QP-2110, MSGP STORMWATER POLLUTION PREVENTION PLAN PREPARATION AND MAINTENANCE

EPC-CP-QP-2110 Effective Date: 01/07/2020		Revision: 0				
		Next Review [Date: 01/07/2023	EST. 1943		
Environment, Safety, Health, Quality, Safeguards, and Security Directorate						
Environmen	t Protection a	nd Complia	nce – Compliance P	rograms Group		
Quality Proc	edure					
Quanty 1100	cuarc					
MSGP	MSGP Stormwater Pollution Prevention Plan Preparation and Maintenance					
Hazard Grading:	🛛 Low	Moderate	High/Complex			
Usage Level:	🛛 Reference] UET	Mixed: UET Sections:			
Status:	🛛 New] Major Revision	Minor Revision			
		 Other:				
-		-	_			
.	Do		/Subject Matter Expert:			
Name:		Organization:	Signature:	Date:		
Holly L. Wheeler		EPC-CP	Signature on File	1-6-2020		
	Derivative	Classifier: 🔀	Unclassified or 🗌			
Name:		Organization:	Signature:	Date:		
Steven E. Wolfel		EPC-CP	Signature on File	1-6-2020		
		Approv	al Signatures:			
EPC-CP Reviewer:		Organization:	Signature:	Date:		
Terrill W. Lemke, Te	eam Leader	EPC-CP	Signature on File	1-7-2020		
EPC-CP RLM:		Organization:	Signature:	Date:		
Taunia Van Valkent	ourg, Group Leader	EPC-CP	Signature on File	1-7-2020		
Taunia Van Valkenburg, Group LeaderEPC-CPSignature on File1-7-2020This copy is uncontrolled.Users are responsible for ensuring they work to the latest approved version.To document a required read, Login to UTrain, and go to the Advanced Search.						

MSGP Stormwater Pollution Prevention Plan Preparation and	No: EPC-CP-QP-2110	Page 2 of 72	
Maintenance	Revision: 0	Effective Date: 01/07/2020	

REVISION HISTORY

Document Number and Revision	Effective Date [Document Control	Description of Changes
[Include revision number, beginning with Revision 0]	Coordinator inserts effective date]	Description of Changes [List specific changes made since the previous revision]
EPC-CP-QP-2110, Rev. 0	01/07/2020	New document

Table of Contents

Revis	ion History		2
1.0	Introduction		4
	1.1 Purpos	5e	4
	1.2 Scope		4
	1.3 Applica	ability	4
2.0	Precautions	and Limitations	4
3.0	Preparing an	MSGP Stormwater Pollution Prevention Plan	4
	3.1 Gather	ring Information for the SWPPP	5
	3.2 Prepar	ing the SWPPP	5
4.0	Maintaining	the MSGP SWPPP	7
	4.1 Availat	pility of the MSGP SWPPP	7
	4.2 Additio	onal Documentation Requirements	7
5.0	Revising the	MSGP SWPPP	8
6.0	Training		9
7.0	Records		.10
8.0	Definitions a	nd Acronyms	.10
		ions	
	8.2 Acrony	/ms	.11
9.0	References		.11
10.0	Attachments	5	.11
	Attachment	1: EPC-CP-QP-2110 R0 Form 1, MSGP SWPPP Template Example	.12
	Attachment	2: MSGP SWPPP Review Guidance Checklist Example	.62

1.0 INTRODUCTION

The Environmental Protection Agency (EPA) National Pollutant Discharge Elimination System (NPDES) Multi-Sector General Permit (MSGP), also referred to as the Permit, contains specific requirements for industrial activities of Los Alamos National Laboratory (LANL) covered by the permit. One requirement is the preparation, maintenance, and routine revision of a Stormwater Pollution Prevention Plan (SWPPP).

1.1 Purpose

Active MSGP facilities must be included in a SWPPP. The SWPPP is intended to document the selection, design, and installation of control measures to meet permit effluent limits. Additional documentation required by the Permit is to be kept with the SWPPP (including inspection maintenance, monitoring, and corrective action) and is intended to document the implementation of permit requirements.

1.2 Scope

This procedure contains information and specific steps for preparing a SWPPP, and identifying and documenting conditions in order to meet Permit requirements. Part 5 of the Permit contains specific requirements for developing, maintaining, and revising a SWPPP for facilities with stormwater discharge associated with industrial activities permitted under an MSGP. Part 5.5 describes the additional documentation required to be kept with the SWPPP.

1.3 Applicability

This procedure applies to Environmental Protection and Compliance-Compliance Programs (EPC-CP) technical staff, Deployed Environmental Professionals (DEPs), and subcontractor personnel (as applicable) who develop and maintain SWPPPs at MSGP regulated LANL facilities operated by Triad, LLC.

2.0 PRECAUTIONS AND LIMITATIONS

The hazard rating for the activities described in this procedure is **LOW** and does not require an Integrated Work Document.

3.0 PREPARING AN MSGP STORMWATER POLLUTION PREVENTION PLAN

Part 5 of the Permit contains the specific requirements for developing, maintaining, and revising a SWPPP. At a minimum, the SWPPP must contain the following elements:

- Stormwater pollution prevention team (Stormwater PPT);
- Site description (including a site map);
- Summary of potential pollutant sources;
- Description of control measures;

- Schedules and procedures;
- Documentation to support eligibility considerations under other federal laws; and
- Signature requirements.

Where the SWPPP refers to procedures in other facility documents, such as a Spill Prevention, Control and Countermeasure Plan or an Environmental Management System, copies of the relevant portions of those documents must be kept with the SWPPP.

The template provided in Attachment 1, EPC-CP-QP-2110 R0 Form 1, *MSGP SWPPP Template Example* contains the elements required in a LANL MSGP SWPPP. Contact the MSGP Program Lead for questions regarding content.

3.1 Gathering Information for the SWPPP

SWPPP Preparer

- [1] Contact the MSGP Program Lead for a copy of the most current SWPPP template.
- [2] Obtain a copy of the previous year's SWPPP for reference (if one is available).
- [3] Review the SWPPP template.
 - [a] Identify information that will need to be included in the SWPPP (e.g., MSGP sector, operational areas, Pollution Prevention Team member names, etc.).
 - [b] Identify documents that will need to be attached to the SWPPP (e.g., certifications, memorandums, maps, data summaries, endangered species reports, etc.).
- [4] Identify documents and/or reports that are provided by EPC-CP.
 - [a] Contact the MSGP Program Lead with a request for needed information.
- [5] Obtain maps as specified in the SWPPP template.
 - [a] Request a new map or update to existing map from the MSGP Program Lead.
 - [b] Provide a draft or map markup with information as required in the Permit.

3.2 Preparing the SWPPP

SWPPP Preparer

- [1] Use a copy of the most current SWPPP template.
- [2] Add information to the relevant sections.
- [3] Text highlighted in yellow indicate areas to be replaced with facility specific information.

- [a] <u>IF</u> text is part of an instruction (e.g., <u>Insert site description text here.</u>)
 THEN delete the entire line and replace with the appropriate information.
- [b] <u>IF</u> text is embedded as part of the line, <u>THEN</u> replace just the yellow highlighted text with appropriate information (e.g., delete <u>Sector XX-(Insert Sector Title)</u> and replace with <u>Sector P – Land</u> <u>Transportation & Warehousing</u>).
- [4] Delete attachments that are not applicable to the active facility specific SWPPP.
- [5] Attach other documentation (e.g., Spill Prevention, Control and Countermeasure Plan, Environmental Management System, copies of relevant portions of documents) as necessary.
- [6] Send the draft SWPPP to the EPC-CP MSGP Program Lead and request a review.

NOTE 1: The EPC-CP MSGP Program Lead may delegate the review to personnel in the Storm Water Permitting/Compliance Team.

MSGP Program Lead or Designee

- [7] Review the SWPPP to ensure information required by the Permit is included.
 - [a] Encourage the use of the *MSGP SWPPP Review Guidance Checklist* as a best management practice to cross-check SWPPP content with the Permit. See checklist example in Attachment 2.
 - [b] Provide comments to the SWPPP Preparer.

SWPPP Preparer

- [8] The Preparer must resolve review comments with the MSGP Program Lead.
- [9] Obtain the signature of a duly authorized representative (refer to Appendix B, Subsection 11 of the Permit) on the certification statements associated with the SWPPP and attachments (refer to Attachment 9 of the *MSGP SWPPP Template* Example).
 - **NOTE 2:** The Review & Approval System for Scientific and Technical Information (RASSTI) system requires upload of only PDF documents. It is highly recommended that all final certifications obtained contain a written signature rather than electronic signature. The RASSTI system adds a cover page to the document containing the LA-UR number, which obviates all electronic signatures due to the document change.

4.0 MAINTAINING THE MSGP SWPPP

4.1 Availability of the MSGP SWPPP

A complete copy of the current SWPPP is required to be kept at the active facility in an accessible format. The SWPPP must be immediately available to facility employees, EPA, and other entities identified in the Permit. The SWPPP must also be made available to the public. LANL meets this requirement by posting SWPPPs to the Public Reading Room internet web page. Refer to Part 5.4 of the Permit for more information.

SWPPP Preparer

- [1] Submit the final certified SWPPP in PDF format to the RASSTI system at *rassti.lanl.gov*.
 - [a] The SWPPP must be identified as Los Alamos Unlimited Release, or LA-UR, to be posted to the Public Reading Room.
 - [b] Identify a derivative classifier to review the document.
 - [c] Identify the document for a **full classification review**. The Designated Unclassified Subject Area, or DUSA, system may **NOT** be used.
 - [d] Identify a line manager for an approval signature.
 - [e] Identify the document for release to Public Reading Room.
- [2] Add the cover page containing the LA-UR number generated by the RASSTI system to the SWPPP.
- [3] Contact the RASSTI staff for questions and assistance using this system.

4.2 Additional Documentation Requirements

The Permit requires additional documentation to be kept with the SWPPP that together keep records complete and up-to-date, and demonstrate full compliance with the conditions of the Permit. Some documents may be generated when a SWPPP is first written (e.g., copy of the permit). Other documents may be generated on an ongoing basis throughout a calendar year (e.g., inspections). Refer to Part 5.5 of the Permit for additional information.

SWPPP Preparer or Owner

[1] IF any of the following documents are generated,

<u>THEN</u> add the document to the facility SWPPP as soon as the document is generated and finalized (i.e., all signatures have been obtained).

 A copy of the Notice of Intent to Discharge (NOI) submitted to EPA and correspondence exchanged between Triad, LLC and EPA specific to coverage under the permit;

- **NOTE:** There may be several modifications to the NOI during a permit term. Ensure you coordinate with the MSGP Program Lead to confirm all modifications are included in the SWPPP.
- A copy of the acknowledgement received from the EPA assigning the NPDES permit identification number
- A copy of the permit;
- Documentation of maintenance and repairs of control measures (refer to Part 2.1.2.3 of the Permit);
- All inspections, including Routine Facility Inspections and Quarterly Visual Assessments (refer to Parts 3.1.2 and 3.2.2 of the Permit);
- Description of any deviations from the schedule for visual assessments and/or monitoring, and the reason for the deviations (refer to Parts 3.2.3 and 6.1.5 of the Permit);
- Corrective action documentation (refer to Part 4.4 of the Permit);
- Documentation of any benchmark exceedances and the type of response to the exceedance employed;
- Documentation to support any determination that pollutants of concern are not expected to be present above natural background levels if stormwater is discharged directly to impaired waters; and
- Documentation to support any claim that the facility has changed its status from active to inactive and unstaffed.

5.0 REVISING THE MSGP SWPPP

The Permit specifies conditions that trigger a SWPPP review to ensure numeric and non-numeric effluent limits are met and to determine if modifications to stormwater controls are necessary (refer to Parts 4.1 and 4.2 of the Permit).

The SWPPP must also be modified based on corrective actions and deadlines required under Part 4.3 of the Permit, and documented in accordance with Part 4.4 of the Permit.

At a minimum, the SWPPP must be reviewed and revised once per calendar year, and no later than 45 days after conducting the final routine facility inspection for the year.

SWPPP Preparer or Owner

- [1] The Stormwater PPT will review the SWPPP for the following at a minimum.
 - The selection, design, installation, and implementation of control measures.
 - Sources of pollution.

- Spill and leak procedures.
- Non-stormwater discharges (as applicable).
- [2] <u>IF</u> any of the following conditions occur or are detected during an inspection, monitoring or other means,

THEN the Stormwater PPT must **immediately** review the SWPPP as specified above.

- Unauthorized release or discharge (e.g., spill, leak, discharge of non-stormwater not authorized by the permit);
- A discharge violates a numeric effluent limit (refer to Table 2-1 of the Permit);
- Controls measures are not stringent enough for discharge to meet applicable water quality standards or the non-numeric effluent limits in the permit;
- A required control measure was never installed, installed incorrectly, or not in accordance with Parts 2 and/or 8, or is not properly operated or maintained;
- Whenever a visual assessment shows evidence of stormwater pollution (e.g., foam, oil sheen, etc.).
- Construction or a change in design, operation, or maintenance at the facility that significantly changes the nature of pollutants discharged in stormwater from the facility, or significantly increases the quantity of pollutants discharged;
 - **NOTE 1:** Changes include building removal or replacement, BMP removal or installation, outfall removal or creating a new outfall, changing drainage pathways or the path of stormwater flow.
- The average of four quarterly sampling results exceeds an applicable benchmark.
 - **NOTE 2:** If less than four benchmark samples have been taken, but the results are such that an exceedance of the four quarter average is mathematically certain this is considered a benchmark exceedance.
- [3] The Stormwater PPT must determine the modification(s) to be made to implement or maintain control measures and/or take corrective action.
- [4] The revision/modification(s) will be implemented at the facility.
- [5] The SWPPP will be revised/modified within 14 days of completion of a modification or corrective action to reflect the modification(s) made.
- [6] Obtain a signature and date from a duly authorized representative on all SWPPP revisions/modifications in accordance with Appendix B, Subsection 11 of the Permit.

6.0 TRAINING

The following personnel require training before implementing this procedure.

- Deployed Environment, Safety, and Health Group and Team Leaders
- EPC-CP MSGP stormwater compliance personnel
- DEPs
- Other LANL or subcontract personnel identified as being required to prepare and maintain MSGP SWPPPs as part of their job duties

All EPC-CP personnel that execute the activities specified in this procedure must meet the minimum qualification and training requirements for their position as identified EPC-CP-PIP-2101, NPDES Multi-Sector General Permit Program. This will include "self-study" (required reading) for this procedure as assigned and documented in accordance with ADSH-TPP-301, *ADESH Training Program Plan*. Other participating LANL groups may require training documentation pursuant to local procedures.

Contract personnel that execute the activities specified in this procedure will be qualified and trained as required by the Exhibit D and Exhibit F. In addition, contract personnel will be required to complete "self-study" (required reading) of this procedure.

7.0 RECORDS

MSGP SWPPPs are signed and certified by a duly authorized representative of the individual facilities. These completed documents are maintained at the permitted facility, managed by the facility's Records Management designated point-of-contact or document manager, and posted to the LANL public reading room. The MSGP team may retain a copy for reference purposes.

Below, are records generated as a result of implementing this procedure. Records generated are identified by title and type.

Record Title	QA Record	Non-QA Record
Stormwater Pollution Prevention Plan	\square	
MSGP SWPPP Review Guidance Checklist	N/A	N/A

8.0 DEFINITIONS AND ACRONYMS

8.1 Definitions

See LANL *Definition of Terms*.

Best Management Practice (BMP) – Schedules of activities, prohibitions of practices, maintenance procedures, and other management practices to prevent or reduce the pollution of "waters of the United States." BMPs also include treatment requirements, operating procedures, and practices to control plant site runoff, spillage or leaks, sludge or waste disposal, or drainage from raw material storage (40 CFR Part 122.2).

Control Measure – Any BMP or other method (including effluent limitations) used to prevent or reduce the discharge of pollutants to waters of the United States.

MSGP Stormwater Pollution Prevention Plan Preparation and	No: EPC-CP-QP-2110	Page 11 of 72
Maintenance	Revision: 0	Effective Date: 01/07/2020

8.2 Acronyms

See LANL Acronym Master List.

EPA	Environmental Protection Agency
EPC-CP	Environmental Protection and Compliance-Compliance Programs
DEP	Deployed Environmental Professional
DUSA	Designated Unclassified Subject Area
LANL or the Laboratory	Los Alamos National Laboratory
LA UR	Los Alamos Unlimited Release
MSGP or Permit	Multi-Sector General Permit
NPDES	National Pollutant Discharge Elimination System
NOI	Notice of Intent to Discharge
SWPPP	Stormwater Pollution Prevention Plan
PDF	Portable Document Format
РРТ	Pollution Prevention Team

9.0 REFERENCES

Unites States Environmental Protection Agency (EPA) National Pollutant Discharge Elimination System (NPDES) Multi-Sector General Permit for Stormwater Discharges Associated With Industrial Activity (MSGP)

Federal Register, Final National Pollutant Discharge Elimination System (NPDES) General Permit for Stormwater Discharges from Industrial Activities. Federal Register: June 16, 2015, Volume 80, Number 115


Clean Water Act, Title 33 U.S.C. 1251

10.0 ATTACHMENTS

Attachment 1: EPC-CP-QP-2110 R0 Form 1, *MSGP SWPPP Template* Example **Attachment 2:** *MSGP SWPPP Review Guidance Checklist* Example

Attachment 1: EPC-CP-QP-2110 R0 Form 1, MSGP SWPPP Template Example

(Page 1 of 50)



MSGP Stormwater Pollution Prevention Plan

Insert Facility Name

Triad National Security, LLC Los Alamos National Laboratory

xx/xx/xxxx

Revision X

Attachment 1: EPC-CP-QP-2110 R0 Form 1, MSGP SWPPP Template Example (cont.)

(Page 2 of 50)

Insert Facility Name MSGP Stormwater Pollution Prevention Plan Document Reference Number Revision X, Date

Page intentionally blank



Insert Facility Name

Attachment 1: EPC-CP-QP-2110 R0 Form 1, MSGP SWPPP Template Example (cont.)

Revision: 0

(Page 3 of 50)

	MSGP Stormwater Pollution Prevention Plan Document Reference Number Revision X, Date
TABL	E OF CONTENTS
DDEE	ACE
PREF	ACE
1.0	FACILITY DESCRIPTION
1.1	Facility Information
1.2	Stormwater Pollution Prevention Team (PPT)7
1.3	Site Description
1.4	General Location Map8
1.S	Site Map8
2.0	POTENTIAL POLLUTANT SOURCES
2.1	Potential Pollutants Associated with Industrial Activity
2.2	Spills and Leaks
2.3	Unauthorized Non-Stormwater Discharges
2.4	Salt Storage
2.S	Historical Data Summary
3.0	STORMWATER CONTROL MEASURES 11
3.1	Non-Numeric Technology-Based Effluent Limits
	3.1.1Minimize Exposure
3.2	Numeric Effluent Limitations Based on Effluent Limitations Guidelines
3.3	Water Quality-Based Effluent Limitations and Water Quality Standards
4.0	SCHEDULES AND PROCEDURES
4.1	Good Housekeeping
4.2	Maintenance
4.3	Spill Prevention and Response
4.4	Erosion and Sediment Control
4.S	Employee Training14
4.6	Routine Facility Inspections and Quarterly Visual Assessments

(Page 4 of 50)

		MSGP Stormwater Pollution Prevention Plan Document Reference Number
		Revision <mark>X, Date</mark>
		utine Facility Inspections
4.7		arterly Visual Assessments
4.7	Noncoring	
5.0		NTATION FOR ELIGIBILITY CONSIDERATIONS UNDER OTHER FEDERAL LAWS20
5.1	-	d Species
5.2	Historic Pro	operties
6.0	CORRECTI	VE ACTIONS AND DEADLINES 20
6.1		Actions
6.2	Subsequen	t Actions
6.3	Corrective	Action Documentation
7.0	ACRONYN	15
8.0	SWPPP CE	RTIFICATION
FIGUR	EA: GE	NERAL LOCATION MAP
FIGUR	EB: MA	AP(S)
ΑΤΤΑΟ	CHMENT 1:	NOTICE OF INTENT, SUPPORTING DOCUMENTATION, AND UPDATES 26
ΑΤΤΑΟ	HMENT 2:	SWPPP AMENDMENTS
ATTAC	CHMENT 3:	CERTIFICATION OF NO UNAUTHORIZED STORMWATER DISCHARGES 28
ATTAC	CHMENT 4:	DULY AUTHORIZED SIGNATORY MEMORANDUM
ΑΤΤΑΟ	CHMENT 5:	DISCHARGE MONITORING REPORTS
ATTAC	CHMENT 6:	ANNUAL REPORTS
ATTAC	CHMENT 7:	ROUTINE FACILITY INSPECTIONS
ΑΤΤΑΟ	CHMENT 8:	QUARTERLY VISUAL ASSESSMENTS
ΑΤΤΑΟ	CHMENT 9:	CORRECTIVE ACTION DOCUMENTATION AND CERTIFICATION
ΑΤΤΑΟ	CHMENT 10	SCHEDULED MAINTENANCE LOG
ΑΤΤΑΟ	CHMENT 11	: TRAINING DOCUMENTATION
ATTAC	CHMENT 12	: MSGP (OR ACTIVE URL)

Revision: 0

Insert Facility Name MSGP Stormwater Pollution Prevention Plan Document Reference Number Revision %, Date ATTACHMENT 13: THREATENED AND ENDANGERED SPECIES HABITAT MANAGEMENT PLAN

FOR LOS AL	AMOS NATIONAL LABORATORY
ATTACHMENT 14:	MSGP IPAC TRUST RESOURCES REPORT
ATTACHMENT 15:	EPC-CP-PIP-2101, NPDES MULTI-SECTOR GENERAL PERMIT
ATTACHMENT 16:	EPC-CP-QP-023, MSGP ROUTINE FACILITY INSPECTIONS
ATTACHMENT 17:	EPC-CP-QP- <mark>022</mark> , MSGP CORRECTIVE ACTIONS
ATTACHMENT 18:	EPC-CP-QP-064, MSGP STORMWATER VISUAL ASSESSMENTS
	EPC-CP-QP- <mark>047</mark> , INSPECTING STORMWATER RUNOFF SAMPLERS AND 5 SAMPLES FOR THE MSGP
ATTACHMENT 20:	EPC-CP-QP-2106, PROCESSING MSGP STORMWATER SAMPLES
	EPC-DO-QP-101, ENVIRONMENTAL REPORTING REQUIREMENTS FOR DR EVENTS
ATTACHMENT 22:	EPC-CP-QP-007, SPILL INVESTIGATIONS
	EPC-CP-QP-2110, MSGP STORMWATER POLLUTION PREVENTION PLAN ON AND MAINTENANCE
ATTACHMENT 24:	LOCAL PROCEDURE
ATTACHMENT 25:	LOCAL PROCEDURE

 \checkmark

(Page 6 of 50)

Insert Facility Name MSGP Stormwater Pollution Prevention Plan Document Reference Number Revision X, Date

Insert Name of Facility STORMWATER POLLUTION PREVENTION PLAN

PREFACE

This Stormwater Pollution Prevention Plan (SWPPP) was developed in accordance with the provisions of the Clean Water Act (33 U.S.C. §§1251 et seq., as amended), and the United States Environmental Protection Agency (EPA) National Pollutant Discharge Elimination System (NPDES) Multi-Sector General Permit for Stormwater Discharges Associated with Industrial Activity (MSGP) (U.S. EPA, June 2015) issued by EPA. The SWPPP uses the industry specific permit requirements for Sector XX-(Insert Sector Title) as a guide. The applicable stormwater discharge permit is EPA General Permit Identification Tracking Number NMR050013 [Triad National Security, LLC (Triad)]. Click here to view contents of the 2015 Multi-Sector General Permit.

This SWPPP applies to discharges of stormwater from the operational areas of (List the operational areas) at Los Alamos National Laboratory. Los Alamos National Laboratory (also referred to as LANL or the "Laboratory") is owned by the Department of Energy (DOE), and is operated by Triad. Throughout this document, the term "facility" refers to (Insert facility name). The current MSGP expires at midnight on June 4, 2020.

1.0 FACILITY DESCRIPTION

1.1 Facility Information

Name of Facility: (Insert facility name e.g., TA-3-22	Power and Steam P	lant)
Street: P.O. Box 1663		
City: Los Alamos	State: NM	ZIP Code: 87545
County: Los Alamos		
NPDES ID (i.e., permit macking number): NMR0500	13	
Primary Industrial Activity SIC code, and Sector and SIC XXXX, Sector X, Subsector XX	Subsector (2015 MS	GP, Appendix D and Part 8):
Estimated area of industrial activity at site exposed	to stormwater: XX a	cres
Discharge Information		
Name(s) of surface water(s)/segment that receives (Sigma Canyon to NPDES outfall 001). Note: For Roa (within LANL)". Note: For Asphalt Batch Plant alone "Mortandad Canyon (within LANL)."	ids and Grounds also	add "and Mortandad Canyon
Does this facility discharge industrial stormwater di (see definition in 2015 MSGP, Appendix A)?	rectly into any segm IYes No	ent of an "impaired water"
Pollutants causing the impairment: (Insert pollutant	s: list can be found i	n the Triad Notice of Intent

(Page 7 of 50)

Insert Facility Name MSGP Stormwater Pollution Prevention Plan Document Reference Number Revision X, Date

Pollutants causing the impairment (see above) that may be present in industrial stormwater discharges from this Facility:

Are any of your stormwater discharges subject to effluent limitation guidelines (ELGs) (2015 MSGP Table 1-1)?

If Yes, which guidelines apply? (Note: Asphalt Batch Plant is subject to ELGs) Not applicable.

1.2 Stormwater Pollution Prevention Team (PPT)

Insert a description of the team

The specific duties of individual team members of the PPT are listed in the table below.

Staff Names	Individual Responsibilities
Group Leader: Name Title, Organization	Responsible for the management of all environmental, safety, health, and quality programs for the yards, buildings and facilities within this Plan. This includes performing oversight and periodic walk downs to ensure implementation of the requirements of the MSGP and this SWPPP including overseeing the assigned duties of other PPT members. The Group Leader is responsible for ensuring
	problems noted during inspections are corrected. The Group Leader must also ensure adequate resources are obtained to ensure compliance requirements of the MSGP and this SWPPP are met.
Deployed Environmental Professional (DEP): Name Title, Organization	Responsible for the management of all environmental programs and issues for the yards, buildings and facilities listed within this Plan. The DEP is responsible for training, recordkeeping, and SWPPP revision. The DEP ensures documentation of inspections and other required MSGP records relative to the SWPPP are managed in accordance with the Permit and established document control procedures and that the SWPPP is kept current. The DEP provides technical and regulatory support to facility and operations personnel regarding implementation of the MSGP and this SWPPP. Lastly, the DEP conducts routine facility inspections and if necessary, visual assessments, in accordance with the Permit. Identified conditions requiring corrective actions from routine facility inspections are entered into the Environmental Protection and Compliance-Compliance Programs (EPC-CP) Corrective Action Report (CAR) database. The DEP is responsible for tracking and updating the status of corrective actions that
Facility Operations Division (FOD) Manager: Name Title, Organization	cannot be implemented immediately. Responsible for managing the maintenance and operation of all aspects of the yards, buildings and facilities listed within this Plan. The manager shall provide review and ensure coordination with core personnel and the PPT, as appropriate, when tenants within

Revision: 0

(Page 8 of 50)

Insert Facility Name MSGP Stormwater Pollution Prevention Plan Document Reference Number Revision X, Date

	the FOD propose new processes, operations, features, or a new site that may be subject to the MSGP.
EPC Core: Name Title, Organization	The MSGP Program Lead is responsible for managing and administering the MSGP Program for all industrial facilities operated by Triad within Los Alamos National Laboratory. The MSGP Program Lead advises and provides guidance to facility or operations personnel on NPDES MSGP regulations/requirements. The Program Lead also acts as the institutional point of contact for all interactions with the regulatory authority (EPA) and supervises personnel implementing stormwater monitoring requirements for the facility.
Operations Manager(s): Name Title, Organization	Responsible for day-to-day operations at the facility. Assists the DEP and EPC with inspections; spill reporting; implementing, installing and maintaining storm water controls (also known as Best Management Practices) (BMPs); and providing documentation as requested by other team members. The Operations Manager is key to ensuring adequate communication and coordination of issues regarding implementation of the MSGP and this Plan. Operations Managers also assist the DEP/EPC with SWPPP training and/or briefings, as requested.

1.3 Site Description

Insert text with site description. Include information on type of operation(s), industrial operating equipment (associated with the Asphalt Batch Plant and the TA-3-22 Power and Steam Plant), main structures, activities, outfalls, and substantially identical outfalls.

1.4 General Location Map

The general location map for the facility can be found in Figure A. Figure B-<mark>X (if you have more than one site map, list them all here)</mark> contains all site maps and identifies all receiving waters associated with stormwater discharges from the facility. X percent of the site flows to (Insert canyon name). The canyon at this location is a (Insert stream type e.g., perennial, ephemeral, intermittent) and eventually flows to the Rio Grande approximately X miles southeast of the site.

1.5 Site Map

The site map is provided as Figure B-X (if you have more than one site map, list them all here) and illustrates the facility's activities: including facility boundary, structures, impervious surfaces, industrial activity areas, spills, operational areas, drainage patterns, stormwater controls, monitoring locations, outfalls and nearby receiving streams.

As required by the 201S MSGP, the following information specific to the facility is either shown on the site map or contained with additional information provided in this SWPPP.

- Site boundaries and acreage. The site covers approximately X acres.
- Significant structures and impervious surfaces. The site is X percent impervious, primarily structures and paved lots.

(Page 9 of 50)

Revision: 0

Insert Facility Name MSGP Stormwater Pollution Prevention Plan Document Reference Number Revision X, Date

- Direction of stormwater flow and site drainage. Direction of flow is indicated with arrows.
- Locations of stormwater control measures.
- Locations of all receiving waters. In the immediate vicinity of the facility, (Indicate if any of the waters are Impaired and, if so, whether the waters have TMDLs established for them. See paragraph below this list). Also, indicate if the receiving water includes a wetland. A map of nearby receiving waters is provided as Figure B-X.
- Locations of all stormwater conveyances. This includes all ditches, pipes, and swales.
- Locations of potential pollutant sources.
- Locations of significant spills or leaks.
- Locations of all stormwater monitoring points.
- Locations of stormwater inlets and outfalls. Of which each will require a unique identification code for each outfall (e.g., Outfall 005, etc.), indicating if you are treating one or more outfalls as "substantially identical" and an approximate outline of the areas draining to each outfall.
- This facility is not associated with a municipal separate storm sewer system (MS4).
- Areas of designated critical habitat for endangered or threatened species. There are (Insert "no areas" or a number of areas) in the direct vicinity of the facility. However, a map for threatened and endangered species within LANL property is included as Figure B-X.
- Locations of the following activities where such activities are exposed to precipitation:
 - Insert all facility activities exposed to stormwater (e.g., fueling locations; loading/unloading areas; locations used for the treatment, storage, or disposal of wastes; liquid storage tanks; processing and storage areas; machinery; location and sources of run-on to the site; transfer areas for substances in bulk; immediate access roads used or traveled by carriers of raw materials, manufactured products, waste material, or by-products used or created by the facility; and vehicle and equipment maintenance and/or cleaning areas. Only include the activity areas specific to the facility (for example, if you do not refuel within the active facility boundary, do not include "fueling locations" in this bulleted list). Use a secondary bullet list level in this section.

2.0 POTENTIAL POLLUTANT SOURCES

Industrial activities that could potentially result in releases to the environment are summarized in 2.1 below. The site map for the facility is provided in Figure B-1.

Insert text describing structures and industrial activities that could potentially result in a release to the environment. Include information on location (e.g. inside, outside), associated containment, protection (e.g., roofed areas or coverings), and other devices or practices to prevent or contain spills, prevent runon and run-off.

2.1 Potential Pollutants Associated with Industrial Activity

List specific areas and activities that could potentially result is a release to the environment and the constituents that may be released. Include a list of any Solid Waste Management Units and Areas of Concern (also known as Consent Order Sites or Potential Release Sites) with a description of each and associated potential pollutants/contaminants.

2.2 Spills and Leaks

(Page 10 of 50)

Revision: 0

Insert Facility Name MSGP Stormwater Pollution Prevention Plan Document Reference Number Revision X, Date

Insert information on spill and leak history at the facility, if any. Text may be in table format as shown below.

Date	Description	Outfall(s) Affected

Insert information on areas where spills and leaks could occur at the facility. Text may be in table format as shown below.

Specific Equipment/Industrial Activity Areas and	Outfall(s) Affected
	1.

In the event of any future spill or leak at any of the facility areas, a spill report, documenting the occurrence and the nature of the spill or leak, will be completed. The spill report will be filed promptly upon completion and documentation of the spill clean-up, and will be summarized in this section of the SWPPP. In addition, spills within MSGP facility boundaries will be entered as conditions requiring corrective action in the MSGP CAR database and will be updated as corrective action occurs, in accordance with EPC-CP-QP-022, *MSGP Corrective Actions*.

The probability of spills or releases at the facility is minimized by (Insert information on how the facility will minimize spills and leaks).

2.3 Unauthorized Non-Stormwater Discharges

Insert information describing any NPDES permitted non-stormwater discharges, unpermitted outfalls, or unauthorized discharges associated with the facility. Describe any potential sources of non-stormwater discharges (e.g., testing of fire hydrants) and where wastewater drains to. Include a reference to the "Non-Stormwater Discharge Assessment and Certification" and indicate that it is provided in Attachment 3.

2.4 Salt Storage

Insert text describing salt storage areas at the facility, if present. If none exists, state salt is not stored at the facility.

2.5 Historical Data Summary

The following tables provide monitoring data at the facility for the past $\frac{X}{X}$ years.

Permitted Facility: (insert facility name)

Calendar Year XXXX

Contact MSGP Program Lead to obtain this information formatted for insertion.

Note: This information will be updated every year during the annual SWPPP update, to include the 3 most current years of monitoring data.

(Page 11 of 50)

Insert Facility Name MSGP Stormwater Pollution Prevention Plan Document Reference Number Revision X, Date

3.0 STORMWATER CONTROL MEASURES

Control measures at the facility are designed to minimize the potential release of pollutants that could adversely affect water quality. Insert text with stormwater control measure information.

3.1 Non-Numeric Technology-Based Effluent Limits

Insert text with non-numeric technology-based effluent limits information. Note: This is specific to Sectors A, AA, N, O and P.

3.1.1 Minimize Exposure

Insert text describing all structural controls (structures or covers) or practices used to minimize the exposure of industrial activities to precipitation. The SWPPP must describe where the controls or practices are being implemented at the facility. Examples of exposure-minimizing control measures include: location and extent of grading, berms, curbs used to contain contaminated stormwater or divert it around areas of industrial activity, materials stored within secondary containment, location of spill cleanup kits, schedule for employee spill abatement and cleanup training, procedure or practices for storage of leaky vehicles and equipment.

3.1.2 Good Housekeeping

Good housekeeping practices specifically applicable to the prevention of stormwater contamination include the following measures: Insert text describing any practices implemented to keep exposed areas at the facility clean. Describe where each practice is being implemented at the facility. Examples of good housekeeping control measures include how workspaces are maintained; routine inspections of heavy equipment, other equipment and waste containers; inspections of material storage areas; identifying specific personnel/positions responsible for empting drip pans, etc. Refer to Section 4.1 of this document for specific schedules for waste and recyclable material pickup and sweeping.

All site areas exposed to precipitation are walked down during daily operations and monthly routine facility inspections to ensure that the grounds are kept in an orderly condition. The outdoor metal storage areas are inspected to ensure all piping and metal raw material is off the ground on storage racks and covered, or stored inside buildings, sheds or transportable containers. Vehicle and forklift parking areas are inspected for leaks or spills as well as storage areas containing oil-filled equipment. The entire site, including loading areas and outfalls, are inspected for floatable debris, garbage, waste and all other potential pollutants. All dumpsters and roll-off bins are inspected to ensure they are closed.

3.1.3 Maintenance

Control measures at the facility will be kept in effective operating condition by the implementation of scheduled preventive maintenance, standard operating procedures (SOPs), engineering guidance, and manufacturer's specifications as applicable. If control measures need to be replaced or repaired to maintain compliance with the 2015 MSGP, necessary modifications will be made according to the timelines specified in the *Corrective Action and Deadlines* requirements of Section 6.0 of this SWPPP.

Deficient items identified during routine facility inspections, walk-downs, or by any other means of identification, will be documented on the routine facility inspection forms and entered into the MSGP CAR database. The condition requiring corrective action will remain open until proper maintenance or

(Page 12 of 50)

Insert Facility Name MSGP Stormwater Pollution Prevention Plan Document Reference Number Revision X, Date

corrective action has been completed. CAR information, along with documentation of maintenance/repair of control measures, is in Attachment 9 of the SWPPP.

Insert text identifying how industrial equipment is maintained to avoid leaks or other releases. Also, include information on how site-specific control measures are maintained to ensure effective operating condition.

3.1.4 Spill Prevention and Response

Spills, leaks, or other releases will be prevented and minimized by <mark>(insert information on how the facility prevents and minimizes unauthorized releases).</mark>

Insert text describing the general facility approach to spill cleanup.

All spills or releases are reported to EPC-CP by using the spills pager (505) 664-7722. Although incidental spills may be cleaned up by facility personnel, all emergency spills or releases are reported to Emergency Management Division-Emergency Response (EMD-ER) and/or the Facility Duty Officer by calling 667-2400. If fire or explosion is present, or if the potential for such exists, the situation must be reported by dialing 911 from a non-cellular phone or by activating a fire pull box. In the event of a spill, EMD-ER will coordinate appropriate cleanup procedures and EPC-CP will notify the individuals or organizations responsible for completing spill reports and providing information needed to fulfill regulatory reporting requirements.

Unauthorized releases or discharges within industrial facility boundaries are entered into the MSGP Corrective Action Reporting database in accordance with EPC-CP-QP-022, *MSGP Corrective Actions*. In addition, the completion of an Unplanned Release Report is required in the event of a spill. The report will be submitted to EPC-CP personnel and handled according to internal spill record keeping procedures. Spills may be "reportable" (requiring external agency notification) depending on the nature of the spilled material and the location of the release. External agency notification may consist of verbal and/or written notification to the National Response Center, Environmental Protection Agency Region VI, or the New Mexico Environment Department (NMED). EMD-ER, the FOD and EPC-CP, in accordance with Laboratory and DOE policies and federal and state regulatory reporting requirements, will make the determination for the type of reporting required. EPC-DO-QP-101, *Environmental Reporting Requirements for Releases or Events* is used for this purpose (see Attachment 21).

Copies of internal spill reports are maintained by the responsible organization and in the EPC-CP database. The EPC-CP procedure for spill reporting and response, ENV-CP-QP-007, *Spill Investigations*, can be found in Attachment 22 of this SWPPP.

3.1.5 Erosion and Sediment Control

Insert text describing how erosion at the facility and sediment transport off the facility is prevented/minimized. Erosion control measures that prevent soil or sediment from becoming mobilized should be used as the primary line of defense. Sediment control measures that trap, infiltrate, or settle out mobilized sediments, should be used to back-up the erosion control measures.

3.1.6 Management of Runoff

Insert text describing how the facility manages stormwater runoff. This will include a description of controls used to divert, infiltrate, reuse, contain, or otherwise reduce stormwater runoff. Installed or utilized control measures may be listed with a description of their function at the facility.

Revision: 0

Insert Facility Name MSGP Stormwater Pollution Prevention Plan Document Reference Number Revision X. Date

3.1.7 Salt Storage Piles or Piles Containing Salt

Insert text describing how the facility manages salt storage piles or piles containing salt. Offloading operations should occur within contained areas with appropriate measures in place to prevent off-site migration or track out of salt from the contained area. Installed or utilized control measures may be listed with a description of their function at the facility. If none exists, state salt is not stored at the facility.

3.1.8 Dust Generation and Vehicle Tracking of Industrial Materials

Insert text describing how the facility manages dust generation and vehicle tracking.

3.2 Numeric Effluent Limitations Based on Effluent Limitations Guidelines

Insert information identifying the facility as meeting or not meeting the industrial category requirements for effluent monitoring as listed in Part 2.1.3 (*Table 2-1 Applicable Effluent Limitation Guidelines*) of the 2015 MSGP and if benchmark monitoring is or is not required.

If the permit does identify sector-specific requirements for the facility, insert a description of specific controls implemented at the facility to ensure numeric effluent limits are met.

3.3 Water Quality-Based Effluent Limitations and Water Quality Standards

Impaired waters monitoring is performed annually at the facility as listed in Section 4.7 of this SWPPP. The pollutants monitored can change yearly based on the requirements of the MSGP. The table in Section 4.7 lists the current year monitoring requirements and standards.

Stormwater from (insert facility name) discharges to (insert canyon name). Insert information on canyon reaches identified as impaired waters, pollutants causing the impairment, and approved or established TMDLs for the canyon. Also, insert specific information relative to the controls measures used to ensure discharges from industrial activities meet the water quality standards.

Refer to Section 4.7 for specific actions that will be taken when a water quality standard is exceeded.

4.0 SCHEDULES AND PROCEDURES

Preventative maintenance of control measures used to comply with the Permit effluent limits can avoid situations that result in discharges to the environment. Part 5.2.5 of the 2015 MSGP specifies control measures will have a schedule or frequency for maintenance and procedures specifying how maintenance is conducted. Part 5.5 requires documentation of maintenance and repairs including the date(s) of regular maintenance. See Attachment 10 for the Scheduled Maintenance Log.

4.1 Good Housekeeping

Insert a schedule for housekeeping activities such as waste and recyclable material (scrap metal, wood tires) pickup, street sweeping, etc. and identify any procedures used to ensure this occurs.

4.2 Maintenance

Insert a discussion of and schedule for preventative or regular maintenance of equipment such as oil/water separators, culvert clean outs, other control measures, etc. Note: Industrial equipment will be

(Page 14 of 50)

Insert Facility Name MSGP Stormwater Pollution Prevention Plan Document Reference Number Revision X, Date

maintained so that leaks and other releases are avoided. All control measures will be maintained in effective operation condition.

4.3 Spill Prevention and Response

Insert a discussion of and schedule for preventing and responding to spills and leaks such as regular maintenance of equipment, placing pans under heavy equipment, and maintaining spill kits. Also, specify cleanup equipment, procedures and spill logs, and identify how often employees are trained in spill response procedures, as appropriate.

4.4 Erosion and Sediment Control

Insert a discussion of and schedule for preventative or regular maintenance of erosion, sediment and velocity control measures. If polymers and/or other chemical treatments are used as erosion or sediment control measures, identify them and include a regular schedule for reapplication. Also, include a schedule for restocking these materials to ensure the facility does not run out.

4.5 Employee Training

Employee training is essential for effective implementation of the SWPPP and MSGP requirements. The goals for the training program are to ensure that employees: (1) are aware of what happens when pollutants come in contact with stormwater; (2) are familiar with and will implement the requirements of this SWPPP; (3) are capable of preventing spills; (4) respond safely and effectively to an accident when one occurs; (5) recognize when there is an issue with a control measure; (6) recognize when additional control measure are necessary; and (7) identify situations that could lead to stormwater contamination.

Per Part 2.1.2.8 of the 2015 MSGP, training relevant to the SWPPP and MSGP is required for all workers at the facility that work in areas where industrial materials or activities are exposed to stormwater (MSGP sites); workers, managers, and supervisors who are responsible for implementing activities necessary to meet the conditions of this permit (e.g., inspectors, maintenance personnel); and all members of the PPT. Training is designed to ensure these personnel understand the MSGP and SWPPP requirements, as well as their specific responsibilities regarding these requirements.

Training provided and assigned to these personnel cover both the specific control measures used at the facility; along with monitoring, inspection, planning, reporting, and documentation requirements described in this SWPPP. Training will be conducted at least annually. The DEP, Deployed Environment Safety and Health (DESH) Group Leader and Pollution Prevention Team members are responsible for ensuring all appropriate personnel receive this training. It is suggested to add a list of job titles per facility that require training (e.g., Mechanics, Heavy Equipment Operators, PPT members, Operations Manager(s), etc.).

Training activities are documented in accordance with LANL's Training Standards. In cases where training is formalized enough to require specific curricula and reoccurrence, the training activity will be recorded in LANL's official U-TRAIN database. Informal briefings, such as those included in-group safety meetings are not typically recorded in U-TRAIN. Sign-in sheets are used to document attendance and will be kept on file in Attachment 11 of this SWPPP.

The topics in this SWPPP that are covered in the latest version of the facility-specific annual MSGP training (see Attachment 11) include the following:

(Page 15 of 50)

Insert Facility Name MSGP Stormwater Pollution Prevention Plan Document Reference Number Revision X, Date

- Overview of the SWPPP contents;
- Spill response and cleanup procedures, good housekeeping, maintenance requirements, and material management practices to prevent stormwater pollution;
- The location of all controls on the site required by this permit and how they are maintained;
- The proper procedures to follow with respect to the permit's pollution prevention requirements; and
- When and how to conduct inspections, record applicable findings, and take corrective actions.

4.6 Routine Facility Inspections and Quarterly Visual Assessments

Routine inspections at this facility are conducted and documented monthly in accordance with EPC-CP-QP-023, *MSGP Routine Facility Inspections* (Attachment 16).

Visual assessments are conducted in accordance with EPC-CP-QP-064, MSGP Stormwater Visual Assessments (Attachment 18).

4.6.1 Routine Facility Inspections

At least once each calendar year, the routine facility inspection is conducted during a period when a stormwater discharge is occurring. A qualified member of the PPT (typically the DEP, a representative from the EPC-CP Storm Water Permitting/Compliance Team or EPC-CP Program Lead) performs the inspection. The 2015 MSGP consolidates the different and separate documentation requirements in the Comprehensive Site Inspection Procedures and Routine Facility Inspection Procedures from the 2008 MSGP. EPC-CP will perform at least one routine inspection per year in order to evaluate corrective action status for the Annual Report requirements.

Routine inspections will evaluate the following areas, at a minimum:

- Areas where industrial materials or activities are exposed to stormwater;
- Areas identified in the SWPPP and those that are potential pollutant sources;
- Areas where spills and leaks have occurred in the last three years;
- Discharge points(outfalls/Substantially Identical Outfalls (SIOs); and
- Control measures used to comply with the effluent limits contained in this permit.
- Specific areas of the facility to be inspected are described in Section 2.1.

During routine inspections, the following must be examined and looked for:

- Industrial materials, residue or trash that may have or could come into contact with stormwater;
- Leaks or spills from industrial equipment, drums, tanks and other containers;
- Offsite tracking of industrial or waste materials, or sediment where vehicles enter or exit the site:
- Tracking or blowing of raw, final or waste materials from areas of no exposure to exposed areas; and
- Control measures needing maintenance, repairs or replacement.

Inspections performed by the PPT member are documented by completing the routine facility inspection form, which identifies all conditions requiring corrective action and other potential stormwater pollution issues that were encountered. All conditions requiring corrective actions identified during the inspection are addressed in accordance with Section 6.0 *Corrective Actions and Deadlines* of this plan. Facility personnel or the DEP may also perform daily, weekly, or other periodic facility surveys (walk downs)

(Page 16 of 50)

Revision: 0

Insert Facility Name MSGP Stormwater Pollution Prevention Plan Document Reference Number Revision X, Date

between monthly routine inspections to ensure compliance with the SWPPP and MSGP. Completed routine facility inspection forms are provided in Attachment 7 of this SWPPP and meet the requirements listed in the 2015 MSGP (Part 3.1.2.).

4.6.2 Quarterly Visual Assessments

Once each quarter, (April 1-May 31, June 1-July 31, August 1-September 30, October 1-November 30) a stormwater sample is obtained and visual assessment performed at each outfall, if a measureable storm event occurred. A qualified member of the PPT (DEP, EPC-CP field team member or MSGP Program Lead) conducts the visual assessment. The visual assessment will be:

- Of a sample in a clean, clear colorless glass or plastic container and examined in a well-lit area;
- On samples collected within the first 30 minutes of an actual discharge from a storm event or as soon as practicable thereafter. Alternatively, document why it was not possible to collect the sample within the first 30 minutes (i.e. adverse conditions, not enough flow, etc.); and
- Conducted at least 72 hours since the last storm event; or document that the 72-hour period is representative of local storm events during the sampling period.

Note: Snowmelt samples need only be collected during a period of measurable discharge.

The visual assessment will inspect for the following water quality characteristics: color, odor, clarity, floating solids, settled solids, suspended solids, foam, oil sheen, and other obvious indicators of stormwater pollution.

Exceptions to visual assessments:

- Document rationale if a visual assessment is unable to be collected in a quarter (no precipitation event or adverse conditions, etc.);
- Perform an additional assessment during the next qualifying storm event if unable to perform in a particular quarter; and
- Perform one quarterly assessment during snowmelt discharge (taken during a measurable discharge from the site).

For facilities with substantially identical outfalls, quarterly visual assessments may be performed at only one of the outfalls, provided that you perform visual inspections on a rotating basis at each substantially identical outfall.

The PPT member performing the visual assessment documents potential stormwater pollution problems that were observed during the assessment on the quarterly visual assessment form. Any required corrective actions identified during the assessment are addressed in accordance with Section 6.0 *Corrective Actions and Deadlines* of this plan. Completed quarterly visual assessments are provided in Attachment 8 of this SWPPP and meet the requirements listed in the 2015 MSGP (Part 3.2.2).

4.7 Monitoring

Analytical monitoring comprised of Impaired Waters [insert Effluent Limitation Guideline monitoring for industrial activity identified in Tables 1-1 and 6-1 of the 2015 MSGP (for example the Asphalt Batch Plant)] monitoring is performed annually on stormwater discharges from the site. Benchmark constituents are monitored quarterly. Monitoring occurs when storm events result in an actual discharge from the site and follow the preceding measurable storm event by at least 72 hours (3 days), unless documented that the storm event is representative of local storm events during the sampling

(Page 17 of 50)

Insert Facility Name MSGP Stormwater Pollution Prevention Plan Document Reference N Revision X. Date period. For runoff from snowmelt, the monitoring is performed at a time when a measurable discharge from the site occurs. Monitoring is conducted according to test procedures approved under 40 CFR Part 136. Runoff samples are collected by taking a minimum of one grab sample from a discharge, collected within the first 30 minutes of a measurable storm event. If it is not possible to collect the sample within the first 30 minutes of a measurable storm event, the sample is collected as soon as practicable after the first 30 minutes and documentation is kept with the SWPPP explaining why it was not possible. LANL is located in a high elevation, semi-arid climate where the majority of rainfall occurs during a period between July and September. Freezing conditions that would prevent runoff from occurring for extended periods may also occur during the winter months. If adverse weather conditions prevent the collection of a sample according to the relevant monitoring schedule, a sample will be collected during the next qualifying storm event or as soon as practicable. Monitoring occurs at automated sampling station [insert automated sampler identifier (e.g., MSGP07501)] as identified in Section 1.5. Discharge from the facility is (insert cardinal direction) to (insert canyon name) (impaired waters), which is a tributary of the Rio Grande located approximately X miles east of the facility. Outfall (insert substantially identical outfall identification number) is "substantially identical" to Outfall (insert monitored outfall identification number) based on (insert the following information: industrial activities conducted in the drainage area, description of control measures implemented in the drainage area of each outfall, description of exposed material located in the drainage area of each outfall that are likely to be significant contributors of pollutants to stor mwater discharges, and an estimate of the runoff coefficient of the drainage areas). Outfall locations are shown on the site map provided in Figure B-1. Note: Delete this paragraph if the facility has no substantially identical outfalls. If the facility has multiple maps, reference them all. Monitoring will continue annually for constituents associated with impaired waters until a constituent is no longer detected in stormwater samples. If the impaired water or benchmark constituent value exceeds the New Mexico Water Quality criterion (insert or ELG value is exceeded, if applicable), the Pollution Prevention Team will: Review the selection, design, installation, and implementation of control measures to determine • if modifications are necessary to meet the effluent limits; Implement the necessary modifications within the timeframe specified for corrective action; and Continue benchmark or annual monitoring of the constituent (as required by Part 6.2 of the 2015 MSGP); If an ELG is exceeded, follow-up monitoring within 30 calendar days (or during the next qualifying runoff event) of implementing corrective action(s) is required. When follow-up monitoring exceeds the applicable effluent limitation, an exceedance report is submitted to EPA and monitoring continues at least quarterly, until the discharge complies with the effluent limit. For each monitoring event, except snowmelt monitoring, the following information will be recorded and maintained through work orders, LANL database systems, and Discharge Monitoring Records: The date, exact place, and time of sampling or measurements; • The date and duration (in hours) of the rainfall event Rainfall total (in inches) for that rainfall event

(Page 18 of 50)

Insert Facility Name MSGP Stormwater Pollution Prevention Plan Document Reference Number Revision X, Date

- The individual(s) who performed the sampling or measurements;
- The date(s) analyses were performed
- The individual(s) who performed the analyses;
- The analytical techniques or methods used; and
- The results of such analyses.

All records of monitoring information, including all calibration and maintenance records are maintained for a minimum period of at least three years from the date the permit expires.

Insert information on guarterly benchmark and annual Impaired Waters or Effluent Limitation Guideline monitoring required for facility and benchmark pollutants to be sampled.

LANL's applicable stormwater monitoring procedures can be found in the following Attachments:

- EPC-CP-QP-047, Inspecting Stormwater Runoff Samplers and Retrieving Samples for the MSGP (Attachment 19)
- EPC-CP-QP-2106, Processing MSGP Stormwater Samples (Attachment 20).

The table on the following page lists the current Summary of Monitoring Requirements. The monitoring values have been modified to reflect New Mexico water quality standards and are based on the most protective water quality standards from the Standards for Interstate and Intrastate Surface Waters (effective on February 28, 2018), 20.6.4.900 NMAC; and as set forth in Part 9.6.2.1 of the 2015 MSGP.

S

	Insert Facility Name
MSGP Storn	nwater Pollution Prevention Plan
	Document Reference Numbe
	Revision X, Date

Summary of Monitoring Requirements

Outfalls: (insert outfall numbers)

Contact MSGP Program Lead to obtain this information formatted for insertion.

ANNA

(Page 20 of 50)

Insert Facility Name MSGP Stormwater Pollution Prevention Plan Document Reference Number Revision X, Date

5.0 DOCUMENTATION FOR ELIGIBILITY CONSIDERATIONS UNDER OTHER FEDERAL LAWS

5.1 Endangered Species

The Final Site-Wide Environmental Impact Statement (EIS) for the Operation of Los Alamos National Laboratory (DOE/EIS-0380) was issued in May 2008, and a Record of Decision in September 2008. Stormwater issues and associated pollution prevention requirements and activities at LANL are analyzed in Chapters 4 and 5 of the 2008 Site-Wide EIS. These activities are integrated into environmental reviews on a project-specific level through LANL's Integrated Review Tool (IRT), which incorporates both the Excavation Permit (EX-ID) and Permit Requirements Identification (PR-ID) process. Stormwater issues are identified and pollution prevention activities are implemented during the design and construction phases of all LANL projects, and as part of facility operations, including routine maintenance. LANL staff monitors stormwater pollution prevention compliance at MSGP sites in accordance with Section 4.7 *Monitoring* of this plan. Corrective actions are taken as necessary as described in Section 6.0 *Corrective Actions and Deadlines* of this plan.

Part 5.2.2 of the 2015 MSGP requires areas of designated critical habitat for endangered or threatened species, as applicable, be included in the SWPPP. The *Threatened and Endangered Species Habitat Management Plan for Los Alamos National Laboratory* (LA-UR-17-29454) was last updated in October 2017 (see Attachment 13). This document provides a management strategy for the protection of threatened and endangered species and their habitats on LANL property. The MSGP IPaC Trust Resource Report (see Attachment 14) is also attached for informational purposes.

5.2 Historic Properties

In August, 2015 and December 2008, the Cultural Resources Team (using GPS spatial data as well as conducting visual inspections), reviewed the Laboratory industrial sites (see list below) and their associated outfalls and monitoring stations subject to the 2015 Multi-Sector General Permit (Permit #NMR050000) for effects on historic properties. All of these sites were found to be undertakings of no effect and in compliance with Section 106 of the National Historic Preservation Act (i.e., Criterion B).

- TA-3-22 Power and Steam Plant
- TA-3-38 Metals Fabrication Shop
- TA-3-38 Wood Shop
- TA-3-39 and 102 Metal Shop
- TA-3-66 Sigma Complex
- TA-60 Asphalt Batch Plant
- TA-60-1 Heavy Equipment Yard
- TA-60 Material Recycle Facility
- TA-60 Roads and Grounds
- TA-60-2 Warehouse
- TA-54 RANT

6.0 CORRECTIVE ACTIONS AND DEADLINES

When any of the following conditions occur or are detected during an inspection, monitoring or any other means, this SWPPP (e.g., sources of pollution; spill and leak procedures; non-stormwater discharges; the selection, design, installation and implementation of control measures) is reviewed and

(Page 21 of 50)

Revision: 0

Insert Facility Name MSGP Stormwater Pollution Prevention Plan Document Reference Number Revision X, Date

revised (as appropriate). The purpose is to ensure effluent limits of the 2015 MSGP permit are met and pollutant discharges are minimized:

- An unauthorized release or discharge (e.g., spill, leak, or discharge of non-stormwater not authorized by this or another NPDES permit to a water of the U.S.) occurs at the facility;
- A discharge violates a numeric effluent limit;
- Control measures are not stringent enough for the discharge to meet applicable water quality standards or non-numeric effluent limits;
- An inspection identifies that a required control measure was never installed, was installed incorrectly or is not being properly operated or maintained; and
- Whenever a visual assessment shows evidence of stormwater pollution.

When any of the following conditions occur, a review of the selection, design, installation, and implementation of control measures is performed to determine if modifications are necessary to meet the effluent limits in this permit:

- Construction or a change in design, operation, or maintenance at the facility significantly changes the nature of pollutants discharged in stormwater from the facility, or significantly increases the quantity of pollutants discharged; or
- The average of 4 quarterly sampling results exceeds an applicable benchmark. If less than 4 benchmark samples have been taken, but the results are such that an exceedance of the 4 quarter average is mathematically certain (i.e., if the sum of quarterly sample results to date is more than 4 times the benchmark level) this is considered a benchmark exceedance, triggering this review (see Section 4.7); or
- If an impaired water constituent exceeds the NM Water Quality criterion (see Section 4.7).

When the review identifies the need to modify the SWPPP, it will be revised within 14 calendar days of completion of the associated condition requiring corrective action.

6.1 Immediate Actions

When a condition requiring corrective action is identified, all reasonable steps necessary to minimize or prevent the discharge of pollutants are immediately taken (i.e. spill clean-up, scheduling repairs) until a permanent solution (if needed) can be implemented. Immediate action means all reasonable steps are taken the same workday or no later than the following workday (when it is too late in the day to take corrective action).

6.2 Subsequent Actions

When additional corrective actions are required (e.g. installing or making operational a new or modified control, completing repairs, ordering BMPs) they will be completed by the next storm event, if possible, or within 14 calendar days (from initial discovery). When it is determined that it is infeasible to complete corrective actions within 14 days, documentation of infeasibility and a schedule for completion of the work is documented in the CAR database, which will be completed no later than 45 days (from initial discovery). When it is determined that is notified and provided justification of why actions will exceed the timeframe; and a minimal amount of additional time to complete the work may be approved.

6.3 Corrective Action Documentation

(Page 22 of 50)

Insert Facility Name MSGP Stormwater Pollution Prevention Plan Document Reference Number Revision X, Date

Upon discovery, conditions requiring corrective action are documented by the DEP or EPC-CP on a Routine Facility Inspection Form and/or entered into the CAR database. The action will be kept open in the database until the issue has been resolved. Documentation of maintenance and repairs of stormwater control measures (BMPs) will be kept in Attachment 10 of this SWPPP. Where corrective actions result in changes to procedures or controls documented in this SWPPP, modifications to the SWPPP are made accordingly within 14 calendar days of completing the corrective action(s). LANL procedure EPC-CP-QP-022, *MSGP Corrective Actions* can be found in Attachment 17.

7.0 ACRONYMS

BMP	Best Management Practice
CAR	Corrective Action Report
DEP	Deployed Environmental Professional
DESH	Deployed Environmental Safety and Health
DOE	Department of Energy
EIS	Environmental Impact Statement
ELG	Effluent Limitation Guidelines
EMD-ER	Emergency Management Division-Emergency Response
EPA	Environmental Protection Agency
EPC-CP	Environmental Protection and Compliance – Compliance Programs
FOD	Facility Operations Division
IPaC	Information for Planning and Consultation
LANL or the Laboratory	Los Alamos National Laboratory
MSGP or Permit	Multi-Sector General Permit
NOI	Notice of Intent
NPDES	National Pollutant Discharge Elimination System
PPT	Pollution Prevention Team
SWPPP	Stormwater Pollution Prevention Plan
URL	Uniform Resource Locator

(Page 23 of 50)

Insert Facility Name MSGP Stormwater Pollution Prevention Plan Document Reference Number Revision <mark>X</mark>, Date

8.0 SWPPP CERTIFICATION


STORMWATER POLLUTION PREVENTION PLAN (Insert Facility Name) Los Alamos National Laboratory

CERTIFICATION STATEMENT

I certify under penalty of law that this document and all attachments were prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gathered and evaluated the information submitted. Based on my inquiry of the person or persons who manage the system, or those persons directly responsible for gathering the information, the information submitted is, to the best of my knowledge and belief, true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment for knowing violations.

Signature (Insert Printed Name) (Insert Title) Date_

(Page 24 of 50)



(Page 25 of 50)

Insert Facility Name
MSGP Stormwater Pollution Prevention Plan
Document Reference Number
Revision X, Date

FIGURE B: MAP(S)

Label the figures as Figure B-1, Figure B-2, etc.

Insert maps in the following order:

- Facility specific site map(s),
- Receiving waters maps, and
- Threatened Endangered Species Map.

Insert Facility Name MSGP Stormwater Pollution Prevention Plan Document Reference Number Revision X, Date

ATTACHMENT 1: NOTICE OF INTENT, SUPPORTING DOCUMENTATION, AND UPDATES

Insert the appropriate attachment. Note: There may be several "Change NOIs" submitted to EPA within a permit term. Contact the MSGP Program Lead to ensure all are included in this attachment.

ANNR

(Page 27 of 50)

ATTACHMEN		PPP AMENDMENTS	Revision <mark>X. [</mark>
and the second star			
nsert text do	cumenting all c	hanges or updates made to the SV	NPPP. Text may be in table format as
hown below.	9		
Date	Plan Section	Reason for Amendment	Amendment

EANNAL

(Page 28 of 50)

Insert Facility Name MSGP Stormwater Pollution Prevention Plan Document Reference Number Revision X, Date

ATTACHMENT 3: CERTIFICATION

CERTIFICATION OF NO UNAUTHORIZED STORMWATER DISCHARGES

Insert the appropriate attachment.

ANNR

(Page 29 of 50)

Insert Facility Name MSGP Stormwater Pollution Prevention Plan Document Reference Number Revision X, Date

ATTACHMENT 4:

DULY AUTHORIZED SIGNATORY MEMORANDUM

Insert the appropriate attachment.

ANNAL

Insert Facility Name MSGP Stormwater Pollution Prevention Plan Document Reference Number Revision X, Date

ATTACHMENT 5:

DISCHARGE MONITORING REPORTS

Insert the discharge monitoring reports.

ANNAL

insert Facility Name MSGP Stormwater Poliution Prevention Plan Document Reference Number Revision X, Date

ATTACHMENT 6:

ANNUAL REPORTS

Insert the annual reports. The MSGP Program Lead provides these.

-ANNR -

Insert Facility Name MSGP Stormwater Pollution Prevention Plan Document Reference Number Revision X, Date

ATTACHMENT 7:

ROUTINE FACILITY INSPECTIONS

Insert completed Routine Facility Inspection forms.

214 2

Insert Facility Name MSGP Stormwater Pollution Prevention Plan Document Reference Number Revision X, Date

ATTACHMENT 8:

QUARTERLY VISUAL ASSESSMENTS

Insert completed Quarterly Visual Assessment forms. EPC-CP provides these by memorandum as they are produced.



(Page 34 of 50)

Insert Facility Name MSGP Stormwater Pollution Prevention Plan Document Reference Number Revision X, Date

ATTACHMENT 9: CORRECTIVE ACTION DOCUMENTATION AND CERTIFICATION

Contact the EPC-CP MSGP Program Lead for an excel spreadsheet of all corrective actions and a certification statement for signature.

(Page 35 of 50)

	Insert Facility Name
MSGP Stor	mwater Pollution Prevention Plan
	Document Reference Number
	Revision X, Date

ATTACHMENT 10:


SCHEDULED MAINTENANCE LOG

SCHEDULED MAINTENANCE LOG

Date	Control Measure or Equipment Description (include location where appropriate)	Action Taken/Comments	Action Taken By (printed name & Z no.)
		11	
		alle	
		2	
	4	Y	
	61		

Page 1 of X

(Page 36 of 50)



ATTACHMENT 11: TRAINING DOCUMENTATION

Insert the appropriate documentation.

Insert Facility Name MSGP Stormwater Pollution Prevention Plan Document Reference Number Revision X, Date

ATTACHMENT 12: MSGP (OR ACTIVE URL)

Either insert a copy of the most current Permit, or insert the URL address (see example below).

A copy of the 2015 MSGP is kept on file with the SWPPP in hard copy.

The active URL for the permit is https://www.epa.gov/npdes/final-2015-msgp-documents

EXAMPLE

(Page 38 of 50)



Insert the most current revision of the management plan for LANL.

Attachment 1: EPC-CP-QP-2110 R0 Form 1, *MSGP SWPPP Template Example* (cont.)

(Page 39 of 50)



ATTACHMENT 14: MSGP IPAC TRUST RESOURCES REPORT

Contact the EPC-CP MSGP Program Lead for this information formatted for insertion.

NOTE: The Permit requires this information. However, LANL EPC-ES has completed consultation with U.S. Fish and Wildlife Service. Letters of Consultation are contained in the NOI (see Attachment

1). Refer to Attachment 13 for the species habitat management plan.

Ň it

Attachment 1: EPC-CP-QP-2110 R0 Form 1, MSGP SWPPP Template Example (cont.) (Page 40 of 50)

Insert Facility Name MSGP Stormwater Pollution Prevention Plan Document Reference Number Revision X, Date

ATTACHMENT 15: EPC-CP-PIP-2101, NPDES MULTI-SECTOR GENERAL PERMIT

Insert the appropriate plan into this SWPPP. Ensure the most current revision of this plan is inserted.

Y 1

MSGP Stormwater Pollution	No: EPC-CP-QP-2110	Page 52 of 72
Prevention Plan Preparation and		
Maintenance	Revision: 0	Effective Date: 01/07/2020

Attachment 1: EPC-CP-QP-2110 R0 Form 1, MSGP SWPPP Template Example (cont.) (Page 41 of 50)

Insert Facility Name MSGP Stormwater Pollution Prevention Plan Document Reference Number Revision %, Date ATTACHMENT 16: EPC-CP-QP-<mark>023</mark>, MSGP ROUTINE FACILITY INSPECTIONS Insert the appropriate procedure or parts of the procedure that pertain to this SWPPP. Ensure the most

current revision of this procedure is inserted.

Attachment 1: EPC-CP-QP-2110 R0 Form 1, MSGP SWPPP Template Example (cont.) (Page 42 of 50)

Insert Facility Name MSGP Stormwater Pollution Prevention Plan Document Reference Number Revision X, Date ATTACHMENT 17: EPC-CP-QP-022, *MSGP CORRECTIVE ACTIONS* Insert the appropriate procedure or parts of the procedure that pertain to this SWPPP. Ensure the most

current revision of this procedure is inserted.

ANNR

42

Attachment 1: EPC-CP-QP-2110 R0 Form 1, MSGP SWPPP Template Example (cont.) (Page 43 of 50)

Insert Facility Name MSGP Stormwater Pollution Prevention Plan Document Reference Number Revision X, Dete ATTACHMENT 18: EPC-CP-QP-064, MSGP STORMWATER VISUAL ASSESSMENTS Insert the appropriate procedure or parts of the procedure that pertain to this SWPPP. Ensure the most current revision of this procedure is inserted.

CANNEL

Attachment 1: EPC-CP-QP-2110 R0 Form 1, MSGP SWPPP Template Example (cont.)

(Page 44 of 50)

Insert Facility Name MSGP Stormwater Pollution Prevention Plan Document Reference Number Revision X, Date

ATTACHMENT 19: EPC-CP-QP-Q47, INSPECTING STORMWATER RUNOFF SAMPLERS AND RETRIEVING SAMPLES FOR THE MSGP

Insert the appropriate procedure or parts of the procedure that pertain to this SWPPP. Ensure the most current revision of this procedure is inserted.

44

Attachment 1: EPC-CP-QP-2110 R0 Form 1, MSGP SWPPP Template Example (cont.) (Page 45 of 50)

Insert Facility Name MSGP Stormwater Pollution Prevention Plan Document Reference Number Revision %, Date

ATTACHMENT 20: EPC-CP-QP-2106, PROCESSING MSGP STORMWATER SAMPLES

Insert the appropriate procedure or parts of the procedure that pertain to this SWPPP. Ensure the most current revision of this procedure is inserted.

CHANNEL -

Attachment 1: EPC-CP-QP-2110 R0 Form 1, MSGP SWPPP Template Example (cont.) (Page 46 of 50)

Insert Facility Name MSGP Stormwater Pollution Prevention Plan Document Reference Number Revision X, Date

ATTACHMENT 21: EPC-DO-QP-101, ENVIRONMENTAL REPORTING REQUIREMENTS FOR RELEASES OR EVENTS

Insert the appropriate procedure or parts of the procedure that pertain to this SWPPP. Ensure the most current revision of this procedure is inserted.

46

Attachment 1: EPC-CP-QP-2110 R0 Form 1, MSGP SWPPP Template Example (cont.) (Page 47 of 50)

Insert Facility Name MSGP Stormwater Pollution Prevention Plan Document Reference Number Revision X, Date

ATTACHMENT 22: EPC-CP

EPC-CP-QP-007, SPILL INVESTIGATIONS

Insert the appropriate procedure or parts of the procedure that pertain to this SWPPP. Ensure the most current revision of this procedure is inserted.

EXAMPLE.

Attachment 1: EPC-CP-QP-2110 R0 Form 1, MSGP SWPPP Template Example (cont.) (Page 48 of 50)

Insert Facility Name MSGP Stormwater Pollution Prevention Plan Document Reference Number Revision X, Date

ATTACHMENT 23: EPC-CP-QP-2110, MSGP STORMWATER POLLUTION PREVENTION PLAN PREPARATION AND MAINTENANCE

Insert the appropriate procedure or parts of the procedure that pertain to this SWPPP. Ensure the most current revision of this procedure is inserted.

48

Attachment 1: EPC-CP-QP-2110 R0 Form 1, MSGP SWPPP Template Example (cont.) (Page 49 of 50)

<text><text><text><text>

49

Insert Facility Name

Attachment 1: EPC-CP-QP-2110 R0 Form 1, MSGP SWPPP Template Example (cont.) (Page 50 of 50)

<text><text><text><text><text>

50

SWPPP Title

REQUIREMENT	YES/NO	NOTES
Stormwater Pollution Prevention Team		
Is the SWPPP being developed or updated by a qualified person?		
Does the SWPPP list Stormwater Pollution Prevention Team members (by name or title) and each		
individual's responsibilities?		
Is a copy of the SWPPP immediately available at the site and on-line?		14
Contents of the SWPPP		
If the SWPPP refers to procedures or other documents, are copies of the relevant portions of these procedures or documents present in the SWPPP?		1
Site Description	6	
Does the SWPPP include the following information?	-	
Identify a description of the nature of the industrial activities at the site		
Provide a general location map (e.g., U.S. Geological Survey (USGS) quadrangle map) with enough detail to identify the location of the site and all receiving waters for industrial stormwater discharges.		
Site map showing the following:		
Boundaries of the property and size of the property in acres		
Location and extent of significant structures and impervious surfaces		
Direction(s) of stormwater flow (using arrows)		
Locations of all stormwater control measures		
• Locations of all receiving waters, including wetlands, in the immediate vicinity of the site. Indicate which water bodies are listed as impaired and which are identified as Tier 2, Tier 2.5, or Tier 3 waters (for LANL, none)		
Locations of all stormwater conveyances including ditches, pipes, and swales		
 Locations of potential pollutant sources associated with each industrial activity (see Part 5.2.3.2) that could be exposed to rainfall or snowmelt and could be discharged from the site. 		
 Locations where significant spills or leaks have occurred (see Part 5.2.3.3) 		
Location(s) of all stormwater monitoring points		
• Location of each stormwater inlet and outfall, with a unique identification code for each outfall (i.e., 001, 002, 003, etc.), indicating if you are treating one or more outfalls as "substantially identical" (see Parts 3.2.3, 5.2.5.3, and 6.1.1)		
• If applicable, location of the MS4 and where your stormwater discharges to it. NOTE: Although LANL does not currently have an MS4, EPA has published a draft permit.		
Areas of designated critical habitat for endangered or threatened species		
Locations of the following activities where such activities are exposed to precipitation:		

Attachment 2: MSGP SWPPP Review Guidance Checklist Example

(Page 1 of 11)

Page 1 of 11

REQUIREMENT	YES/NO	NOTES
- Fueling station(s)		
 Vehicle and equipment maintenance and/or cleaning area 		
- Loading/unloading areas		
 Locations used for the treatment, storage, or disposal of wastes 		
- Liquid storage tanks		
- Processing and storage areas		
- Immediate access roads used by carriers of raw materials, manufactured products, waste		
material, or by-products used or created by the site		
- Transfer areas for substances in bulk		
- Machinery		
- Locations and sources of run-on to the site from adjacent property that contains significant	1.	
quantities of pollutants	-	
Potential Pollutant Sources		
Are areas described in the SWPPP where industrial material or activities are exposed to stormwater or		
from which allowable non-stormwater discharges originate?		
NOTE 1: Industrial material or activities include material handling equipment or activities; industrial		
machinery; raw material; industrial production and processes; and intermediate products; by-products;		
final products, and waste products. Material handling activities include the storage, loading and		
unloading, transportation, disposal or conveyance of any raw material, intermediate product, final		
product or waste product.		
Are all pollutants or pollutant constituents (e.g., zinc, sulfuric acid, cleaning solvents, motor oil, diesel,		
gasoline, brake fluid, etc.) associated with each activity identified?		
NOTE 2: The list must include all pollutants/materials that have been handled, treated, stored, or		
disposed and that have been exposed to stormwater in the three years prior to the date the SWPPP is		
prepared or amended.		
Are areas where potential spills and leaks could occur that could contribute pollutants to stormwater		
discharges and the corresponding outfall(s) that would be affected by such spills and leaks identified in		
the SWPPP?		
Are all significant spills and leaks of oil or toxic or hazardous substances identified that actually		
occurred at exposed areas, or that drained to a stormwater conveyance, in the three years prior to the		
date the SWPPP was prepared or amended?		
Has an evaluation for the presence of unauthorized non-stormwater discharges (see Part 1.1.3) been		
done and does it include the following information?		
Date of the evaluation		
A description of the evaluation criteria used		
A list of the outfall or onsite drainages points that were directly observed during the evaluation		

Attachment 2: MSGP SWPPP Review Guidance Checklist Example (cont.)

(Page 2 of 11)

Effective Date: 01/07/2020 Page 63 of 72 No: EPC-CP-QP-2110 Revision: 0 MSGP Stormwater Pollution Prevention Plan Preparation and Maintenance

Page 2 of 11

REQUIREMENT	YES/NO	NOTES
• The action(s) taken, such as a list of control measures used to eliminate unauthorized discharge(s),		and the second sec
or documentation that a floor drain was sealed, re-routed to sanitary, or an NPDES permit		
application was submitted for an unauthorized cooling water discharge.		
Is there documentation of the location of any salt storage piles used for deicing or other commercial or		
industrial purposes?		
Is all stormwater discharge sampling data collected at the site during the precious permit term		
summarized in a narrative description? This may include data tables and figures.		
Control Measures to Meet Effluent Limits		
Does the SWPPP indicate whether the following control measure selection and design criteria were considered?	0	
 Preventing stormwater from coming into contact with polluting materials is generally more effective, and less costly, than trying to remove pollutants from stormwater 	/	
• Using control measures in combination which may be more effective than using control measures in isolation for minimizing pollutants in stormwater discharge		
 Assessing the type and quantity of pollutants, including their potential to impact receiving water quality, is critical to designing effective control measures that will achieve the limits in this permit 		
 Minimizing impervious areas at the facility and infiltrating runoff onsite (including bio-retention cells, green roofs, and impervious pavement, among other approaches) can reduce runoff and improve ground water recharge and stream base flows in local streams, although care must be taken to avoid ground water contamination 		
 Attenuating flow using open vegetated swales and natural depressions can reduce in-stream impacts of erosive flows 		
 Conserving and/or restoring riparian buffers will help protect streams from stormwater runoff and improve water quality 		
 Using treatment interceptors (e.g., swirl separators and sand filters) may be appropriate in some instances to minimize the discharge of pollutants. 		
Does the SWPPP indicate how the control measure addresses the potential pollutant sources?		
Are the selection and design considerations for control measures to meet the following non-numeric technology-based effluent limits (see Part 2.1.2) identified in the SWPPP?		
• Minimize Exposure: All manufacturing, processing and material storage areas (including loading and		
unloading, storage, disposal, cleaning, maintenance, and fueling operations) must have controls that		
minimize exposure to pollutant discharges by either locating these industrial materials and activities		
inside or protecting them with storm resistant coverings.		
- Use grading, berming or curbing to prevent runoff of contaminated flows and divert run-on away		
from these areas:		

Page 3 of 11

Attachment 2: MSGP SWPPP Review Guidance Checklist Example (cont.)

(Page 3 of 11)

MSGP Stormwater Pollution Prevention Plan Preparation and Maintenance

Effective Date: 01/07/2020

No: EPC-CP-QP-2110

REQUIREMENT	YES/NO	NOTES
- Locate materials, equipment, and activities so that potential leaks and spills are contained or able		
to be contained or diverted before discharge;		
- Clean up spills and leaks promptly using dry methods (e.g., absorbents) to prevent the discharge		
of pollutants;		
- Store leaky vehicles and equipment indoors or, if stored outdoors, use drip pans and absorbents;		
 Use spill overflow protection equipment; 		
 Perform all vehicle and/or equipment cleaning operations indoors, under cover, or in bermed areas that prevent runoff and run-on and also that capture any overspray; and 		
 Drain fluids from equipment and vehicles that will be decommissioned, and, for any equipment and vehicles that will remain unused for extended periods of time, inspect at least monthly for leaks. 	1	
• Good housekeeping (all areas where potential pollutants are exposed to stormwater must be kept clean).	1	
 Sweep or vacuum at regular intervals or wash down the area and collect and/or treat and properly dispose of the wash down water. 		
- Store materials in appropriate containers.		
- Keep all dumpster lids closed when not in use. For dumpsters and roll off boxes that do not have		
lids and could leak, ensure that discharges have a control (e.g., secondary containment). Part 1.1.3 of the permit does not authorize dry weather discharges from dumpsters or roll off boxes.*		
* You may include extra information, or you may just "cut-and-paste" the effluent limits verbatim into the SWPPP w/out providing additional documentation.		
 Minimize the potential for waste, garbage, and floatable debris to be discharged by keeping exposed areas free of such materials. 		
 Maintenance (All industrial equipment, systems and control measures must be maintained in effective operating condition in order to minimize pollutant discharges). 		
Perform inspections and preventive maintenance of stormwater drainage, source controls, treatment systems, and plant equipment and systems that could fail and result in contamination of stormwater.		
 Diligently maintain non-structural control measures (e.g., keep spill response supplies available, and personnel appropriately trained). 		
 Inspect and maintain baghouses at least quarterly to prevent the escape of dust from the system and immediately removing any accumulated dust at the base of the exterior baghouse.* 		
- Cleaning catch basins when the depth of debris reached two thirds (2/3) of the sump depth and keeping the debris surface at least six inches below the lowest outlet pipe.*		
Does the SWPPP contain language indicating immediate action must be taken to minimize pollutant		
discharges if control measures need routine maintenance?		
Is there language in the SWPPP indicating in instances where control measures need repair or		
replacement that the facility (or associated representatives thereof) must immediately take all		

Attachment 2: MSGP SWPPP Review Guidance Checklist Example (cont.)

(Page 4 of 11)

MSGP Stormwater Pollution Prevention Plan Preparation and Maintenance

Page 65 of 72 Effective Date: 01/07/2020

Revision: 0

No: EPC-CP-QP-2110

REQUIREMENT	YES/NO	NOTES
reasonable steps (see Part 4.3.1 for definition) to prevent or minimize the discharge of pollutants until		
the final repair or replacement is implemented, including cleaning up any contaminated surfaces so		
that the material will not be discharged during subsequent storm events. Final repairs/replacement of		
stormwater controls should be completed as soon as feasible but must be no later than the		
timeframes established in Part 4.3 for corrective actions, i.e., within 14 days or, if that is infeasible,		
within 45 days.	-	
Is there language in the SWPPP indicating corrective action must be taken (in accordance with Part 4.0)		
if a control measure was never installed, was installed incorrectly or not in accordance with Parts 2 🌙		
and/or 8, or isn't being properly operated or maintained?		
 Spill Prevention and Response - The potential for leaks, spills, and other release must be minimized by the development of plans for effective response to such spills if or when they occur in order to minimize pollutant discharges. 		
 Plainly label containers (e.g., "Used Oil," "Spent Solvents," "Fertilizers and Pesticides") that could be susceptible to spillage or leakage to encourage proper handling and facilitate rapid response if spills or leaks occur:* 		
- Implement procedures for material storage and handling including use of secondary containment and barriers between material storage and traffic areas.		
 Develop training on the procedures for expeditiously stopping, containing, and cleaning up leaks, spills, and other releases as soon as possible. 		
 Keep spill kits on-site, located near areas where spills may occur or where a rapid response can be made 		
- Notify appropriate facility personnel when a leak, spill, or other release occurs. Where a leak, spill		
or other release containing a hazardous substance or oil in an amount equal to or in excess of a		
reportable quantity established under either 40 CFR Part 110, 40 CFR Part 117, or 40 CFR part 302,		
occurs during a 24-hour period, you must notify the National Response Center (NRC) at (800) 424-		
8802 in accordance with the above referenced requirements as soon as you have knowledge of		
the discharge.		
- In the event of a spill, does the SWPPP indicate where the contact information is so that it is		
readily accessible and available?		
Erosion and Sediment Controls		
- Does the SWPPP identify how exposed soils will be stabilized to minimize pollutant discharges?		
- Does the SWPPP identify flow velocity dissipation devices placed at discharge locations to		
minimize channel and streambank erosion and scour in the immediate vicinity of discharge points?		
 Does the SWPPP identify structural and non-structural control measure to minimize the discharge of sediment? 		

Attachment 2: MSGP SWPPP Review Guidance Checklist Example (cont.) (Page 5 of 11)

Page 5 of 11

the of other include offecting	MSGP SWPPP	Review	Guidance	Checklist
--------------------------------	-------------------	--------	----------	-----------

REQUIREMENT	YES/NO	NOTES
- If polymers and/or other chemical treatments are used for dust control or stabilization, does the		
SWPPP must identify the polymers and/or chemicals used and the purpose?		
• Management of Runoff - Does the SWPPP identify how stormwater runoff is diverted, infiltrated,		
reused, contained, or otherwise reduced to minimize pollutants in the discharge?		
• Salt Storage Piles or Piles Containing Salt - Does the SWPPP identify how salt piles are enclosed or covered?		
 Are controls in place to minimize exposure to stormwater resulting from adding to or removing materials from the salt pile? 		
 Non-Stormwater Discharges - Does the SWPPP indicate that personnel will evaluate the site for non-stormwater discharges not explicitly authorized in Part 1.1.3 or covered by another NPDES permit and eliminate the discharge?) 	-	
 Dust Generation and Vehicle Tracking of Industrial Materials - Does the SWPPP indicate dust generation and off-site tracking of raw, final, or waste materials must be minimized in order to minimize pollutant discharges?) 		
Control Measures to Meet Numeric Effluent Limitations Guidelines-Based Limits (see Part 2.1.3 and Pa	art 8)	
Are effluent limitations identified for the Sector D facility (Asphalt Paving) (see Part 8.D.4)?		
Are effluent limitations identified for the Sector A facility (Timber Products) (see Part 8.A.7)?		
Control Measures to Meet Water Quality Based Effluent Limits (see Part 2.2 and Part 9.6.2)		
Are the benchmark values (i.e., the Lowest New Mexico Water Quality Standard) listed in MSGP Section 9.6.2.1 identified in the SWPPP?		
Schedules and Procedures - Control Measures		
Does the SWPPP contain a schedule or convention used for determining when pickup or disposal of waste materials occurs?		
Are preventative maintenance procedures (including regular inspections, testing, maintenance and repair) for all control measures included in the SWPPP to avoid situations that may result in leaks, spills, and other releases?		
Are backup practices in place should a runoff event occur while a control measure is off line?		
Is there a schedule or frequency for maintaining all control measures?		
Are procedures included in the SWPPP for preventing and responding to spills and leaks, including notification procedures?		
Are control measures for material handling and storage identified?		
Are clean-up equipment, procedures and spill logs (i.e., reportable and non-reportable spill reports and the MSGP Corrective Action Reporting database) identified?		
Schedules and Procedures - Employee Training		

Attachment 2: MSGP SWPPP Review Guidance Checklist Example (cont.)

(Page 6 of 11)

MSGP Stormwater Pollution Prevention Plan Preparation and Maintenance

Effective Date: 01/07/2020 Page 67 of 72

No: EPC-CP-QP-2110

Revision: 0

Page 6 of 11

REQUIREMENT	YES/NO	NOTES
Personnel who are responsible for the design, installation, maintenance and/or repair of controls		
(including pollution prevention measures)		
 Personnel responsible for the storage and handling of chemicals and materials that could become 		
contaminants in stormwater discharges		
 Personnel who are responsible for conducting and documenting monitoring and inspections 		
 Personnel who are responsible for taking and documenting corrective actions. 		
Are the following identified as elements of required training?		
An overview of what is in the SWPPP		
Spill response procedures, good housekeeping, maintenance requirements, and material management practices		
• The location of all controls on the site required by this permit and how they are to be maintained	/	
The proper procedures to follow with respect to the permit's pollution prevention requirements		
When and how to conduct inspections, record applicable findings, and take corrective actions		
Are the following elements of the training plan documented in the SWPPP?		
Content of the training		
Frequency/schedule of training		
Are records of completed training kept in the SWPPP?		
Schedules and Procedures - Inspections and Assessments		
Is the procedure identified for conducting routine facility inspections?		
Is the procedure identified for conducting visual assessments?		
For each type of inspection performed (i.e., routine inspection and visual assessments) does the		
SWPPP identify the person (s) or positions of person(s) responsible for the inspection?		
Does the SWPPP contain an alternative schedule for conducting visual assessments in climates with		
irregular stormwater runoff discharges (see Part 3.2.3)?		
Are specific items to be covered by the inspection, including schedules for specific outfalls identified in the SWPPP?		
Is the facility claiming an exception as an inactive and unstaffed site? If yes, the facility must include		
information in the SWPPP that supports this claim as required by Parts 3.1.1, 3.2.3, 6.2.1.3 and 6.2.4.2.		
That is, the SWPPP must contain a signed certification indicating that there are no industrial materials		
or activities exposed to precipitation at the site and the NOI must be modified and re-certified.		-
Schedules and Procedures - Monitoring	-	
Does the SWPPP contain documentation of procedures used to conduct benchmark, effluent		
limitations guidelines and impaired waters monitoring?	-	
Are locations where samples are collected, including any determination that two or more outfalls are substantially identical, in the SWPPPP?		
Are parameters for sampling and the frequency of sampling for each parameter listed?		

Effective Date: 01/07/2020

Attachment 2: MSGP SWPPP Review Guidance Checklist Example (cont.) (Page 7 of 11)

Revision: 0

MSGP Stormwater Pollution Prevention Plan Preparation and Maintenance

Page 7 of 11

Page 68 of 72 No: EPC-CP-QP-2110

REQUIREMENT	YES/NO.	NOTES
Does the SWPPP contain schedules for monitoring at the facility, including a schedule for alternate		
monitoring periods for climates with irregular stormwater runoff (see Part 6.1.6)?		
Are numeric control values (benchmark, effluent limitations guidelines, water quality standards)		
applicable to discharges from each outfall identified?		
Does the SWPPP list procedures for gathering storm event data (see Part 6.1)?		
Schedules and Procedures - Substantially Identical Outfalls (SIOs)		Ĵ.
Does the SWPPP contain the following relative to SIOs?		
Location of each of the substantially identical outfalls		
• Description of the general industrial activities conducted in the drainage area of each outfall	4	
Description of the control measures implemented in the drainage area of each outfall	4	
• Description of the exposed material located in the drainage area of each outfall that are likely to be		
significant contributors of pollutants to stormwater discharges	V.	
• An estimate of the runoff coefficient of the drainage areas (low = under 40%, medium = 40% to 65%, high = above 65%		
Justification as to why the outfalls are expected to discharge substantially identical effluents		
Do Substantially Identical Outfalls identified on the SWPPP map match those identified in MDMRs?		
Is there language indicating quarterly visual assessments of substantially identical outfalls will be performed on a rotating basis throughout the permit term?		
Is there language indicating quarterly visual assessment of the discharge at one SIO will also apply to the other SIOs?		
Corrective Action Documentation - If an event triggering corrective action is associated with an SIO, did the review of the need for action encompass all related substantially identical outfalls?		
Documentation	-	
Does the SWPPP contain the following up-to-date and complete inspection, monitoring, and certification records?		
• Copy of NOI submitted to EPA along with any correspondence exchanged between the facility and EPA specific to coverage under this permit.		
 Copy of the acknowledgement you receive from the EPA assigning your NPDES ID. 		
• Copy of the MSGP Permit (an electronic copy easily available to SWPPP personnel is also acceptable).		
• Documentation of maintenance and repairs of control measures, including the date(s) of regular		
maintenance, date(s) of discovery of areas in need of repair/replacement, and for repairs, date(s) that the control measure(s) returned to full function, and the justification for any extended maintenance/repair schedules (See Part 2.1.2.3).		
• All inspection reports, including the Routine Facility Inspection Reports (see Part 3.1.2) and Quarterly Visual Assessment Reports (see Part 3.2.2).		

Attachment 2: MSGP SWPPP Review Guidance Checklist Example (cont.)

(Page 8 of 11)

MSGP Stormwater Pollution Prevention Plan Preparation and Maintenance

Page 69 of 72

Effective Date: 01/07/2020

Revision: 0

No: EPC-CP-QP-2110

REQUIREMENT	YES/NO	NOTES
• Description of any deviations from the schedule for visual assessments and/or monitoring, and the		
reason for the deviations (e.g., adverse weather or it was impracticable to collect samples within the		
first 30 minutes of a measurable storm event) (see Parts 3.2.3 and 6.1.5)		
 Corrective action documentation (see Part 4.4) 		
 Documentation of any benchmark exceedances and the type of response to the exceedance 		
employed including the following:		
- The corrective action taken;		
- A finding that the exceedance was due to natural background pollutant levels;		
 A determination from EPA that benchmark monitoring can be discontinued because the exceedance was due to run-on; OR 	1	
 A finding that no further pollutant reductions were technologically available and economically practicable and achievable in light of best industry practice consistent with Part 6.2.1.2 		
Documentation to support any determination that pollutants of concern are not expected to be		
present above natural background levels if you discharge directly to impaired waters and that such		
pollutants were not detected in your discharge or were solely attributable to natural background		
sources. (see Part 6.2.4.1)		
• Documentation supporting that stormwater discharges, allowable non-stormwater discharges, and		
stormwater discharge-related activities are not likely to adversely affect any species that are		
federally listed as endangered or threatened ("listed") and are not likely to adversely affect habitat		
that is designated as "critical habitat" under the Endangered Species Act (see Part 1.1.4.5).		
 Documentation supporting the determination that stormwater discharges, allowable non- 		
stormwater discharges, and stormwater discharge-related activities meet one of the eligibility		
criteria for historic property preservation (Criterion A, B, C or D) (see Part 1.1.4.6).		
All Discharge Monitoring Reports and Annual Reports		
 Support for claim that facility has changed its status from active to inactive and is unstaffed with 		
respect to the requirements to conduct routine facility inspections, quarterly visual assessments,		
benchmark monitoring, and/or impaired waters monitoring.		
Is the SWPPP signed and dated by a duly authorized representative (per Part B.11)?		
Is the Annual Report signed by a duly authorized representative (per Part B.11)?		
SWPPP Modifications		
Where a corrective action triggers a change in any of the control measures or procedures, has the		
SWPPP been updated within 14 calendar days of completing the corrective action (see Part 4.4)?		
Are SWPPP modifications signed and dated by a duly authorized representative?		
Has the SWPPP been reviewed and does documentation exist as to the modifications made or why		

Attachment 2: MSGP SWPPP Review Guidance Checklist Example (cont.)

(Page 9 of 11)

MSGP Stormwater Pollution Prevention Plan Preparation and Maintenance

 110
 Page 70 of 72

 Effective Date:
 01/07/2020

Revision: 0

REQUIREMENT	YES/NO	NOTES
• An unauthorized release or discharge (e.g., spill leak, or discharge of non-stormwater not authorized		
by this or another NPDES permit to a water of the U.S.) occurs at your facility.		
• A discharge violates a numeric effluent limit listed in Table 2-1 and in the sector specific		
requirements.		
• The control measures are not stringent enough for the discharge to meet applicable water quality		
standards or the non-numeric effluent limits in this permit.		
• A required control measure was never installed, was installed incorrectly, or not in accordance with		
Parts 2 and/or 8, or is not being properly operated or maintained.		
Whenever a visual assessment shows evidence of stormwater pollution (e.g., color, odor, floating	15	
solids, settled solids, suspended solids, foam).		
Construction or a change in design, operation, or maintenance at your facility that significantly		
changes the nature of pollutants discharged in stormwater from the facility, or significantly	have	
increases the quantity of pollutants discharged.		
• The average of four quarterly sampling results exceeds an applicable benchmark (see Part 6.2.1.2). If		
less than four benchmark samples have been taken, but the results are such that an exceedance of		
the four quarter average is mathematically certain (i.e., the sum of quarterly sample results to date		
is more than four times the benchmark level) this is considered a benchmark exceedance.		-
Public Accessibility of SWPPP		
Is your SWPPP uploaded to the URL provided in the NOI?		
Are subsequent SWPPP modifications (updates), records and all other reporting elements required for		
the previous year updated no later than 45 days after conducting the final routine facility inspection		
for the year?		
If you did not upload your SWPPPs to a URL, was the following information provided in the NOI and		
documented in the SWPPP?		
Onsite industrial activities exposed to stormwater, including potential spill and leak areas (see Parts		
5.,2.3.1, 5.2.3.3 and 5.2.3.5);		
Pollutants or pollutant constituents associated with each industrial activity exposed to stormwater		
that could be discharged in stormwater and/or any authorized non-stormwater discharges listed in		
Part 1.1.3 (see Part 5.2.3.2)		
• Stormwater control measures employed to comply with the non-numeric technology-based effluent		
limits required in Part 2.1.2 and Part 8, and any other measures taken to comply with the		
requirements in Part 2.2, Water Quality Based Effluent Limitations. If polymers and/or other		
chemical treatments are used as controls, these must be identified and the purpose explained.		
• The schedule for good housekeeping, maintenance, and schedule for all inspections required in Part		
3.		

Effective Date: 01/07/2020

Page 71 of 72

Attachment 2: MSGP SWPPP Review Guidance Checklist Example (cont.)

(Page 10 of 11)

No: EPC-CP-QP-2110 Revision: 0 MSGP Stormwater Pollution Prevention Plan Preparation and Maintenance

Page **10** of **11**

REQUIREMENT	YES/NO	NOTES
Are modifications to the SWPPP information required in the four bullets above submitted on a "Change		
NOI" form no later than 45 days after conducting the final routine facility inspection for the year?		
Corrective Actions		
Are corrective actions documented within 24 hours of becoming aware of such condition?		5 C
Is the condition triggering the need for the corrective action identified?		
Is the date the corrective action was identified captured?		
Was immediate action taken to minimize or prevent the discharge of pollutants?		
In the case of leaks and spills, were response actions, date/time of clean up, notification, etc.		
documented?		

Attachment 2: MSGP SWPPP Review Guidance Checklist Example (cont.)

(Page 11 of 11)

Page 11 of 11

Effective Date: 01/07/2020 Revision: 0 MSGP Stormwater Pollution Prevention Plan Preparation and

Maintenance

Page 72 of 72 No: EPC-CP-QP-2110

ATTACHMENT 24: WFO-IWD-00016, SPILL RESPONSE AND CLEAN UP IN WEAPONS FACILITIES OPERATIONS (WFO) AREAS

WEAPONS FACILITIES	Document Number:	WFO-IWD-0016
OPERATIONS	Revision:	G

Spill Response and Clean Up in Weapons Facilities Operations (WFO) Areas

Effective Date: 10/28/2020		Ex	Expiration Date(Maximum 3 years): 10/28/2023		
Hazard Category	High/Complex	Moderate			
Standing IWD?	Standing IWD? Yes (one Pre-Job Brief. If High/Compler required for each evolution)			D No	
R&D IWDs Only Annual REVIEW DUE DATE		DA	FE ANNUAL REVI	EW CONDUCTED:	

Reviewed and Approved for Use By:

	Printed Name	Z#	Org	Signature	Date
Person in Charge (PIC)	Kelkenny Bileen	178009	EPC-CP	Kelkenny Bileen Breisen und Bileen Breisen Bileen B	
Peer Reviewer	Bruce Dahlquist	234968	OSH-DS	Bruce Danguist	9/28/2020
Responsible Line Manager	Taunia S. Valkenburg	145666	FPC-CP	apen Still	U 10/26/200
Operations Manager	John Branch	232120	WFO-HE	JOHN BRANCH (Affiliate) (Affiliat	ly signed by JOHN BRANC te) 020 10 27 12:03:20 -06:00

The Facility Operations Director (FOD) approval indicates that the work is appropriate to be conducted in the facility, the work is bounded by the facility authorization basis, that facility safety basis, aggregate hazards, and co-located hazards will be managed, and that the facility entry, training and coordination requirements are fully captured within this document. Unless otherwise indicated, approval indicates work release (i.e., no signature required on Part 3).

	Printed Name	Z#	Org	Signature	Date
Facility Operations Director (FOD)	Derek Clark	332752	WFO-DO	PETER RICE (Affiliate)	Digitally signed by PETER RICE (Affiliate) Date: 2020.10.28 09:14:19 -06'00'
For Document Control Team Reference USQ (applicable to WETF)	re:	USI (applicab	le to DARHT)	N/A	

Users are responsible for verifying that they are working to the most current revision of a document

Page 1 of 53

Spill Response and Clean	Up in Weapons Facilities
Operations (WFO) Areas	

Document No.: WFO-IWD-0016 Revision: G

Effective Date: 10/28/2020

Revision	Effective Date	Action	Description	
A (0)	11/19/2008	New Procedure	Initial release.	
А	11/20/2014	EXT1	60-day extension to allow time to review and revise.	
В	02/25/2015	Minor Revision	Minor revision. Added TA-49 to list of applicable buildings, updated references. Renumbered document from IWD-WFO- 99-999-999-0016 to WFO-IWD-0016 to reflect current WFO numbering convention. This document supersedes IWD- WFO-99-999-999-0016, Rev A; this is not a new document but a revision to an existing document; revision starts at B as document type did not change.	
С	12/21/2016	Minor Revision	Minor revision:	
			 Updated approvals on cover page Updated SMEs and Alternate PICs on Page 6 Added Course # 22956 for HAZCOM Training on Page 7 through 9 Updated reference documents on Page 13 Updated POC from Brian Watkins to Thomas Sisneros on Pages 13 and 14. Replaced 2102 forms with 2101 forms. 	
С	11/30/2017	EXT1	60-day extension to allow time to review and revise.	
D	02/28/2018	Major Revision	Major revision. Updated cover page format. Updated approvals on cover page. Added Note in Section 1.3 to clar that EPC-CP must be notified of all spills (inside or outside) Replaced 2101 and 2103 forms. Added 2102 form.	
D	05/22/2018	RAC	RAC. Added new page 47 with additional worker signature (Paul Gonzales, Z# 169004) to Form 2103, Part 3 Validation and Work Release.	
D	10/01/2018	EXT1	30-day extension to review and revise.	
E	10/15/2018	Minor Revision	Minor revision. Inserted 2101s for WETF, DARHT and 2102s for WFO BOP with updated expiration dates for CY 2019. Updated acronym EO to read SEO throughout. Updated references to organization ENV-CP to EPC-CP throughout.	
Е	09/27/2019	EXT1	30-day extension until 10/30/2019 requested to allow time for final signatures and USQ/USI reviews for Revision F.	
F	10/02/2019	Major Revision	Updated acronym SEO to read EOSC and updated phone number from 667-6211 to 667-2400 in Sections 1.1, 1.2, 1.3 and 1.6. Attachment A: Removed references to WFO- PLAN-035 and replaced with WFO-BEP-378. Removed references to WFO-PRO-FI-1084 and WFO-PRO-FI-1086 an replaced with WFO-AP-263.	
F	09/28/2020	EXT1	Extension to allow time to review and revise.	
G	10/28/2020	Major Revision	Updated approvals on cover page. Updated Application of Micro Blaze work steps. Inserted Opening and Securing of Waste Containers work step. Inserted 2101s for WETF, DARHT and 2102s for WFO BOP with updated expiration dates for CY 2021.	

Spill Response and Clean Up in Weapons Facilities
Operations (WFO) Areas

Document No.:	WFO-IWD-0016
Revision:	G

Effective Date: 10/28/2020

Table of Contents

1.0	Introduction	4
1.1	Purpose	4
1.2	Scope	4
1.3	Applicability	4
1.4	Definitions and Acronyms	5
1.5	Hazard Analysis	5
1.6	Site Emergency Contacts	5
2.0	Procedural Steps	5
3.0	Forms	5
4.0	Attachments	5
Attachme	ent A Integrated Work Document (IWD) Part 1, Activity Specific Information	6
Attachme	ent B Integrated Work Document (IWD) Part 2 (Non Tenant)1	4
Attachme	ent C Integrated Work Document (IWD) Part 2 (Tenant)4	4
Attachme	ent D Integrated Work Document (IWD) Part 3 Validation and Work Release5	1
Attachme	ent E Integrated Work Document (IWD) Part 4, (Feedback/Post Job Reviews)5	3

Document No.: WFO-IWD-0016 Revision: G

Effective Date: 10/28/2020

1.0 Introduction

1.1 Purpose

This procedure describes clean up of spills following notification to the Duty Officer. The objective of this task is spill response and the cleanup of spills deemed a non-emergency by EOSC or EPC-CP.

1.2 Scope

This IWD is to be implemented for the clean up of spills following notification to the Duty Officer. The objective of this task is spill response and the cleanup of spills deemed a non-emergency by EOSC or EPC-CP. These spills could occur at or within any WFO-FOD facility including TAs,6, 8, -9, 11, 14, 15, 16, 22, 36, 37, 39, 40, and 49. Depending on the location of the spill, additional contaminants such as heavy metals, beryllium, trace amounts of or nonhazardous amounts of HE or DU could also exist in the soil and therefore the waste stream. WFO's waste management coordinators will make waste determinations and manage the wastes per P409, *Waste Management*.

Note: In the event that an item is encountered within an HE area that cannot be immediately identified as normal firing site debris work shall be paused and an explosives SME will be contacted to identify the item in question.

Note: In active HE areas a person with site specific knowledge will be consulted to identify any hazards prior to the start of work"

1.3 Applicability

This document applies to WFO workers at TAs,6, 8, 9, 11, 14, 15, 16, 22, 36, 37, 39, 40, and 49.who are performing spill clean up activities as described in 1.2 Scope. There are two types of spills:

- simple spills (incidental release), which can be cleaned up by knowledgeable chemical workers (workers with knowledge of the chemical, appropriate training, materials and PPE needed to clean the spill). A simple spill shall be defined as one that:
 - 1. Does not spread rapidly
 - 2. Does not endanger people or property (except by direct contact)
 - 3. Does not endanger the environment
 - 4. Does not involve fire or an explosive condition or the potential for such. All others are complex spills.
- complex spills (significant spills), which require outside assistance (Emergency Operations Support Center(EOSC)).

NOTE: All spills (both outside or indoors) must be reported to EPC-CP to ensure each incident is evaluated, documented and remediated. EPC-CP is responsible for fulfilling any required external notifications associated with the release. Contact the EPC-CP Spills Pager (664-7722) to promptly notify EPC-CP of any spills. Contact EOSC (667-2400) in the event of an emergency.

Spill Response and Clean Up in Weapons Facilities Operations (WFO) Areas Document No.: WFO-IWD-0016 Revision: G

Effective Date: 10/28/2020

1.4 Definitions and Acronyms

None.

1.5 Hazard Analysis

Hazard Analysis (HA) Method Used: Brainstorming Other: List Names of HA Team (Attach sheet if necessary): DESHF-WFO Industrial Hygiene Team Date HA Performed: 11/03/2014.

1.6 Site Emergency Contacts

- Weapons Duty Officer: 664-2926
- Trit-HE Duty Operation Page; 664-6679
- WETF On-Call pager: 664-3426
- EOSC 667-2400
- EPC-CP Spills Pager:664-7722

2.0 Procedural Steps

See procedural steps, hazards, and controls in Attachment A.

3.0 Forms

Number	Title
2100	Integrated Work Document (IWD) Part 1, Activity Specific Information
2101	Integrated Work Document (IWD) Part 2, FOD Requirements and Approval for Entry and Area Hazards and Controls, Non-Tenant Activity Form
2102	Integrated Work Document (IWD) Part 2, FOD Requirements and Approval for Entry and Area Hazards and Controls, Tenant Activity Form
2103	Integrated Work Document (IWD) Part 3, Validation and Work Release
2104	Integrated Work Document (IWD) Part 4, Post Job Review

4.0 Attachments

Forms 2100, 2101, 2102, 2103, 2104.

Work Tasks/Steps Identify work steps/tasks in sequence when such sequencing contributes to safety, security, and/or environmental protection. Spill Response	Hazards, Concerns, and Potential Accidents/Incidents Identify both activity and work- area hazards for each task/step.	Controls, Preventive Measures, and Bounding Conditions Specify preventive measures, controls for each hazard (e.g., lockout/tagout points, specific Personal Protective Equipment [PPE], Tamper Indicating Devices [TIDs], alarms, safes, recycle, waste minimization).	Reference Documents List permits, operating manuals, security plans, and other reference procedures.	Training List training and qualification requirements. (<u>P300,</u> <u>Integrated Work Management,</u> <u>Section 6.1</u>)
Assess site for hazards	Previously unknown hazards or changed conditions	 Perform windshield survey of the area Interview workers knowledgeable of the spill Identify hazards Determine source, type and quantity of spilled material Walk down site prior to activity Communicate hazards to other workers 	WFO-BEP-378, WFO Building Emergency Plan	HAZCOM, Course 22956 Item # 27205, WFO (FOD- 3 Building Emergency Plan
	Slips, trips and falls	 Avoid stepping in spilled material Be aware of footing and surroundings at all times. Identify hazards prior to initiating work. Use caution and be observant while moving in areas with potential slip, trip or fall hazards. Implement good housekeeping practices. No open-toed shoes 	None	None
Control site Access	Previously unknown hazards or changed conditions	Administratively control areaBarriers: tape, rope	None	HAZCOM, Course 22956

Work Tasks/Steps Identify work steps/tasks in sequence when such sequencing contributes to safety, security, and/or environmental protection.	Hazards, Concerns, and Potential Accidents/Incidents Identify both activity and work- area hazards for each task/step.	Controls, Preventive Measures, and Bounding Conditions Specify preventive measures, controls for each hazard (e.g., lockout/tagout points, specific Personal Protective Equipment [PPE], Tamper Indicating Devices [TIDs],	Reference Documents List permits, operating manuals, security plans, and other	Training List training and qualification requirements. (P300, Integrated Work Management, Section 6.1)
Deploy Spill control measures (loose absorbents, pads and booms)	Incompatible materials	 alarms, safes, recycle, waste minimization). Determine type of spilled material Select proper spill control material 	 reference procedures. Manufacturer instructions MSDS 	HAZCOM, Course 22956
	Inhalation hazards	 Minimize time in the vicinity of the spilled material Position personnel up wind of plume 	 Manufacturer instructions MSDS 	HAZCOM, Course 22956
	Contact with spilled material	 Proper PPE Hands: Compatible gloves. Eyes: Safety glasses with side shields for all operations Body: Long pants and sleeved shirt When caustics are present, ensure the availability of eyewash station within 100 feet or 10 seconds with unobstructed access 	 Consult with the WFO Industrial Hygienist (IH), MSDS 	HAZCOM, Course 22956

Work Tasks/Steps Identify work steps/tasks in sequence when such sequencing contributes to safety, security, and/or environmental protection.	Hazards, Concerns, and Potential Accidents/Incidents Identify both activity and work- area hazards for each task/step.	Controls, Preventive Measures, and Bounding Conditions Specify preventive measures, controls for each hazard (e.g., lockout/tagout points, specific Personal Protective Equipment [PPE], Tamper Indicating Devices [TIDs], alarms, safes, recycle, waste minimization).	Reference Documents List permits, operating manuals, security plans, and other reference procedures.	Training List training and qualification requirements. (<u>P300</u> , <u>Integrated Work Management,</u> <u>Section 6.1</u>)
Clean up of absorbent material (loose absorbents, pads and booms)	Inhalation hazards	 Minimize generation of dust or splash Minimize time in the vicinity of the spilled material Position personnel up wind of spill 	Manufacturer instructionsMSDS	HAZCOM, Course 22956
	Contact with spilled material	 Proper PPE Hands: Compatible gloves. Eyes: Safety glasses with side shields for all operations. spills Body: Long pants and sleeved shirt When caustics are present, ensure the availability of eyewash station within 100 feet or 10 seconds with unobstructed access 	 Consult with the WFO Industrial Hygienist (IH), MSDS 	HAZCOM, Course 22956
Application of Micro Blaze Emergency Liquid Spill Control.	Contact with Micro Blaze Be upwind when applied	 Proper PPE: Eyes: Safety glasses with side shields for all operations Do not direct spray towards personnel Instruct personnel to be upwind when Micro Blaze is applied. 	Manufacturer instructionsMSDS	HAZCOM, Course 22956
	Low pressure (<100 psi)	• Follow sprayer manufacturers instructions	 Manufacturer instructions 	None
	Slippery surfaces (when applied to asphalt or concrete)	 Avoid stepping in treated area If necessary, spray treated area with clean water after 15 minutes 	None	None

Work Tasks/Steps Identify work steps/tasks in sequence when such sequencing contributes to safety, security, and/or environmental protection.	Hazards, Concerns, and Potential Accidents/Incidents Identify both activity and work-area hazards for each task/step.	Controls, Preventive Measures, and Bounding Conditions Specify preventive measures, controls for each hazard (e.g., lockout/tagout points, specific Personal Protective Equipment [PPE], Tamper Indicating Devices [TIDs], alarms, safes, recycle, waste minimization).	Reference Documents List permits, operating manuals, security plans, and other reference procedures.	Training List training and qualification requirements. (<u>P300, Integrated Work</u> <u>Management, Section 6.1</u>)
Recharge of sprayer with Micro Blaze Emergency Liquid Spill Control	Contact with Micro Blaze	Proper PPE Eyes: Safety glasses with side shields for all operations.	• MSDS	HAZCOM, Course 22956
	Compressed Air: Low pressure (<100 psi)	 Follow manufactures instructions Proper PPE: Eyes: Safety glasses with side shields for all operations Hand tighten nozzle assembly onto canister Do not charge sprayer over 100 psi 	Manufacturer Instructions	None

Work Tasks/Steps Identify work steps/tasks in sequence when such sequencing contributes to safety, security, and/or environmental protection.	Hazards, Concerns, and Potential Accidents/Inciden Identify both activity and work area hazards for each task/step.		zard (e.g., Equipment	manuals plans, ar	ents nits, operating s, security	Training List training and qualification requirements. (<u>P300,</u> <u>Integrated Work</u> <u>Management, Section</u> 6.1)
Excavation of Contaminated Soil						
Excavation of soil stained with spilled material.	Excavation hazards associated with underground utilities: electrocution, explosion	 Excavation Permit as required 	 P101-17 Excavati /Soil Disturba 	ion/Fill	None	
	Use of hand tools: Pinch points, mashing fingers and/or toes	 All hand tools will be inspected for integrity before use. Personnel will be instructed to use hand tools in the intended manner. Proper PPE: Eyes: Safety glasses with side shields Hands: Work gloves Foot: safety shoes 	None		None	
	Use of Heavy Equipment: Workers struck or crushed by equipment, Rollover	 Only qualified equipment operators are allowed to operate heavy equipment. Equipment shall be inspected daily or before each use Heavy equipment shall be inspected for engineering controls Persons on the ground are instructed to get and maintain eye contact with heavy equipment operators with pre-established hand signals. 	• Subparts 29 CFR and 29 (1910	1926	None	

Revision: G Effective Date:

10/28/2020

Work Tasks/Steps Identify work steps/tasks in sequence when such sequencing contributes to safety, security, and/or environmental protection.	Hazards, Concerns, and Potential Accidents/Incidents Identify both activity and work- area hazards for each task/step.	Controls, Preventive Measures, and Bounding Conditions Specify preventive measures, controls for each hazard (e.g., lockout/tagout points, specific Personal Protective Equipment [PPE], Tamper Indicating Devices [TIDs], alarms, safes, recycle, waste minimization).	Reference Documents List permits, operating manuals, security plans, and other reference procedures.	Training List training and qualification requirements. (<u>P300,</u> <u>Integrated Work</u> <u>Management, Section</u> 6.1)
Excavation of soil stained with spilled material., cont'd	Potential for historical site contaminants, SWMUs: DU, HE, Beryllium, Lead	 Signs and postings Consult with Industrial Hygienist (IH), RCTs and HE Operations Team Leader Consult EPC-CP and WES-DO Have soil surveyed by an RCT prior to and as excavated, as necessary. Additional PPE as required by IH and RCT <i>Note:</i> In the event that an item is encountered within an HE area that cannot be immediately identified as normal firing site debris work shall be paused and an explosives SME will be contacted to identify the item in question. <i>Note:</i> In active HE areas a person with site specific knowledge will be consulted to identify any hazards prior to the start of work. 	 WFO-AP-263, WFO Access Requirements for Knowledgeable Persons P 101-17 Excavation/Fill/ Soil Disturbance Decision Support Application (DSA) 	
	Heavy Lifting.	 Proper lifting techniques Lift only what you are capable of but not more than 50 pounds. Use two or more people to lift heavy or awkward loads Position load to be lifted directly in front of body. Bend knees and grasp load underneath with both hands and raise load using legs (not back). Do not lift and twist 	None	None

Work Tasks/Steps Identify work steps/tasks in sequence when such sequencing contributes to safety, security, and/or environmental protection.	Hazards, Concerns, and Potential Accidents/Incidents Identify both activity and work- area hazards for each task/step.	Controls, Preventive Measures, and Bounding Conditions Specify preventive measures, controls for each hazard (e.g., lockout/tagout points, specific Personal Protective Equipment [PPE], Tamper Indicating Devices [TIDs], alarms, safes, recycle, waste minimization).	Reference Documents List permits, operating manuals, security plans, and other reference procedures.	Training List training and qualification requirements. (<u>P300,</u> <u>Integrated Work</u> <u>Management, Section</u> <u>6.1</u>)
Containerize wastes	Direk reinte versking	Keen hende ever frem ninsk meinte		None
Containerize waste absorbent material, excavated soil and other waste	Pinch points, mashing fingers and/or toes	 Keep hands away from pinch points. Proper PPE: Eyes: Safety glasses with side shields Hands: Work gloves Foot: safety shoes 	None	None
	Use of hand tools: Pinch points, mashing fingers and/or toes	 All hand tools will be inspected for integrity before use. Personnel will be instructed to use hand tools in the intended manner. Proper PPE: Eyes: Safety glasses with side shields Hands: Work gloves Foot: safety shoes 	None	None
	Heavy Lifting.	 Proper lifting techniques Lift only what you are capable of but not more than 50 pounds. Use two or more people to lift heavy or awkward loads Position load to be lifted directly in front of body. Bend knees and grasp load underneath with both hands and raise load using legs (not back). Do not lift and twist 	None	None
	Incorrect waste determination and management	 WMC determines waste type WMC will label waste container WMC will manage wastes 	P-409 Waste Management	Waste Generator Overview

Attachment A Integrated Work Document (IWD) Part 1 Activity Specific Information (cont'd)

Work Tasks/Steps Identify work steps/tasks in sequence when such sequencing contributes to safety, security, and/or environmental protection.	Hazards, Concerns, and Potential Accidents/Incidents Identify both activity and work- area hazards for each task/step.	Controls, Preventive Measures, and Bounding Conditions Specify preventive measures, controls for each hazard (e.g., lockout/tagout points, specific Personal Protective Equipment [PPE], Tamper Indicating Devices [TIDs], alarms, safes, recycle, waste minimization).	Reference Documents List permits, operating manuals, security plans, and other reference procedures.	Training List training and qualification requirements. (<u>P300,</u> <u>Integrated Work</u> <u>Management, Section</u> <u>6.1</u>)
Opening and Securing of Waste Co				
	Do not use or open drums with apparent bulging; even empty drums may be pressurized.	 Inspect before opening; even empty drums may be pressurized. 	P-409 Waste Management	Waste Generator Overview
Transport fo Waste Containers				
Waste Management Coordinator (WMC) transports waste containers to designated waste storage area	Operation of lift gate: Pinch points, mashing fingers and/or toes	 Advise nearby workers that the lift gate is being operated Kept clear of lift gate swing radius Proper PPE: Eyes: Safety glasses with side shields Hands: Work gloves 	Manufacturer instructions	None
	Heavy Lifting	 Proper lifting techniques Lift only what you are capable of but not more than 50 pounds. Use two or more people to lift heavy or awkward loads Position load to be lifted directly in front of body. Bend knees and grasp load underneath with both hands and raise load using legs (not back). Do not lift and twist 	None	None
	Shifting loads	Secure loads in truck bed	None	None

Spill Response and Clean Up in Weapons Facilities Operations (WFO) Areas

Document No.: WFO-IWD-0016

Revision:GEffective Date:10/28/2020

Attachment B Integrated Work Document (IWD) Part 2 (Non Tenant) Form 2101 Integrated Work Document (IWD) Part 2. oś Alamos Non-Tenant FOD Requirements and Approval for Entry and Area Hazards and Controls NATIONAL LABORATORY Activity Form Facility Operation Director (FOD) must determine the facility entry and coordination requirements and identify the Environment, Safety, Health (ESH)/Security and Safeguards (S&S) hazards and controls associated with the activity location. IWD No./Work Request No: WFO-IWD-0016 FOD TA 16 Bldg 205 Room Other Location 100, 100A, 101, 102, 103, 104, 104A, 106, 110 Name Phone FOD Designated Facility Point-of-Contact Pager: 4-6314 4-3070 4-6586 Email: Don Hyatt Mel Ortiz 7-7519 7-5419 5-5339 hyatt@lanl.gov msortiz@lanl.gov Byron Denny byron@lanl.gov jvongphachan@lanl.gov Jamia Vongphachan 4-0842 4-8254 Entry and Coordination Requirements (Check one or more of the fol ina) No Entry/Coordination Requirements FOD-designated facility Point-of-Contact must sign IWD Part 3 Plan of the Day/Plan of the Week (POTD/POTW) Check in at Start of Work Vvork-Area Training Required Security Clearance Requirements Work must be Scheduled Check in Daily Co-located Hazards/Concerns Other Security Requirements (ex.: Cellphone, No Foreign Nationals, etc.) Check out at End of Work C Quality Issues Check out Daily S Escort Required Review under Authorization Basis (AB)/Safety Basis/Unreviewed Safety Question (USQ) Other Bounding Conditions: Additional Comments (refer to Job Hazard Analysis [JHA] Tool Facility Notes) WTEF is a Category II Nuclear Facility, Check in with the WETF Duty Operator, 7-2080, 16-205-110, prior to start of work. The WETF work control process must be followed. Security Requirements: No 2-way pages or personal cell phones. Blackbernies are allowed except in the "Closed Area". Government issued cell phones must have the battery removed. "Q" clearance and be complete on all WETF and Lab-Wide requirements for WETF access unless escorted. "L" clearance and Un-Cleared personnel must be escorted at all limes. Instructions: In the block below, identify work-area hazards that could potentially affect the worker(s) or others. Avoid using the same Part 2, Form 2101 for multiple facilities. Ensure that work area hazards, specific to the facility or work location are identified and controlled. Specify the facility controls and preventive measures that must be implemented by the worker(s) to protect against the site hazards as well as any special training required. ESH/S&S WORK AREA HAZARDS & CONTROLS Facility Controls/ Preventive Measures/ **Bounding Conditions** Reference Documents Training and Qualification Specify preventive measures. Work Area Hazards/Concerns List permits, operating manuals, and other List training requirements (P300, Integretated Work controls and Identify site hazards and concerns that could potentially affect the worker(s) or others. Work Area Hazard Present bounding conditions for each site hazard reference procedures

Form 2101 (12/17)

No Work Area Hazards

Attachment B Integrated Work Document (IWD) Part 2 (Non Tenant) (cont'd)

Work Area Hazards/Concerns Identify site hazards and concerns that could potentially affect the worker(s) or others.	Work Area Hazard Present	Facility Controls/ Preventive Measures/ Bounding Conditions Specify preventive measures, controls and bounding conditions for each site hazard	Reference Documents List permits, operating manuals, and other reference procedures	Training and Qualification List training requirements (P300, Integretated Work Management, Section 8.1)
Ionizing Radiation Work in posted radiological areas, work with radioactive materials, or work on or near radiation producing devices. Specify Hazard:	🗌 Yes 🛛 No			
Worker Exposure Working near non-ionizing radiation, beryllium, noise, chemicals, hazardous biological materials, lead, asbestos, temperature/humidity extremes, or high explosives. Specify Hazards:	🗆 Yes 🖾 No			
Energized and Operative Systems Working near energized electrical parts, pressure systems, steam lines; near unprotected belts, pulleys, chains or rotating equipment; fuel fired equipment other than vehicles; or spark or flame producing operations. Specify Hazards:	🗌 Yes 🖾 No			
Confined Spaces Entry into tanks, manholes, cooling towers, sumps, or any other area with potentially low oxygen concentration or other hazards such as toxic vapors or engulfment. Specify Hazards:	□Yes ⊠No			
Elevated Work Surface Elevated work when fall protection is not provided by conventional handrail systems or required per <u>P101-20, Fall Protection Program</u>	Ves 🛛 No			
Environmental Impact Activities conducted in areas containing potential release site, contaminated soil, sensitive species, watercourse wellands, floodplain, historical/archeological sites, or other work area condition that can be impacted by or can impact the environment. Specify Hazards:	🗌 Yes 🖾 No			

Form 2101 (12/17)

Revision:GEffective Date:10/28/2020

Attachment B Integrated Work Document (IWD) Part 2 (Non Tenant) (cont'd

Work Area Hazards/Concerns Identify site hazards and concerns that could potentially affect the worker(s) or others.	Work Area Hazard Present	Preventive Measures/ Bounding Conditions Specify preventive measures, controls and bounding conditions for each site hazard	Reference Documents List permits, operating manuals, and other reference procedures	Training and Qualification List training requirements (P300, Integretated Work Management, Section 6.1)
Specify:	Yes No	Q or L Clearance or Escorted	P202-1 Security Areas, Property Protection Areas, and General Access Areas	U-Train 1425 Annual Security Refresher
Other Hazards Specify:	Yes No			

Form 2101 (12/17)

Attachment B Integrated Work Document (IWD) Part 2 (Non Tenant) (cont'd

VD No./Work Request No: WFO	FOD Rec		and Approva	ument (IWD) Part 2, for Entry and Area Hazards and	Non-Tenant Controls Activity Form		
acility Operation Director (FOD) mu (&S) hazards and controls associa			ination requirements	and identify the Environment, Safety, Health (ESH)/Security and Safeguards		
FOD 3	TA 16		Bldg. 205	Room 112, 114, 115, 116, 100B, 120, 122, 124, 126	Other Location		
FOD Designated Facility Point-of-Contact	Name Don Hyatt Mei Ortiz Byron Denny Jamie Vongphachan		Phone 7-7519 7-5419 5-5339 4-0842	Pager 4-6314 4-3070 4-6586 4-8254	Email hyatt@lanl.gov msortiz@lanl.gov byron@lanl.gov ivongphachan@lanl.gov		
Entry and Coordination Requirem			wing)				
No Entry/Coordination Requirements		⊠ FO	FOD-designated facility Point-of-Contact must sign IWD Part 3				
Plan of the Day/Plan of the Wee	k (POTD/POTW)	🖾 Ch	Check in at Start of Work Work-Area Training Required				
Security Clearance Requirement	ts	N We	Work must be Scheduled Check in Daily				
Co-located Hazards/Concerns		IS OU	ner Security Require	nents (ex.: Cellphone, No Foreign Nationals, e	ic.)		
Check out at End of Work		Qu	Check out Daily				
Escort Required		🖾 Re	Review under Authonization Basis (AB)/Safety Basis/Unreviewed Safety Question (USQ)				
Other Bounding Conditions:	and the second sec						

Instructions: In the block below, identify work-area hazards that could potentially affect the worker(s) or others. Avoid using the same Part 2, Form 2101 for multiple facilities. Ensure that work area hazards, specific to the facility or work location are identified and controlled. Specify the facility controls and preventive measures that must be implemented by the worker(s) to protect against the site hazards as well as any special training required.

Work Area Hazards/Concerns Identify site hazards and concerns that could potentially affect the worker(s) or others.	Work Area Hazard Present	Facility Controls/ Preventive Measures/ Bounding Conditions Specify preventive measures, controls and bounding conditions for each site hazard	Reference Documents List permits, operating manuals, and other reference procedures	Training and Qualification List training requirements (P300, Integretated Work Management, Section 6, 1)
No Work Area Hazards				

Form 2101 (12/17)

Revision:GEffective Date:10/28/2020

Attachment B Integrated Work Document (IWD) Part 2 (Non Tenant) (cont'd

ESF	ISAS WORK ARE	A HAZARDS & CONTROLS Facility Controls/		
Work Area Hazards/Concerns Identify site hazards and concerns that could potentially affect the worker(s) or others.	Work Area Hazard Present	Preventive Measures/ Bounding Conditions Specify preventive measures, controls and bounding conditions for each site hazard	Reference Documents List permits, operating manuals, and other reference procedures	Training and Qualification List training requirements (P300, Integretated Work Management, Section 6.1)
onizing Radiation Nork in posted radiological areas, work with radioactive materials, or work on or near radiation producing devices. Specify Hazard: Work in posted radiological areas, work with adioactive materials, or work on or near radiation producing devices.	🛛 Yes 📄 No	Facility and job-specific pre-job briefing, facility postings	Job specific RWPs and work package instructions and WETF-AP-FRPR-34 Facility Radiation Protection Requirements Weapons Engineering Trilium Facility	RAD Worker II and Facility Access Training unless escorted
Worker Exposure Working near non-ionizing radiation, beryllium, noise, chemicals, nazardous biological materials, lead, asbestos, lemperature/humidity extremes, or high explosives. Specify Hazards: Nitrogren/Beryllium in Room 120 cabinet and Room 126 drums.	⊠ Yes □ No	 Facility and job-specific pre-job briefing. Oxygen monitors are present throughout areas with potential for low oxygen concentration If accessing the Be cabinet in room 120, contact IH for Beryllium evaluation and controls. If accessing the drums or handling beryllium articles or items from the drums in room 126, contact IH for evaluation and controls. 	P101-5 Cryogens P101-21 Chronic Berylium Disease Prevention Program	Facility Briefing by Duty Operator Beryllium Awareness Training Course 28340
Energized and Operative Systems Working near energized electrical parts, pressure systems, steam lines; near unprotected belts, pulleys, chains or rotating equipment; fuel fired equipment other than vehicles; or spark or lame producing operations. Specify Hazards:	🗋 Yes 🖾 No			
Confined Spaces Entry into tanks, manholes, cooling towers, sumps, or any other area with potentially tow oxygen concentration or other hazards such as toxic vapors or engulfment. Specify Hazards:	🗆 Yes 🖾 No			

Form 2101 (12/17)

Revision:GEffective Date:10/28/2020

Attachment B Integrated Work Document (IWD) Part 2 (Non Tenant) (cont'd

🖾 No			
	·		
🖾 No		Last	
□ No	Q or L Clearance or Escorted	P202-1 Security Areas, Property Protection Areas, and General Access Areas	U-Train 1425 Annual Security Refresher
No			C
1] No	No Q or L Clearance or Escorted	No Q or L Clearance or Escorted P202-1 Security Areas, Property Protection Areas, and General Access Areas

Form 2101 (12/17)

Attachment B Integrated Work Document (IWD) Part 2 (Non Tenant) (cont'd

S&S) hazards and controls associated association (1998)	ated with the activity location	on.	and the second second	nd identify the Environment, Safety, Health	(ESH)/Security and Saleguards		
FOD 3	TA 16		Bidg. 205	Room UPS and Equipment Rooms	Other Location Roof		
FOD Designated Facility Point-of-Contact	Name: Don Hyatt Mel Ortiz Byron Denny Jamie Vongphachan		Phone: 7-7519 7-5419 5-5339 4-0842	Pager: 4-6314 4-3070 4-6586 4-6254	Email: hyatt@lanl.gov msofiz@lanl.gov byron@lanl.gov jvongphachan@lanl.gov		
Entry and Coordination Requiren				,	1 Jeongphachan@sani.gov		
No Entry/Coordination Requirem	nents	IN FOR	-designated facility Pr	pint-of-Contact must sign IWD Part 3			
Plan of the Day/Plan of the Week (POTD/POTW)		🖾 Che	Check in al Start of Work Work-Area Training Required				
Security Clearance Requirement	ts	Work must be Scheduled Check in Daily					
Co-located Hazards/Concerns		Other Security Requirements (ex.: Cellphone, No Foreign Nationals, etc.)					
Check out at End of Work		Quality Issues Check out Daily					
S Escort Required		🖾 Revi	iew under Authorizatio	n Basis (AB)/Safety Basis/Unreviewed Sal	ety Question (USQ)		
Other Bounding Conditions:							

Work Area Hazards/Concerns Idenlify site hazards and concerns that could potentially affect the worker(s) or others.	Work Area Hazard Present	Facility Controls/ Preventive Measures/ Bounding Conditions Specify preventive measures, controls and bounding conditions for each aite hazard	Reference Documents List permits, operating manuals, and other reference procedures	Training and Qualification List training requirements (P300, Integretated Work Management, Section 6.1)
No Work Area Hazards				
orm 2101 (12/17)			11	Page 1


Revision:GEffective Date:10/28/2020

Attachment B Integrated Work Document (IWD) Part 2 (Non Tenant) (cont'd

		A HAZARDS & CONTROLS Facility Controls/	1.	
Work Area Hazards/Concerns Identify site hazards and concerns that could potentially affect the worker(s) or others.	Work Area Hazard Present	Preventive Measures/ Bounding Conditions Specify preventive measures, controls and bounding conditions for each site hazard	Reference Documents List permits, operating manuals, and other reference procedures	Training and Qualification List training requirements (F300, Integratated Work Management, Section 6.1)
Ionizing Radiation Work in posted radiological areas, work with radioactive materials, or work on or near radiation producing devices, Specify Hazard:	Yes 🛛 No			
Worker Exposure Working near non-ionizing radiation, beryllium, noise, chemicals, hazardous biological materials, lead, asbestos, temperature/humidity extremes, or high explosives. Specify Hazards: Potential for low oxygen concentration due to liquid nitrogen system.	🛛 Yes 🗌 No	Facility and job-specific pre-job briefing oxygern monitors are present throughout areas with potential for low oxygen concentration	P101-5 Cryogens	Facility Briefing by Duty Operator
Energized and Operative Systems Working near energized electrical parts, pressure systems, steam lines; near unprotected belts, pulleys, chains or rolating equipment; fuel fired equipment other than vehicles; or spark or lame producing operations. Specify Hazards:	🗆 Yes 🖾 No			
Confined Spaces Entry into tanks, manholes, cooling towers, sumps, or any other area with potentially low oxygen concentration or other hazards such as toxic vapors or engulfment. Specify Hazards:	Yes No			
Elevated Work Surface Elevated work when fall protection is not provided by conventional handrail systems or required per <u>P101-20, <i>Fall Protection Program</i></u>	🗆 Yes 🖾 No	1		
Environmental Impact Activities conducted in areas containing potential release site, contaminated soil, sensitive species, watercourse wetlands, floodplain, historical/archeological sites, or other work area condition that can be impacted by or can impact the environment. Specify Hazards:	Yes X No			

Form 2101 (12/17)

Attachment B Integrated Work Document (IWD) Part 2 (Non Tenant) (cont'd



Form 2101 (12/17)

Attachment B Integrated Work Document (IWD) Part 2 (Non Tenant) (cont'd

LOS Alamos	FOD Rec			ment (IWD) Part 2, or Entry and Area Hazard	ds and Controls	Non-Tenan Activity Form
to no, tooth negacot no.	O-IWD-0016			Revision #:		
acility Operation Director (FOD) mus S&S) hazards and controls associat	t determine the facility e ed with the activity locat	ntry and coordina ion.	tion requirements an	id identify the Environment, Salety,	Health (ESH)/Security and Safe	eguards
FOD	TA 16		lldg. 05/450	Room Exterior Areas	Other Location	
FOD Designated Facility Point-of-Contact	Name Don Hyatt Mei Ortiz Byron Denny Jamie Vongphac	F	-0842	Pager 4-8314 4-3070 4-6586 4-6254	Email hyatt@lanl.gov msortiz@lanl.gov byron@lanl.gov jvongphechen@la	nl.gov
Entry and Coordination Requirem	nents (Check one or m	ore of the follow	ing)			
No Entry/Coordination Requireme	ents	S FOD-	designated facility Pr	oint-of-Contact must sign IWD Part	3	
Plan of the Day/Plan of the Week	(POTD/POTW)	Check	Check in at Start of Work Swork-Area Training Required			
Security Clearance Requirements	5	Work	must be Scheduled	Check in Dail	ly.	
Co-located Hazards/Concerns		Ø Other	Other Security Requirements (ex.: Cellphone, No Foreign Nationals, etc.)			
Check out at End of Work		Qualit	y Issues	Check out Da	aily	
Escort Required		🖾 Revie	Review under Authorization Basis (AB)/Safety Basis/Unreviewed Safety Question (USQ)			
Other Bounding Conditions:						

Instructions: In the block below, identify work-area hazards that could potentially affect the worker(s) or others. Avoid using the same Part 2, Form 2101 for multiple facilities. Ensure that work area hazards, specific to the facility or work location are identified and controlled. Specify the facility controls and preventive measures that must be implemented by the worker(s) to protect against the site hazards as well as any special training required.

Work Area Hazards/Concerns Identify site hazards and concerns that could potentially affect the worker(s) or others.	Work Area Hazard Present	Facility Controls/ Preventive Measures/ Bounding Conditions Specify preventive measures, controls and bounding conditions for each site heazerd	Reference Documents List permits, operating manuals, and other reference procedures	Training and Qualification List training requirements (P300, Integretated Work Management, Section 6.1)
🗌 No Work Area Hazards				

Form 2101 (12/17)

Revision:GEffective Date:10/28/2020

Attachment B Integrated Work Document (IWD) Part 2 (Non Tenant) (cont'd

		A HAZARDS & CONTROLS Facility Controls/	1	
Work Area Hazards/Concerns Identify site hazards and concerns that could potentially affect the worker(s) or others.	Work Area Hazard Present	Preventive Measures/ Bounding Conditions Specify preventive measures, controls and bounding conditions for each site hazard	Reference Documents List permits, operating manuals, and other reference procedures	Training and Qualification List training requirements (P300, Integretated Work Management, Section 6, 1)
Ionizing Radiation Work in posted radiological areas, work with radioactive materials, or work on or near radiation producing devices. Specify Hazard:	🗆 Yes 🖾 No			
Worker Exposure Working near non-ionizing radiation, beryllium, noise, chemicals, hazardous biological materials, lead, asbestos, temperature/humidity extremes, or high explosives. Specify Hazards:	Yes 🛛 No			
Energized and Operative Systems Working near energized electrical parts, pressure systems, steam lines; near unprotected belts, pulleys, chains or rotating equipment; fuel fired equipment other than vehicles; or spark or fiame producing operations. Specify Hazards:	Yes 🛛 No			
Confined Spaces Entry into tanks, manholes, cooling towers, sumps, or any other area with potentially low oxygen concentration or other hazards such as toxic vapors or engulfment. Specify Hazards:	🗆 Yes 🖾 No			
Elevated Work Surface Elevated work when fall protection is not provided by conventional handrail systems or required per P101-20, Fall Protection Program	Yes 🖾 No			
Environmental Impact Activities conducted in areas containing potential release site, contaminated soil, sensitive species, watercourse wetlands, floodplain, historical/archeological sites, or other work area condition that can be impacted by or can impact the environment. Specify Hazards:	Ves 🛛 No			

Form 2101 (12/17)

Revision:GEffective Date:10/28/2020

Attachment B Integrated Work Document (IWD) Part 2 (Non Tenant) (cont'd)

Work Area Hazards/Concerns Identify site hazards and concerns that could potentially affect the worker(s) or others.	Work Area Hazard Present	Facility Controls/ Preventive Measures/ Bounding Conditions Specify preventive measures, controls and bounding conditions for each site hazard	Reference Documents List permits, operating manuals, and other reference procedures	Training and Qualification List training requirements (P300, Inlegretated Work Management, Section 6,1)
Security Requirements Specify:	Yes 🗆 No	Q or L Clearance or Escorted	P202-1 Security Areas, Property Protection Areas, and General Access Areas	U-Train 1425 Annual Security Refresher
Other Hazards Specify:	Yes No		1	

Form 2101 (12/17)

Attachment B Integrated Work Document (IWD) Part 2 (Non Tenant) (cont'd

VD No./Work Request No: WFG	O-IWD-0016 I determine the facility en	uirements a	nd Approval for	ent (IWD) Part 2, Entry and Area Haza Revision # idenlify the Environment, Safe	G	Non-Tenant Activity Form eguards
Salar Sector	TA 16	E	ldg. 29	Room	Other Location	
FOD Designated Facility Point-of-Contact	Name: Don Hyatt Mel Ortiz Byron Denny Jamie Vongphach	F 77 75	-7519 -5419 -5339 -0842	All Pager: 4-6314 4-3070 4-6586 4-6254	Email: hyatt@lanl.gov msortiz@lanl.gov byron@lanl.gov jvongphachan@la	
Entry and Coordination Requireme			ig)		1 Periodicial State	
No Entry/Coordination Requireme	ents	TFOD-	lesignated facility Poin	t-of-Contact must sign IWD Pa	art 3	
Plan of the Day/Plan of the Week	(POTD/POTW)	S Check	in at Start of Work	Work-Area	Training Required	
Security Clearance Requirements		VVork	must be Scheduled	Check in D	Jaily	
Co-located Hazards/Concerns		Other	Security Requirements	(ex.: Cellphone, No Foreign I	Nationals, etc.)	
Check out at End of Work		Qualit	Quality Issues Scheck out Daily			
Escort Required		C Revie	w under Authorization I	Basis (AB)/Safety Basis/Unrev	iewed Safety Question (USQ)	
Other Bounding Conditions:						

Instructions: In the block below, identify work-area hazards that could potentially affect the worker(s) or others. Avoid using the same Part 2, Form 2101 for multiple facilities. Ensure that work area hazards, specific to the facility or work location are identified and controlled. Specify the facility controls and preventive measures that must be implemented by the worker(s) to protect against the site hazards as well as any special training required.

Work Area Hazards/Concerns Identify sile hazards and concerns that could potentially affect the worker(s) or others.	Work Area Hazard Present	Facility Controls/ Preventive Measures/ Bounding Conditions Specify preventive measures, controls and bounding conditions for each site hazard	Reference Documents List permits, operating manuals, and other reference procedures	Training and Qualification List training requirements (P300, Integretated Work Management, Section 5.1)
🗋 No Work Area Hazards				

Form 2101 (12/17)

Revision:GEffective Date:10/28/2020

Attachment B Integrated Work Document (IWD) Part 2 (Non Tenant) (cont'd

Work Area Hazards/Concerns Identify site hazards and concerns that could potentially affect the worker(s) or others.	Work Area Hazard Present	A HAZARDS & CONTROLS Facility Controls/ Proventive Measures/ Bounding Conditions Specify preventive measures, controls and bounding conditions for each site hazard	Reference Documents List permits, operating manuals, and other reference procedures	Training and Qualification List training requirements (P300, Integretated Work Management, Section 6.1)
Ionizing Radiation Work in posted radiological areas, work with radioactive materials, or work on or near radiation producing devices. Specify Hazard:	🗋 Yes 🖾 No			
Worker Exposure Working near non-ionizing radiation, beryllium, noise, chemicals, hazardous biological materials, lead, asbestos, temperature/humidity extremes, or high explosives. Specify Hazards:	□Yes ⊠No			
Energized and Operative Systems Working near energized electrical parts, pressure systems, steam lines; near unprotected belts, pulleys, chains or rotating equipment; fuel fired equipment other than vehicles; or spark or liame producing operations. Specify Hazards:	□Yes ⊠No			
Confined Spaces Entry into tanks, manholes, cooling towers, sumps, or any other area with potentially low oxygen concentration or other hazards such as toxic vapors or engulfment. Specify Hazards:	🗆 Yes 🖾 No			
Elevated Work Surface Elevated work when fall protection is not provided by conventional handrail systems or required per <u>P101-20, Fall Protection Program</u>	🗆 Yes 🖾 No			
Environmental Impact Activities conducted in areas containing potential release site, contaminated soil, sensitive species, watercourse wellands, floodplain, historical/archeological sites, or other work area condition that can be impacted by or can impact the environment. Specify Hazards:	🗆 Yes 🖾 No			

Form 2101 (12/17)

Revision:GEffective Date:10/28/2020

Attachment B Integrated Work Document (IWD) Part 2 (Non Tenant) (cont'd

Work Area Hazards/Concerns Identify site hazards and concerns that could potentially affect the worker(s) or others.	Work Area Hazard Present	Facility Controls/ Preventive Measures/ Bounding Conditions Specify preventive measures, controls and bounding conditions for each site hazard	Reference Documents List permits, operating manuals, and other reference procedures	Training and Qualification List training requirements (P300, Integretated Work Management, Section 6.1)
Security Requirements Specify:	Yes 🗍 No	Q or L Clearance or Escorted	P202-1 Security Areas, Property Protection Areas, and General Access Areas	U-Train 1425 Annual Security Refresher
Other Hazards Specify:	Ves No			
I have venified that the hazards identified above adequately identify FOD or Representative (Signature/Z #/Date) Approval Required Date Approval Expires: <u>September 30, 2021</u>	(Y)	I that the IWM precess, has been at	pplied appropriately.	1

Form 2101 (12/17)

Attachment B Integrated Work Document (IWD) Part 2 (Non Tenant) (cont'd

Los Alamos NATIONAL LABORATORY ID: 101 ID: 101 VD No. Work Request No: <u>WFO</u> acility Operation Director (FOD) mu &Sb) hazards and controls associat	-IWD-0016 Rev	ision #: _G	for Entry and Area Hazards and and identify the Environment, Safety, Health (E	Activity Form		
FOD 3	TA 16	Bidg. 450	Room 160, 161, 162, 163 Equip. Rooms	Other Location Roof		
FOD Designated Facility Point-of-Contact	Name: Don Hyatt Mel Ortiz Byron Denny Jamie Vongphachan	Phone: 7-7519 7-5419 5-5339 4-0842	Pager. 4-6314 4-3070 4-6586 4-6254	hyatt@lanl.gov msortiz@lanl.gov byron@lanl.gov jvongphachan@lanl.gov		
Entry and Coordination Requiren	nents (Check one or more of	f the following)				
No Entry/Coordination Requires	ients	FOD-designated facility F	Point-of-Contact must sign IWD Part 3			
Plan of the Day/Plan of the Wee	k (POTD/POTW)	Check in at Start of Work Work-Area Training Required				
Security Clearance Requiremen	ls	Work must be Scheduled				
Co-located Hazards/Concerns		Other Security Requirem	ents (ex.: Cellphone, No Foreign Nationals, et	2.)		
Check out at End of Work		Quality Issues	Check out Daily			
Escort Required		Review under Authorizati	on Basis (AB)/Safety Basis/Unreviewed Safet	Question (USQ)		
Other Bounding Conditions:		Carlos and a second				
Requirements: No 2-way pagers or	lity, Check in with the WETF I personal cell phones. Blackbo	Duly Operator, 7-2060, 16-205-1	10, prior to start of work. The WETF work con Closed Area". Government issued cell phones	trol process must be followed. Security must have the battery removed. "Q" / "L"		

Work Area Hazards/Concerns Idenlify site hazards and concerns that could potentially affect the worker(s) or others.	Work Area Hazard Present	A HAZARDS & CONTROLS Facility Controls/ Preventive Measures/ Bounding Conditions Specify preventive measures, controls and bounding conditions for each site hazard	Reference Documents List permits, operating manuals, and other reference procedures	Training and Qualification List training requirements (P300, Integretated Work Management, Section 6.1)
Form 2101 (12/17)				Page 1

Revision:GEffective Date:10/28/2020

Attachment B Integrated Work Document (IWD) Part 2 (Non Tenant) (cont'd

Work Area Hazards/Concerns Identify site hazards and concerns that could potentially affect the worker(s) or others.	Work Area Hazard Present	A HAZARDS & CONTROLS Facility Controls/ Preventive Measures/ Bounding Conditions Specify preventive measures, controls and bounding conditions for each sile hazard	Reference Documents List permits, operating manuals, and other reference procedures	Training and Qualification List training requirements (P300, Integretated Work Management, Section 5 1)
Ionizing Radiation Work in posted radiological areas, work with radioactive materials, or work on or near radiation producing devices. Specify Hazard:	🗌 Yes 🖾 No			
Worker Exposure Working near non-ionizing radiation, beryllium, noise, chemicals, nazardous biological materials, lead, asbestos, emperature/humidity extremes, or high explosives. Specify Hazards:	🗆 Yes 🖾 No			
Energized and Operative Systems Working near energized electrical parts, pressure systems, sleam lines; near unprotected bells, pulleys, chains or rotating squipment; fuel fired equipment other than vehicles; or spark or lame producing operations. Specify Hazards:	□Yes ⊠No			
Confined Spaces Entry into tanks, manholes, cooling lowers, sumps, or any other area with potentially low oxygen concentration or other hazards such as toxic vapors or engulfment. Specify Hazards:	🗆 Yes 🖾 No			
Elevated Work Surface Elevated work when fail protection is not provided by conventional handrail systems or required per <u>P101-20, Fail Protection Program</u>	Yes 🖾 No			
Environmental Impact Activities conducted in areas containing potential release site, contaminated soil, sensitive species, watercourse wetlands, floodplain, historical/archeological sites, or other work area condition that can be impacted by or can impact the environment. Specify Hazards:	□Yes ⊠No			


Form 2101 (12/17)

Revision:GEffective Date:10/28/2020

Attachment B Integrated Work Document (IWD) Part 2 (Non Tenant) (cont'd ESH/S&S WORK AREA HAZARDS & CONTROLS Facility Controls/ Preventive Measures/ **Bounding Conditions** Training and Qualification Specify preventive measures, **Reference Documents** Work Area Hazards/Concerns controls and List permits, operating List training requirements Work Area Hazard Present Identify site hazards and concerns that could potentially affect the worker(s) or others. bounding conditions for manuals, and other (P300, Integretated Work Management, Section 6.1) each site hazard reference procedures P202-1 Security Areas, Security Requirements Q or L Clearance or Escorted U-Train 1425 Annual Security Property Protection Areas, and General Specify: Refresher Access Areas Yes No Other Hazards Specify: I have verified that the hazards identified above adequately identify the area hazards and that the IWM process has been applied appropriately. 9/3 120007 200 FOD or Representative (Signature/Z #/Date) Approval Required Date Approval Expires: September 30, 2021

Form 2101 (12/17)

Attachment B Integrated Work Document (IWD) Part 2 (Non Tenant) (cont'd



Instructions: In the block below, identify work-area hazards that could potentially affect the worker(s) or others. Avoid using the same Part 2, Form 2101 for multiple facilities. Ensure that work area hazards, specific to the facility or work location are identified and controlled. Specify the facility controls and preventive measures that must be implemented by the worker(s) to protect against the site hazards as well as a well as any special training required.


	er (P300, Integretated Work res Management, Section 6.1)
No Work Area Hazards	

Attachment B Integrated Work Document (IWD) Part 2 (Non Tenant) (cont'd

	1	A HAZARDS & CONTROLS Facility Controls/		
Work Area Hazards/Concerns Identify site hazards and concerns that could potentially affect the worker(s) or others.	Work Area Hazard Present	Preventive Measures/ Bounding Conditions Specify preventive measures, controls and bounding conditions for each site hazard	Reference Documents List permits, operating manuals, and other reference procedures	Training and Qualification List training requirements (P300, Integretated Work Management, Section 6.1)
Ionizing Radiation Work in posted radiological areas, work with radioactive materials, or work on or near radiation producing devices. Specify Hazard:	🗆 Yes 🖾 No			
Worker Exposure Working near non-ionizing radiation, beryllium, noise, chemicals, hazardous biological materials, fead, asbestos, temperature/humidity extremes, or high explosives. Specify Hazards:	🗆 Yes 🖾 Nö			
Energized and Operative Systems Working near energized electrical parts, pressure systems, steam lines; near unprotected belts, pulleys, chains or rotaling equipment; fuel fired equipment other than vehicles; or spark or flame producing operations. Specify Hazards:	🗆 Yes 🖾 No			
Confined Spaces Entry into tanks, manholes, cooling towers, sumps, or any other area with potentially low oxygen concentration or other hazards such as toxic vapors or engulfment. Specify Hazards:	🗆 Yes 🖾 No			
Elevated Work Surface Elevated work when fall protection is not provided by conventional handrall systems or required per <u>P101-20, <i>Fall Protection Program</i></u>	Yes 🛛 No			
Environmental Impact Activities conducted in areas containing potential release site, contaminated soil, sensitive species, watercourse wellands, floodplain, historical/archeological sites, or other work area condition that can be impacted by or can impact the environment. Specify Hazards:	🗌 Yes 🖾 No			

Revision:GEffective Date:10/28/2020

Attachment B Integrated Work Document (IWD) Part 2 (Non Tenant) (cont'd



Form 2101 (12/17)

Attachment B Integrated Work Document (IWD) Part 2 (Non Tenant) (cont'd

NATIONAL LABORATORY 157,1943 WD No.Work Request No: WFO		Integrated Work Docum uirements and Approval for Revision #: <u>G</u>		rds and Controls	Non-Tenant Activity Form
acility Operation Director (FOD) mu S&S) hazards and controls associa		try and coordination requirements and	d identify the Environment, Safet	y, Health (ESH)/Security and Sa	leguards
FOD	TA 16	Bidg. 824	Room	Other Location	
FOD Designated Facility Point-of-Contact	Name: Don Hyati Mel Ortiz Byron Denny Jamie Vongphach	Phone: 7-7519 7-5419 5-5339	Pager: 4-6314 4-3070 4-6586 4-6254	Email: hyatt@lanl.gov msortiz@lanl.gov byron@lanl.gov jvongphachan@la	
Entry and Coordination Requirem	ents (Check one or mor	e of the following)			
No Entry/Coordination Requirem	ents	FOD-designated facility Po	int-of-Contact must sign IWD Pa	rt 3	
Plan of the Day/Plan of the Wee	k (POTD/POTW)	Check in at Start of Work	Work-Area	Training Required	
Security Clearance Requirement	ls	Work must be Scheduled	Check in D	aily	
Co-located Hazards/Concerns		Other Security Requirements (ex.: Cellphone, No Foreign Nationals, etc.)			
Check out at End of Work		Quality Issues	Quality Issues Check out Daily		
Escort Required		Review under Authorization	Basis (AB)/Safety Basis/Unrevi	iewed Safety Question (USQ)	
Other Bounding Conditions:	a second second	and the second se			
	lity, Check in with the WE personal cell phones. Blac	TF Duty Operator, 7-2060, 16-205-111 ckberries are allowed except in the *C	losed Area". Government issued		

Instructions: In the block below, identify work-area hazards that could potentially affect the worker(s) or others. Avoid using the same Part 2, Form 2101 for multiple facilities. Ensure that work area hazards, specific to the facility or work location are identified and controlled. Specify the facility controls and preventive measures that must be implemented by the worker(s) to protect against the site hazards as well as any special training required.

Work Area Hazards/Concerns Identify site hazards and concerns that could potentially affect the worker(s) or others.	Work Area Hazard Present	Facility Controls/ Preventive Measures/ Bounding Conditions Specify preventive measures, controls and bounding conditions for each site hazard	Reference Documents List permits, operating manuals, and other reference procedures	Training and Qualification List training requirements (P300, Integretated Work Management, Section 6.1)
🗌 No Work Area Hazards				
orm 2101 (12/17)				Page 1

Revision:GEffective Date:10/28/2020

Attachment B Integrated Work Document (IWD) Part 2 (Non Tenant) (cont'd

Work Area Hazards/Concerns Identify site hazards and concerns that could potentially affect the worker(s) or others.	Work Area Hazard Present	A HAZARDS & CONTROLS Facility Controls/ Preventive Measures/ Bounding Conditions Specify preventive measures, controls and bounding conditions for each site hazard	Reference Documents List permits, operating manuals, and other reference procedures	Training and Qualification List training requirements (P300, Integretated Work Management, Section 6.1)
Ionizing Radiation Work in posted radiological areas, work with radioactive materials, or work on or near radiation producing devices. Specify Hazard:	🗌 Yes 🖾 No			
Worker Exposure Working near non-ionizing radiation, beryllium, noise, chemicals, hazardous biological materials, lead, asbestos, temperature/humidity extremes, or high explosives. Specify Hazards:	🗆 Yes 🛛 No			
Energized and Operative Systems Working near energized electrical parts, pressure systems, steam lines; near unprotected belts, pulleys, chains or rotating equipment; fuel fired equipment other than vehicles; or spark or flame producing operations. Specify Hazards:	🗆 Yes 🖾 No			
Confined Spaces Entry into tanks, manholes, cooling towers, sumps, or any other area with potentially low oxygen concentration or other hazards such as toxic vapors or engulfment. Specify Hazards:	🗆 Yes 🖾 Na			
Elevated Work Surface Elevated work when fall protection is not provided by conventional handrail systems or required per P101-20, <i>Fall Protection Program</i>	🗆 Yes 🖾 No			
Environmental Impact Activities conducted in areas containing potential release site, contaminated soil, sensitive species, watercourse wetlands, floodplain, historical/archeological sites, or other work area condition that can be impacted by or can impact the environment. Specify Hazards:	🗆 Yes 🖾 No			

Form 2101 (12/17)

Revision:GEffective Date:10/28/2020

Attachment B Integrated Work Document (IWD) Part 2 (Non Tenant) (cont'd

Work Area azard Present	controls and bounding conditions for each site hazard	List permits, operating manuals, and other reference procedures	Training and Qualification List training requirements (P300, Integretated Work Management, Section 6.1)
Yes 🗌 No	Q or L Clearance or Escorted	P202-1 Security Areas, Property Protection Areas, and General Access Areas	U-Train 1425 Annual Security Refresher
Yes No			
	Yes No	zzard Present each sile hazard Yes No Q or L Clearance or Escorted	zzard Present each site hazard reference procedures Yes ☐ No Q or L Clearance or Escorted P202-1 Security Areas, Property Protection Areas, and General Access Areas

Form 2101 (12/17)

Attachment B Integrated Work Document (IWD) Part 2 (Non Tenant) (cont'd

				Form 2101				
016				Non-Tenant DIS Activity Form				
(FOD) must determine the facility entry		equirements and identify the Enviro	onment, Safety, Health (ESH)/Security and Safeguards				
TA 15	Bldg. 312	Room All Interior Spaces	Other Location					
Name Edward Jacquez	Phone 7-8170	Pager 4-6188	Email ebj@lanl.gov					
irements (Check one or more of the	e following)	I S I I I I I I I I I I I I I I I I I I						
uirements	FOD-designated fac	cility Point-of-Contact must sign IW	/D Part 3					
Plan of the Day/Plan of the Week (POTD/POTW)		Check in at Start of Work Work-Area Training Required						
Security Clearance Requirements		Work must be Scheduled Check in Daily						
Co-located Hazards/Concerns		Other Security Requirements (ex.: Cellphone, No Foreign Nationals, etc.)						
Check out at End of Work		Quality Issues Check out Daily						
Escort Required		Review under Authorization Basis (AB)/Safety Basis/Unreviewed Safety Question (USQ)						
_			and the second second second					
oved on the DARHT Plan of the Day (POI	D). Workers must che	ck/sign in and out on a daily basis.						
any activities that require:		the second second second second		and the second sec				
to the facility or work location are iden	ntified and controlled							
		A HAZARDS & CONTROLS						
Hazards/Concerns terns that could potentially affect the (s) or others.	Work Area Hazard Present	Facility Controls/ Preventive Measures/ Bounding Conditions Specify preventive measures, controls and bounding conditions for each site hazard	Reference Documents List permits, operating manuals, and other reference procedures	Training and Qualification List training requirements (E300_Inteoretated_Work Management_Section 6.1)				
		Accelerator Halls are exclusion areas during accelerator operations.						
	RY FOD Requirem Revision #: G Revision #: G (FOD) must determine the facility entry ociated with the specific activity location TA TA TA Name Edward Jacquez airements (Check one or more of the uirements (Check one or more of the uirements Maximum Check one or more of the uirements Week (POTD/POTW) X ements X arms X stress X	RY Integrated FOD Requirements and App FOD Requirements and App Revision #: G (FOD) must determine the facility entry and coordination processing with the specific activity location. TA Bldg. 15 312 Name Phone Edward Jacquez 7-8170 uirements (Check one or more of the following) uirements uirements FOD-designated fac Week (POTD/POTW) Check in at Start of emore of the security Requirements ements Other Security Requirements Quality Issues Review under Authors s:	RY Integrated Work Document (IWD) FOD Requirements and Approval for Entry and Area	RY Integrated Work Document (IWD) Part 2, FOD Requirements and Approval for Entry and Area Hazards and Control				

Revision:GEffective Date:10/28/2020

Attachment B Integrated Work Document (IWD) Part 2 (Non Tenant) (cont'd

S&S WOR	RK ARE	A HAZARDS & CONTROLS		
		Facility Controls/ Preventive Measures/ Bounding Conditions Specify preventive measures, controls and bounding conditions for each site hazard	Reference Documents List permits, operating manuals, and other reference procedures	Training and Qualification List training requirements (P300, Integretated Work Management, Section 6.1)
Y 🗌 Yes	No No			
🗌 Yes	No No			
				· · · · · · · · · · · · · · · · · · ·
Ves	No No			
1.11				
☐ Yes	No No			
Yes	⊠ No			· · · · · · · · · · · · · · · · · · ·
X Yes	No No	Q-Cleared or escorted	· · · · · · · · · · · · · · · · · · ·	
	No			
	Hazard I Hazard I Yes Yes Yes Yes N Yes	Yes ⊠ No Yes ⊠ No Yes ⊠ No Yes ⊠ No Yes ⊠ No	Work Area Hazard Present Preventive Measures/ Bounding Conditions Specify preventive measures, controls and bounding conditions for each site hazard IV Yes No IV Yes No	Work Area Hazard Present Preventive Measures/ Bounding Conditions Specify preventive measures, controls and bounding conditions for each site hazard Reference Documents List permits, operating manuals, and other reference procedures V Yes No □ Yes No □ Yes No □ Yes No

Form 2101 (12/17)

SAVE PRINT CLEAR FORM

Page 2 of 2

Attachment B Integrated Work Document (IWD) Part 2 (Non Tenant) (cont'd

NATIONAL LABORAT UST 1943 WFO-IWD-00	FOD Requirem		l Work Document (IWD) roval for Entry and Area		Form 2101 Non-Tenant DIS Activity Form
WD No./Work Request No: _ The Facility Operation Directo	Revision #: G or (FOD) must determine the facility entr	v and coordination r	equirements and identify the Envir	onment Safety Health (ESH	VSecurity and Safequards
(S&S) hazards and controls a	ssociated with the specific activity locati	on.			proceeding and calloguards
FOD WFO	TA 15	Bldg. 312	Room N/A	Other Location Firing Point, to include ber	m and other exterior areas
FOD Designated Facility Point-of-Contact	Name Edward Jacquez	Phone 7-8170	Pager 4-6188	Email ebj@lanl.gov	
Entry and Coordination Re	quirements (Check one or more of th	e following)			
This IWD Part 2 does not addres nstructions: In the block bel nat work area hazards, speci	he Week (POTD/POTW)	Check in at Start of Work must be Sche Other Security Req Quality Issues Review under Auth D). Workers must che d potentially affect t thified and controlle	duled Check in Daily uirements (ex.: Cellphone, No Fore Check out Daily orization Basis (AB)/Safety Basis/U ck/sign in and out on a daily basis.	ing Required sign Nationals, etc.) Jnreviewed Safety Question	1 for multiple facilities. Ensure
forker(s) to protect against tr			A HAZARDS & CONTROLS		
Identify site hazards and co	a Hazards/Concerns ncems that could potentially affect the er(s) or others.	Work Area Hazard Present	Facility Controls/ Preventive Measures/ Bounding Conditions Specify preventive measures, controls and bounding conditions for each site hazard	Reference Documents List permits, operating manuals, and other reference procedures	Training and Qualification List training requirements (P300, Integretated Work Management, Section 6.1)
No Work Area Hazards				1000 - 1 YOLLY -	
Ionizing Radiation Work in posted radiological a	areas, work with radioactive materials, producing devices.	X Yes INO	Accelerator Halls are exclusion areas during accelerator operations. These areas will be locked. In		

Revision:GEffective Date:10/28/2020

Attachment B Integrated Work Document (IWD) Part 2 (Non Tenant) (cont'd

Work Area Hazards/Concerns Identify site hazards and concerns that could potentially affect the worker(s) or others.	Work Area Hazard Present	Facility Controls/ Preventive Measures/ Bounding Conditions Specify preventive measures, controls and bounding conditions for each site hazard	Reference Documents List permits, operating manuals, and other reference procedures	Training and Qualification List training requirements (P300. Integretated Work Management, Section 6.1)
Worker Exposure Working near non-ionizing radiation, beryllium, noise, chemicals, hazardous biological materials, lead, asbestos, temperature/humidity extremes, or high explosives.	🗌 Yes 🛛 No			
Specify Hazards:				
Energized and Operative Systems Working near energized electrical parts, pressure systems, steam lines; near unprotected belts, pulleys, chains or rotating equipment. fuel fired equipment other than vehicles; or spark or flame producing operations.	Yes X No			
Specify Hazards:				
Confined Spaces Entry into tanks, manholes, cooling towers, sumps, or any other area with potentially low oxygen concentration or other hazards such as toxic vapors or engulfment.	🗌 Yes 🛛 No			
Specify Hazards:				
Elevated Work Surface Elevated work when fall protection is not provided by conventional nandrail systems or required per P101-20, <i>Fall Protection Program</i>	Yes 🛛 No			
Environmental Impact Activities conducted in areas containing potential release site, contaminated soil, sensitive species, watercourse wetlands, floodplain, historical/archeological sites, or other work area condition that can be impacted by or can impact the environment. Specify Hazards:	🗌 Yes 🛛 No			
Security Requirements Specify:	Yes No	Q-Cleared or escorted		
Other Hazards Specify:	Yes No			
I have verified that the hazards identified above adequately identify the	ne area hazards and	t that the IWM process has been a	pplied appropriately.	1

Form 2101 (12/17)

SAVE PRINT CLEAR FORM

Page 2 of 2

Attachment B Integrated Work Document (IWD) Part 2 (Non Tenant) (cont'd

A					Form 2101
LOS Alame NATIONAL LABORAT 257, 1943 WFC WD No./Work Request No:	OBY		l Work Document (IWD) roval for Entry and Area		Non-Tenant DIS Activity Form
	or (FOD) must determine the facility entrussociated with the specific activity location		equirements and identify the Enviro	onment, Safety, Health (ESH	l)/Security and Safeguards
FOD	TA 15	Bldg. 662	Room	Other Location	
FOD Designated Facility Point-of-Contact	Name Edward Jacquez	Phone 7-8170	Pager 4-6188	Email ebj@lanl.gov	
This IWD Part 2 does not addres	K	Quality Issues Review under Auth D). Workers must sign		Inreviewed Safety Question	
	fic to the facility or work location are ide ne work area hazards, and also special t		d. Specify the facility controls and p	preventive measures that mu	ist be implemented by the
			A HAZARDS & CONTROLS		
	a Hazards/Concerns incerns that could potentially affect the er(s) or others.	Work Area Hazard Present	Facility Controls/ Preventive Measures/ Bounding Conditions Specify preventive measures, controls and bounding conditions for each site hazard	Reference Documents List permits, operating manuals, and other reference procedures	Training and Qualification List training requirements (P300, Integretated Work Management, Section 6.1)
		1	The second secon		

Revision:GEffective Date:10/28/2020

Attachment B Integrated Work Document (IWD) Part 2 (Non Tenant) (cont'd

Work Area azard Present	Facility Controls/ Preventive Measures/ Bounding Conditions Specify preventive measures, controls and bounding conditions for each site hazard	Reference Documents List permits, operating manuals, and other reference procedures	Training and Qualification List training requirements (P300, Integretated Work Management, Section 6.1)
1 Van 17 11-	· · · · · · · · · · · · · · · · · · ·		
Yes 🛛 No			
Yes 🛛 No			
]Yes 🛛 No			
Yes 🗌 No	Q-cleared, or escorted		
Yes No	Exclusion area locked with engineered controls		
]	Yes No Yes No Yes No Yes No Yes No	Yes No Yes No Yes No Yes No Q-cleared, or escorted Yes No Exclusion area looked with eighnered controls sea hazards and that the IWM process has been a ADD ACOLIEZ / (Affiliato)	Yes No Yes No Yes No Yes No Yes No Pes No Pes No Pes No Pes No Evaluation area tooked with engineered controls ea hazards and that the IWM process has been applied appropriately.

Form 2101 (12/17)

SAVE PRINT CLEAR FORM

Page 2 of 2

Attachment C Integrated Work Document (IWD) Part 2 (Tenant)

				Form 2102
				nd Controls Tenant Activity Form
: WFO-IWD-0016, Spill	Response and Clean Up	o in Weapons Facilities	Operations (WFO) Areas	Revision #: G
acility entry and coordinat	ion requirements and ide	entify the ESH/S&S ha	zards and controls associat	ed with the activity location.
TA 6, 8 , 9, 11, 14, 15, 16	, 22, 36, Bldg. All excep	t WETF & Room	All Other Loc	
Facility Point-of-Contact Designee		Pager	Email jbranch@ etmedina(rfarmer@l	@lanl.gov
Requirements D FO Ch lled D Ch concerns C Ch	D designated facility poi eck in at Start of Work eck in Daily eck out at End of Work	nt-of-contact must sigr Work-Area Traini Escort Required Quality Issues	ng Required 🛛 Security Other S	y Clearance Requirements ecurity Requirements ENTRY to Confined Spaces under
	b: WFO-IWD-0016, Spill acility entry and coordinati TA 6, 8, 9, 11, 14, 15, 16 37, 39, 40, 49, 67 Name John Branch, WFO OM Designee Erlinda Gonzales, WFO Designee Ritanne Campbell, WFO Designee Requirements (Check o n Requirements FO Manual Check o n Requirements Check o n Check o Check o Chec	FOD Requirements and A c: WFO-IWD-0016, Spill Response and Clean Up acility entry and coordination requirements and id Bldg. A 6, 8, 9, 11, 14, 15, 16, 22, 36, 37, 39, 40, 49, 67, 68 Bldg. Name Phone 412-9696 John Branch, WFO OM Erlinda Gonzales, WFO OM 500-7878 Ritance Campbell, WFO OM 500-7878 500-7878 Requirements (Check one or more of the folloon Requirements FOD designated facility point Check in at Start of Work Ided Check in Daily Check out at End of Work Check out at End of Work	FOD Requirements and Approval for Entry SC WFO-IWD-0016, Spill Response and Clean Up in Weapons Facilities acility entry and coordination requirements and identify the ESH/S&S hat TA 6, 8, 9, 11, 14, 15, 16, 22, 36, 37, 39, 40, 49, 67, 68 Bldg. Room Name Phone Pager John Branch, WFO OM 412-9696 412-8133 Erlinda Gonzales, WFO OM 500-7878 500-7878 Requirements FOD designated facility point-of-contact must sign Check in at Start of Work Work-Area Traini Ided Check in Daily Escort Required Concerns Check out at End of Work Quality Issues	FOD Requirements and Approval for Entry and Area Hazards and controls associated for entry and coordination requirements and identify the ESH/S&S hazards and controls associated for a state of the following): TA Bidg. Room All Other Loc TA 6, 8, 9, 11, 14, 15, 16, 22, 36, 37, 39, 40, 49, 67, 68 Bidg. All except WETF & All Other Loc Name Phone Pager Email ibranch@ietmediate John Branch, WFO OM Phone 412-9696 412-8133 etmedinate Erlinda Gonzales, WFO OM 500-7878 rfarmer@i rfarmer@i Requirements FOD designated facility point-of-contact must sign IWD Part 3 Security Check in at Start of Work Work-Area Training Required Security Ided Check out at End of Work Quality Issues

Instructions: In the block below, provide facility or work-area information needed by the workers on this activity. (Things to consider include specific work-area hazards and controls, potential conflicts with co-located activities, or any facility restrictions on the activity.) Identify relevant reference documents and any training required.

Facility/Work-Area Information Relevant to this Activity

Work within VTRs requires check-in first with appropriate Access Control Office and coordination with respective Program Office to ensure coordination with programmatic activities.

Follow ALL Postings:

TA-6

ACCESS CONTROL: Work within TA-6 requires check-in first with TA-40-1 ACO for access to fire roads, canyons, etc. Inform ACO what locations and routes will be taken while on site (use a map of area if possible).

Form 2102 (4/12)

Page ____ of ____

Attachment C Integrated Work Document (IWD) Part 2 (Tenant) (cont'd)

Specify Hazards: PRS, sensitive species-e.g. spotted owl, historical/archeological sites, and waste generation.
 PRS exists. Notify WFO Environmental Generalist, if required. Archeological sites exist within open areas. Do not disturb any marked archeological sites. If entry into any area required contact Environmental
 Ancheological sites exist within open areas. Do not distuib any marked archeological sites. In entry into any area required contact Environmental Stewardship Group.
 Work during threatened and endangered species seasons will restricts outdoor activities.
Excavation Permit for soil disturbance activities
TA-8
ACCESS CONTROL: Must check-in with TA-8-21 Access Control to sign in locally and receive a briefing on site hazards AND to inform ACO what locations
and routes will be taken while on site (use a map of area if possible).
CAUTION: This area uses Radiography equipment – specifically Buildings TA-8-22, TA-8-23, TA-8-70, and TA-8-120. Work group shall adhere to all local ACO instructions as to where access is allowed and where it is restricted, e.g. areas around buildings performing radiography.
Specify Hazards: Radiography Activities, High Explosives Area, PRS, sensitive species-e.g. spotted owl, historical/archeological sites, and waste generation. PRS exists. Notify WFO Environmental Generalist. if required.
 Archeological sites exist within open areas. Do not disturb any marked archeological sites. If entry into any area required contact Environmental Stewardship Group.
 Work during threatened and endangered species seasons will restricts outdoor activities. Excavation Permit for soil disturbance activities
TA-9
1A-9 ACCESS CONTROL: Work within TA-9 requires check-in first with TA-9 ACO for access.
CAUTION: This area is a HE Area. Work group shall adhere to all TA-9 local ACO instructions as to where access is allowed and where it is restricted, e.g.
areas around HE facilities and magazines.
Specify Hazards: High Explosives Area, PRS, sensitive species-e.g. spotted owl, historical/archeological sites, and waste generation.
PRS exists. Notify WFO Environmental Generalist, if required.
Work during threatened and endangered species seasons restricts outdoor activities. Excavation Permit for soil disturbance activities
Excavation Femilit for soil disturbance activities
ACCESS CONTROL: Work within TA-11 requires check-in first with TA-16 ACO for access to fire roads, canyons, etc. AND to inform ACO what locations and routes will be taken while on site (use a map of area if possible).
CAUTION: This area has resumed High Explosive Operations. Work group shall adhere to all local ACO instructions and posted area as to where access is
allowed and where it is restricted.
ESH CONCERNS: Entry into HE and DU contaminated areas may be required. Notify the TA-16 ACO prior to accessing areas to ensure area is safe for
activities and to coordinate RCT support.
Specify Hazards: High Explosives Area, PRS, sensitive species-e.g. spotted owl, historical/archeological sites, and waste generation.
 Follow all postings
PRS exists. Notify WFO Environmental Generalist, if required.
 Archeological sites exist within open areas. Do not disturb any marked archeological sites. If entry into any area required contact Environmental Stewardship Group.
Stewardship Group.

Form 2102 (4/12)

Page ___ of ___

Attachment C Integrated Work Document (IWD) Part 2 (Tenant) (cont'd)

	 Work during threatened and endangered species seasons will restricts outdoor activities. Excavation Permit for soil disturbance activities
	TA-14 ACCESS CONTROL: Work within TA-14 requires check-in first with TA-15 ACO for access to fire roads, canyons, etc. AND to inform ACO what locations and routes will be taken while on site (use a map of area if possible). CAUTION: This area is a HE Firing Site Area. Work group shall adhere to all local ACO insructions as to where access is allowed and where it is restricted, e.g. areas around firing sites.
	 ESH CONCERNS: Entry into HE and DU contaminated areas may be required. Notify the TA-15 ACO and area Group office prior to accessing area to ensure area is safe for activities and to coordinate RCT support. Follow all postings Contact applicable SME as needed: IH, RCT, ExSO Specify Hazards: High Explosives Area, PRS, sensitive species-e.g. spotted owl, historical/archeological sites, and waste generation. PRS exists. Notify WFO Environmental Generalist, if required. Archeological sites exist within open areas. Do not disturb any marked archeological sites. If entry into any area required contact Environmental Stewardship Group. Work during threatened and endangered species seasons will restricts outdoor activities. Excavation Permit for soil disturbance activities
	TA-15 ACCESS CONTROL: Work within TA-15 requires check-in first with TA-15 ACO for access to fire roads, canyons, etc. and to get a radio AND to inform ACO what locations and routes will be taken while on site (use a map of area if possible). CAUTION: This area is a HE Firing Site Area. Work group shall adhere to all local ACO insructions as to where access is allowed and where it is restricted, e.g. areas around firing sites.
	ESH CONCERNS: Entry into HE, beryllium, and DU contaminated areas may be required. Notify the TA-15 ACO and area Group office prior to accessing area to ensure area is safe for activities and to coordinate RCT support.
	 Specify Hazards: High Explosives Area, PRS, sensitive species-e.g. spotted owl, historical/archeological sites, and waste generation. PRS exists. Notify WFO Environmental Generalist, if required. Archeological sites exist within open areas. Do not disturb any marked archeological sites. If entry into any area required contact Environmental Stewardship Group. Work during threatened and endangered species seasons will restricts outdoor activities. Excavation Permit for soil disturbance activities
	TA-16 ACCESS CONTROL: Work within TA-16 requires check-in first with TA-16 ACO for access to fire roads, canyons, etc. and to get a radio AND to inform ACO what locations and routes will be taken while on site (use a map of area if possible). CAUTION: This area is a High Explosives Area. Work group shall adhere to all local ACO insructions as to where access is allowed and where it is restricted, e.g. areas around firing sites.
L	Specify Hazards: High Explosives Area, PRS, sensitive species-e.g. spotted owl, historical/archeological sites, and waste generation. PRS exists. Notify WFO Environmental Generalist, if required. Form 2102 (4/12) Page of
	rage0_

Page ____ or ____

Attachment C Integrated Work Document (IWD) Part 2 (Tenant) (cont'd)

 Archeological sites exist within open areas. Do not disturb any marked archeological sites. If entry into any area required contact Environmental Stewardship Group. Work during threatened and endangered species seasons will restricts outdoor activities.
Excavation Permit for soil disturbance activities
TA-22 ACCESS CONTROL: Work within TA-22 requires check-in first with TA-22 ACO for access to fire roads, canyons, etc. and to get a radio AND to inform ACO what locations and routes will be taken while on site (use a map of area if possible).
CAUTION: This area is a High Explosives Area. Work group shall adhere to all local ACO insructions as to where access is allowed and where it is restricted, e.g. areas around HE facilites and magazines.
Specify Hazards: High Explosives Area, PRS, sensitive species-e.g. spotted owl, historical/archeological sites, and waste generation. PRS exists. Notify WFO Environmental Generalist, if required.
Archeological sites exist within open areas. Do not disturb any marked archeological sites. If entry into any area required contact Environmental Stewardship Group.
 Work during threatened and endangered species seasons will restricts outdoor activities. Excavation Permit for soil disturbance activities
TA-36
ACCESS CONTROL: Work within TA-36 requires check-in first with TA-15 ACO for access to fire roads, canyons, etc. and to get a radio AND to inform ACO what locations and routes will be taken while on site (use a map of area if possible).
CAUTION: This area is a Firing Site Area. Work group shall adhere to all local ACO insructions as to where access is allowed and where it is restricted, e.g. areas around firing sites.
ESH CONCERNS: Entry into HE, beryllium, and DU contaminated areas may be required. Notify the TA-15 ACO prior to accessing area to ensure area is safe for activities and to coordinate SME support (ExSO, IH, RCT).
Specify Hazards: High Explosives Area, PRS, sensitive species-e.g. spotted owl, historical/archeological sites, and waste generation. PRS exists. Notify WFO Environmental Generalist, if required.
Archeological sites exist within open areas. Do not disturb any marked archeological sites. If entry into any area required contact Environmental Stewardship Group.
 Work during threatened and endangered species seasons will restricts outdoor activities. Excavation Permit for soil disturbance activities
TA-37 ACCESS CONTROL: Work within TA-37 requires check-in first with TA-16 ACO for access to fire roads, canvons, etc. and to get a radio AND to inform ACO
what locations and routes will be taken while on site (use a map of area if possible). CAUTION: This area is a High Explosives Magazine Area
Specify Hazards: High Explosives Area, PRS, sensitive species-e.g. spotted owl, historical/archeological sites, and waste generation. PRS exists. Notify WFO Environmental Generalist, if required.
Archeological sites exist within open areas. Do not disturb any marked archeological sites. If entry into any area required contact Environmental Stewardship Group.
Form 2102 (4/12) Page of

Attachment C Integrated Work Document (IWD) Part 2 (Tenant) (cont'd)

 Work during threatened and endangered species seasons will restricts outdoor activities. Excavation Permit for soil disturbance activities
TA-39 ACCESS CONTROL: Work within TA-39 requires check-in first with TA-39 ACO for access to fire roads, canyons, etc. and to get a radio AND to inform ACO what locations and routes will be taken while on site (use a map of area if possible). CAUTION: This area is a HE Firing Site Area. Work group shall adhere to all local ACO insructions as to where access is allowed and where it is restricted, e.g. areas around firing sites.
ESH CONCERNS: Entry into HE and DU contaminated areas (off-road) may be required. Notify the TA-39 ACO and area Group office prior to accessing area to ensure area is safe for activities and to coordinate RCT support.
 Specify Hazards: High Explosives Area, PRS, sensitive species-e.g. spotted owl, historical/archeological sites, and waste generation. PRS exists. Notify WFO Environmental Generalist, if required. Archeological sites exist within open areas. Do not disturb any marked archeological sites. If entry into any area required contact Environmental Stewardship Group. Work during threatened and endangered species seasons will restricts outdoor activities. Excavation Permit for soil disturbance activities
TA-40 ACCESS CONTROL: Work within TA-40 requires check-in first with TA-40 ACO for access to fire roads, canyons, etc. and to get a radio AND to inform ACO what locations and routes will be taken while on site (use a map of area if possible). CAUTION: This area is a HE Firing Site Area – specifically buildings TA-40-5, TA-40-9, TA-40-9, and TA-40-15. Work group shall adhere to all local ACO insructions as to where access is allowed and where it is restricted, e.g. areas around firing sites.
Specify Hazards: Designated/Posted Contamination Areas: Beryllium, Depleted Uranium, High Explosive Area, PRS, sensitive species-e.g. spotted owl, historical/archeological sites, and waste generation. Follow all postings
 PRS exists. Notify WFO Environmental Generalist, if required. Archeological sites exist within open areas. Do not disturb any marked archeological sites. If entry into any area required contact Environmental Stewardship Group. Work during threatened and endangered species seasons will restricts outdoor activities. Excavation Permit for soil disturbance activities
TA-49 ACCESS CONTROL: Work within TA-49 requires check-in first with TA-16 ACO for access to fire roads, canyons, etc. and to get a radio AND to inform ACO what locations and routes will be taken while on site (use a map of area if possible). Accessing the HE Area within TA-49 also requires check in at TA-49-113.
Specify Hazards: Designated/Posted Contamination Areas: Beryllium, Depleted Uranium, High Explosive Area, PRS, sensitive species-e.g. spotted owl, historical/archeological sites, and waste generation. Follow all postings DRS evides Nettic WEO Environmental Constraint if convised
PRS exists. Notify WFO Environmental Generalist, if required.

Form 2102 (4/12)

Page ____ of ____

Revision:GEffective Date:10/28/2020

Attachment C Integrated Work Document (IWD) Part 2 (Tenant) (cont'd)

 Archeological sites exist within open areas. Do not disturb any marked archeological sites. If entry into any area required contact Environmental Stewardship Group. Work during threatened and endangered species seasons will restricts outdoor activities. Excavation Permit for soil disturbance activities
TA-67 ACCESS CONTROL: Work within TA-67 requires check-in first with TA-15 ACO for access to fire roads, canyons, etc. and to get a radio AND to inform ACO what locations and routes will be taken while on site (use a map of area if possible). CAUTION: This area is near a Firing Site Area. Work group shall adhere to all local ACO insructions as to where access is allowed and where it is restricted, e.g. areas around firing sites.
 Specify Hazards: Designated/Posted Contamination Areas: Beryllium, Depleted Uranium, High Explosive, PRS, sensitive species-e.g. spotted owl, historical/archeological sites, and waste generation. Follow all postings PRS exists. Notify WFO Environmental Generalist, if required. Archeological sites exist within open areas. Do not disturb any marked archeological sites. If entry into any area required contact Environmental Stewardship Group. Work during threatened and endangered species seasons will restricts outdoor activities. Excavation Permit for soil disturbance activities
TA-68 ACCESS CONTROL: Work within TA-68 requires check-in first with TA-15 ACO for access to fire roads, canyons, etc. and to get a radio AND to inform ACO what locations and routes will be taken while on site (use a map of area if possible). CAUTION: This area is near a Firing Site Area. Work group shall adhere to all local ACO insructions as to where access is allowed and where it is restricted, e.g. areas around firing sites.
 Specify Hazards: Designated/Posted Contamination Areas: Beryllium, Depleted Uranium, High Explosive, PRS, sensitive species-e.g. spotted owl, historical/archeological sites, and waste generation. Follow all postings Contact applicable SME as needed: IH, RCT, ExSO PRS exists. Notify WFO Environmental Generalist, if required. Archeological sites exist within open areas. Do not disturb any marked archeological sites. If entry into any area required contact Environmental Stewardship Group. Work during threatened and endangered species seasons will restricts outdoor activities. Excavation Permit for soil disturbance activities
ABNORMAL EVENTS: Any injury, accident, spill, off normal occurrence, etc. MUST be reported immediately to the WFO-FOD Duty Officer @ 664-2926 AND the Access Control Office.
Reference Documents: P101-8, Explosives Safety; P121 Radiation Safety; P101-21 Chronic Beryllium Disease Prevention Program, WFO-OP-1137 WFO Lightning Threat Actions, WFO-BEP-378 WFO Building Emergency Plan
Training Requirements: Per: WFO-IWD-0016, Spill Response and Clean Up in Weapons Facilities Operations (WFO) Areas, Site Specific Training for ALL areas

Form 2102 (4/12)

Page ___ of ___

Attachment C Integrated Work Document (IWD) Part 2 (Tenant) (cont'd)

	FOD Approval	
I have verified that the hazards identified above adequately identify t FOD or Representative (Signature/Z #/Date) Approval Required _	he area hazards and that the IWM process has been applied appropriately. Digitally signed by JOHN BRANCH JOHN BRANCH (Affiliate) (Affiliate) Date: 2020:10:21 16:52:29-06'00'	
Date Approval Expires: Upon Expiration of WFO-IWD-0016. Spill Re	sponse and Clean Up in Weapons Facilities Operations (WFO) Areas, Rev. G	

Form 2102 (4/12)

Page ____ of ____


Spill Response and Clean Up in Weapons Facilities Operations (WFO) Areas

MATIONAL LABORATORY

Document No.:	WFO-IWD-00016
Revision:	G
Effective Date:	10/28/2020

Attachment D Integrated Work Document (IWD) Part 3 Validation and Work Release Validation and Work Release

Form 2103



• IWD #WFO-IWD-0016 Revision #: G Work Release By signing below, I verify this activity is compatible with current facility configuration and operating conditions. FOD designated Operations Manager or other facility point of contact for work area JOHN BRANCH (Affiliate) Signature/Z#/Date (If required by FOD): _ Note: For Standing IWD, release may be given concurrently with signatures on Fart 2. Date: 2020.10.27 12:03:47 -06'00' By signing below, I have verified the following: I have verified authorization by ensuring approval signatures of the RLM and FOD. I have jointly conducted a validation walkdown with workers to confirm the IWD can be performed as written, and that required initial conditions and other prerequisites are in place. The assigned workers are authorized and are competent to perform the work in a safe, secure, and environmentally responsible manner I have conducted the pre-job briefing, and all workers (including support workers) have been briefed. I have ensured coordination with any required FOD work-area representatives (e.g., area work coordinators). PIC (Signature/Z#/Date) Required: Alternate PIC Signatures acknowledges PIC authority is assumed for the first time. (Note: Alternate PICs are required to sign only once, but formal handoff includes conferring with previous PIC to obtain all required information associated with the handoff.) Alternate PIC (Signature/Z#/Date) Required: Alternate PIC (Signature/Z#/Date) Required: Pre-Job Brief Content What are the critical steps* or phases of this activity? How can we make a mistake at that point? What is the worst thing that can go wrong? • What controls, preventive measures, and bounding conditions are needed? What work permits are required and how will we meet their requirements? What are the handoffs and coordination requirements among workers and multiple PICs?

- Are there hold-points including those that require sign-offs?
- What are the pause/stop work responsibilities and expectations (e.g., for unanticipated conditions or hazards)?
- How would we respond to alarms and emergencies?
- Are there lessons learned from previous similar work?
- Is other information needed to perform this activity in a safe, secure, and environmentally responsible manner?
 Does everyone agree to the work tasks/steps, hazards, and controls and commit to follow them?

* "Critical steps occur anytime human performance involves a substantial transfer of energy, or movement of solids, liquids, and gases, or the transmission of data and information that , if not performed under control, could cause serious harm to one or more important assets." (Performance Improvement, vol. 53, no. 9, October 2014)

Form 2103 (7/17)

Page 51 of 53

Spill Response and Clean Up in Weapons Facilities Operations (WFO) Areas

Document No.:	WFO-IWD-00016
Revision:	G

Effective Date: 10/28/2020

IWD #WFO-IWD-0016

 $Revision \, \#: G \quad \text{Work Release}$

Pre-Job Brief Attendance Roster

By signing below **as required**, I agree to the following:

- I agree to follow the work steps and implement the controls as written as applicable to my work assignments.
- I agree to pause/stop work when conditions or hazards change or when I encounter unexpected conditions during the execution of work, or when work cannot be performed as written, or instructions become unclear during execution.
- I confirm that I am authorized, qualified, and fit to perform the work.

Marker (Circeture /7#/Dete)	Morker (Cimeture /7#/Deta)
Worker (Signature/Z#/Date)	Worker (Signature/Z#/Date)
Marker (Circeture 774/Data)	Warker (Cirreture (74/Dete)
Worker (Signature/Z#/Date)	Worker (Signature/Z#/Date)
Worker (Signature/Z#/Date)	Worker (Signature/Z#/Date)
Worker (Signature/Z#/Date)	Worker (Signature/Z#/Date)
······································	
Worker (Signature/Z#/Date)	Worker (Signature/Z#/Date)
Worker (Signature/Z#/Date)	Worker (Signature/Z#/Date)
Worker (Signature/Z#/Date)	Worker (Signature/Z#/Date)

Spill Response and Clean Up in Weapons Facilities Operations (WFO) Areas Document No.: WFO-IWD-0016 Revision: G

Effective Date: 10/28/2020

Attachment E Integrated Work Document (IWD) Part 4, (Feedback/Post Job Reviews)

IWD #: WFO-IWD-0016 Revision #: G

Feedback of ongoing activities/post job review with the workers and Person in Charge (PIC) should include the following:

- identify inefficiencies, problems during the activity, coordination issues, unanticipated conditions, near misses; and
- develop recommendations for improvement.

A post-job review with the workers and PIC should include the following:

- verify that the activity is complete and make notifications in accordance with Facility Operations Director (FOD) requirements; and
- ensure that follow-through actions (e.g., clean-up, recycle, waste disposal, equipment removal, and secure storage) are completed.

Lessons learned; safety, secu	rity, and environmental issues	; coordination issues; and une	expected
conditions.			

Suggested improvements to enter into the Job Hazard Analysis (JHA) Tool, FootPrints, or other Integrated Work Control data bases supported by <u>Lessons Learned</u>.

Other recommendations for improvements to performing this activity. State the positive attributes of this activity.

Completion Statement

Name (print) of PIC/Z #:	Signature	Date

ATTACHMENT 25: WEAPONS FACILITIES OPERATIONS CLEAN FILL ACCEPTANCE AND REUSE PROCESS

WEAPONS FACILITIES	Document Number:	WFO-OP-415	
	Revision:	A	

Effective Date:	05/21/2020		Next Review Date:	05/21/2022	
Review Cycle:	🗌 l year	2 years	3 years		
Usage Mode:	Reference	🛛 UET	🗌 Both UET	& Reference	
Reviewed and App	roved for Use By:			-	·
SHERE Y	Printed Name	Z#	Org	Signature	Date
Responsible Line Manager, Acting	Robert Lechel	169521	DESH-WFO	ROBERT LECHEL (Affiliate)	Digitally signed by ROBERT LECHEL (Affiliate) Date: 2020.05.20 14:00:10 -06'00'
SME Reviewer	Holly Wheeler	118432	ЕРС-СР	HOLLY WHEELER (Affiliate)	Digkally signed by HOLLY WHEELER (Affiliate) Date 2020 05 21 11:15 19-06'00'
Approved and Autl	horized for Use By:				
	Printed Name	e Z#	Org	Signature	Date
Facility Operations Dir (FOD)	rector Brian L. Watkin	ıs 206831	WFO-DO	BRIAN WATKINS (Affiliate)	Digitally signed by BRIAN WATKINS (Affiliate) Date: 2020.05.21 12:03 07 -06'00'

For Document Control Team Reference:

USQ (applicable to WETF)

USI (applicable to DARHT) \boxtimes N/A

Users are responsible for verifying that they are working to the most current revision of a document.

Document No.: WFO-OP-415 Revision: A

Effective Date: 05/21/2020

REVISION HISTORY

Revision	Effective Date	Action	Description
А	05/21/2020	New Procedure	

TABE OF CONTENTS

Section	· · · · · · · · · · · · · · · · · · ·
	TITLE PAGE1
	REVISION HISTORY
	TABLE OF CONTENTS 3
1.0	PURPOSE
2.0	SCOPE
3.0	RESPONSIBILITIES
3.1	WFO High Explosives/Weapons Facilities (WFO-HE) Operations Manager (OM) and Deployed DESH-WFO Managers
3.2	DESH-WFO DEP
4.0	TRAINING AND QUALIFICATION
5.0	PROCEDURAL STEPS
5.1	Clean Fill Criteria
5.2	Acceptance of Material
5.3	Process for Acceptance
5.4	Characterization/Verification
5.5	Approval7
5.6	Transfer of Material
5.7	Requesting Clean fill
6.0	POST- PERFORMANCE ACTIVITY9
6.1	Records Processing
7.0	REFERENCES9
8.0	ACRONYMS/DEFINITIONS9
8.1	Acronyms
9.0	ATTACHMENTS9
ATTA	CHMENT 1 EXAMPLE WFO CLEAN FILL ACCEPTANCE REQUEST FORM10
ATTA	CHMENT 2 EXAMPLE WFO SOIL REUSE REQUEST FORM 11

1.0 PURPOSE

The purpose of this procedure is to describe Weapons Facilities Operations (WFO) processes for

a. Accepting transfer of material from a LANL technical area to the LANL TA-16 Stockpile Area

AND

b. Requesting transfer of material from the TA-16 Stockpile Area for use within WFO FOD.

2.0 SCOPE

This procedure does not replace or supersede ADESH-AP-TOOL-704.0, Construction and Demolition Debris. It provides additional details, including documentation required if material is to be accepted at the TA-16 Stockpile Area.

Persons or organizations generating material and requesting acceptance for its use as clean fill (Acceptance Material Generator) should first refer to the ADESH-AP-TOOL-704.0.

This procedure applies to WFO High Explosives/Weapons Facilities (WFO-HE) Operations Manager (OM), Deployed Environment, Safety, and Health (DESH)-WFO Deployed Environmental Professional (DEP), DESH-WFO Managers, WFO Maintenance and Site Services (MSS) personnel; clean fill material generators; clean fill material requestors.

3.0 RESPONSIBILITIES

3.1 <u>WFO High Explosives/Weapons Facilities (WFO-HE) Operations Manager (OM) and</u> <u>Deployed DESH-WFO Managers</u>

- Responsible for developing, maintaining and revising this procedure.
- Responsible for ensuring procedure compliance.

3.2 DESH-WFO DEP

- Responsible for evaluation, maintenance and follow up of this procedure.
- Complying with requirements of this procedure.
- Notifying supervisory personnel of conditions that could require corrective action.
- Issuing a PAUSE/STOP Work Order whenever warranted by conditions related to health or safety in accordance with P101-18, Procedure for Pause/Stop Work.

4.0 TRAINING AND QUALIFICATION

The following required reading must be completed prior to implementing this procedure:

WFO-OP-415, Weapons Facilities Operations Clean Fill Acceptance and Reuse Process

5.0 **PROCEDURAL STEPS**

WFO operates and maintains the TA-16 Stockpile Area for receipt, storage, and distribution of WFO clean fill. This section sets forth the requirements (a) for accepting material at the facility and (b) for accepting requests to use the material.

5.1 <u>Clean Fill Criteria</u>

- 1. Clean fill may contain the following materials only:
 - a. Soil, including top soil
 - b. Soil and gravel
 - c. Sand
 - d. Tufa (a soft mixture of silica, calcium carbonate, and/or volcanic ash)
- 2. Clean fill may **NOT** contain:
 - a. Pieces larger than 12 inches in diameter.
 - b. Material that has been subjected to a spill or release of chemical contaminants, e.g., petroleum products.
 - c. Material that has received prior treatment to remediate contamination.

AND/OR

d. Material containing land-clearing debris, construction and demolition debris, municipal solid waste, radioactive waste, hazardous waste, New Mexico special waste, or any other solid waste not meeting clean fill criteria.

5.2 Acceptance of Material

5.2.1 Acceptance Criteria

- 1. There must be a need for the material offered.
- 2. Material must meet the Clean Fill Criteria specified in Section 5.1.
- 3. All material analytical data will be screened to NMED Technical Background Document for Development of Soil Screening Levels.
- 4. The following documentation must be provided:
 - a. All projects will need to sample for the full Analytical Suite containing sample analysis or (if requested by deployed DESH-WFO DEP) results of material sampling.

OR

- b. Acceptable Knowledge (AK) Documentation, provided by Material Generator.
- **OR** (IF AK DOCUMENTATION IS NOT AVAILABLE)

c. Database Verification, performed by DESH-WFO DEP/Verifier, equivalent to acceptable AK documentation; see Section 5.4.1, Step 3 below.

5.3 <u>Process for Acceptance</u>

5.3.1 Material Generator

[1]	ACCESS WFO Clean Fill Acceptance Request Form (WFO-FORM-416).
[2]	OBTAIN and ATTACH :
	a. Analytical Report.
	b. Sampling results if requested by DESH-WFO DEP.
	c. Acceptable Knowledge (AK) documentation if available. DESH-WFO DEP can assist Material Generator with the form and attachments.
[3]	SUBMIT completed form and documentation to DESH-WFO DEP. Note: Form may be submitted to DESH-WFO DEP via e-mail.

5.4 <u>Characterization/Verification</u>

5.4.1 Deployed DESH-WFO DEP /Verifier

[1]	COMPLETE Characterization/Verification portion of WFO-FORM-416.
[2]	REVIEW Analytical Report data as follows:
	 Levels presented in Inorganic and Radionuclide Background Data for Soils, Canyon Sediments, and Bandelier Tuff at Los Alamos National Laboratory, Sept 22, 1998.
	b. If Toxicity Characteristic Leaching Procedure (TCLP) analytical data provided, compare to regulatory TCLP levels.
	c. NMED Technical Background Document for Development of Soil Screening Levels.
	d. Ensure that petroleum analytical results meet the following requirements:
	i. Benzene concentration ≤ 10 mg/kg.
	ii. Total benzene, toluene, ethyl benzene, and xylene isomer (BTEX) concentration \leq 50 mg/kg.
	iii. Total petroleum hydrocarbon (TRPH) concentration $\leq 100 \text{ mg/kg}$
	(i.e., is below New Mexico Special Waste levels)
[3]	If necessary, PERFORM review of applicable databases (EX-ID, GIS, PRS, PR-ID, and Stack Emission d/base). To evaluate Be, DU, and HE see IRT GIS Map and WFO-MAP-016, <i>WFO Large Area Map</i> .

Document No.: WFO-OP-415 Revision: A

Effective Date: 05/21/2020

[4]	If you have concerns (e.g., Haz, Rad, PCB, asbestos), based on these analytical results, refer Material Generator to WFO Waste Management Coordinator (WMC) for resolution.
	DO NOT proceed until all concerns are resolved.
[5]	PERFORM field inspection of material for size, etc. (See Section 5.1of this procedure.)
[6]	<u>IF</u> material is not acceptable (i.e., reusable), <u>THEN</u> reject it; explain reason for rejection.
[7]	IF you find that clean fill acceptance criteria are met, THEN:
	SIGN and DATE verification and SUBMIT form to WFO-HE Operations Manager (or designee).

5.5 <u>Approval</u>

5.5.1 WFO-HE Operations Manager (or designee)

[1]	DETERMINE and CONCUR that clean fill acceptance criteria have been met. Note: WFO-HE Operations Manager (or designee) determination is made by reviewing
	the analytical data, applicable AK documentation, applicable databases, and manager's knowledge of the operation that generated the material.
[2]	INDICATE concurrence/approval by SIGNING and DATING certification on form.
	IF not approved, THEN explain why.
[3]	RETURN form to DESH-WFO DEP.

5.6 <u>Transfer of Material</u>

5.6.1 DESH-WFO DEP

[1]	On approval by WFO-HE Operations Manager (or designee), ADVISE Material Generator that transfer of material has been approved
[2]	ASSIST with arrangements for transfer of material to TA-16 Stockpile Area.
[3]	CONFIRM transfer of material.
[4]	COMPLETE last section of WFO Clean Fill Acceptance Request Form (WFO-FORM-416).
[5]	SEND copy of form to Material Generator.
[6]	UPDATE WFO ESH server.
[7]	FILE documentation on the WFO ESH server in the Clean Fill folder.

5.7 <u>Requesting Clean fill</u>

5.7.1 Soil Requestor

[1]	ACCESS WFO Soil Reuse Request Form (WFO-FORM-417).
[2]	COMPLETE the top portion of the form and SUBMIT to DESH-WFO DEP. Note: Form may be submitted to DESH-WFO DEP via e-mail.

5.7.2 <u>DESH-WFO DEP</u>

[1]	Upon receipt of WFO Soil Reuse Request Form (WFO-FORM-417), DETERMINE if requested material is available.
[2]	IF the material is available, THEN arrange for safe transfer to Soil Requestor's site.
[3]	COMPLETE bottom section of WFO Soil Reuse Request Form.
	IF material was not transferred, THEN explain under Comments.
	SIGN and DATE WFO Soil Reuse Request form.
[4]	PROVIDE a copy of the signed form to the Soil Requestor and WFO-HE Operations Manager. Note: Copies of signed form may be sent to Soil Requestor and WFO-HE Operations Manager via e-mail.
[5]	UPDATE Clean Fill Database (WFO ESH server).
[6]	FILE documentation on the WFO ESH server in the Clean Fill folder.

6.0 **POST- PERFORMANCE ACTIVITY**

6.1 <u>Records Processing</u>

Records generated while performing this procedure must be processed and maintained in accordance with WFO-AP-150, WFO Records Management Program.

7.0 **REFERENCES**

- ADESH-AP-TOOL-704.0, Construction and Demolition Debris
- NMED Technical Background Document for Development of Soil Screening Levels
- New Mexico Solid Waste Rules 20.9.2 20.9.10 NMAC
- WFO-AP-150, WFO Records Management Program

8.0 ACRONYMS/DEFINITIONS

8.1 <u>Acronyms</u>

Term	Description
AK	Acceptable Knowledge (Documentation)
DESH	Deployed Environment, Safety, and Health
DEP	Deployed Environmental Professional
WFO-HE	WFO High Explosives/Weapons Facilities
ESH	Environment, Safety, and Health
FOD	Facilities Operations Director
GIS	Geographic Information System
IRT	Integrated Review Tool
OM	Operations Manager
TCLP	Toxicity Characteristic Leaching Procedure
WFO	Weapons Facilities Operations
WMC	Waste Management Coordinator

9.0 ATTACHMENTS

Attachment 1: Example WFO Clean Fill Acceptance Request Form Attachment 2: Example WFO Soil Reuse Request Form

Document No.: WFO-OP-415 Revision: A

Effective Date: 05/21/2020

ATTACHMENT 1 Example WFO Clean Fill Acceptance Request Form Page 1 of 1

WFO Clean Fill Acceptance Request Form

ype of soil requested [e.g. top so	oil, soil/gravel, sa	ind, tufa]		Location of Soil	lê.			
'olume [e.g. 1 yd ³ ,5 yds ³]	PR-ID# (f known)		Excavation ID #				
Senerator/Requestor: Prin	t Name		Z-num	lber	с	Cost Codes		
itle			Phone		D	ate		
ubcontractor Technical Represe	entative (STR) if a	applicable	Name				Phone	
ection 2: Characterization/Ver	ification. (DESH	-WFO DEP /Ve	erifier to fill in t	his section, then s	ubmit to WFO-H	E Operations Mana	ager (OM) (or	designee))
nalytical Report Attached? [Yes 🗌 No	lfn	ot, why not?	(explain)				
ompare Analytical Report to Inorgani ational Laboratory, September 22, 15	c and Radionuclide 198, and NMED bac	Background Data kground documen	for Soils, Canyo t for residential	on Sediments, Bandel soil screening (SSLs)	ier Tuff at Los Alan :	os OK? 🗆 Y	′es □N/A	
ampling Required:		lf y	res, sample fo	r what? (explain)	1	\mathcal{O}		
Yes N/A								
cceptable Knowledge (AK) Doci	umentation attac	hed? 🗌 Yes [No	1		If not, why not	? (explain)	
atabase verification. (Required IOT attached.	d if AK Documen	tation is	(If there are	concerns (e.g., H Wast	az, Rad, PCB, a	cerns sbestos), refer Ma Coordinator (WM	aterial Gener C).	ator to internal
X-ID database	No Concerns		775					
SIS database	No Concerns		2.7	1.				
PRS database	No Concerns		_					
R-ID database	No Concerns							
Stack emission d/base database	No Concerns							
ield verification (size)	No Concerns							
ESH-WFO DEP verifies that all cceptance criteria have been sa		DESH-WFC	DEP Printed	Name	Signature			Date
Section 3: Approval. (WFO-HE Approved: Yes No	Operations Mana			in this section, the why not? (explain)		H-WFO DEP)		
certify under penalty of law that I am in applicable databases and that to the	familiar with the ope	ration that genera	ted the material	through personal kno	wiedge as well as i	AK information provide	ed by Material G	enerator and verif
VFO-HE Operations Manager (C			Signature		would cause it to t	Date	or a pollutant.	
ection 4: Receipt. (DESH-WFC	DEP to fill in thi	s section, then s	send copy to I	Material Generator).			
	DE		If reject	ed, explain why:				
RECEIVED 🗆 REJECTE								

WFO-FORM-416A Ref. Doc.: WFO-OP-415

Document No.: WFO-OP-415 Revision: A

Effective Date: 05/21/2020

ATTACHMENT 2 Example WFO Soil Reuse Request Form Page 1 of 1

WFO Soil Reuse Request Form

Type of soil requested [e.g. top soil, soil/gravel, sand, tufa]		be transferred to			
	TA-	TA-			
Volume [e.g. 1 yd ³ ,5 yds ³]	Excavati	Excavation ID #			
Comments:					
		. 0.			
Soil Requestor Printed Name	Z-Number	Signature			
Title	Phone	Date			
Section 2: Soil Reuse Request. (DESH-WFO DEP to fi	ll in this section)				
Volume [e.g. 1 yd ³ ,5 yds ³]	Excavatu	on ID #			
Comments:	2				
	10-				
Section 3: Release (DESH-WFO DEP to fill in this sec	ion)				
Section 3: Release (DESH-WFO DEP to fill in this see DESH-WFO DEP Printed Name	tion) Z-Number	Signature			

WFO-FORM-417A Ref. Doc.: WFO-OP-415