LA-UR-14-25781

Approved for public release; distribution is unlimited.

Title: Microfluidic Design and Manufacture Using Laser Engraving & Cutting Technology

Author(s): Tkach, Louis Patrick

Intended for: Presentation for student symposium

Issued: 2014-07-24

Disclaimer:

Los Alamos National Laboratory, an affirmative action/equal opportunity employer, is operated by the Los Alamos National Security, LLC for the National Nuclear Security Administration of the U.S. Department of Energy under contract DE-AC52-06NA25396. By approving this article, the publisher recognizes that the U.S. Government retains nonexclusive, royalty-free license to publish or reproduce the published form of this contribution, or to allow others to do so, for U.S. Government purposes. Los Alamos National Laboratory requests that the publisher identify this article as work performed under the auspices of the U.S. Department of Energy. Los Alamos National Laboratory strongly supports academic freedom and a researcher's right to publish; as an institution, however, the Laboratory does not endorse the viewpoint of a publication or guarantee its technical correctness.

Microfluidic Design and Manufacture Using Laser Engraving & Cutting Technology

Louis Tkach

Mentor: Dr. Gao

LA-UR-14-25676

TABLE OF CONTENTS

- Background on Laser Engraving Technology
- Overall Fabrication Process

Laser engraving & cutting technology

- Engraving
- Cutting
- Welding

Welding video
http://www.youtube.com/watch?v=OsQ_q3wl1ak

Fabrication Process

Different Designs (pre-manufacture)

- Design A

Requirements, Constraints, & Specifications

- Device Geometry
 - Depth (thickness of material)
 - Straight, Curved or multiple
 - Physical affects
 - Efficiency
- Material Assessment
 - Acrylic, PVC, polycarbonate
 - inertness/non-reactivity
 - Interaction with laser
 - Trace materials?
 - Resin (Filtration-mass); same identification
 - Filtration System to prevent mass transport
 - Various Frit materials
 - Same identification as other assessments
- Specifics on how to manufacture:
 - Laser settings
 - Speed
 - Power
 - Jigs and tools to secure device
 - Centrifuge Settings for packing

Post
Manufacture &
Evaluations

- Successive Design B

Requirements & Constraints

- Device Geometry
- Material Assessment
- Specifics on how to manufacture

This is a determined by Design A

Manufacture

- Material
 - Thermal plastics
 - Acrylic
 - Polycarbonate
 - PVC
 - Glass
- Manufacture Video using Thermal Plastics
- Manufacture Video using glass

UTEM

Evaluation

- Valve setup
- Flow rate
- Percent Volume of Elute in Column
- Image of basic valve setup
- Flow rate test video; determination of max. flow based
- Video demonstrating qualitative success of volume of elute in column

Evaluation: Control Valves

Evaluation: Percent Elution in Column

Results

- Design 1
 - Design 2
 - Design 3
- Images

Current Optimal Design

- Materials
 - Zero Dead Volume Valves
 - Affects:
 - Frits
 - Ensure no filtration mass transfer
 - Thinner materials (depth)
- Geometry
 - Decrease in volume function (depth)
 - Affects on flow rate
 - Shear stresses
 - Degree of flow confinement¹
- Zero dead volume valves components picture
- Frit (filter) in device picture

Future studies

- Reduction of volume

Acknowledgement

- Dr. Jun Gao
- Dr. Ning Xu
- Dr. Alonso

- Jeff
- Steven
- Melanie

- Funding: LDRD

References

- ¹Lawrenz A., Nason F., Cooper-White J., Geometrical effects in microfluidic-based microarrays for rapid, efficient single-cell capture of mammalian stem cells and plant cells, 17 April 2012
- ²Kaoui B., Harting J., Misbah C., Two-dimensional Vesicle Dynamics under Shear Flow: Effect of Confinement. June 1, 2011
- ³Russell J., Introduction to Design; UNM FSAE 2014