LA-UR-19-26114

Approved for public release; distribution is unlimited.

Title: Design-by-contract and test-driven software development

Author(s): Hakel, Peter

Intended for: guest lecture at the University of Colorado Boulder

Issued: 2019-07-29 (rev.1)

Disclaimer:

Los Alamos National Laboratory, an affirmative action/equal opportunity employer, is operated by Triad National Security, LLC for the National Nuclear Security Administration of U.S. Department of Energy under contract 89233218CNA000001. By approving this article, the publisher recognizes that the U.S. Government retains nonexclusive, royalty-free license to publish or reproduce the published form of this contribution, or to allow others to do so, for U.S. Government purposes. Los Alamos National Laboratory requests that the publisher identify this article as work performed under the auspices of the U.S. Department of Energy. Los Alamos National Laboratory strongly supports academic freedom and a researcher's right to publish; as an institution, however, the Laboratory does not endorse the viewpoint of a publication or guarantee its technical correctness.

Design-by-contract and test-driven software development

Guest lecture at the Computational Multi-Physics Production Software Development class
University of Colorado Boulder

Peter Hakel

22 July 2019

Managed by Triad National Security, LLC for the U.S. Department of Energy's NNSA

Outline

22 July 2019

Boulder, Colorado

- Introduction
- Documentation
- Contracts
- Unit testing
- Compilation
- Examples
- Summary

Spectroscopy in visible and infrared regimes

CompB:

$T = 1574 \text{ K}$ (Planckian source)

$\rho = 0.5 \text{ g/cm}^3$

thin shell, radius 15 cm

spherical geometry

Air:

$T = 296 \text{ K}$

standard conditions

length 100 m

planar geometry

Transport medium (air)

*Synthetic spectrum
("detector")*

*EOS and opacity data
were provided by
Eddy Timmermans (T-4)
Josh Coe (T-1)
Leanne Duffy (AOT-AE),
Cristiano Nisoli (T-4).
Dima Mozyrsky (T-4).*

Spectrum no lower
than the $T = 296 \text{ K}$
Planckian (air)

Spectrum no higher
than the $T = 1574 \text{ K}$
Planckian (CompB)

*Acknowledgements to
Jim Reynolds (now at Sandia)
Rod Whitaker (EES-17)*

Spectroscopy in x-ray regime

P. Hakel et al., “X-ray spectroscopic diagnostics and modeling of polar-drive implosion experiments on the National Ignition Facility”, *Physics of Plasmas* **21**, 063306 (2014).

NIF target bay
Image credit:

Lawrence Livermore National Laboratory

FIG. 9. Comparison of instrumentally broadened synthetic spectrum from post-processed rad hydro simulation with Supersnout II experimental data for the N130617 target (Cu dopant).

FIG. 11. Comparison of instrumentally broadened synthetic spectrum from a single temperature-density fit with continuum-subtracted Supersnout II experimental data for the N130617 target (Cu dopant).

FESTR: Finite-Element Spectral Transfer of Radiation

P. Hakel, *Computer Physics Communications* **206**, 415 (2016).

<https://github.com/LANLhakel/FESTR>

Doxygen documentation

<http://www.doxygen.nl/>

The screenshot shows the Doxygen web interface. At the top are navigation tabs: Main Page, Related Pages, Namespaces, Classes, and Files. On the left is a sidebar with a tree view showing the project structure: FESTR, Todo List, Namespaces, Classes, and a Class List. Under the Class List, the 'utils' class is selected, and its members are listed: ArrDbI, Cell, CellEOS, Cone, Database, Detector, Diagnostics, and Face. The main content area displays the documentation for the 'double_to_string()' function. It includes the function signature: `std::string utils::double_to_string ( const double x )`. Below the signature is a brief description: 'Conversion of a real number to a formatted string.' This is followed by sections for 'Parameters' (listing '[in] x Real number to be converted') and 'Returns' (listing 'String version of x using scientific notation'). At the bottom, it states 'Definition at line 66 of file utilities.cpp.'

Contract

Prototype, Input / Output

```
/**
 * @brief Conversion of a real number to a formatted string
 * @param[in] x Real number to be converted
 * @return String version of x using scientific notation
 */
std::string double_to_string(const double x);
```

Example of a unit test

```
{
    utilities name category  
    Test t(GROUP, "double_to_string", "fast");  
  
    check_to_disable_test(t, disabled_test_count);  
    if (t.is_enabled())  
    {  
        double x = -1.0e99;  
        std::string expected = " -1.000000e+99";  
        std::string actual = utils::double_to_string(x);  
  
        failed_test_count += t.check_equal(expected, actual);  
    }  
}
```

-
- returns 0 for PASS
 - returns 1 for FAIL

J. Langr, “Modern C++ Programming with Test-Driven Development” (2013).

Compilation using the make utility

- The source code is partitioned into logical units (classes, namespaces) that can be modified and tested (largely) independently.
 - only changed source files need to be recompiled
 - facilitates team collaboration and version control via repositories (`git`)
- All object code (except the small `main`) is assembled into a library file.
 - helps with possible future reuse in another application
- `make`
 - compile the code (debug version) with the default compiler (`g++`)
- `make tests`
 - compile the unit-test suite
- `make comp=intel opt=yes`
 - compile the code (optimized version) with a different compiler

Running the unit-test suite

- `./tests`
 - run all tests; only failed tests are printed
- `./tests all verbose`
 - run all tests; the PASS or FAIL result is shown for all tests
- `./tests <GROUP>`
 - run tests for the selected group, e.g., `./tests utilities`
- `./tests only <GROUP-test_name>`
 - run a specific test, e.g., `./tests only utilities-double_to_string`
- Selected individual tests can be disabled.

Examples

- The factorial function
 - exact comparisons of integers (`int`, also `size_t`, ...)
- Solution of the quadratic equation
 - floating-point comparisons with a tolerance (`double`, also `float`)
 - exact comparisons of strings (`string`, also `char`)
 - whole-object comparisons with a tolerance (user-defined types)

Procedure

- Write the contract
 - define the function's prototype (i.e., its inputs and outputs)
- Write unit tests, aim for full coverage of all logical paths
 - compilation fails (i.e., testing the scope)
- Write code to return results outside the contract / unit tests
 - test code runs, new unit tests fail (i.e., testing the tests)
- Write production code
 - test code runs, all unit tests pass (i.e., newly added functionality works correctly and no previous code was broken)

Summary

- Modularity and reusability of components
 - large number of short routines and small files
- Design by contract
 - specification of interfaces, up-to-date documentation
- Test-driven development with unit tests
 - simple, but general, native unit-test framework
- Portability across platforms and compilers
 - tested with Linux & Mac platforms, GNU / Intel / Portland compilers
- Stateless kernels to aid parallelization & threading
 - data external to a class are passed via explicit argument lists instead of being shared via global variables